
# Rocket Design



Rocket Stages: 1

Mass (with motor): 985 g

Stability: 1.91 cal CG: 311 mm CP: 413 mm

### G74W-4

0, 1,, 1									
Altitude	274 m	Motor	Avg Thrust	Burn Time	Max Thrust	Total Impulse	Thrust to Wt	Propellant Wt	Size
Flight Time	91.5 s	G74W	76.2 N	1.12 s	91.2 N	85.3 Ns	7.89:1	39.3 g	29/83
Time to Apogee	7.85 s								mm
Optimum Delay	6.7 s								
Velocity off Pad	12.2 m/s								
Max Velocity	75.6 m/s								
Velocity at Deployment	14.8 m/s								
Landing Velocity	3.47 m/s								

#### F37-6

Altitude	85.5 m	Motor	Avg Thrust	Burn Time	Max Thrust	Total Impulse	Thrust to Wt	Propellant Wt	Size
Flight Time	31.2 s	F37	32.6 N	1.55 s	46.5 N	50.7 Ns	3.31:1	28.2 g	29/99
Time to Apogee	4.89 s								mm
Optimum Delay	3.39 s								
Velocity off Pad	7.75 m/s								
Max Velocity	35.5 m/s								
Velocity at Deployment	10.5 m/s								
Landing Velocity	3.33 m/s								

### E15-7

Altitude	34.6 m	Motor	Avg Thrust	Burn Time	Max Thrust	Total Impulse	Thrust to Wt	Propellant Wt	Size
Flight Time	15.2 s	E15	15.7 N	2.53 s	28.8 N	39.8 Ns	1.68:1	20.1 g	24/70
Time to Apogee									mm
Optimum Delay									
Velocity off Pad	5.65 m/s								
Max Velocity	19.8 m/s								
Velocity at Deployment	16.4 m/s								
Landing Velocity	3.29 m/s								
B1-P		l							

Altitude	0 m	Motor	Avg Thrust	Burn Time	Max Thrust	Total Impulse	Thrust to Wt	Propellant Wt	Size
Flight Time	2.91 s	B1	1.88 N	2.42 s	3.87 N	4.61 Ns	0.19:1	24 g	24/40
Time to Apogee	0 s								mm
Optimum Delay	N/A								
Velocity off Pad	N/A								
Max Velocity	0 m/s								
Velocity at Deployment	N/A								
Landing Velocity	0 m/s								

## **Parts Detail**

Sustainer

	Nose cone	PLA (1.3 g/cm³)	Parabolic series	Len: 180 mm	Mass: 47 g
	Parachute	Ripstop nylon (67 g/m²)	Diaout 1782 mm	Len: 102 mm	Mass: 174 g
	Shroud Lines	Elastic cord (flat 6 mm, 1/4 in) (4.3 g/m)	Lines: 8	Len: 200 mm	
M	Shock cord	Tubular nylon (25 mm, 1 in) (29 g/m)		Len: 200 mm	Mass: 5.8 g
	Body tube	PLA (1.3 g/cm³)	Diain 50 mm Diaout 53.6 mm	Len: 180 mm	Mass: 68.5 g
M	Shock cord	Tubular nylon (25 mm, 1 in) (29 g/m)		Len: 200 mm	Mass: 5.8 g
kg	Altimeter		Diaout 50 mm		Mass: 300 g
	Electronics bay	Cardboard (0.68 g/cm³)	Diain 49.4 mm Diaout 53 mm	Len: 100 mm	Mass: 19.7 g
	Extra trube	PLA (1.3 g/cm³)	Diain 50 mm Diaout 53.6 mm	Len: 100 mm	Mass: 38.1 g
kg	Tolerance		Diaout 50 mm		Mass: 100 g
	Tail	PLA (1.3 g/cm³)	Diain 50 mm Diaout 53.6 mm	Len: 150 mm	Mass: 57.1 g
$\Box$	Trapezoidal fin set (3)	PLA (1.3 g/cm³)	Thick: 3.6 mm		Mass: 33.7 g
	Launch lug	PLA (1.3 g/cm³)	Diain 10 mm Diaout 13.6 mm	Len: 30 mm	Mass: 2.6 g
	Motor bracket	PLA (1.3 g/cm³)	Diain 48 mm Diaout 50 mm	Len: 100 mm	Mass: 20 g
0	Engine block	PLA (1.3 g/cm³)	Diain 0 mm Diaout 50 mm	Len: 10 mm	Mass: 25.5 g

