

Todo list

John: Do this section	5
John: Finish this section	6
John: Add the traffic circles section	27
John: Add the midblock crossings section	28
Jake: Talk about the methodology we used	29
Jake: Rank the practices	30
Jake: Discuss the results	31
Nakul: Conclude	32

University of Southern California
Los Angeles
California 90007

6th December 2013

Community Health Councils, Inc.
3731 Stocker Street,
Suite 201
Los Angeles, CA 90008

To whom it may concern,

We are four students at University of Southern California expected to graduate next year, May of 2014. With each of us majoring in a different subfield/subject, we tried to see this project from various perspectives in order to seek what fits best for CHC.

After the insightful site visit, we decided to target ways in which we can improve pedestrian and biker safety as well as for mobility as a whole for the greater Los Angeles. With many traffic-calming techniques already available, we have narrowed down the list to eight specific techniques that we found to be the most reliable and efficient and analyzed them thoroughly. Those eight techniques are chokers, curb radius, raised crosswalks, curb extensions, textured pavements, dignified zones, traffic circles, and midblock crossings. After going deeply into each technique, we have ranked them from top to bottom for you to easily be able to see which ones are the most suitable for Los Angeles.

We have focused this project to cater to CHCs needs and we hope that you find this information helpful for your future plans and projects. Furthermore, we have included references for you to be able to easily find additional information on the given practices. Thank you so much for taking the time to answer our emails whenever we needed any clarifications.

Sincerely,

Jake Hermle
Nakul Joshi
John Lally
Christine Noh

An Analysis of Best Practices in Traffic Calming

Jake Hermle

Civil Engineering

Nakul Joshi

Computer Engineering

John Lally

Mechanical Engineering

Christine Noh

International Relations

6th December, 2013

Abstract

In order to improve mobility and safety in Los Angeles, we have looked upon eight distinctive traffic-calming practices. These include chokers, curb radius, raised crosswalks, curb extensions, textured pavements, dignified zones, traffic circles, and midblock crossings. We will go in detail for each of these techniques and in the end, discuss which one would be the better alternative for Los Angeles specifically.

Contents

1 Executive Summary	5
2 Introduction and Background	6
3 Best Practices	7
3.1 Chokers	7
3.1.1 Advantages and Disadvantages	7
3.1.2 Effectiveness	8
3.1.3 Cost and Considerations	8
3.2 Curb Radius	10
3.2.1 Effectiveness	10
3.2.2 Cost and Considerations	11
3.3 Raised Crosswalks	14
3.3.1 Advantages and Disadvantages	14
3.3.2 Effectiveness	14
3.3.3 Cost and Considerations	15
3.4 Curb Extensions	17
3.4.1 Advantages and Disadvantages	17
3.4.2 Effectiveness	17
3.4.3 Cost and Considerations	18
3.5 Textured Pavements	19
3.5.1 Materials	19
3.5.2 Cost	21
3.6 Pedestrian & Restricted Traffic Zones	23
3.6.1 Pedestrian Zones	23
3.6.2 Restricted Traffic Zone	24
3.6.3 Costs and Considerations	25
3.7 Traffic Circles	27
3.8 Midblock Crossings	28
4 Analysis	29
4.1 Methodology	29
4.2 Rankings	30
4.3 Discussion	31
5 Conclusion	32

List of Figures

1	Choker	7
2	Two-Lane Chokers	8
3	Speed Hump	9
4	Different curb radii	10
5	Effect of changing curb radius	11
6	Plot of crossing times against curve radii	11
7	Pedestrian Facing Back Against the Car	12
8	Different Curb Radii Depending on the Location	13
9	A raised crosswalk	14
10	Various raised crosswalk styles	16
11	Curb extension	17
12	Cobblestone street in Lymm Cross, Cheshire, England	19
13	Streets paved with setts	20
14	Speed hump utilizing brick paving	20
15	Concrete block paving	21
16	Green-colored bike lanes in Portland	21
17	Brown coloring used to distinguish a bike path crossing in the Netherlands	22
18	Example of pedestrian zone design	23
19	Bollards restricting access to a pedestrian area	23
20	A temporary pedestrian zone in Tokyo	24
21	A pedestrian zone	24
22	<i>Zona traffico limitato</i> warning sign and accompanying cameras .	25

List of Tables

1	Average pedestrian crossing times for various curb radii	10
2	Speed reduction due to raised crosswalks	15
3	Average number of vehicles passing before a pedestrian-cross . .	18
4	Percents of pedestrian crossings with yield	18
5	Percent of vehicles yielding at advance stop bar	18
6	Cost estimates of various elements of pedestrian zones	26

1 Executive Summary

John: Do this section

2 Introduction and Background

Community Health Councils (CHC) is producing a report for the City of Los Angeles that recommends and details guidelines for complete streets design to be included in the Mobility Element of the city's General Plan. This CHC report will be describing various best practices that can be implemented so that LA streets better adhere to the principles of complete streets. The following report details eight specific best practices that CHC may implement in their report to the City of Los Angeles. For each best practice, a general description is provided, as well as a discussion of its impact and cost. Additionally, each practice was evaluated based on its cost, impact, and ease of implementation to determine whether it is worth recommending as a design guideline in the Mobility Element. A usability index was created to more quantitatively evaluate these practices, and allowed for better comparison between them. In addition to complete street design, this report is also mindful of CHCs overarching goals of improving health in South LA.

John: Finish this section

3 Best Practices

3.1 Chokers

Chokers are curb extensions at midblock locations that narrow a street by ultimately creating wider sidewalks. They are also known as safe crosses when marked as crosswalks. Chokers can be made by widening one side of the curb or by bringing both curbs in, giving it the pinch point along the street (See Figure 1). The main purpose of chokers is to decrease speed of incoming vehicles at a mid-point along the streets, create a seamless transition between a commercial and a residential area, and to narrow exceedingly wide intersections [1].



Figure 1: This choker requires drivers to yield upon entering

Two-lane chokers (See Figure 2) leave two lanes in the street cross section narrower than the width of a normal cross section, while one-lane chokers narrow the width to allow travel in only one direction at a time. These chokers are effective for areas with substantial speed problems and streets with minimum or no parking on-site.

3.1.1 Advantages and Disadvantages

The various advantages of chokers are:

- ability to reduce both speed and volume significantly
- easily negotiable by large vehicles (for example, fire trucks)
- improving aesthetic value when well designed

The disadvantages include:



Figure 2: Two-Lane Chokers

- Eliminates on-street parking
- Requires bicyclists to briefly merge with vehicular traffic
- Absence of vertical or horizontal deflation limiting the effect of chokers on vehicle speed.

3.1.2 Effectiveness

Chokers can ultimately increase the visibility of pedestrians as well as to reduce pedestrian crossing width, while the speed of vehicles is reduced by 4 percent on average for two-lane chokers and 14 percent on average for one-lane chokers [7]. Also since chokers work well with speed humps, speed tables, and raised intersections, (See Figure 3) it can be created in many sites with no extreme difficulty.

3.1.3 Cost and Considerations

Factors to consider when creating chokers are to consult with the local fire and sanitation department before setting minimum width and to double check to make sure that the bicyclist safety and mobility are not diminished. Also when reducing two-lane street to one lane, the width of the travel way should not be wide enough for 2 cars to pass at the same time. This equals to the travel way not being wider than 4.9 meter, or 16 to 17 feet; by doing so, the effectiveness of



Figure 3: Speed Hump

the choker is maximized [1]. The cost to create chokers varies depending on the site and landscape but most are along the lines of \$5,000 to \$20,000 (drainage representing a significant amount).

3.2 Curb Radius

Curb radius is a traffic calming technique in which the grid of intersecting streets is reshaped and the radius of the curb is significantly reduced. As you can see in Figure 4a, a large curb radius will enable vehicles to go around corners faster while in Figure 4b, a smaller curb radius will slow vehicles down when turning into the corner.




Figure 4: Different curb radii

3.2.1 Effectiveness

The purpose of curb radii is to slow vehicles down by enabling them to make smaller turns, which ultimately reduces the risk of pedestrians being struck by vehicles when turning into a corner. Also, small curve radii can create safer intersections, improve the visibility between drivers and pedestrians, and lead to improved signal timing. By reducing the curb radii, not only will it slow down vehicles when turning, but it will also shorten the distance and time it takes for pedestrians to cross the street by nearly half of what it used to be (See Table 1 and Figures 5 and 6).

Curb Radius (ft)	Time (s)
10	7.9
15	9.8
25	14.1

Table 1: Average pedestrian crossing times for various curb radii

When streets have a large curb radius, motorists can make turns at relatively high speeds that decrease pedestrian safety. By contrast, 90-degree intersections and corners with tight curb radii tend to slow motorists down and




Figure 5: Change in Distance from 25ft. Radius to 8ft. Radius




Figure 6: A plot of the data from Table 1

therefore increase pedestrian safety. Motorists turning right at high speed can cut off bicyclists/pedestrians traveling straight on the arterial street. In addition, pedestrians crossing the residential street adjacent to the arterial may not expect high-speed turning traffic, or they may have their backs facing the turning cars as you can see in Figure 7.

3.2.2 Cost and Considerations

The cost of reconstructing tighter turning radii is in between \$5,000 to \$40,000 per corner depending on the site locations/conditions. When considering curb radii, it is important to note that in order for it to be effective, the design should meet the needs of the design vehicles with consideration for nearby land uses and prevalence of roadway users. So if there are high volumes of large vehicles making turns in a given location, a poorly designed curb radius could potentially cause the vehicles to drive over the curb and onto the sidewalk endangering pedestrians. In addition, you should always accommodate emergency vehicles,



Figure 7: Pedestrian Facing Back Against the Car

as well as school buses, and public maintenance vehicles when designing curb radii [5].

There is no magic number for the appropriate curb radius because it differs case by case depending on where it is located (See Figure 8). The length of the curb radius that should be used wherever possible is 5 to 10 feet, whereas an effective radius for urban streets with high volumes of pedestrians is 15 to 20 ft. For arterial streets with a substantial volume of turning buses/trucks, an appropriate effective curb radius is about 25 to 30 ft.; and the maximum desired effective curb radius is typically 35 feet for large vehicles [5].




Figure 8: Different Curb Radii Depending on the Location

3.3 Raised Crosswalks

A raised crosswalk (Figure 9) is a designated street crossing that simultaneously acts as a speed hump by bringing the level of the roadway to that of the sidewalk.




Figure 9: A raised crosswalk [11]

3.3.1 Advantages and Disadvantages

The advantages of such a traffic calming measure include:

- Forces traffic to slow down, improving pedestrian safety.
- Draws attention to the pedestrian, especially when combined with signage and markings.
- Makes crossing the street easier for those on wheelchairs.

The drawbacks are:

- The textured materials used tend to be expensive.
- Not suitable for emergency or bus routes.
- Drainage, especially in snowy or rainy areas, requires additional management.

3.3.2 Effectiveness

Raised crosswalks are an effective traffic calming technique in that they can reduce vehicular speed (See Table 2). Further, they have also been shown effective at encouraging pedestrians to use the crosswalk instead of crossing the road elsewhere. One study [9] found that raising the crosswalk increased the percentage of pedestrians using it from 11.5% to 38.3%.

City and Measure	50th percentile speed (km/h)		Speed reduction (km/h)
	Treatment Site	Control Site	
Durham, NC Research Drive <i>Raised crosswalk</i>	33.3	39.8	6.5
Durham, NC Towerview Drive <i>Raised crosswalk, overhead flasher</i>	18.5	38.4	19.3
Montgomery County, MD <i>Raised Crosswalk</i>	34.6	38.6	4.0

Table 2: Speed reduction due to raised crosswalks (Data from [9])

According to PEDSAFE [9], raised crosswalks can mitigate dart-and-dash type incidents in which the driver was unable to see the pedestrian until just before impact. They also prevent vehicles from ‘trapping’ pedestrians. Raised crosswalks are best used in areas of low-volume, low-speed traffic where safety of pedestrians takes a priority, such as residential areas and near schools. As a side benefit, they make crossings much easier for the elderly, the disabled, and the young in these areas.

3.3.3 Cost and Considerations

The cost of such a crosswalk varies from \$2000 to \$15000, with typical cost estimate for one unit being \$4000 [6]. However, this might be significantly increased if a drainage system has to be added.




Figure 10: Various raised crosswalk styles. [6]

3.4 Curb Extensions

A curb extension (Figure 11) is an extension of the curb onto the roadway. As a traffic calming measure, they are primarily used to assist pedestrians by reducing crossing distance and slowing traffic down.



Figure 11: Curb extension

3.4.1 Advantages and Disadvantages

Curb extensions are thought to have the following advantages:

- Reduce the time that pedestrians are exposed to traffic.
- Increase the visibility of pedestrians attempting to cross.
- Shield parking lanes from oncoming traffic and prevent drivers from using them as right turn lanes.

The various drawbacks are:

- They pose a threat to bicyclists, who are forced into a narrowed gap along with traffic.
- Like raised crosswalks, they complicate drainage since they obstruct the gutter.
- Reduce the availability of parking spaces, which can hurt local businesses.

3.4.2 Effectiveness

One study [10] found that curb extensions significantly reduced the number of vehicles pedestrians had to wait for before one yielded. The same study also found minor increases in percents of crossings where a motorist yielded, and of vehicles yielding at advance stop bars. These results are shown in Tables 3, 4 and 5.

3.4.3 Cost and Considerations

Curb extensions cost between \$5,000 and \$25,000 per corner [3]. As with most sidewalk retrofitting, a large portion of the cost goes to drainage. If it is also necessary to remove a utility pole or other such existing infrastructure element, costs can become much higher.

Lane	Non-curb extension	Curb extension	Difference	Sample Size
Near	2.58	1.81	-42.7 %	219
Far	2.36	1.76	-33.9 %	214

Table 3: Average number of vehicles passing before a pedestrian-cross. Results found significant by the t-test.

Lane	Non-curb extension	Curb extension	% difference	Sample Size
Near	64.9%	66.7%	2.7%	234
Far	58.6%	63.4%	7.7%	234

Table 4: Percents of pedestrian crossings with yield. The results were found insignificant by the t-test.

Lane	Non-curb extension	Curb extension	% difference	Sample Size
Near	42.6%	53.8%	21.0%	99
Far	42.6%	51.9%	18.0%	99

Table 5: Percent of vehicles yielding at advance stop bar. The results were found insignificant by the t-test.

3.5 Textured Pavements

Textured and colored pavements refers to the use of varied pavement materials to alter the color or texture of a street surface. This practice can be used as a traffic calming measure or as a way to distinguish special areas of the street.

Changes in pavement texture from normal concrete or asphalt surfaces can cause a change in audible road noise inside the car body. This effect can be utilized to alert drivers to slow down or take notice of potential hazards. Textured or colored pavements can also be used to visually distinguish special areas of the street, such as crosswalks or bike lanes, to make drivers more aware of their location [?].

Altered pavement textures and colors have been found to cause reductions in vehicle speed, though there is limited data available to quantify this [?]. This practice can be used in combination with other practices to produce a traffic calming effect, such as raised crosswalks, speed tables, or raised intersections.

3.5.1 Materials

Cobblestones Cobblestone roads are paved with quarried stone with rounded tops. The advantages of this material are that it will create a significant audible disturbance to drivers and can provide a unique aesthetic appeal; however, cyclists and wheelchair users might find this pavement difficult to navigate. Additionally, the unevenness of the pavement makes it more difficult to remove snow and ice [?].




Figure 12: Cobblestone street in Lymm Cross, Cheshire, England

Setts and Bricks Setts are quarried stone blocks that are flat-topped (in contrast with round-topped cobblestones). They are typically arranged in a uniform manner, as pictured in Figure 13. Bricks are used and placed in a similar nature, but come from a different source material. The road texture of sett-paved roads can vary depending on the evenness of the selected setts [?].



Figure 13: Streets paved with setts



Figure 14: Speed hump utilizing brick paving

Concrete Blocks Concrete blocks are pre-cast, individual blocks of concrete that are placed similarly to bricks or setts. An advantage of using concrete blocks is that they can be shaped and colored in different ways to create a desired appearance. For example, concrete blocks can be made to look like setts and bricks by casting them in a certain size and applying the proper coloring. An additional advantage of concrete blocks is their reduced cost [?].



Figure 15: Concrete block paving

Colored Pavement Pavement can be colored through the use of pavement striping paint, as similarly used to make normal pavement markings. While textured pavements generally are made up of more earthen tones, bright colors can be used to create a very noticeable visual effect, as demonstrated by the green bike lanes in Figure 16.



Figure 16: Green-colored bike lanes in Portland

3.5.2 Cost

The cost of utilizing textured or color pavements is dependent on a) the material used and b) the total area of the pavement. The Victoria Transport Policy Institute estimates a cost range of \$5–\$16 per square foot [?]. A crosswalk 10 feet in width crossing a four-lane road, for example, would have a total material cost ranging from \$2400–\$7680.



Figure 17: Brown coloring used to distinguish a bike path crossing in the Netherlands

3.6 Pedestrian & Restricted Traffic Zones

3.6.1 Pedestrian Zones

A pedestrian zone is an urban area in which motorized vehicle access is disallowed. In some instances, all wheeled vehicles (including bicycles) are banned from the zone. Barriers are typically put in place to physically obstruct motorized vehicles from entering. These barriers typically come in the form of bollards (pictured below) and can be either permanent or removable, if access is required for certain motorized vehicles. Pedestrian zones can be created temporarily by closing off a normal street to motorized traffic by placing temporary barriers. Alternatively, permanent pedestrian zones can be designed without motorized traffic in mind. Figure 18, Figure 20, and Figure 21 illustrate examples of permanent pedestrian zones [?].



Figure 18: Example of pedestrian zone design: enough space allowed in the middle for essential motor vehicles, textured pavements to indicate an alternative purpose for the space, and bike racks in place to encourage bicycle use.



Figure 19: Bollards restricting access to a pedestrian area

Pedestrians zones make land that was previously used for roads or parking available for gathering space or green space. Pedestrian zones increase the local



Figure 20: A temporary pedestrian zone in Tokyo, created by placing temporary barriers in front of a normal street

populations use of walking as a mode of transportation, which in turn decreases usage of automobiles, as businesses in the zone have increased their accessibility to pedestrians. Additionally, these zones are also known to increase rates of physical activity, particularly amongst children [?].



Figure 21: A pedestrian zone

3.6.2 Restricted Traffic Zone

Restricted Traffic Zones are urban areas where non-essential motorized traffic is disallowed. This is a practice most commonly found in Italy, known as a *zona traffico limitato*. The practice is used to reduce congestion and pollution in historical city centers. Cameras are placed at strategic checkpoints entering the zone to check control access. A picture is taken of every vehicle, and its license plate is cross-referenced against a list of permitted vehicles. Prohibited vehicles are fined. Depending on the characteristic of the restricted zone, other vehicles can be allowed as well, such as merchant vehicles, taxis, emergency vehicles, maintenance vehicles, and diplomats [?]. In combination with the

closure of these zones to non-essential traffic, Italian cities increased public transit services to improve mobility. In Milan, for example, this practice proved to reduce automobile traffic in the zone by 50%. In Freiburg, Germany, traffic restriction and public transit improvements caused bicycle usage to double from 1976 to 1986 and led 18% of drivers to switch to public transit [?].



Figure 22: *Zona traffico limitato* warning sign and accompanying cameras

3.6.3 Costs and Considerations

The primary costs of a restricted traffic zone are the construction and maintenance of the monitoring equipment; however, the fines (starting at an equivalent of \$50 in Italy) collected due to violations would make up the difference [?]. One problem with these fines is that it is a nuisance to unsuspecting tourists who are not aware of the laws and fines. Additionally, if measures aren't taken to reduce total automobile traffic through public transit improvements, the traffic that is redirected due to these restrictions could cause significant congestion in other city zones.

The cost of introducing a pedestrian zone to an urban area depends on its design. Table 6 lists selected pedestrian improvements that could potentially be implemented in a pedestrian zone, and their estimated costs based on data from the San Francisco Bay Areas Metropolitan Transportation Commission [?].

Total maintenance costs would also be dependent on the particular facilities. For an example of these costs, one can look to Corona Plaza in New York City. This proposed plaza is currently a dilapidated access road and parking lot, and is planned to be converted to a 13,000 square foot pedestrian public space [?]. It is estimated that it will cost between \$50,000 and \$75,000 a year to maintain this plaza [?].

Element	Estimate	
	Lower	Upper
Paving (textured or non-textured) (per square foot)	\$5	\$16
Concrete Sidewalk Removal and Replacement (per square foot)	\$20	
Pedestrian-Level Street Lights (ea.)	\$3000	\$5000
Cobra Head Standard Lights (ea.)	\$10000	
6 Wide Bench (ea.)	\$1500	\$3000
Bike Rack (ea.)	\$600	\$1200
Bollards (ea.)	\$500	\$750
24 Box Trees (ea.)	\$1820	
Trash Cans (ea.)	\$800	\$1500
Water Fountain (Aesthetic) (ea.)	\$15,000	\$50,000
Tree Grates (ea.)	\$680	\$750
60 Day Maintenance for mile of street (lump sum)	\$3000	\$4000
Signage (Standard vs. High Visibility) (ea.)	\$300	\$400

Table 6: Cost estimates of various elements of pedestrian zones [?].

3.7 Traffic Circles

John: Add the traffic circles section

3.8 Midblock Crossings

John: Add the midblock crossings section

4 Analysis

4.1 Methodology

Jake: Talk about the methodology we used

4.2 Rankings

Jake: Rank the practices

4.3 Discussion

Jake: Discuss the results

5 Conclusion

Nakul: Conclude

References

- [1] Chokers. <http://www.walkinginfo.org/engineering/calming-chokers.cfm>. WalkingInfo.org.
- [2] Chokers. <http://www.trafficcalming.net/chokers.htm>. Traffic Calming.
- [3] Crossing enhancements. <http://www.walkinginfo.org/engineering/crossings-enhancements.cfm>. WalkingInfo.org.
- [4] Curb radius: Better walking through geometry. <http://www.missionped.org/archive/curbrad.html>. Mission Pedestrian.
- [5] Curb radius reduction. <http://www.walkinginfo.org/engineering/crossings-curb.cfm>. WalkingInfo.org.
- [6] Raised crosswalks. <http://www.trafficcalming.net/raised-crosswalks.htm>. Traffic Calming.
- [7] Traffic calming measures - choker. <http://www.ite.org/traffic/choker.asp>. Institute of Transportation Engineers.
- [8] What are chokers? <http://www.sinoconcept.com/2012/01/chokers/>, 2012. Sino Concept.
- [9] Herman F. Huang and Michael J. Cynecki. The effects of traffic calming measures on pedestrian and motorist behavior. *Pedestrian Safety Guide and Countermeasure Selection System*, 2001.
- [10] Randal S. Johnson. Pedestrian safety impacts of curb extensions: A case study. *Transportation Development - Research Section*, 2005.
- [11] Kimley-Horn and Associates, Inc.
- [12] Edward R. Stollof. Developing curb ramp designs based on curb radius. *ITE Journal*, 2005.
- [13] Charles Zegeer, Dan Nabors, and Peter Lagerwey. Curb radius reduction. *Pedestrian Safety Guide and Countermeasure Selection*, 2013.

James (Jake) Hermle

3335 S. Figueroa Street #510 • Los Angeles, CA 90007 • (703) 869-6066 • hermle@usc.edu

EDUCATION

University of Southern California, Los Angeles, CA

Viterbi School of Engineering

Bachelor of Science, Civil Engineering

Expected May 2014

Cumulative GPA: 3.668

Honors: Viterbi Dean's List, Presidential Scholar, Chi Epsilon Honor Society, Rusch Engineering Honors Program

Thomas Jefferson High School for Science and Technology, Alexandria, VA

June 2010

GPA: 4.319

EXPERIENCE

Arup, Los Angeles, CA

Summer 2012, Summer 2013

Infrastructure Intern

- Modeled light rail underground guideways to perform soil settlement analyses.
- Produced horizontal and vertical roadway alignments for the Gerald Desmond Bridge Replacement Project.
- Chaired civil engineering group task force meetings and took minutes.
- Coordinated with the NOAA PORTS program to determine design constraints for bridge air gap sensor.
- Created utility routing plan for pipes servicing Gerald Desmond Bridge maintenance vehicles.
- Produced potholing and CCTV surveying exhibits for utility upgrading projects.

Dominion Virginia Power, Woodbridge, VA

Summer 2011

Design Intern

- Designed new service lines to connect businesses and residencies requesting electricity to the power grid.
- Communicated with customers to configure power line designs to individual needs.

American Society of Civil Engineers, USC Chapter

January 2011 - Present

Concrete Canoe Co-Captain (August 2011 – Present)

- Manage a team of 30 students to design and construct a concrete canoe to be raced against other universities in the Pacific southwest.
- Coordinate team paddling practices, design and construction meetings.
- Developed concrete mix design using lightweight aggregates to design a concrete mix that floats in water while staying within ASCE rules and regulations.
- Composed technical write-ups of the design and construction of the canoe.

Troy Camp, USC

September 2012 – Present

Counselor

- Assisted in the organization of specialized programming for students at West Vernon Elementary in musical theater and leadership programming for middle school students in the Leaders In Training program.

Institute of Transportation Engineers, USC Chapter

April 2011 - Present

Publicity Chair (August 2011 – August 2012)

- Helped establish newly formed chapter of ITE.
- Maintain communication with member base concerning ITE events.

SKILLS

Software: MS Office (Word, Excel, Powerpoint), AutoCAD, Revit Architecture, SolidWorks, SAP2000, MicroStation (+InRoads)

Languages: Conversational German

Nakul Joshi

(213) 610 6105 nakul.joshi@usc.edu 3335 S Figueroa St, Apt 629 Los Angeles, CA 90007

EDUCATION

B.S. Computer Engineering/Computer Science

University of Southern California GPA: 3.575/4

Relevant Coursework

Data Structures	Computer Architecture	Object-oriented Programming	Software Engineering
Web Publishing	Calculus & Statistics	Artificial Intelligence	Digital Forensics

Expected Graduation May 2014

TECHNICAL SKILLS

Languages Java, C/C++, Python, HTML, JavaScript, Verilog

Tools Eclipse, NetBeans, SVN, Git, Mathematica, Xilinx ISE

Packages Microsoft Office, L^AT_EX

WORK EXPERIENCE

Viterbi School of Engineering

Undergraduate Teaching Assistant, Data Structures

January 2013 - Present
Los Angeles, CA

- Led lab sections for the course.
- Graded assignments and tests.
- Held office hours during which I answered students' questions.

University of Paderborn

Research Intern

May 2012 - July 2012
Paderborn, Germany

- Co-authored a paper on Digital Rights Management (DRM) with a Ph.D. student.
- Gained a background in cryptography through research and applied it to develop a protocol for a cloud-based DRM solution.

Viterbi Academic Resource Center

Peer Tutor/Supplemental Instruction Leader

January 2012 - Present
Los Angeles, CA

- Assisted students with engineering classes in one-on-one sessions.
- Led weekly group sessions to supplement introductory computer science lectures.

PUBLICATIONS

Towards practical privacy-preserving Digital Rights Management for Cloud Computing IEEE CCNC 2013
Co-author

- Created a cryptographic protocol that protected the copyright on cloud-based software.
- The protocol specifically protected the privacy and anonymity of users in the system.

ACADEMIC PROJECTS

Factory simulation

Fall 2011

- Collaborated with seventeen students to simulate a multi-agent system.
- Designed and implemented the user interface.

Constraint Satisfier

Fall 2012

- Wrote a program that found boolean assignments that satisfied a given set of logical statements.
- Applied the program to create a Sudoku-style puzzle solver.

HONORS AND ACHIEVEMENTS

Dean's List

Fall 2010, Spring 2011, Fall 2011, Spring 2012

Engineering Honors Colloquium

Southern California Regional International Collegiate Programming Contest
Placed 6th out of over 90 teams

Fall 2010

IEEE Eta Kappa Nu Honors Society

Member since Spring 2012

JOHN TIMOTHY LALLY

325 W Adams Blvd, Apt 5002, Los Angeles, CA 90007 • 781-462-8120 • lally@usc.edu

BS in Mechanical Engineering
Minor in Engineering Management
Viterbi School of Engineering
University of Southern California

Expected 12/2014

Relevant Coursework:

Fundamentals of Physics I, II, III	Strength of Materials
Technical Entrepreneurship	Statics, Dynamics
Introduction to Computational Methods	Engineering Statistics
Probability Concepts in Engineering	Thermodynamics
Fluid Dynamics	Materials Science
Mechophtronics Laboratory	Heat Transfer
Computational Solutions to Eng. Problems	Aero-Mechanical CAD
Linear Control Systems	Flight Mechanics

Work Experience:

Co-op Mechanical Engineer

Carlisle Interconnect Technologies

5/2013 – 8/2013
Cerritos, CA

- Utilized engineering principles, processes, and methods to satisfy project objectives related to manufacturing support/development of connectors/cable process
- Created plant and equipment layouts, wrote manufacturing procedures and specifications, investigated and corrected process and tooling abnormalities
- Led investigation and implementation of SPC program on five production lines
- Trained in ITAR and EAR compliance for aerospace and military technology

Student Associate

USC Stevens Center for Innovation

5/2013 – Present
Los Angeles, CA

- Member of Operations Team for technology licensing and commercialization
- Reviewed technology disclosures from professors and graduate students in Viterbi School of Engineering, Information Sciences Institute, and Keck School of Medicine
- Improved and developed business processes, reviewed data accuracy and metric reporting, and provided input on projects and strategic decisions

Construction Manager

Summer Real Estate

5/2008 – 8/2012
Boston, MA

- Maintained and updated Boston-area residential properties
- Designed and led remodeling and renovation projects
- Carpentry, roofing, flooring, heating, electrical, plumbing

Valet Attendant

Chatham Bars Inn Resort and Spa

5/2012 – 8/2012
Chatham, MA

- Provided valet, bellman, and chauffeur services to resort guests
- Managed department operations as bell captain during evening shifts

Affiliations/Leadership:

Delta Chi Fraternity – House Manager

1/2011 – Present

- Developed projects with Alumni Board of Trustees and USC Housing officials
- Led 10 member committee in planning and executing construction projects

National Organization for Business and Engineering – Officer of Investments

1/2011 – Present

- Planned guest speakers, networking events, and professional workshops

Rocket Propulsion Laboratory – Junior Member

9/2010 – 5/2012

- Cut carbon fiber and constructed wet-layup fiberglass body

Christine Noh

E-Mail: cnoh@usc.edu; christinenoh@gmail.com

CN

Education

Smith College, Northampton, MA.

Date Attended: August 2010 – May 2011

University of Southern California, Los Angeles, CA.

Expected Graduation Date: May 16, 2014

Major: *Bachelor of Arts* – International Relations

Skills/Qualifications Summary

- Bilingual; Ability to speak and write English and Korean fluently with no grammatical errors.
- Avid user of Microsoft Word, PowerPoint, and Excel.
- Experience with both PC and Macintosh computers
- Able to work calmly with various groups of people under difficult situations and communicate well with others.

Professional Experience

Paralegal at Law Offices of Kyung Hee Lee, PC (March 2013 – August 2013)

- Assisted an attorney with various types of immigration cases, and accumulated extensive experience in the areas of B-1; E-1/2; F-1; employment-based immigration petitions (1st, 2nd and 3rd preferences); H-1B; L-1; TN; NIW; all family-based immigration petitions; and extensions/transfers for the aforementioned nonimmigrant visas - strong background in E-2, EB-1, 2 and 3, H-1B and L-1