# PIZZA HUT SALES





# INTRODUCTION





THE PIZZA HUT SALES ANALYSIS PROJECT IS A SQL-BASED DATA ANALYTICS PROJECT FOCUSED ON ANALYZING PIZZA SALES DATA TO UNDERSTAND BUSINESS PERFORMANCE AND CUSTOMER PURCHASING PATTERNS. THE PROJECT USES SQL QUERIES TO ANALYZE KEY METRICS SUCH AS TOTAL REVENUE, TOTAL ORDERS, AVERAGE ORDER VALUE, BEST-SELLING PIZZAS, SALES BY CATEGORY, AND SALES TRENDS OVER TIME



# RETRIEVE THE TOTAL NUMBER OF ORDERS PLACED.

```
SELECT
    COUNT(order_id) AS total_orders
FROM
    orders;
```

| | total_orders |
|---|---|
| ▶ | 21350 |





# CALCULATE THE TOTAL REVENUE GENERATED FROM PIZZA SALES.

```sql
SELECT
    ROUND(SUM(order_details.quantity * pizzas.price),
            2) AS total_sales
FROM
    order_details
        JOIN
    pizzas ON pizzas.pizza_id = order_details.pizza_id
```

| | total_sales |
|---|---|
| ▶ | 817860.05 |



# IDENTIFY THE HIGHEST-PRICED PIZZA.



```sql
SELECT
    pizza_types.name, pizzas.price
FROM
    pizza_types
        JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
ORDER BY pizzas.price DESC
LIMIT 1;
```

| | name | price |
|---|---|---|
| ▶ | The Greek Pizza | 35.95 |



# IDENTIFY THE MOST COMMON PIZZA SIZE ORDERED.

```sql
SELECT
    pizzas.size,
    COUNT(order_details.order_details_id) AS order_count
FROM
    pizzas
        JOIN
    order_details ON pizzas.pizza_id = order_details.pizza_id
GROUP BY pizzas.size
ORDER BY order_count DESC;
```

| size | order_count |
|---|---|
| L | 18526 |
| M | 15385 |
| S | 14137 |
| XL | 544 |
| XXL | 28 |







# LIST THE TOP 5 MOST ORDERED PIZZA TYPES ALONG WITH THEIR QUANTITIES.

```sql
SELECT
    pizza_types.name, SUM(order_details.quantity) AS quantity
FROM
    pizza_types
        JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
        JOIN
    order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.name
ORDER BY quantity DESC
LIMIT 5;
```

| | name | quantity |
|---|---|---|
| ▶ | The Classic Deluxe Pizza | 2453 |
| | The Barbecue Chicken Pizza | 2432 |
| | The Hawaiian Pizza | 2422 |
| | The Pepperoni Pizza | 2418 |
| | The Thai Chicken Pizza | 2371 |

# JOIN THE NECESSARY TABLES TO FIND THE TOTAL QUANTITY OF EACH PIZZA CATEGORY ORDERED.

```sql
SELECT
    pizza_types.category,
    SUM(order_details.quantity) AS quantity
FROM
    pizza_types
        JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
        JOIN
    order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.category
ORDER BY quantity DESC;
```



| | category | quantity |
|---|---|---|
| ▶ | Classic | 14888 |
| | Supreme | 11987 |
| | Veggie | 11649 |
| | Chicken | 11050 |

# DETERMINE THE DISTRIBUTION OF ORDERS BY HOUR OF THE DAY.



```sql
SELECT
    HOUR(order_time), COUNT(order_id) AS order_count
FROM
    orders
GROUP BY HOUR(order_time);

-- Join relevant tables to find the category-wise distribution of pizzas.
SELECT
    category, COUNT(name)
FROM
    pizza_types
GROUP BY category;
```

| | category | COUNT(name) |
|---|---|---|
| ▶ | Chicken | 6 |
| | Classic | 8 |
| | Supreme | 9 |
| | Veggie | 9 |


THANK YOU