Design of a drift chamber tracking system for the IDEA experiment at FCC-ee

Niloufar Alipour Tehrani (CERN), Benedikt Hegner, Giovanni Francesco Tassielli, Francesco Grancagnolo, P. Janot, A. M. Kolano, G. Voutsinas

2018 IEEE Nuclear Science Symposium and Medical Imaging Conference, Sydney, Australia

The Future Circular Collider Experiment (FCC)

- A future possibility for the post-LHC era
- 3 options of circular colliders
  - FCC-ee: electron - positron collisions
  - FCC-hh: proton - proton collisions
  - FCC-eh: electron - proton collisions
- ∼100 km tunnel in Geneva area
- FCC-ee collider parameters:

Stages	Z	WW	H (ZH)	tt̄
Beam energy [GeV]	45.6	80	120	182.5
Average bunch spacing [ns]	19.6	163	994	3396



FCCSW: Physics and Detector simulations with FCCSW

- Common software for all FCC experiments (ee, hh & eh)
- Detector and physics studies
  - Fast & full simulations
  - One software stack from event generation to physics analysis
- Collaborative approach with other CERN experiments
  - Gaudi from LHC
  - DD4hep from CLIC & LHCb
  - New solutions where needed

Geometry DDhep → Segmen-tation → Geant4 simulation → Digiti-zation

The IDEA detector concept for FCC-ee

- The IDEA detector is one of the two detector concepts for the FCC-ee
- Ultimate goal for the IDEA detector concept
  - Vertex detector: MAPS
  - Ultra-light drift chamber with particle identification
  - Double readout calorimetry
  - Aditional silicon disk layers placed in the space between the drift chamber and the dual readout calorimeter to increase the forward coverage
  - 2 T solenoidal magnetic field
  - Instrumented return yoke
  - Large tracking volume (R ∼ 8 m) for very weakly coupled (long-lived) particles



- The IDEA detector as simulated with FCCSW



The drift chamber

- The parameters of the drift chamber

Gas	90 % Helium & 10 % isobutane (
Length	4500 mm
Inner radius	345 mm
Outer radius	2000 mm
Nb. layer	112
Cell size	12 mm - 14.7 mm
Number of sensitive wires	56448
Single cell resolution	0.1 mm
Longitudinal resolution	1 mm



- The first layer of the drift chamber
- Wires are illustrated using different colors
- The wires are rotated by a stereo angle to increase the hit resolution



- In the barrel region, the drift chamber has a high coverage of ∼ 112 wires in average.
- In the forward region, silicon disks are foresean to increase the number of layers measuring the tracks.



Main sources of beam-induced backgrounds

- Three main sources of beam-induced backgrounds
  - Incoherent e^+e^- pairs du to bremstrahlung photons ⇒ highest source of background
  - $\gamma\gamma \rightarrow$ hadrons ⇒ Expected to have a very low impact
  - Synchrotron radiation (SR) ⇒ Dictates the design of the interaction region (IR)
    - Defines the beampipe radius, the design of the shielding (in Tungesten)
    - Mostly stopped by the shielding, few SR photons can hit the detector

- The trajectory c
  2 T magnetic fie



3 main sources of beam-induced backgrounds at the top stage

- Incoherent e^+e^- pairs



Background	Average occupancy E_{cm} = 91.2 GeV	Average occupancy E_{cm} = 365 GeV
e^+e^- pair background	1.1%	2.9%
$\gamma\gamma \rightarrow$ hadrons	0.001%	0.035%
Synchrotron radiation	-	0.2%

- The overall impact remains low and the results are promising for the track reconstruction with this detector.