Design of a drift chamber tracking system for the IDEA experiment at FCC-ee

Niloufar Alipour Tehrani (CERN), Benedikt Hegner, Giovanni Francesco Tassielli, Francesco Grancagnolo, P. Janot, A. M. Kolano, G. Voutsinas

2018 IEEE Nuclear Science Symposium and Medical Imaging Conference, Sydney, Australia

The Future Circular Collider Experiment (FCC)

- A future possibility for the post-LHC era
- 3 options of circular colliders
  - FCC-ee: electron - positron collisions
  - FCC-hh: proton - proton collisions
  - FCC-eh: electron - proton collisions
- ∼100 km tunnel in Geneva area
- FCC-ee collider parameters:

Stages	Z	WW	H (ZH)	tt̄
Beam energy [GeV]	45.6	80	120	182.5
Average bunch spacing [ns]	19.6	163	994	3396



FCCSW: Physics and Detector simulations with FCCSW

- Common software for all FCC experiments (ee, hh & eh)
- Detector and physics studies
  - Fast & full simulations
  - One software stack from event generation to physics analysis
- Collaborative approach with other CERN experiments
  - Gaudi from LHC
  - DD4hep from CLIC & LHCb
  - New solutions where needed

Geometry DDhep → Segmen-tation → Geant4 simulation → Digiti-zation

The IDEA detector concept for FCC-ee

- The IDEA detector is one of the two detector concepts for the FCC-ee
- Ultimate goal for the IDEA detector concept
  - Vertex detector: MAPS
  - Ultra-light drift chamber with particle identification
  - Double readout calorimetry
  - Aditional silicon disk layers placed in the space between the drift chamber and the dual readout calorimeter to increase the forward coverage
  - 2 T solenoidal magnetic field
  - Instrumented return yoke
  - Large tracking volume (R ∼ 8 m) for very weakly coupled (long-lived) particles



- The IDEA detector as simulated with FCCSW



The drift chamber

- The gas volume is divided into a set of hyperboloid layers.
- Each layer contains one sensitive wire for signal acquisition.
- Field wires surround the sensitive wires to provide homogeneous electric field for each cell.
- The wires are rotated with a stereo angle of 0.1 radians to improve the longitudinal resolution along them.
- The parameters of the drift chamber

Gas	90 % Helium & 10 % isobutane (C_4H_{10})
Length	4500 mm
Inner radius	345 mm
Outer radius	2000 mm
Nb. layer	112
Cell size	12 mm - 14.7 mm
Number of sensitive wires	56448
Single cell resolution	0.1 mm
Longitudinal resolution	1 mm



The simulation of the drift chamber with FCCSW

- The first layer of the drift chamber with wires rotated with a certain stereo angle.
- The DD4hep segmentation (DDSegmentation) is responsible to associate a hit to the wire it drifts to.
- Wires are illustrated using different colors.



- The coverage of the drift chamber as a function of the polar angle θ is investigated using FCCSW.
- High coverage in the barrel region by ∼ 112 wires in average.
- In the forward region, silicon disks are foresean to increase the number of layers measuring the tracks.



Main sources of beam-induced backgrounds at the FCC-ee and the impact on the IDEA drift chamber

- Three main sources of beam-induced backgrounds
  - Incoherent e^+e^- pairs du to bremstrahlung photons ⇒ highest source of background
  - $\gamma\gamma \rightarrow$ hadrons ⇒ Expected to have a very low impact
  - Synchrotron radiation (SR) ⇒ Dictates the design of the interaction region (IR)
    - Defines the beampipe radius, the design of the shielding (in Tungesten)
    - Mostly stopped by the shielding, few SR photons can hit the detector
- The trajectory of the e^+e pairs in a 2 T magnetic field.



- Incoherent e^+e^- pairs



Background	Average occupancy	
	E_{cm} = 91.2 GeV	E_{cm} = 365 GeV
e^+e^- pair background	1.1%	2.9%
$\gamma\gamma \rightarrow$ hadrons	0.001%	0.035%
Synchrotron radiation	-	0.2%

- The overall impact remains low and the results are promising for the track reconstruction with this detector.