

(1) Select the correct option?

<html> <body>

<c:if> !> anum = 5 </c:if>

Value is <c:if> anum </c:if> </body> </html>

(Ans) It will show compile time error because of an incorrect declaration.

(2) <c:if> "Hello" + userName </c:if> is an example of

(Ans) Jsp Expression

(3) A JSP page uses the java.util.ArrayList class many times. Instead of referring the class by its complete package name each time, we want to \_\_\_\_\_? (a) extend (b) include (c) package.

(a) extends ~~import~~ (b) include (c) package.

(4) Which core JSTL tag is used to display the result of an expression?

(a) <c:set> (b) <c:if> (c) <c:forEach>

(d) <c:out>

(5) A bean with a property color is loaded using the foll. statement

<jsp:usebean id="fruit" class="Fruit"/>

which of the foll. statements is used to print the value of color property?

(Ans) <jsp:getProperty name="fruit" property="color">

(6) JSP lifecycle will have these different stages.

(a) page translation (b) page compilation

(c) jspinit() (D) All

(7) <html><body>

<a href="/servlet/HelloServlet">POST</a>  
</body></html>

Which method of Hello Servlet will be invoked when the hyperlink displayed by the above page is clicked?

doGet (b) doPost (c) doForm (d) doPut

(8) Out of these Servlet life cycle methods, which will get called only once in whole life cycle by the container?

- (a) public void init()
- (b) public void service()
- (c) public void destroy()  A & C

(9) Which of the foll. deployment descriptor snippet correctly associates a servlet implemented by a class named com.abc.SalesServlet?

(Ans) `< servlet >`  
~~< servlet >~~ `< servlet-name > SalesServlet < /servlet-name >`  
~~< servlet >~~ `< servlet-class > com.abc.SalesServlet < /servlet-class >`  
~~< servlet >~~ `< /servlet >`

(10) Which of the following deployment descriptor element is used to specify the initialization parameters, for a servlet named?

- (a) `< init-param >`  < init-param >
- (b) `< param >`
- (c) `< param >`
- (d) `< servlet-param >`

(11) \_\_\_\_\_ are pieces of data which are stored at the client's browser to track info regarding the user?  a) Cookies  b) URL rewriting  
 c) Session and Hidden field

(12) What is the name of the deployment descriptors file of a web application named BankApp?

- (a) BankApp.xml (b) Bankapp.xml (c) web.xml (d) WebApp.xml

(13) Which method is used to get value of attribute from servlet context?

(Ans) String getAttribute (String name)

(14) The root element of the web.xml is \_\_\_\_\_

- (a) web (b) web-app (c) name (d) display-name

(15) Which of the is true about deployment

(doubt) descriptors (dd)

(a) The order of elements in dd is not important. The elements can follow any order.

(b) The elements of dd are case insensitive.

(c) The servlet-mapping element, if defined must be included within the servlet element.

(d) The web-app element must include the

(16) General format of connection?

(Ans) `getconnection ( sun.jdbc.odbc.JdbcOdbcDriver )`

(17) Connection is present in which package?

(Ans) java.sql, java.sql

(18) What happens when the foll. statement is executed?

`<jsp:setProperty name="fruit" property="*"/>`

(Ans) All the properties of the fruit bean were assigned the values of input parameters of the jsp page that have the same name.

(19) `ResultSet.close()`? what will happen?

(a) no close for `ResultSet`

(b) Resultset along with statement is closed.

(20) URI to be sent then \_\_\_\_\_?

your redirect (b) `RequestDispatcher(forward)`

(c) `RequestDispatcher(include)`

Q21) ResultSet metadata, count no. of columns;

(a) DatabaseMetadata smd = getMetaData();  
int a = smd.getColCount();

(b) ResultSetMetaData rsmid = smd.getMetaData();  
int a = rsmid.getColumnCount();

Q22) This is called driver type.

Q23) fastest driver, thin is Thin - Type 4

Q24) Vendor Specific communicates directly with  
(doubt)  
Server using

(a) Type 1 drivers (b) Type 2 drivers.

(c) Type 3 drivers (d) Type 4 drivers

Q25) Welcome - file - list

Q26) Welcome - file (b) servlet (c) webapp

Q27) getResultSetMetaData ?

(a) DatabaseMetadata (b) ResultSetMetaData

(c) getMetaData

(Q7) < servlet-name > Test < servlet-name >  
(doubt) < servlet-mapping >  
< url > ". \* .asp" >

What does "Test" mean here?

- (a) \home.asp (b) \gin\home.asp  
(c) \*.asp (bin\asp)

(Q8) What is used to achieve the DriverManager?

- (a) getConnection (b) getDriverName (c) getName

- (d) getDriver

(Q9) 3 Transactions - 2 Transactions - correct  
(doubt)

1 - transaction - wrong. SQL exception

(Q10) savpoint (b) Roll back and abort transaction

- (c) commit

(Q11) If we want to group 2 statements in a single transaction, should do?

- (a) set AutoCommit (true)

Set AutoCommit (false)

- (c) set AutoTransaction (true)

- (d) set AutoTransaction (false)

(31) To retrieve init parameters, which method be used.

Ans) public ~~was~~ String getInitParameter(String name)

(32) What will return the ResultSet?

Ans) executeQuery / executeUpdate

(33) Which of the method is called only once in the Servlet lifecycle?

Ans) public void init()

(34) Which of the foll. is not a standard method in JSP's?

(a) Jsp Service (b) jsp destroy (c) jsp request()

(35) Syntax for Request Dispatcher?

Ans) RequestDispatcher rd = request.getRequestDispatcher("Servlet");  
rd.forward(request, response);

(36) which directive allows us to use `std::lib` in coding?

Ans taglib:

(37) XML equivalent of `<%@ include file = "a.jsp" %>`

(38) Where will you keep a class file in your web app?

(AM) WEB-INF / classes

(39) getSessionId() method, when web server just started?

(a) NullPointerException ~~empty page~~

(c) Not compiled (d) session id generated.

(40) Which of the foll. is true for

`<jsp:useBean>`

\* (a) The `id` attribute optional for `<jsp:useBean>`.

\* (b) The `scope` attribute must be defined for `<jsp:useBean>`

(c) The `class` attribute must be defined for `<jsp:useBean>`

(d) The `<jsp:useBean>` must include either type or class attributes or both.

(101) core tag to display result of expression

ans) <c:out>

(102) callable st: ?

(43) <html> body > form >

`<input type = "text" name = "name" >` Name

`<input type = "submit" name = "submit" >`

</form>

</body> </html>

(a) `getParameterValue("name")`

b) `getParameter("name")`

(c) `getParameterValues("name")`

(d) `getValue("name")`

(44) which of these are page directives?

Q5) Which JSP variable is not available in JSP expression?

- (a) session (b) page (c) Response (~~but~~) HTTPSession

Q6) Which of these are legal attributes of (doubt) page directives?

- (a) include (b) exception (c) session (~~but~~) b & c

Q7) Example of JSP directive?

- ~~✓~~ include (b) exclude (c) import (~~but~~) taglib.

Q8) Which JSTL tag displays content only if expression evaluates to true?

(Ans) <c:if>

Q9) Which is used to print the factorial?

- (a) <%.! fact %.> (b) <% fact %.>

~~✓~~ <% = fact %.> (d) <% = fact ; %.>

Q10) user = " " name = " " password = " "

which method is used?

~~✓~~ get method (b) post method

(51) what is the correct syntax?

(Ans) `<? . @ page import = "java.util.*" ?>`

(52) Which statement object is pre compiled?

(Ans) prepared statement.

(53) Which interface accepts values at runtime?

(a) prepared stmt (b) callable stmt (c) MetaData

(d) ResultSetMetadata

(54) Which of the following interface gives info  
to retrieve about Database elements?

(Ans) DataBase metaData

(55) error page and still session is continued?

(Ans) isForwarPage = "true" session = "true"

(56) get Session() method is in which package?

(a) HttpServletRequest (b) HttpServletresponse

(c) servletConfig (d) servletContext

(57) Railbank is

- (a) should be called
- (b) where engines coaches
- (c) program is abnormally terminated

~~• tip • (Ans) All •~~

(58) How to do

(58) How to retrieve an attribute in ServletContext

~~• tip •~~

(Ans) Object getAttribute( string name )

(59) <c:choose> used when ?

(Ans) It is used when <c:when> and  
<c:otherwise> are used as nested tags.

(60) what is mandatory for <c:if> ?

(Ans) test.

(61) What is mandatory for <c:useBean>?

(Ans) id.

(62) javax.servlet.HttpServlet is an interface.

(G2) Isolation level Dirty read Non-repeatable read Phantom read

Transaction - NO NO NO

Read uncommitted

Transaction

Read-committed Yes No No

Transaction Yes No No

Repeatable-Read Yes

Transaction Yes Yes

S Serializable Yes

\* Yes - PO prevented.

(G3) Get Method has data access limit?

(Ans) Only 4kb limit

(G4) If invalidate() is called in

invalidate session then what type of exception?

(Ans) Illegal State Exception (b) Invalidate State Exception

a) Session Invalidated Exception

(65) To iterate string ?

Ans) < c:forEach > or

< c:forTokens > tag is used to break a string into tokens and iterate through each of the tokens.

(66) ResultSet (Attribute types)

- (a) getString (int) (b) getString (String)
- (c) getString (int, int) ✓ Both a & b.

(67) Hidden form fields, cookie, HttpSession, URL rewriting are used in Session Management.

(68) In JSP, which is implicit object for < context-param >? application.

Ans) application.

(69) Session is best for Controlling?

True.

(70) To know the driver name?

Ans) DatabaseMetaData.getMetaData().

(71) To know the type of column, property of column? (Ans) ResultSetMetaData.

(72) HttpRequest.getCookies() returns Cookies

(73) How to transfer control to webpage  
if exception occurs?

(Ans) <%@ include page="error.jsp" %>

(74) isThreadSafe(true) → single thread

(75) addBatch(), executeBatch() is a statement

(76) The root element of web application is  
<web-app>

(77) For iterating the elements in array list,  
we use <c:forEach>

(78) One ServletConfig per Servlet

(79) one ServletContext per web application

(80) stored procedures or functions can be  
called using "callable statements"

- (81) Transaction Read uncommit  
dirty read is No
- (82) TER forward slash (/) is necessary  
when ServletContext is used.
- (83) forward slash (/) is not must for  
"Request Dispatcher".
- (84) JSTL is JSP standard tag library
- (85) Cookie is a class.
- (86) Exception is an implicit object is  
present by default  
(a) True (b) false
- (87) What do you use to set a value  
to bean property?
- (Ans) <c: setProperty >
- (88) JspService() cannot be overridden
- (89) ResultSetMetaData.setColumnCount()  
returns int (no. of columns in a  
result set object)

- (90) executeBatch() returns int.
- (91) resultSet.next() returns boolean.
- (92) Connection, statement, preparedStatement are interfaces.
- (93) setAutoCommit(false) implies transaction is started?
- (a) True    (b) False
- (94) SQLException, ClassNotFoundException are checked exceptions.
- (95) doGet(), doPost() doesn't throw RuntimeException.
- (96) The collection of individual tasks is known as "Transactional management".
- (97) Which one in JSTL URL-related tags performs URL rewriting?  
Ans) <c:url>

~~gat 647, 672, 657, 82N.~~

(98) ~~Ques~~ \$ {application.mail} is similar to 'jstl expr' (doubt)

(Ans)  $\langle \text{el} \rangle = \text{context.getParameters}(\text{"mail"}) \cdot \text{l.} >$   
~~or~~  $\langle \text{el} \rangle = \text{context.getAttribute}(\text{"mail"}) \cdot \text{l.} >$

(99) What is the meaning of transaction isolation

level transaction - ~~repeatable~~ read ?

(Ans) dirty reads, non repeatable reads are preventable, phantom reads can occur.

(100) What directive is used to include ~~content~~ other pages ?

(Ans)  $\langle \text{el} \rangle @\text{include}$

(101) Which below options are used to include a resource called foo.jsp ?

(Ans)  ~~$\langle \text{jsp:import} \text{ include page = "foo.jsp" } \rangle$~~   
 ~~$\langle \text{jsp:include page = "foo.jsp" } \rangle$~~

(102) JSP is best presentation.

(103) How would you execute a stored procedure in the database? call method execute() on CallableStatement.

(Ans) select the correct type of

\* call method executeQuery() or execute() on a CallableStatement object

- (104) Which of the below techniques are used  
(a) Cookies (b) URL Rewriting (c) HttpSession (d) All
- (105) Which of the foll. is valid?
- (Ans) <jsp:include page = "a.jsp" />
- (106) Which page directive attribute is used to declare a JSP page as errorpage?
- (Ans) isErrorPage.
- (107) Select the JSTL tag to tokenize a string.
- (Ans) <c:forTokens>
- (108) Select the JSTL tag to import standard java packages.
- (Ans) (a) None. (b) <c:importPackages> (c) <c:import> (d) <c:importPackage>
- (109) javax.servlet.Servlet is a java class?
- (Ans) false.
- (110) Which implicit object is used to access all other implicit objects?
- (Ans) pageContext.

(1) Which of the foll. objects is not a thread-safe?

(Ans) Context.

(2) Which of the foll. HTTP methods is considered as idempotent?

(Ans) GET.

(3) What is clp for foll. code?

<jsp:useBean id="test" class="Test.Test"  
scope="request"/>

<jsp:setProperty name="test" property="name"/>

<jsp:getProperty name="test" property="name"/>

(Ans) null.

(4) Servlet A ~~forwards the control to~~ needs to share data with Servlet B.

using Request Dispatcher. Servlet A needs to share data with Servlet B, so that data must not be visible to other servlet in application in which object can the data.

that A share B be stored?

(Ans) (d) HttpServletRequest ✓

(115) Select the name of Type1 driver.

(Ans) JDBC-ODBC bridge driver.

(116) What is the data type of "out" implicit object?

(Ans) PrintWriter java.servlet.jsp.TJSPWriter

(117) Syntax used to import class in a java?

(Ans) <@ page import = "java.util.Date" %>

(118) Which will having setAttribute()?

(Ans) HttpServletRequest

(119) How would servlet code from a doPost()

retrieve a value of the user agent header from the request?

(Ans) String userAgent = request.getHeader("user-agent");

(120) Is Every JSP will be transmitted into a servlet?

(Ans) false

(181) Doubt method need to add a cookie ?

(Ans) response.addCookie(cookie);

or response.addCookie("username","pe").

(181) Sequence of those arguments we need to get Connection() method of connection ?

(Ans) url, username, password.

(182) Can we update actual table using Updatable Result Set ?

(Ans) Yes.

(183) <@ taglib prefix="c" uri="http://java.sun.com/jsp/jstl/core">  
</taglib> <head> </head> <body> <c:out value="  
\$(20\*3)"></body> </html>  
O/P ?

(Ans) Syntax error

(184) methods available in RequestDispatcher ?

(Ans) forward() and include()

(185) Which among the foll. points II ?

(Ans)  $\left( \begin{array}{l} \langle \text{@! int } i=10, j; \text{@} \rangle \\ \langle \text{@! } j=j+1, j=i-j \text{@} \rangle \\ \langle \text{@! } =j \text{@} \rangle \end{array} \right)$

(126) which method of HttpServletResponse is used to redirect request to another URL?

(Ans) sendRedirect().

(127) Select the return type of executeQuery method?

(Ans) gives a single ResultSet object. ResultSet

(128) What happens if you call deleteRow() on a ResultSet object?

(Ans) The row you are positioned on is deleted from the resultset and from the database.

(129) method used to retrieve an attribute available in the scope?

(Ans) getAttribute()

(130) What is initial cursor position in Resultset?

(Ans) BeforeFirst

(131) Which directive specifies content type of JSP response as ?

(Ans) `<%@ page contentType = "image/svg" %>`

(132) Which is false ?

(Ans) One servlet config per web app.

(133) public class Test {

    public void (String args[]) {

        Class.forName("sun.jdbc.odbc.JdbcOdbcDriver")

    } } Will it compile ?

(Ans) No

(134) Which implicit object refers servlet context ?

(Ans) \*application

(135) Will the below piece of code compile ?

Cookie c = new Cookie(1, "username");

(Ans) No

(136) Which of the foll. is a valid JSP scriptlet ?

(Ans) `<% String uid = loginHelper.login(request); %>`

(139) Need to create a java bean object that is used only with the current JSP page. It must not be accessible to a page, including those that this page might import. Which JSP standard action can accomplish this goal?

(Ans) `<jsp:useBean id='pageBean' class='com.example.MyBean'>`

(140) Session Management : Cookies, URL rewriting, HttpSession.

(141) Where JSP pages gets deployed?

(Ans) Web server or JSP engine

(142) Implicit variable available to jsp page?

- (a) connection
- (b) request
- (c) context
- (d) object

(143) Default value of scope attribute

<jsp:usebean>

\ (a) page (b) application (c) session (d) request.

(144) What does this do?

class DriverClass = Class.forName("org.  
hsqldb.jdbcDriver")

(Ans) loading and registering of driver

(145) purpose of Class.forName()?

(Ans) used to create an instance of a driver and  
register it with DriverManager.

(146) stat = obj. prepareStatement("select \*  
from publishers where pub\_id = ?")

(Ans) obj is of which object type?

connection

(147) Connection con = DriverManager.getConnection  
("jdbc:odbc:wombat", "logins", "pwd") ?

(Ans) The Resultset returns primitive  
types for integers and floats.

(M8) Which of the foll. is used to retrieve data

fetched from database table in the program.

(Ans) ResultSet

(M9) In which package Connection if ?

(Ans) java.sql

(M10) In a Transaction there are three starts.

While executing this transaction, 3<sup>rd</sup> start raised an SQLException?

(Ans) Should call the rollback() to abort the transaction

(M11) Retrieve info - about the databases? If?

(Ans) ResultSetMetaData

(M12) Loading the JDBC ODBC bridge driver?

(Ans) Class.forName ("sun.jdbc.odbc.JdbcOdbcDriver")

Statement of Driver class

Statement st = connection.createStatement();

String sql = "select \* from emp";

ResultSet rs = st.executeQuery(sql);

(153) Which of the foll. gives information about the data, such as structure and properties of the table?

- (a) Index (b) Record (c) Metadata (d) Table info.

(154) Consider

```
Class.forName("sun.jdbc.odbc.JdbcOdbcDriver");
connection con = DriverManager.getConnection("",
"","");
```

(Ans) ✓ ResultSetMetaData rsmd = result.getMetaData();
int columns = rsmd.getColumnCount();

(155) When rollback of a transaction happen?

(Ans) rollback() called, abnormal program termination

(156) Which driver in JDBC is called as this driver?

(Ans) Type 4 driver.

(157) Which of the foll. Resultset interface field specifies the concurrency mode that does not allow you to update the Resultset object?

(Ans) CONCUR\_READ\_ONLY

(158) Servlet is used to write business logic for web application.

(Ans) True.

(159) Which of these are used to maintain the state?

(a) URL rewriting (b) cookies (c) Hidden fields

(d) All

(160) Resource not found?

(Ans) Code 404

(161) Not a standard method in JSP?

(Ans) Jsp request,

(162) Used to retrieve the Request Name ?

(Ans) getServletName()

(163) getWriter is present in which If ?

(Ans) HttpServlet Response

(164) Retrieve init parameters ?

(Ans) String getInitParameter (String name)

(165) Servlet interface contains lifecycle methods.

(166) doTrace() : method throws the client  
what server is receiving

(167) we can't call sendRedirect after response  
is committed.

(168) init method doesn't exist in HttpServlet class

(169) SendRedirect () takes a string not URL

(170) response . setIntHeader ("203", 17)

replaces the value to integer to  
existing header.

(171) forward() : redirect the resources  
to different servers internally.

(172) Servlet config parameter ?

(Ans) <init-param>

(173) Context -- context.params

(174) JSP pages deployed in JSP engine

(175) post method ?

(Ans) Sends data in body of request -

(176) http://...?username ?

(Ans) GET method

(177) HttpServletRequest contains ?

(Ans) (a) getContentType (b) AddHeader (c) getCookies  
getOutputStream

(178) Data can be retrieved using

(a) order name (b) column name (c) all

(179) XML Equivalent way to include file asp-jsp ?

(Ans) <jsp:include file = "asp-jsp" />

- (180) Root tag in web.xml is  
(Ans) web-app
- (181) Servlet uses a utility com.abc.toy class file  
Q "toy.class" is present in ?  
(Ans) WEB-INF / classes / com / abc ,
- (182) <context-param> contains what  
<param-name> </param-name>  
<param-value> </param-value>  
</context-param>
- (183) <%@page i=1 j=1 %> <% = i / j %> ✓
- (184) <jsp:getProperty name="" value="" />  
What are uses of jsp:property tag
- (185) "taglib" is the one which can be  
used as directive among all given options
- (186) JSP lifecycle does not contain  
method by which we can invoke JSPGet() method

(187) Web Server that executes the Servlet code  
on HTTPServletRequest

(188) Which of the foll. describe ways that dynamic  
info. can be available to all Servlet requests  
sent to an application?

(Ans) Store the info. on HTTPSession.

(189) getBytes() against HttpServletRequest:  
used to retrieve form data from client

(190) Deployment descriptor describes web component  
settings

(191) what type of diagrams does Java architect  
frequently produce?

(Ans) Attribute diagram.

(192) URL connection instance represents a link  
for accessing the resource at the location?

True.

(193) If session object is invalidated, can it be regained or refreshed?

(Ans) NO

(194) <%. return; %> aborts the processing of JSP.

true

(195) Can't implement if in JSP.

(196) The listener is notified when ServletContext (i.e. web app is initialized and destroyed)

(Ans) ServletContext Listener

(197) cookie.setMaxAge(int seconds);

(198) Req, Res, Session : implicit objects

(199) possible ways b/w applet & servlet

(A) HTTP (B) RMI All (D) some

(200) Sharing of session data across multiple load web servers is called "clustering".

- (201) `<c:while>` not a core JSTL tag
- (202) `<% int sum = sum + i; %>` // Java script
- (203) `<% for (int i=0; i<3; i++) { %>`  
`out.print(i);`  
`<% } %>`
- private void printNum (int i)  
0 1 2 3
- (204) To declare a variable, we use "`!`"
- (205) init-param can define servlet config, in web.xml.  
init-param: does not have getAttribute() (don't have getAttribute() and setAttribute())
- (206) init parameters are read by container when servlet & initialised
- (207) GET is faster than POST.
- (208) 1024 characters are sent through doGet()
- (209) context-param can define servlet context in web.xml.

- (210) How can we get context init parameter and run some code before rest of the app can service a client?
- (Ans) ServletContextListener.
- (211) protocols supported by HttpServlet
- (Ans) http and https ✓
- (212) GenericServlet doesn't extend HTTPServlet and doesn't override doGet() method.
- (213) Jsp expression contains Session, page Context only.
- (214) HTML is part of http request ? True or False
- (Ans) True.
- (215) Which of the foll. interprets html code and renders webpages to user ?
- (Ans) Browser.
- (216) Which of these are MIME types ?
- (Ans) {  
Image / bmp  
text / html } ✓

(216) Is JSP a part of Web logic?

(Ans) False

(217) We must have configure and map jsp files into web.xml?

(Ans) No

(218) JSP can be run by

(doubt)

(a) Apache Tomcat (b) BEA web logic

(c) JSP engine (d) All

(219) Is JSP a part of Apache tomcat?

(Ans) NO

(220) JSP is basically used today?

(Ans) None

(221) Which of the foll. is true by default

(a) Session (b) language is ThreadSafe (isrf)

(222) JSP technology is extensible? True

(223) <sup>(doubt)</sup> Browsers are only required to accept  
the cookies for file?

(224) <jsp:plugin> tag is used to insert the  
browser specific objects and embed elements?

(Ans) True

(225) JSP variables are not available within a  
JSP expression (contains only session & page context)

~~(Ans)~~ HttpSession is not there.

(226) <% x=1; %> is correctly represented by  
<jsp:script> x =1; </jsp:script>

(227) <% session.setAttribute("name", "john"); %>  
<% session.getAttribute("john") %>

(Ans) null

(228) Syntax: void - jspService (HttpServletRequest,  
HttpServletResponse) throws IoException,  
ServletException).

(Q29) jspService() shouldn't be overridden by the author? True

(230) Signature of JspDestroy() of Jsp page?

Void jspDestroy() throws ServletException.

(231) Valid argument for a Jsp page directive?

isThreadSafe = "yes/no".

(232)  $\text{if } \text{Math.random}() \geq 0.5 \text{ then}$   
 $\text{hello}$

$\text{else } \text{world}$

$\text{if } \text{Math.random}() > 0.5 \text{ then}$

(Ans) Jsp file will not compile.

(Q33) How to send data in get method?

URL

(234) MIME (multiple internet mail extensions)

(multiple internet mail extensions)

(multiple internet mail extensions)

Content-type

(Q35) Which tag of DD maps internal name of servlet to a fully qualified classname?

(Ans) servlet.

(Q36) glassfish is not a webserver.

(Q37) Web server serves only static pages.

(Q38) Dynamic interpretation of request and response to transform the info. is done by servletfilter.

(Q39) Servlet mapping defines association b/w a URL pattern & a servlet.

(Q40) Unit of data to be passed from HTML when `doGet()` method is used?

(Ans) 8k

(Q41) `<servlet-name>` and `<servlet-class>` in web.xml file values may be same.