

SQL Tutorial



SQL

Agenda





	Employee							
e_id ‡	e_name ‡	e_salary ‡	e_age ‡	e_gender ‡	e_dept ‡			
1	Sam	95000	45	Male	Operations			
2	Bob	80000	21	Male	Support			
3	Anne	125000	25	Female	Analytics			
4	Julia	73000	30	Female	Analytics			
5	Matt	159000	33	Male	Sales			
6	Jeff	112000	27	Male	Operations			


	l	Бератине	
	d_id	d_name	d_location
П	1	Content	New York
П	2	Support	Chicago
П	3	Analytics	New York
П	4	Sales	Boston
П	5	Tech	Dallas
П	6	Finance	Chicago

Department

Inner Join



Inner Join returns records that have matching values in both tables. It is also known as a simple join.



Inner Join: Syntax






SELECT columns
FROM table1
INNER JOIN table2
ON table1.column_x = table2.column_y;

Left Join



Left Join returns all the records from the left table and the matched records from the right table.



Left Join: Syntax






SELECT columns
FROM table1
LEFT JOIN table2
ON table1.column_x = table2.column_y;

Right Join



RIGHT JOIN returns all the records from the right table and the matched records from the left table.



Right Join: Syntax






SELECT columns
FROM table1
RIGHT JOIN table2
ON table1.column_x = table2.column_y;

Full Join



It returns all rows from the LEFT table and the RIGHT table with NULL values in place where the join condition is not met.



Full Join: Syntax





SELECT columns
FROM table1
FULL JOIN table2
ON table1.column_x = table2.column_y;

Insert Query: Syntax





INSERT INTO table_name
VALUES (value1,
value2,value3,...valueN);

Update Statement



Update is used to modify the existing records in a table.

UPDATE table_name
SET col1=val1, col2=val2.....
[WHERE condition];


Update Using Join




Department Table

Employee Table

Updated Employee Table





e_id	e_name	e_salary	e_age	e_gender	e_dept
1	Sam	93000	40	Male	Operations
3	Anne	140000	35	Female	Analytics
6	Jeff	112000	27	Male	Operations
7	Adam	110000	38	Male	Content
8	Priya	85000	37	Female	Tech


Delete Using Join




Department Table

Employee Table


Modified Employee Table





e_id	e_name	e_salary	e_age	e_gender	e_dept
1	Sam	93000	40	Male	Operations
6	Jeff	112000	27	Male	Operations
8	Priya	85000	37	Female	Tech







Source Table

e_id	e_name	e_salary	e_age	e_gender	e_dept
1	Sam	93000	40	Male	Operations
2	Bob	80000	21	Male	Support
3	Anne	130000	25	Female	Analytics
6	Jeff	112000	27	Male	Operations
7	Adam	100000	28	Male	Content
8	Priya	85000	37	Female	Tech

Target Table


e_id ‡	e_name ‡	e_salary [‡]	e_age 🗦	e_gender 🔅	e_dept 🔅
1	Sam	95000	45	Male	Operations
2	Bob	80000	21	Male	Support
3	Anne	125000	25	Female	Analytics
4	Julia	73000	30	Female	Analytics
5	Matt	159000	33	Male	Sales
6	Jeff	112000	27	Male	Operations



Source Table

Target Table

e_id	e_name	e_salary	e_age	e_gender	e_dept
1	Sam	93000	40	Male	Operations
2	Bob	80000	21	Male	Support
3	Anne	130000	25	Female	Analytics
6	Jeff	112000	27	Male	Operations
7	Adam	100000	28	Male	Content
8	Priya	85000	37	Female	Tech



e_id ‡	e_name ‡	e_salary ‡	e_age ‡	e_gender ‡	e_dept 🔅
1	Sam	95000	45	Male	Operations
2	Bob	80000	21	Male	Support
3	Anne	125000	25	Female	Analytics
4	Julia	73000	30	Female	Analytics
5	Matt	159000	33	Male	Sales
6	Jeff	112000	27	Male	Operations





MERGE [Target] AS T
USING [Source] AS S
ON [Join Condition]
WHEN MATCHED
THEN [Update Statement]
WHEN NOT MATCHED BY TARGET
THEN [Insert Statement]
WHEN NOT MATCHED BY SOURCE
THEN [Delete Statement];



Source Table

e_id	e_name	e_salary	e_age	e_gender	e_dept
1	Sam	93000	40	Male	Operations
2	Bob	80000	21	Male	Support
3	Anne	130000	25	Female	Analytics
6	Jeff	112000	27	Male	Operations
7	Adam	100000	28	Male	Content
8	Priya	85000	37	Female	Tech

Employee_Source

Target Table

e_id ‡	e_name ‡	e_salary ‡	e_age ‡	e_gender ‡	e_dept ‡
1	Sam	95000	45	Male	Operations
2	Bob	80000	21	Male	Support
3	Anne	125000	25	Female	Analytics
4	Julia	73000	30	Female	Analytics
5	Matt	159000	33	Male	Sales
6	Jeff	112000	27	Male	Operations

Employee_Target



Quiz

Quiz



With an inner join, we are:

A Matching information between two or more tables

B Selecting non-correlated information from two tables

C Selecting information inside one table

D None of these



Solution



With an inner join, we are:

A Matching information between two or more tables

B Selecting non-correlated information from two tables

C Selecting information inside one table

D None of these



Quiz



Which of these is True about right join:

Α

Returns all the records from the left table and the matched records from the right table

В

It returns all rows from the LEFT table and the RIGHT table with NULL values in place where the join condition is not met

C

Returns all the records from the right table and the matched records from the left table.

D

None of these



Solution



Which of these is True about right join:

Α

Returns all the records from the left table and the matched records from the right table

В

It returns all rows from the LEFT table and the RIGHT table with NULL values in place where the join condition is not met

C

Returns all the records from the right table and the matched records from the left table.

D

None of these



Quiz



Which of the following is the correct UPDATE statement:

Α

UPDATE Customers SET CustmerName='Aled' Where empNo=10;

В

UPDATE table Customers SET CustmerName='Aled' Where empNo=10;

C

UPDATE Customers table SET CustmerName='Aled' Where empNo=10;

D

UPDATE Customers SET CustmerName='Aled' as empNo=10;



Solution



Which of the following is the correct UPDATE statement:

A

UPDATE Customers SET CustmerName='Aled' Where empNo=10;

В

UPDATE table Customers SET CustmerName='Aled' Where empNo=10;

C

UPDATE Customers table SET CustmerName='Aled' Where empNo=10;

D

UPDATE Customers SET CustmerName='Aled' as empNo=10;



Quiz



The MERGE statement can have at most WHEN MATCHED clauses

A | | 2

В


C 2

D



Solution







Thank You