

No. 1

```
package main
import "fmt"

func main() {
    var n int
    fmt.Scan(&n)
    printNumRecursive(n)
}

func printNumRecursive(n int) {
    if n > 0 {
        printNumRecursive(n-1)
        fmt.Print(n, " ")
    }
}
```

```
C:\Belajargolang\sem2\T>go run no1.go
1
1
C:\Belajargolang\sem2\T>go run no1.go
2
1 2
C:\Belajargolang\sem2\T>go run no1.go
5
1 2 3 4 5
C:\Belajargolang\sem2\T>go run no1.go
7
1 2 3 4 5 6 7
C:\Belajargolang\sem2\T>
```

No. 2

```
package main
import "fmt"

func main() {
    var n int
    fmt.Scan(&n)
    fmt.Println(sumNumSeq(n))
}

func numSeq(n int) int {
    if n == 1 || n == 0 {
        return 1
    } else {
        return n * numSeq(n-1)
    }
}

func sumNumSeq(n int) int {
    if n == 1 {
        return numSeq(1)
    } else {
        return numSeq(n) + sumNumSeq(n-1)
    }
}
```

```
C:\Belajargolang\sem2\T>go run no2.go
1
1

C:\Belajargolang\sem2\T>go run no2.go
2
3

C:\Belajargolang\sem2\T>go run no2.go
5
153

C:\Belajargolang\sem2\T>go run no2.go
7
5913
```

No. 3

```
package main
import "fmt"

func main(){
    var n, i int
    var nama string
    var status string
    var angkatan int

    fmt.Scan(&n)
    for i = 0; i < n; i++){
        inpData(&nama, &status, &angkatan)
        if i == 0{
            fmt.Println("DATA")
            fmt.Println(" ")
        }
        outputData(nama, status, angkatan)
    }
}

func inpData(nama *string, status *string, angkatan *int){
    fmt.Scan(nama, status, angkatan)
}

func outputData(nama, status string, angkatan int){
    fmt.Printf("| %-15s | %-20s | %-5d |\n", nama, status, angkatan)
}
```

C:\Belajargolang\sem2\T>go run no3.go

4

Bellingham ASDOS/ASPRAK 23 Roberto ASDOS 22 Carlos ASPRAK 19 Lamine ASLAB 20

DATA

Bellingham	ASDOS/ASPRAK	23
Roberto	ASDOS	22
Carlos	ASPRAK	19
Lamine	ASLAB	20

C:\Belajargolang\sem2\T>|