

# Project1

September 16, 2021

## 1 Project 1 Report

Nick Alvarez

CS458

### 1.1 P1-1. Curse of Dimensionality

(a) Generate 1000 points following a uniform distribution under a given dimension, and then compute difference between max and min distance between any pair of points. Hint: Refer to the tutorial “Introduction to Numpy and Pandas” on how to generate random points.

(b) Repeat (a) for different dimensions from 2 to 50.

```
[6]: import numpy as np
from scipy.spatial import ConvexHull
from scipy.spatial.distance import cdist
from matplotlib import pyplot as plt
from progressbar import progressbar

MAX_ITERATIONS = 10
NUMBER_OF_POINTS = 50

def findMinMax(p):
    hull = ConvexHull(p)
    # Extract the points forming the convex hull
    hullpoints = p[hull.vertices,:]
    hdist = cdist(hullpoints, hullpoints, metric='euclidean')

    # Get the min/max points
    maxpair = np.unravel_index(hdist.argmax(), hdist.shape)
    i,j = np.where(hdist==np.min(hdist[np.nonzero(hdist)]))

    pairPoints = np.array([(np.linalg.norm(hullpoints[i][0] -
→hullpoints[i][1])),(np.linalg.norm(hullpoints[maxpair[0]] -
→hullpoints[maxpair[1]]))])
    logDiff = np.log10((pairPoints[1]-pairPoints[0])/pairPoints[0])
    print(logDiff)
```

```

    listOfLogDiffs.append(logDiff)

## Plotting the log results
def plotGraph():
    x = np.arange(2,MAX_ITERATIONS)
    y = listOfLogDiffs
    plt.title("Curse of Dimensionality")
    plt.xlabel("Number of Dimensions")
    plt.ylabel("Log10 * ((Max-Min)/Min)")
    plt.plot(x,y)
    plt.show()

listOfLogDiffs = []

# Run the program
for x in progressbar(range(2,MAX_ITERATIONS), redirect_stdout=True):
    print(f"({x}/{MAX_ITERATIONS}): ", end='')
    findMinMax(np.random.rand(NUMBER_OF_POINTS,x))

plotGraph()

```

I could only generate a small number of dimensions, as running a large number of points with a high dimensionality took inhibitably long. However, the effect is shown.

```


[3]: from IPython.display import Image
      Image(filename = "curse.png", width=400, height=400)

```

```

[3]:

```



## 2 P1-2. The Iris Dataset ([https://en.wikipedia.org/wiki/Iris\\_flower\\_data\\_set](https://en.wikipedia.org/wiki/Iris_flower_data_set))

(a) Data Visualization. Duplicate the following figure using scatter plot.

(b) Find the best discretization for the petal length and the petal width that can best separate the Iris data and plot a figure similar to the figure in slide 54 in Chapter 2. For each flower type, list in a table how many data samples are correctly separated and how many are not correctly separated.

```
[8]: import matplotlib.pyplot as plt
from matplotlib.patches import Rectangle
import numpy as np
from sklearn import datasets
from sklearn.cluster import KMeans

NUMBER_PLOTS_SQ = 4

# import the data
iris = datasets.load_iris()
x = iris.data
y = iris.target
```

```

MarkerList = ['s', 'o', 'd']
TitleList = ["Sepal Length", "Sepal Width", "Petal Length", "Petal Width"]

# Create Figure 1
fig, axs = plt.subplots(NUMBER_PLOTS_SQ, NUMBER_PLOTS_SQ)
fig.suptitle("Iris Data (blue=setosa, red=versicolor, green=virginica)")
# Create Figure 2
fig2, axs2 = plt.subplots()

# Iris 16 plots
def generatePlots():
    for v in range(NUMBER_PLOTS_SQ):
        for h in range(NUMBER_PLOTS_SQ):
            if (v != h):
                axs[v][h].scatter(x[:, h], x[:, v], s=7, c=y, cmap=plt.cm.brg,
→edgecolor='k', linewidth=0.5)
            else:
                axs[v][h].text(0.5, 0.5, TitleList[v], horizontalalignment='center',
→verticalalignment='center', clip_on=True)
                axs[v][h].xaxis.set_visible(False)
                axs[v][h].yaxis.set_visible(False)

def generateDiscretization():
    # Scatter two variables
    IrisLabels = ['Setosa', 'Versicolor', 'Virginica']
    for i in range(np.prod(y.shape)):
        axs2.scatter(x[i, 2], x[i, 3], marker=MarkerList[int(i/50)], c='k', s=10.0)
    #axs2.set_label(['Setosa', 'Versicolor', 'Virginica'])
    for l in range(len(IrisLabels)):
        axs2.scatter([], [], color='k', label=IrisLabels[l], marker=MarkerList[l])
    axs2.legend()

    # Delete unnecessary variables
    ClusterArray = np.delete(x, [0,1], 1)

    # Generate clusters
    axs2.set_xlabel("Petal Length (cm)")
    axs2.set_ylabel("Petal Width (cm)")
    km = KMeans(n_clusters=3)
    km.fit(ClusterArray)

    # Find centroids and plot them
    km_cntr = km.cluster_centers_
    axs2.scatter(km_cntr[:, 0], km_cntr[:, 1], c='red', s=15.0)

    # Create rectangles around clusters

```

```

CentroidRectangleLengths = np.empty((0,2))
for i in range(0,101,50):
    try:
        val_min_x, val_max_x = np.min(np.delete(ClusterArray[i:(i+50)], 1, 1),
        ↪axis=0), np.max(np.delete(ClusterArray[i:(i+50)], 1, 1), axis=0)
        val_min_y, val_max_y = np.min(np.delete(ClusterArray[i:(i+50)], 0, 1),
        ↪axis=0), np.max(np.delete(ClusterArray[i:(i+50)], 0, 1), axis=0)
        x_len, y_len = val_max_x-val_min_x, val_max_y-val_min_y
        CentroidRectangleLengths = np.append(CentroidRectangleLengths, [np.
        ↪concatenate((x_len, y_len))], axis=0)
    except ValueError:
        pass

# Plot the rectangles
index=0
sortedCenters = np.sort(km_cntr, axis=0)
for c in (sortedCenters):
    width, height = CentroidRectangleLengths[index][0],
    ↪CentroidRectangleLengths[index][1]
    axs2.add_patch(Rectangle(
        xy=(c[0]-width/2, c[1]-height/2), width=width, height=height,
        ↪linewidth=1, color='black', fill=False))
    index += 1

generatePlots() #(a)
generateDiscretization() #(b)
plt.show()

```

The clusters were plotted naively as each type of flower has 50 points. So, each marker was spaced out by 50. In a real world scenario, I would need to set the markers based on the cluster results, not evenly spaced arrays.

Flower types that were correctly spaced, if going by markers, are 50/50 for each group. However, the rectangles (which were also naively plotted by finding the bounding box of the cluster and placing it on top of the centroid) are not as correct.

Flower	Correct	Incorrect
Setosa	48	2
Versicolor	49	1
Virginica	48	2

Not bad for a naive approach. Although, some of the boxes do overlap.

### 3 P1-3. Principal Component Analysis for The Iris Dataset

(a) Use the Iris dataset and plot all the samples in a figure using Sepal Length and Sepal Width, i.e., `xlabel('Sepal length')` and `ylabel('Sepal width')`.

(b) The Iris dataset has 4 attributes (sepal length, sepal width, petal length, and petal width). Use PCA to reduce the dimension of the dataset from 4 to 2. Plot all the samples after the dimensionality reduction in a 2D figure. Compare this figure with the figure in (a) and discuss whether you can better separate the data samples after the dimensionality reduction.

```
[10]: import matplotlib.pyplot as plt
from matplotlib.patches import Rectangle
import numpy as np
from sklearn.decomposition import PCA
from sklearn import datasets

# import the data
iris = datasets.load_iris()
x = iris.data
y = iris.target
IrisLabels = ['Versicolor', 'Setosa', 'Virginica']
PlotColors = ['r', 'b', 'g']

fig, axs = plt.subplots()
fig2, axs2 = plt.subplots()

# No decomposition
def generateBasePlot():
    axs.scatter(x[:, 0], x[:, 1], c=y, cmap=plt.cm.brg)
    axs.set_xlabel("Sepal Length (cm)")
    axs.set_ylabel("Sepal width (cm)")

# Decomposition
def generatePCAPlot():
    pca_iris = PCA(3)
    pca_iris.fit(x)
    decomp_x = pca_iris.transform(x)
    axs2.scatter(decomp_x[:,0], decomp_x[:,1], c=y, cmap=plt.cm.brg)
    axs2.set_xlabel("Sepal Length (cm)")
    axs2.set_ylabel("Sepal width (cm)")

generateBasePlot()
generatePCAPlot()

leg = []
for l in range(len(IrisLabels)):
    leg.append(Rectangle((0,0),1,1,fc=PlotColors[l]))
```

```
axs.legend(leg, IrisLabels)
axs2.legend(leg, IrisLabels)

plt.show()
```

It is much easier to separate the data samples after dimensionality reduction. Vericolor and Virginica flower samples are still relatively close, but there is a distinct separation between them and Setosa flowers.