

12. Build an online Book Store project using MongoDB, Express.js, React, Node.js (MERN)

Server/app.js

```
* To run this file:
* 1. Ensure you have Node.js installed.
* 2. Create a new directory for your project.
* 3. Save this code as app.js'.
* 4. Run 'npm init -y' in your terminal.
* 5. Run 'npm install express mongoose dotenv'.
* 6. Create a file named '.env' and add your connection string:
*
MONGO_URI="mongodb+srv://<username>:<password>@<cluster>.mongodb.net/<database
Name>" or "mongodb://127.0.0.1:27017/BOOKSTORE
7. Run 'node app.js'.
*
* API Endpoints:
* - GET /api/books          -> Get all books
* - GET /api/books/:id      -> Get a single book by ID
* - POST /api/books         -> Create a new book (requires JSON body)
* - PUT /api/books/:id      -> Update a book by ID (requires JSON body)
* - DELETE /api/books/:id   -> Delete a book by ID
*/

const express = require('express');
const mongoose = require('mongoose');
const dotenv = require('dotenv');
const cors = require('cors');

// Load environment variables from .env file
dotenv.config();
const app = express();
app.use(cors());
const PORT = process.env.PORT || 5000;

// Middleware for parsing JSON body in requests
app.use(express.json());

// Simple welcome route
app.get('/', (req, res) => {
  res.send('Welcome to the Book Store API. Access book data via
/api/books');
});
// -----
// 2. MONGOOSE SCHEMA AND MODEL
// -----
```

```

// Define the Book Schema
const BookSchema = new mongoose.Schema({
  title: {
    type: String,
    required: [true, 'Book title is required'],
    trim: true,
  },
  author: {
    type: String,
    required: [true, 'Author name is required'],
    trim: true,
  },
  isbn: {
    type: String,
    required: [true, 'ISBN is required'],
    unique: true,
    trim: true,
  },
  price: {
    type: Number,
    required: [true, 'Price is required'],
    min: [0, 'Price cannot be negative'],
  },
  description: {
    type: String,
    required: false,
    default: 'No description provided.',
  },
  publishedDate: {
    type: Date,
    default: Date.now,
  },
  // Optional field for stock tracking
  stock: {
    type: Number,
    default: 1,
    min: [0, 'Stock cannot be negative'],
  }
}, {
  timestamps: true // Adds createdAt and updatedAt fields
});

// Create the Book Model
const Book = mongoose.model('Book', BookSchema);
// -----
// 3. MONGODB CONNECTION
// -----

```

```

const MONGO_URI = process.env.MONGO_URI;

if (!MONGO_URI) {
  console.error("FATAL ERROR: MONGO_URI not defined. Please create a .env
file.");
  process.exit(1);
}

const connectDB = async () => {
  try {
    const conn = await mongoose.connect(MONGO_URI, {
      // These options are now deprecated/defaulted in Mongoose 6+ but
are included for clarity
      // useNewUrlParser: true,
      // useUnifiedTopology: true,
    });
    console.log(`MongoDB Connected: ${conn.connection.host}`);
  } catch (error) {
    console.error(`Error connecting to MongoDB: ${error.message}`);
    process.exit(1); // Exit process with failure
  }
};

connectDB(); // Connect to the database

// -----
// 4. API ROUTES (CRUD OPERATIONS)
// -----

const bookRouter = express.Router();

// @route   GET /api/books
// @desc    Get all books
bookRouter.get('/', async (req, res) => {
  try {
    const books = await Book.find({}).sort({ title: 1 }); // Find all,
sort by title
    res.status(200).json(books);
  } catch (error) {
    // Handle database or server errors
    res.status(500).json({ message: 'Server error while fetching books',
error: error.message });
  }
});

// @route   GET /api/books/:id
// @desc    Get a single book by ID

```

```

bookRouter.get('/:id', async (req, res) => {
  try {
    const book = await Book.findById(req.params.id);

    if (!book) {
      return res.status(404).json({ message: 'Book not found' });
    }

    res.status(200).json(book);
  } catch (error) {
    // Handle invalid ID format or server error
    if (error.kind === 'ObjectId') {
      return res.status(400).json({ message: 'Invalid Book ID format'
});
    }
    res.status(500).json({ message: 'Server error while fetching book',
error: error.message });
  }
});

// @route   POST /api/books
// @desc    Create a new book
bookRouter.post('/', async (req, res) => {
  // req.body contains the JSON data for the new book
  try {
    const newBook = new Book(req.body);
    const book = await newBook.save();
    res.status(201).json(book); // 201 Created
  } catch (error) {
    // Handle validation errors (e.g., missing title, duplicate ISBN)
    if (error.name === 'ValidationError') {
      return res.status(400).json({ message: 'Validation failed',
errors: error.errors });
    }
    if (error.code === 11000) { // MongoDB duplicate key error (for unique
ISBN)
      return res.status(400).json({ message: 'ISBN already exists',
fields: error.keyPattern });
    }
    res.status(500).json({ message: 'Server error while creating book',
error: error.message });
  }
});

// @route   PUT /api/books/:id
// @desc    Update a book by ID

bookRouter.put('/:id', async (req, res) => {

```

```

    try {
      // Set 'new: true' to return the updated document
      // Set 'runValidators: true' to re-run schema validators on update
      const book = await Book.findByIdAndUpdate(
        req.params.id,
        req.body,
        { new: true, runValidators: true }
      );

      if (!book) {
        return res.status(404).json({ message: 'Book not found for update'
});
      }

      res.status(200).json(book);
    } catch (error) {
      if (error.name === 'ValidationError') {
        return res.status(400).json({ message: 'Validation failed',
errors: error.errors });
      }
      if (error.kind === 'ObjectId') {
        return res.status(400).json({ message: 'Invalid Book ID format'
});
      }
      res.status(500).json({ message: 'Server error while updating book',
error: error.message });
    }
  });

// @route   DELETE /api/books/:id
// @desc    Delete a book by ID
bookRouter.delete('/:id', async (req, res) => {
  try {
    const book = await Book.findByIdAndDelete(req.params.id);

    if (!book) {
      return res.status(404).json({ message: 'Book not found for
deletion' });
    }

    res.status(200).json({ message: 'Book successfully deleted',
deletedBook: book });
  } catch (error) {
    if (error.kind === 'ObjectId') {
      return res.status(400).json({ message: 'Invalid Book ID format'
});
    }
  }
}

```

```

        res.status(500).json({ message: 'Server error while deleting book',
error: error.message });
    }
});

// Use the book routes under the /api/books path
app.use('/api/books', bookRouter);

// -----
// 5. START SERVER
// -----
app.listen(PORT, () => {
    console.log(`Server running in development mode on port ${PORT}`);
});

```

Server/.env

```
MONGO_URI=mongodb://127.0.0.1:27017/BOOKSTORE
```

Client/src/app.js

```

import React, { useState, useEffect } from 'react';

// The base URL for the backend API
const API_URL = 'http://localhost:5000/api/books';

// Helper function for making API calls with exponential backoff
const fetchWithRetry = async (url, options, retries = 3) => {
    for (let i = 0; i < retries; i++) {
        try {
            const response = await fetch(url, options);
            if (!response.ok) {
                // If the response is not OK, throw an error to be caught
                below
                const errorData = await response.json();
                throw new Error(errorData.message || `HTTP error! Status:
${response.status}`);
            }
            // For DELETE requests, response.json() might throw an error if
the body is empty.
            if (options?.method === 'DELETE' || response.status === 204) {
                return {};
            }
            return await response.json();
        } catch (error) {

```

```

        console.error(`Attempt ${i + 1} failed for ${options?.method ||
'GET'} ${url}:`, error.message);
        if (i === retries - 1) throw error; // Re-throw on last attempt
        // Wait for 2^i seconds before retrying
        await new Promise(resolve => setTimeout(resolve, Math.pow(2, i) *
1000));
    }
}
};

// --- Styles (Inline CSS Object) ---
const styles = {
  container: {
    maxWidth: '900px',
    margin: '0 auto',
    padding: '20px',
    fontFamily: 'Arial, sans-serif',
    backgroundColor: '#f4f7f6',
    minHeight: '100vh',
  },
  header: {
    backgroundColor: '#007bff',
    color: 'white',
    padding: '15px',
    borderRadius: '8px',
    textAlign: 'center',
    marginBottom: '20px',
    boxShadow: '0 4px 8px rgba(0, 0, 0, 0.1)',
  },
  form: {
    backgroundColor: 'white',
    padding: '20px',
    borderRadius: '8px',
    marginBottom: '30px',
    boxShadow: '0 2px 4px rgba(0, 0, 0, 0.05)',
    display: 'grid',
    gridTemplateColumns: 'repeat(3, 1fr)',
    gap: '10px',
  },
  inputGroup: {
    display: 'flex',
    flexDirection: 'column',
  },
  label: {
    marginBottom: '5px',
    fontWeight: 'bold',
    fontSize: '14px',
    color: '#333',
  },

```

```

},
input: {
  padding: '10px',
  border: '1px solid #ccc',
  borderRadius: '4px',
  fontSize: '14px',
},
submitButton: {
  gridColumn: 'span 3',
  padding: '12px',
  backgroundColor: '#28a745',
  color: 'white',
  border: 'none',
  borderRadius: '4px',
  cursor: 'pointer',
  fontWeight: 'bold',
  marginTop: '10px',
},
listTitle: {
  fontSize: '1.5rem',
  color: '#333',
  borderBottom: '2px solid #ccc',
  paddingBottom: '10px',
  marginBottom: '15px',
},
bookList: {
  display: 'grid',
  gridTemplateColumns: 'repeat(auto-fill, minmax(280px, 1fr))',
  gap: '20px',
},
bookCard: {
  backgroundColor: 'white',
  borderLeft: '5px solid #007bff',
  padding: '15px',
  borderRadius: '8px',
  boxShadow: '0 4px 12px rgba(0, 0, 0, 0.1)',
  display: 'flex',
  flexDirection: 'column',
  justifyContent: 'space-between',
},
cardTitle: {
  fontSize: '1.2rem',
  fontWeight: 'bold',
  color: '#007bff',
  marginBottom: '5px',
},
cardAuthor: {
  fontSize: '0.9rem',

```



```

        color: '#6c757d',
        marginBottom: '10px',
    },
    cardDetails: {
        fontSize: '0.85rem',
        color: '#333',
    },
    deleteButton: {
        marginTop: '15px',
        padding: '8px',
        backgroundColor: '#dc3545',
        color: 'white',
        border: 'none',
        borderRadius: '4px',
        cursor: 'pointer',
        alignSelf: 'flex-start',
    },
    error: {
        backgroundColor: '#f8d7da',
        color: '#721c24',
        padding: '10px',
        border: '1px solid #f5c6cb',
        borderRadius: '4px',
        marginBottom: '20px',
        textAlign: 'center',
    },
    loading: {
        textAlign: 'center',
        padding: '20px',
        fontSize: '1.2rem',
        color: '#007bff',
    },
};

/**
 * Main application component for the Book Store UI.
 * Handles state, API calls, and rendering.
 */
export default function App() {
    const [books, setBooks] = useState([]);
    const [loading, setLoading] = useState(false);
    const [error, setError] = useState(null);
    const [newBook, setNewBook] = useState({
        title: '',
        author: '',
        isbn: '',
        price: '', // Use string for input, convert to number on submission
        description: '',
    });

```

```

    });

    // --- API Fetching Functions ---

    // 1. Fetch all books
    const fetchBooks = async () => {
        setLoading(true);
        setError(null);
        try {
            const data = await fetchWithRetry(API_URL);
            setBooks(data);
        } catch (err) {
            setError('Failed to load books. Is the backend server running on port 5000?');
            console.error(err);
        } finally {
            setLoading(false);
        }
    };

    // 2. Add a new book
    const addBook = async (bookData) => {
        setError(null);
        try {
            const data = await fetchWithRetry(API_URL, {
                method: 'POST',
                headers: { 'Content-Type': 'application/json' },
                // Ensure price is converted to a number
                body: JSON.stringify({ ...bookData, price:
Number(bookData.price) }),
            });
            // Update the local state with the new book returned by the server
            setBooks(prevBooks => [...prevBooks, data]);
            // Reset the form after success
            setNewBook({ title: '', author: '', isbn: '', price: '',
description: '' });
        } catch (err) {
            setError(`Failed to add book: ${err.message}`);
            console.error(err);
        }
    };

    // 3. Delete a book
    const deleteBook = async (id) => {
        setError(null);
        try {
            await fetchWithRetry(`${API_URL}/${id}`, {
                method: 'DELETE',

```

```

    });
    // Remove the book from the local state
    setBooks(prevBooks => prevBooks.filter(book => book._id !== id));
  } catch (err) {
    setError(`Failed to delete book: ${err.message}`);
    console.error(err);
  }
};

// Initial load effect
useEffect(() => {
  fetchBooks();
}, []);

// --- Event Handlers ---

const handleInputChange = (e) => {
  const { name, value } = e.target;
  setNewBook(prev => ({
    ...prev,
    [name]: value,
  }));
};

const handleSubmit = (e) => {
  e.preventDefault();
  // Basic validation check
  if (!newBook.title || !newBook.author || !newBook.isbn ||
!newBook.price) {
    setError("Please fill in all required fields (Title, Author, ISBN,
Price).");
    return;
  }
  addBook(newBook);
};

// --- Renderer ---

const BookCard = ({ book }) => (
  <div style={styles.bookCard}>
    <div>
      <div style={styles.cardTitle}>{book.title}</div>
      <div style={styles.cardAuthor}>by {book.author}</div>
      <div style={styles.cardDetails}>
        <p><strong>ISBN:</strong> {book.isbn}</p>
        <p><strong>Price:</strong> ${book.price.toFixed(2)}</p>
        <p><strong>Stock:</strong> {book.stock}</p>
        <p><em>{book.description}</em></p>

```

```

        </div>
      </div>
      <button
        style={styles.deleteButton}
        onClick={() => deleteBook(book._id)}
      >
        Delete
      </button>
    </div>
  );

  return (
    <div style={styles.container}>
      <header style={styles.header}>
        <h1>Book Store</h1>
        <p>Add and manage books via the Node.js/Express backend
API.</p>
      </header>

      { /* Error Message Display */ }
      {error && <div style={styles.error}>{error}</div>}

      { /* Add New Book Form */ }
      <h2 style={styles.listTitle}>Add New Book</h2>
      <form onSubmit={handleSubmit} style={styles.form}>
        <div style={styles.inputGroup}>
          <label style={styles.label} htmlFor="title">Title*</label>
          <input
            style={styles.input}
            type="text"
            id="title"
            name="title"
            value={newBook.title}
            onChange={handleInputChange}
            required
          />
        </div>
        <div style={styles.inputGroup}>
          <label style={styles.label}
htmlFor="author">Author*</label>
          <input
            style={styles.input}
            type="text"
            id="author"
            name="author"
            value={newBook.author}
            onChange={handleInputChange}
            required

```

```

        />
    </div>
    <div style={styles.inputGroup}>
        <label style={styles.label} htmlFor="isbn">ISBN*</label>
        <input
            style={styles.input}
            type="text"
            id="isbn"
            name="isbn"
            value={newBook.isbn}
            onChange={handleInputChange}
            required
        />
    </div>
    <div style={styles.inputGroup}>
        <label style={styles.label} htmlFor="price">Price
($)*</label>
        <input
            style={styles.input}
            type="number"
            id="price"
            name="price"
            value={newBook.price}
            onChange={handleInputChange}
            min="0"
            step="0.01"
            required
        />
    </div>
    <div style={{ ...styles.inputGroup, gridColumn: 'span 2' }}>
        <label style={styles.label}
htmlFor="description">Description</label>
        <input
            style={styles.input}
            type="text"
            id="description"
            name="description"
            value={newBook.description}
            onChange={handleInputChange}
        />
    </div>
    <button type="submit" style={styles.submitButton}>
        Add Book to Inventory
    </button>
</form>

{/* Book List Display */}

```

```

    <h2 style={styles.listTitle}>Current Inventory ({books.length}
Books)</h2>

    {loading && <div style={styles.loading}>Loading books...</div>}

    {!loading && books.length === 0 && !error && (
      <p style={{ textAlign: 'center', color: '#6c757d' }}>No books
found in the inventory. Add one above!</p>
    )}

    <div style={styles.bookList}>
      {books.map(book => (
        <BookCard key={book._id} book={book} />
      ))}
    </div>
  </div>
);
}

```

OUTPUT:

Book Store

Add and manage books via the Node.js/Express backend API.

Add New Book

Title*

Author*

ISBN*

Price (\$)*

Description

Add Book to Inventory

Current Inventory (1 Books)

Ikigai

by Kala

ISBN: fdsfds432

Price: \$250.00

Stock: 1

No description provided.

Delete