

Notes:

1. Output fields marked with * can be passed into the HTTP request header to filter results.
2. Parameters in red are required.
3. The following HTTP methods signify the following:
 - (a) GET is used to retrieve data from the database.
 - (b) POST is used to insert new data into the database.
 - (c) PUT is used to update existing data in the database.
 - (d) DELETE is used to remove existing data from the database.

◇ **GET /entities/{entity}**

Description	Gets an entity from the Firebase database. This finds the external Firebase ID associated with the specified entity PK, and then uses the external Firebase ID to get all of the entity's credentials from Firebase.		
HTTP Header Params	None.		
HTTP Body Params	None.		
Output	FIREBASE OUTPUT	Refer to the fields stored in Firebase for details on what this route returns.	

◇ **GET /entity/{entity}/events/**

Description	Gets all events that a specified entity is either the owner of or a guest of, and the roles they have for those events. Multiple records will be returned for the same event if the entity has more than one role for that event.		
HTTP Header Params	None.		
HTTP Body Params	None.		
Output	*entity	The PK of the guest.	
	*estimated_budget	The budget that the guest should dedicate to this role.	
	*event	The PK of the event.	
	*event_entity_role	Record PK.	
	*role	The PK of the role.	
	*role_name	The name of the role.	
	event_name	The name of the event.	

◇ **GET /event/{event}/guests/**

Description	Returns all guests attending a specific event and their roles. The result set does NOT include the owner of the event. Multiple records will be returned for the same guest if they have more than one role.	
HTTP Header Params	None.	
HTTP Body Params	None.	
Output	*entity	The PK of the guest.
	*estimated.budget	The budget that the guest should dedicate to this role.
	*event	The PK of the event.
	*event_entity_role	Record PK.
	*role	The PK of the role.
	*role_name	The name of the role.
	event_name	The name of the event.

◇ GET /event/{event}/guests/{guest}

Description	Returns a specific guest attending a specific event and their roles. No results will be returned if the specified guest is the owner. Multiple records will be returned for the same guest if they have more than one role. This is identical to calling GET /event/{event}/guests/?entity=guest.	
HTTP Header Params	None.	
HTTP Body Params	None.	
Output	*entity	The PK of the guest.
	*event	The PK of the event.
	*event_entity_role	Record PK.
	*role	The PK of the role.
	*role_name	The name of the role.
	event_name	The name of the event.

◇ GET /event/{event}/owner/

Description	Gets the owner of a specific event and their roles. Multiple records will be returned for the owner if they have more than one role.	
HTTP Header Params	None.	
HTTP Body Params	None.	
Output	*entity	The PK of the guest.
	*estimated.budget	The budget that the guest should dedicate to this role.
	*event	The PK of the event.
	*event_entity_role	Record PK.
	*role	The PK of the role.
	*role_name	The name of the role.
	event_name	The name of the event.

◇ GET /event/{event}/roles/

Description	Returns all roles needed for a specific event.	
HTTP Header Params	None.	
HTTP Body Params	None.	
Output	*description	The event-level description, or default description if an event-level description doesn't exist, of the role needed by the event.
	*estimated_budget	The amount of money that should be dedicated to this role.
	*event_needed_role	Record PK.
	*needed_role	The PK of the role needed by the event.
	*needed_role_name	The name of the role needed by the event.
	*quantity_needed	The number of people needed to perform this role.
	event	The PK of the event.

◇ GET /event/{event}/roles/{role}

Description	Gets a specific needed role for a specific event.	
HTTP Header Params	None.	
HTTP Body Params	None.	
Output	*description	The event-level description, or default description if an event-level description doesn't exist, of the role needed by the event.
	*estimated_budget	The amount of money that should be dedicated to this role.
	*quantity_needed	The number of people needed to perform this role.
	event	The PK of the event.
	event_needed_role	Record PK.
	needed_role	The PK of the role needed by the event.
	needed_role_name	The name of the role needed by the event.

◇ GET /events/

Description	Gets all events.	
HTTP Header Params	None.	
HTTP Body Params	None.	
Output	*created	The exact moment this event was created.
	*end_time	The date and time the event ends at.
	*event	Record PK.
	*name	The name of the event.
	*start_time	The date and time the event begins at.

◇ GET /events/{event}

Description	Gets a specific event.	
HTTP Header Params	None.	
HTTP Body Params	None.	
Output	created	The exact moment this event was created.
	end_time	The date and time the event ends at.
	event	Record PK.
	name	The name of the event.
	start_time	The date and time the event begins at.

◇ **GET /roles/**

Description	Gets all roles from the database.	
HTTP Header Params	None.	
HTTP Body Params	None.	
Output	*description	The default description of the role.
	*name	The name of the role.
	*role	Record PK.

◇ **GET /roles/{role}**

Description	Gets a specific role from the database. This is equivalent to calling GET /roles/?role={role} .	
HTTP Header Params	None.	
HTTP Body Params	None.	
Output	*description	The default description of the role.
	*name	The name of the role.
	*role	Record PK.

◇ **POST /entities/**

Description	Adds a new entity.	
HTTP Header Params	None.	
HTTP Body Params	ext.firebase_id	The external Firebase ID corresponding to the newly-created entity.
Output	entity	The PK of the entity that was just created.

◇ **POST /event/{event}/entities/{entity}/roles/**

Description	Adds a role to a specific entity attending a specific event. Note that the specified entity can be either the owner or a guest. Additionally, because this creates a new event_entity_role record, if an entity is not already associated with an event, calling this route will associate them with the event.		
HTTP Header Params	None.		
HTTP Body Params	estimated.budget	The budget that the entity should allocate to performing the role.	
	role	The role that should be given to the specified entity attending the specified event.	
Output	event_entity_role	The PK of the record that was created.	

◇ **POST** /event/{event}/guests/

Description	Adds a guest to a specific event. This creates a new event_entity_role record with the specific event, specified entity, and the Guest role.		
HTTP Header Params	None.		
HTTP Body Params	entity	The PK of the entity who should be added to the specified event as a guest.	
Output	event_entity_role	The PK of the record that was created.	

◇ **POST** /event/{event}/roles/

Description	Adds a needed role to a specific event.		
HTTP Header Params	None.		
HTTP Body Params	description	The event-level description of the role needed by this event.	
	estimated.budget	The amount of money that should be dedicated to this role.	
	needed.role	The PK of the role needed by the event.	
	quantity_needed	The number of people needed to perform this role.	
Output	event_needed_role	The PK of the record that was created.	

◇ **POST** /events/

Description	Creates an event.		
HTTP Header Params	None.		
HTTP Body Params	end_time	The date and time the event ends at.	
	name	The name of the event.	
	start_time	The date and time the event begins at.	
Output	event	The PK of the event that was created.	

◇ **POST** /roles/

Description	Adds a new role to the database. This does not add a role to any specific event, nor does it add a role to any specific entity.		
HTTP Header Params	None.		
HTTP Body Params	description	The default description of the role to create.	
	name	The name of the role to create.	
Output	role	The PK of the role that was created.	

◇ **PUT /event/{event}/entities/{entity}/roles/{role}**

Description	Updates the role information for a specific entity at a specific event. Note that the entity may be either the owner or a guest of the event.		
HTTP Header Params	None.		
HTTP Body Params	estimated_budget	The new amount of money that the entity should dedicate to this role.	
Output	event_entity_role	The PK of the record that was updated.	

◇ **PUT /event/{event}/roles/{role}**

Description	Updates a specific needed role for a specific event.		
HTTP Header Params	None.		
HTTP Body Params	description	The new event-level description of the role needed by this event.	
	estimated_budget	The new amount of money that should be dedicated to this role.	
	quantity_needed	The new number of people needed to perform this role.	
Output	event_needed_role	The PK of the recorded that was updated.	

◇ **PUT /events/{event}**

Description	Updates an event.		
HTTP Header Params	None.		
HTTP Body Params	end_time	The date and time the event ends at.	
	name	The name of the event.	
	start_time	The date and time the event begins at.	
Output	event	The PK of the event that was updated.	

◇ **PUT /roles/{role}**

Description	Updates an existing role in the database.		
HTTP Header Params	None.		
HTTP Body Params	description	The new default description the role should have.	
	name	The new name the role should have.	
Output	role	The PK of the role that was updated.	

◇ **DELETE** /event/{event}/guests/{guest}

Description	Completely removes a specified guest from an event. This removes every <code>event_entity_role</code> record that has the specified guest as the entity.		
HTTP Header Params	None.		
HTTP Body Params	None.		
Output	<code>event_entity_role</code>	The PK of the record that was deleted.	

◇ **DELETE** /event/{event}/roles/{role}

Description	Removes a needed role from an event.		
HTTP Header Params	None.		
HTTP Body Params	None.		
Output	<code>event_needed_role</code>	The PK of the record that was deleted.	

◇ **DELETE** /events/{event}

Description	Deletes an event.		
HTTP Header Params	None.		
HTTP Body Params	None.		
Output	<code>event</code>	The PK of the event that was deleted.	

◇ **DELETE** /roles/{role}

Description	Deletes an existing role from the database.		
HTTP Header Params	None.		
HTTP Body Params	None.		
Output	<code>role</code>	The PK of the role that was deleted.	