

C++ Friend function

If a function is defined as a friend function in C++, then the protected and private data of a class can be accessed using the function.

By using the keyword friend compiler knows the given function is a friend function.

For accessing the data, the declaration of a friend function should be done inside the body of a class starting with the keyword friend.

Declaration of friend function in C++

```
class class_name
{
    friend data_type function_name(argument/s);    // syntax of friend function.
};
```

In the above declaration, the friend function is preceded by the keyword friend. The function can be defined anywhere in the program like a normal C++ function. The function definition does not use either the keyword **friend** or **scope resolution operator**.



Characteristics of a Friend function:

- The function is not in the scope of the class to which it has been declared as a friend.
- It cannot be called using the object as it is not in the scope of that class.
- It can be invoked like a normal function without using the object.
- It cannot access the member names directly and has to use an object name and dot membership operator with the member name.
- It can be declared either in the private or the public part.

C++ friend function Example

Let's see the simple example of C++ friend function used to print the length of a box.

```
#include <iostream>
using namespace std;
class Box
{
    private:
        int length;
```

```
public:
    Box(): length(0) { }
    friend int printLength(Box); //friend function
};
int printLength(Box b)
{
    b.length += 10;
    return b.length;
}
int main()
{
    Box b;
    cout<<"Length of box: "<< printLength(b)<<endl;
    return 0;
}
```

Output:

Length of box: 10

Let's see a simple example when the function is friendly to two classes.



```
#include <iostream>
using namespace std;
class B;      // forward declarartion.
class A
{
    int x;
    public:
    void setdata(int i)
    {
        x=i;
    }
    friend void min(A,B);      // friend function.
};
class B
{
    int y;
    public:
    void setdata(int i)
    {
        y=i;
    }
}
```

```
}  
friend void min(A,B);           // friend function  
};  
void min(A a,B b)  
{  
    if(a.x<=b.y)  
        std::cout << a.x << std::endl;  
    else  
        std::cout << b.y << std::endl;  
}  
int main()  
{  
    A a;  
    B b;  
    a.setdata(10);  
    b.setdata(20);  
    min(a,b);  
    return 0;  
}
```

Output:

10

In the above example, min() function is friendly to two classes, i.e., the min() function can access the private members of both the classes A and B.

C++ Friend class

A friend class can access both private and protected members of the class in which it has been declared as friend.

Let's see a simple example of a friend class.

```
#include <iostream>  
  
using namespace std;  
  
class A  
{  
    int x =5;  
    friend class B;           // friend class.  
};
```



```
class B
{
    public:
        void display(A &a)
        {
            cout<<"value of x is : "<<a.x;
        }
};

int main()
{
    A a;
    B b;
    b.display(a);
    return 0;
}
```

Output:

```
value of x is : 5
```

In the above example, class B is declared as a friend inside the class A. Therefore, B is a friend of class A. Class B can access the private members of class A.

[< prev](#)[next >](#)

Please Share



Join Javatpoint Test Series

Placement	AMCAT	Bank	GATE
Papers	eLitmas	PO/Clerk	NEET
TCS	Java	UPSSSC	CAT
HCL	Python	Government	Railway
Infosys	C	Exams	CTET
IBM	Programming	SSC	IIT JEE
Accenture	Networking	Civil Services	