Bai 1:
PS D:\LabTerminal> pwd
PS D:\LabTerminal> mkdir logs, reports, backup
PS D:\LabTerminal> mkdir "Bai Tap IT01"
PS D:\LabTerminal> cd "Bai Tap IT01"
PS D:\LabTerminal\Bai Tap IT01> cd..
PS D:\LabTerminal> mv access.log logs
PS D:\LabTerminal> cp logs/access.log backup/access_backup.log
PS D:\LabTerminal> New-Item .\reports\ghi_chu.txt -ItemType File
PS D:\LabTerminal> Rename-Item .\reports\ghi_chu.txt notes.txt
PS D:\LabTerminal> ls -Recurse
PS D:\LabTerminal> rm .\reports\notes.txt -WhatIf
PS D:\LabTerminal> rm '.\Bai Tap IT01\'

Bai2:
PS D:\LabTerminal> Get-Content .\logs\access.log
PS D:\LabTerminal> Get-Content -TotalCount 3 .\logs\access.log
PS D:\LabTerminal> Get-Content -Tail 4 .\logs\access.log
PS D:\LabTerminal> (Get-Content .\logs\access.log).Count

Bai3:
PS D:\LabTerminal> Get-Content .\logs\access.log | Select-String "Error"
PS D:\LabTerminal> (Get-Content .\logs\access.log | Select-String "404").count
PS D:\LabTerminal> Get-Content .\logs\access.log | Select-String "500" >
.\logs\back_up_500.log
PS D:\LabTerminal> (Get-Content .\logs\access.log | Select-String "500").count
Wxrdie
Bai 4:
b1:
"A" > t.txt —> trong file se co 1 dong A
"B" >> t.txt —> trong file se co them 1 dong B duoi dong A
"C" > t.txt —-> trong file se co 1 dong C
"D" >> t.txt —> trong file se co them 1 dong D duoi dong A
Cuoi cung chi hien:
C
D
b2:
Get-Content logs\access.log | Select-String "404" > r.txt —> trong file se co 1 dong 3
Get-Content logs\access.log | Select-String "500" >> r.txt —> trong file se co them dong 2 duoi dong 3
Cuoi cung file hien:
2
3
Bai 5
Tac gia: HOANG XUAN NAM
Ngay tao: 10/14/2026
Write-Host "Dang loc log..."
"=== BAO CAO LOI ===" > report.txt

```
Get-Content HOAN_THIEN | Select-String "HOAN_THIEN" >> HOAN_THIEN
Write-Host "Hoan thanh!"
```