:- Arrays :

→ Data Structure :

Store Data in an organized Manner.



→ Arrays :

- Linear Data Structure
- Contigous fashion Data Store
  - Adjacent Memory location.
- Homogenious
  - L> Store same type of Data.

Ex :-

int 4 bytes

Store Roll No. of 4 Students.



→ **Declaration of Array :-**

```
int arr[] = new int [4]
```

- int → Data Type
- arr → Name
- new int [4] → Object create, Space of arr Array.

```
arr [ ]
```

- arr → Name of Array
- [ ] → Sign of Array.

arr[4] =	5	1	2	4
index →	0	1	2	3
Memory →	3000	3004	3008	3012

- Index will be mapped to Memory.

Operation 1 → Accessing of Array

```
int el = arr[2]
Print (el);
```

Output will be 2.

→ Formula to find location in array

index → i

Starting Memory location → m

Data Size → 8.

arr[2]

→ 3000 + 2 × 4

[m + i × s]

→ Where is an array store

: Heap

→ Insert array data

```
{
  arr[i+1] = arr[i]
    i--;
}
  arr[pos] = 5;
```

Pos 1 → store 5

arr[] = 2, 4, 6, 0, 0 (i, i+1)

0 1 2 3 4

m-2 m-1

→ Delete an element in array

arr[3] = arr[i+1];

i → m-2.

arr[] = 2, 4, 8, 12 (i, i+1)

0

→ Dynamic Array

- Size is not fixed
- Sub can vary.
- Can increase the size of an Array.

- Size
- Capacity :
  Store max element.
  S/L → How many elements are there.

- How to increase capacity.
  → 10 — 11th
  → Old capacity + Half of old cap.

Formula. → nc = OC + OC/2.

Can be changed on new versions of Java.

✕ If the memory is not free then this will throws an error called.

→ Memory Out of Space
(M.O.S.)

→ Multi Dimensional Array (MDA) - 2D Array.

(2D) → Array inside an array.



→ Represent Multi Dimensional Array.

2D array `int arr[][] = new int[5][2];`

- Level 1 array will be of 5 size
- Level 2 array will be of 2 size.