1.6 Turbidity and TSS sensor

Features

- ✓ IR optical sensor without optical fibre
- ✓ Ranges : 0 to 4000 NTU or 0 to 4500 mg/L
- ✓ Robust and waterproof (IP68)
- ✓ Ultra low-power consumption
- ✓ ISO 7027 compliance (Nephelometry)

Applications

- ✓ Urban wastewater treatment (inlet / outlet)
- ✓ Sanitation network
- ✓ Industrial effluent treatment
- ✓ Surface water monitoring
- ✓ Drinking water

Description

The measuring principle is based on IR nephelometry / 880 nm (ISO 7027). The sensor can be calibrated with a formazine standard solution.

The NTU sensor integrates a low-cost optical technology, with a very few maintenance and no consumables.

DATALINK INSTRUMENTS DTLI
36A rue des Vingt Toises
F-38950 Saint Martin Le Vinoux
France

Tel. +33 (0) 4 76 94 90 83
Fax. +33 (0) 4 76 94 18 14

Specifications

Dissolved oxygen sensor	Specifications	
Principle	Diffusion IR at 90°	
Measuring ranges	0 to 4000 NTU in 5 ranges: ✓ 0 – 50 NTU ✓ 0 – 200 NTU ✓ 0 – 1000 NTU ✓ 0 – 4000 NTU ✓ AUTOMATIC	0 to 4500 mg/L Calibration : ✓ Range 0-500 mg/L according to NF EN 872 ✓ Range >500 mg/L according to NF T 90 105 2
Resolution	0,01 to 1 NTU - mg/L	
Accuracy	< 5% of the reading	
Working temperature	0°C to 50°C	
Temperature compensation	Via CTN	
Stocking temperature	-10°C to + 60°C	
Maximum refreshing time	< 1 s	
Dimensions	Diameter : 27 mm; Length : 170 mm	
Weight	300 g (sensor + 3 m cable)	
Material	PVC, Quartz, PMMA, Nickel-plated brass	
Pressure	5 bars	
Cable length	Standard 3 m	
Protection	IP68	