



Wilhelm-Kabus-Str. 72
10829 Berlin/Germany

+49 (0) 30 78 95 50 11
+49 (0) 30 78 95 50 12

info@leckel.de
www.leckel.de

SVEN LECKEL
Ingenieurbüro GmbH

PMX INLET FOR SMALL FILTER DEVICE (Kleinfiltergerät - KFG) LVS/LVS6-RV

X = 10 µm – 4,0 µm – 2,5 µm – 1,0 µm

The fractionating PMX IMPACTOR INLET of the Small Filter Device **LVS/LVS6-RV** can be equipped with jet sets (8 pieces each) for **PM10 - PM4,0 - PM2,5 - PM1,0**. The jets are to be stuck into the jet plate and are sealed by O-rings. The jet plate together with the protection roof and the flow plate can be pulled out of the inlet's outer tube (sealed also by O-rings). The flow plate and the protection roof as well are made of polished stainless steel.

All jet sets are available for flow rates of **3,0 m³/h - 2,3 m³/h - 1,0 m³/h**.

The impaction plate is exchangeable and can be prepared (cleaning and greasing) e. g. in the laboratory. Under the impaction plate is a deep well for condensation or penetrated rain.

The inlet's filter holder is directly attached to the pre-impactor. The filters are contained in cassettes; which are to be inserted into the filter holder. Two filter cassettes capable to take in filters with diameters of **47 mm respectively 50 mm** (alternatively) belong to each inlet.

The filter holder has a thread piece (M12x1) made of brass at its bottom side. The suction pipe (stainless steel) of the device or a hose nipple for the external set-up of the inlet can be gas tightly screwed in this thread piece.



**PM10 and PM2,5 STANDARD INLET
with filter holder
according to CEN EN 12341**