



Wilhelm-Kabus-Str. 72
10829 Berlin/Germany

+49 (0) 30 78 95 50 11
+49 (0) 30 78 95 50 12

info@leckel.de
www.leckel.de

SVEN LECKEL
Ingenieurbüro GmbH

PMX INLET FOR SEQUENTIAL SAMPLER SEQ47/50

X = 10 µm – 4,0 µm – 2,5 µm – 1,0 µm

The fractionating PMX impactor inlet of the sequential sampler **SEQ47/50** can be equipped with jet sets (8 pieces, each) for **PM10 – PM 4,0 - PM2,5 - PM1,0**. The jets are to be stuck into the jet plate and are sealed by O-rings. The jet plate together with the protection roof and the flow plate can be pulled out of the inlet's outer tube (sealing also by O-rings).

All jet sets are available for flow rates of **3,0 m³/h - 2,3m³/h - 1,0 m³/h**.

The impaction plate is exchangeable and can be prepared (cleaning and greasing) e. g. in the laboratory. Under the impaction plate is a deep well for condensation or penetrated rain. Furthermore, the inlet can be equipped with a **drainage bottle** according to the requirements of **CEN EN 12341**.



PM10 and PM2,5 STANDARD-REFERENCE-INLET (with sheath air) according to CEN EN 12341