



Wilhelm-Kabus-Str. 72 ☎ +49 (0) 30 78 95 50 11 ✉ info@leckel.de
10829 Berlin/Germany 📠 +49 (0) 30 78 95 50 12 www.leckel.de

SVEN LECKEL
Ingenieurbüro GmbH

PMX INLET FOR INSTRUMENTS IN STATIONS

X = 10µm – 4,0 µm – 2,5 µm – 1,0 µm

The fractionating PMX-INLET for instruments, which are built in e. g. 19" racks in cabins, can be equipped with jet sets (8 pieces, each) for **PM10 - PM4,0 - PM2,5 - PM1,0**. The jets are to be stuck into the jet plate and are sealed by O-rings. The jet plate together with the protection roof and the flow plate can be pulled out of the inlet's outer tube (sealing also by O-rings). The flow plate and the protection roof as well are made of polished stainless steel.

All jets are available for flow rates of **3,0 m³/h - 2,3 m³/h - 1,0 m³/h**.

The impaction plate is exchangeable and can be prepared (cleaning and greasing) e. g. in the laboratory. Under the impaction plate is a deep well for condensation or penetrated rain. Furthermore, the inlet is equipped with a **drainage bottle**.

The inlet's adapter with stick-in connection can be designed for optional diameters of the instrument's sampling tube (e. g. 16 mm, up to max. 1,246" / US inlets).

The equivalence of the **PM10 INLET for the flow rate of 1,0 m³/h** to the PM10 inlet for 1,0 m³/h standardized by the US EPA has been proved in a thorough field study (CNR-IIA and JRC Ispra: PM10 FIELD STUDIES, BERLIN APRIL-NOVEMBER 1999. Ed. by CNR-Instituto Sull' Inquinamento Atmosferico, Via Salaria KM 29. 300 CP10, 00016-Monterotondo Stazione (Roma), Italy).



PMX INLET with drainage bottle and adapter for pipe connections

Subject to alterations Ed 03-16