



COMPANY PROFILE

HONGKONG BONAD TECHNOLOGY LIMITED, SHENZHEN BONAD INSTRUMENT CO.,LTD, is a high-tech company in Hong Kong, producing all kinds of precision instrument and equipment. We specialize in the high quality of: Electronic safety tester, Accessibility test probe and test finger, Laboratory test equipment, Test Chamber, Environmental test Equipment, Freezing test package, all kinds of Gauge and Sensor and so on.

We have gathered lots of experienced researchers and administrators on this electric products. All products manufactured are strictly in accordance with various EN, IEC, CE, UL, VDE, VS, JIS, ISO, CEE, BS, FMV, GB and other similar international standards.

Our business partners are from all around the world, Europe, Asia, North America, South America, Africa, Oceania and other countries and regions. We are always one of the most popular precision instrument and equipment manufacturers and partners in the whole world because of our best service and high quality product!

Our creed QCDS(High quality, Cost-efficiency, Delivery-in-time, Best-service) are the bases of our company. We always want our customers get the best product and service from us.

We have established stable cooperation relationships with many famous international laboratory and company, such as: PTL, WAZAU, TUV, SGS, CAS, UL, MUNRO, GTE, OPHIR, FEMTO, LG. We also welcome OEM and ODM requirement, distribution and other cooperation in business.

HONG KONG BONAD TECHNOLOGY LIMITED

301,hongdu building,45 district,Bao'an,Shenzhen,518101,China

Tel:+86 0755 66608016

Fax:+86-0755 28721200

Web. : http://szbonad.com/index_en.html

Contact: Alice Lee

Mail: Alice@szbonad.com

Phone/whatsapp:+86 18825130384

skype:shenzhen.bonad

CONTENT

Company profile.....	
Waterproof test equipment.....	1-6
IPX1 IPX2.....	1-2
IPX3 IPX4.....	2-3
IPX5 IPX6.....	3
IPX7/ IPX8.....	4-5
IPX3X4 Spray nozzle/ IPX5/X6 Jet nozzle.....	6
Flammability test equipment.....	7-9
Glow wire test equipment.....	7
Needle flame test equipment.....	7
Tracking index test equipment.....	8
Horizontal vertical flame tester.....	9
Car Inner Ornament combustion test machine.....	9
Environment test equipment.....	10-23
Salt spray test chamber.....	10
Dust test chamber.....	10
Ozone aging test chamber.....	11
Xenon lamp climatic test chamber	12
UV aging test chamber	13
high and low temperature test chamber.....	14
Fast temperature change chamber.....	14
Low air pressure test chamber.....	15
Vacuum drying oven	15
Rain test chamber.....	16
Solar radiation test chamber.....	17
Blast oven	18

Nitrogen vacuum oven	19
High temperature and pressure cooking device	20
Walk-in environmental test chamber	21
Motor transport simulation shake table	22
Three intergrated chamber	23
Safety test equipment.....	24-28
Sharp edge / Sharp point tester.....	24
Inclined plane device.....	24
Test Corner.....	25
Drop ball impact strength tester.....	25
Dielectric strength tester.....	26
Socket-outlet torque balance tester.....	26
Tumbling barrel drop tester.....	27
Free fall drop test equipment	27
Wind proof tester.....	28
Power cord flexibility tester.....	28
Safety accessories test probes.....	29-33
Other test accessories.....	34-35
Spring impact hammer	36
Freezing load test package / M-package.....	37-38
ISO15502 IEC62552 International standard	37
AS1731 Australia standard	38
AS72 North America standard.....	38
AHAMHRF-1 SASO2664 standard sawdust package.....	38
Plug socket switch test equipment	38-52

BND-IPX12A rain test chamber



Technical parameter :		
No.	model	BND-IPX12A-600
1	Drip area	600*600 mm
2	Inner size	L800*D800*H1000mm
3	Outer size	About 1250*1000*1750mm
4	Turntable diameter	Φ 600 mm
5	Turntable bearing	50KG
6	Turntable lifting range	350-700 mm
7	Dripping aperture	Φ 0.4mm。
8	Distance between holes	20*20 mm
9	Rainfall	1-5 mm/min(±0.5mm/min)
10	Flow adjustment mode	Manual
11	Turntable speed	1 r/min
12	Turntable tilt	0° or 15°
13	Testing times	0-999 min
14	protector	Leakage, water short-circuit
15	voltage (V)	220V
16	power (KW)	1.0
17	standard	IEC60529:1989+A1:1999、GB4208、GB7000. (IPX1、IPX2)

IPX1 IPX2 Drip Box of Rain Tester (BND-IPX12B)



Technical parameters:				
NO.	Model	BND-IPX12B-800	BND-IPX12B-1000	BND-IPX12B-1600
1	Drip area	800*800mm	1000*1000mm	1600*1600mm
2	Outlet size(L*D*H)	1400×1500×2400 mm	1500*1100*2400mm	2160*1800*2700mm
3	Turntable diameter	Φ 500 mm	Φ 600 mm	Φ 800 mm
4	Dripping aperture	Φ 0.4mm。		
5	Distance between holes	20*20 mm		
6	rainfall	1-5mm/Min(±0.5mm/min)		
7	Flow adjustment mode	Manual		
8	Drop box height	1000*1800 adjustable		
9	Turntable bearing	50KG		
10	Turntable speed	1 r/min		
11	Turntable tilt	0° or 15°		
12	Testing times	0-999 min		
13	protector	Leakage, water short-circuit		
14	Power supply (V)	220V		
15	Power (KW)	1		
16	standard	IEC60529:1989+A1:1999、GB4208、GB7000. (IPX1、IPX2)		

IPX1 IPX2 Drip Box of Rain Tester (BND-IPX12C)



Technology parameter:		
No.	model	BND-IPX12C-1000
1	Drop of rain area	1000*1000mm (can customize)
2	Equipment outer dimensions	L1200*D1200*H2500mm
3	Turntable diameter	Φ 600 mm
4	Dripping aperture	Φ 0.4mm。
5	The distance between holes	20*20 mm
6	Rainfall	1-5mm/Min(±0.5mm/min)
7	Flow adjustment mode	manual setting
8	Drop of rain tank lifting height	1000*1800 adjustable
9	Turntable bearing	50KG
10	Turntable Speed	1 r/min
11	Turntable Adjustable Incline	0° or 15°
12	Turntable lifting range	Fixed
13	Testing time	0-999 min
14	Protective device	Leakage, water shortage, short circuit
15	Power (V)	380V
16	Power (KW)	3
17	Standards compliant	IEC60529:1989+A1:1999 (IPX1 IPX2)

IPX3/4 Oscillating Tubes Rain Test Equipment (BND-IPX34)



No	Model	IPX34-R1600	IPX34-R1400	IPX34-R1200	IPX34-R800
1	Swing pipe size (mm)	R1600	R1400	R1200	R800
2	External size(L*D*H)	4000*3200*2800	3800*3000*2600	3200*2400*2400	2400*800*2000
3	Flow (L / mm))	0-10L/min	0-10L/min	0-6L/min	0-4L/min
4	Turntable Size (mm)	Φ 1000 (can customize, Φ 800 Φ 600、Φ 400、Φ 200 turntable)			
5	Turntable height	1750-2350mm	1750-2350mm	1350-1950mm	950-1550mm
6	tube diameter (mm)	>15			15
7	Water pore size (mm)	0.4 mm			
8	Pendulum tube angle	120° (IPX3) , 350° (IPX4) or customize			
9	Swing speed tube	120°(to and fro) 4S、360°(to and fro) 12S(accurate control)or customize			
10	Swing pipe material	SUS304 stainless steel			
11	Turntable speed test	1-5r/min(accurate control)			
12	protective device	Leakage, water shortage, short circuit			
13	Power supply (V)	220V			
14	Power (KW)	1			
15	Standards	IEC60529:1989+A1:1999、 (IPX3、IPX4)			

BND-IPX34B Swing tube rain test chamber



Technology parameter:				
No.	Model	BND-IPX34B-R200	BND-IPX34B-R400	BND-IPX34B-R600
1	Swing tube size	R200mm	R400mm	R600mm
2	Internal size(L*D*H)	500*500*500	900*900*900	1300*1300*1300
3	External size(L*D*H)	1000*700*1400	1400*1120*1750	1800*1520*1950
4	Flow(L/min)	0-1L/min	0-2L/min	0-3 L/min
5	Turntable size mm	φ 200	φ 400	φ 600
6	Turntable height	150-250mm	350-600mm	550-1000mm
7	Sprinkler size (mm)	0.4		
8	Swing tube diameter	15mm		
9	Swing tube angle	120° (IPX3) 、 350° (IPX4) or custom setting		
10	Swing tube speed	120° to and fro 4S、 360°to and fro 12S(Precise control)or custom set		
11	Swing tube materials	SUS304 stainless steel		
12	Test turntable speed	1-5r/min(precise control)		
13	protective device	Leakage, water, short circuit		
14	Power voltage (V)	220V		
15	power (KW)	1		
16	Standard	IEC60529:1989+A1:1999、 GB4208-2008、 GB7000.1 (IPX3、 IPX4)		

BND-IPX56A Strong Water Jet Test Equipment



No.	Model	BND-IPX56A
1	Control System	(touch-tone) Time relay + switch
2	Equipment Outer size	L1000 * D800 * H1300mm (including casters)
3	Water tank capacity	550L, 800 × 600 × 1145 (mm), 304 stainless steel
4	IPX5 water aperture	IPX5:6.3mm ; IPX6:12.5mm
6	IPX5 water flow	12.5±0.625L / min
7	IPX6 water flow	100±5L/min
8	Water pressure	Prescribed water flow regulator(Mpa)
9	Flow control	Using band regulating flow meter
10	Spray distance	2.5*3m (test personnel Control)
11	Gun fixation	Handheld
13	Waterway material	Stainless steel + PPR pipe welding
14	Turntable Diameter	600mm
15	Turntable load power	AC220V
16	Material	SUS304#Stainless steel
17	protective device	Leakage, water shortage, short circuit
18	Power supply(V)	380V
19	Power (KW)	3
20	Standard	IEC60529:1989+A1:1999. (IPX5 IPX6)

BND-IPX7A immersion test equipment



Technology parameter :				
No.	Model	IPX7A-432L	IPX7A-768L	IPX7A-1200L
1	Inner size mm	600*600*1200	800*800*1200	1000*100*1200
2	External size mm	660*660*1400	860*860*1400	1060*1060*1400
3	glass thickness	12mm	12mm	15mm
3	max water depth	1.2m		
4	Water level method	Manual adjustment		
5	Water level display	Stainless steel ruler (show several degree 1mm)		
6	Rack material	Stainless steel		
17	Standard	IEC60529:1989+A1:1999、GB4208、GB7000.		

BND-IPX7B stainless steel immerstion test equipment



Technology parameter:						
No.	Model	IPX7B-108L	IPX7B-432L	IPX7B-960L	IPX7B-1200L	IPX7B-1728L
1	Inner size (cm)	30*30*120	60*60*120	100*80*120	100*100*120	120*120*120
2	External size	36*36*130	66*66*130	108*88*130	108*108*130	128*128*130
3	inside box thick	1.5mm	1.5mm	1.5mm	2mm	2mm
4	Max depth	1.2m				
5	Water level	Manual adjustment				
6	Water level display	Stainless steel ruler visual (display number 1mm)				
7	Box materials	Stainless steel				
8	Standards	IEC60529:1989+A1:1999、GB4208、GB7000. (IPX7)				

BND-IPX8 Water Immersion Test Chamber



No.	Model	IPX8-30M-100L	IPX8-30A-100L	IPX8-50M-100L	IPX8-50M-100L
1	Pressure method	manual adjustment	automatic adjustment	manual adjustment	automatic adjustment
2	Control accuracy	visual inspection (manual)	±0.002Mpa(AUTO)	visual inspection (manual)	±0.002Pa(AUTO)
3	Pressure range	0.05-0.3Mpa	0-0.3Mpa	0.05-0.3Mpa	0-0.3Mpa
4	Test water depth range	5-30M	0-30M	5-30M	0-30M
5	Safety exhaust Pressure	0.31Mpa	0.31Mpa	0.51Mpa	0.51Mpa
6	Max limit of pressure	0.4Mpa	0.4Mpa	0.6Mpa	0.6Mpa
7	accuracy	1.6 class	0.001Mpa	1.6 class	0.001Mpa
8	The thickness of the tank	3mm	3mm	4mm	4mm
9	Thickness of flange	20mm	20mm	25mm	25mm
10	Diameter of the tank	0.5M			
11	Height of water level	0.5M			
12	Outer size	500*600*1300MM			
13	Material of tank	SUS304#			
14	Control time	0-999Min			
15	Protection function	pressure safety protection, anticreeping switch			
16	voltage	AC220V			
17	Power (w)	100w			
18	weight	60kg	80kg		
19	Standard	IEC60529:1989+A1:1999			

BND-IPX34P Spray Nozzle



No.	Item	BND-IPX3/4 SPRAY NOZZLE
1	Water supply	Water flow rate is 50~150kpa clean water without inclusion.
2	Spray nozzle parameters	External diameter: 102mm Spherical diameter: S 75.5mm There is a middle hole and 24 holes in the internal circle which the included angle is 30°. There are 96 holes in the external circle of holes of which the included angle is 15°.
3	Water flow	10L/min±5%, Flow meter is adjustable
4	Baffle	Removable
5	Pressure gauge	0~0.25MPa
6	Site requirements	Dedicated IP waterproof test room The ground should be flat with illumination with good function of inflow and drainage.

BND-IPX5P / BND-IPX6P Jet Nozzle



Item	BND-IPX5P	BND-IPX6P
Nozzle diameter	6.3mm	12.5mm
Pressure Gauge	0~0.25MPa	0~0.25MPa
Water discharge	12.5±0.625L/min, adjustable	100±5L/min, adjustable
Test time	More than 1min/m2 and 3mins	More than 1min/m2 and 3mins
Conforms to	IEC60529	



Model	BND-ZRS	Glow Wire Test Equipment
Glow wire temperature	500 ~ 1000 °C ± 2 °C	adjustable
Heating time	0-999.9s ± 0.1s,	adjustable (normally choose to 30s)
Ignition timer	0-999.9s ± 0.1s,	automatically records, manually suspended
Thermocouple	Φ0.5mm sheathed K-type	thermocouple.
Flame extinguish time	0-999.9s ± 0.1s,	automatically records, manually suspended
Glow wire	Φ4 mm	nickel chromium wire.
Hot depth	7mm ± 0.5mm (to maintain the pressure of 1N ± 0.2N hot products into the test)	
Sample frame speed	about 14mm / s	
The pilot background	black background.	
The pilot process	automatic testing procedures, independent ventilation	
Reference	IEC60695-2-10, UL746A, GB/T5169.10-2006	
Studio volume	0.5 cubic	
Equipment size	1000mm wide × 650mm deep × 1300mm high	
Power supply	AC220V ± 5%, 50Hz, 0.6KVA	



Model	BND-ZY	Needle Flame Test Equipment
Needle burner	the hole Φ 0.5mm ± 0.1mm, outside diameter ≤ Φ 0.9mm, length ≥ 35mm,	
Material	stainless steel	
Burner angle	tilt 45 ° (test) or vertical (adjust the flame height)	
Application time	0-999 .9 s ± 0.1s adjustable (normally choose to 30s)	
Burning duration	0-999 .9 s ± 0.1s, auto record, manual suspension	
Flame height	12mm ± 1mm (with a height measurement apparatus)	
Burn gas	95% of the butane gas (Pressure: Less than 0.2MP)	
Temperature range	0 ~ 1000 °C	
Flame temperature requirements	from 100 °C ± 2 °C 700 °C ± 3 °C rise to the time in 23.5 seconds ± 1 seconds	
Thermocouple	Φ0.5mm (K type)	
Test procedure	automatic control	
Reference standard	IEC60695 -11-5-2004, GB/T5169.5-2008	
Inside dimension	0.5 cubic meters, stainless steel chassis	
Equipment dimensions	1000mm wide × 650mm deep × 1300mm high	
Power supply	AC220V ± 5%, 50Hz, 0.3KVA	



Model	BND-LD Tracking Index Test Equipment
The electrode material	rectangular electrode - platinum metal
The electrode pressure	1.0 ± 0.05N
The distance between electrodes	4.0mm ± 0.01mm, angle 60° ± 5
The electrode voltage	100 ~ 600V (48 ~ 60HZ) adjustable short-circuit current 1.0± 0.1A, voltage drop is less than 10%
Drops of liquid height	30 ~ 40mm adjustable
The size of the drops	44 to 55 drops / 1cm3 Adjustable
Drops Time	30s± 5s,
The number of drops	0 to 9999 times adjustable
The leakage judge	loop current greater than 0.5A and maintain the 2 seconds the relay to cut off the current, indicating that the sample failed
The test process	automatic control of test procedures, independent ventilation
Reference standards	IEC60112-2003, GB/T4207-2003, GB4706.1-2005
The studio volume	0.5 cubic
The device outer dimensions	1000mm wide x 650mm deep x 1300mm high



Model	BND-DDR Single Cable Vertical Burning Test Equipment
Burner	1pcs Inner diameter 2mm ± 0.5mm and 1pcs inner diameter 9.5mm ± 0.5mm Bunsen burner
Burn height	20mm ± 2mm to 190mm±1mm adjustable
Ignition time	0-999.9s±0.1s adjustable
Burning time	0-999.9s±0.1s, auto record, manual stop
Gas	98% propane (can be replaced by liquefied petroleum gas in normal case)
Flow pressure	Double-range recording meter and pressure gauge(gas and air)
Dimension	385x204x360 mm
Temperature range	0~1000℃
Fire temperature requirement	From 100℃±5℃ rise to 700℃±3℃ in 45sec±2sec
Thermometer	Φ0.5mm (K type)
Process	Auto test, no individual ventilation
Standard	IEC60332-1 GB/T18380.11 GB/T18380.12 GB/T18380.21 GB/T18380.22
Chamber dimension	0.15 m3 , exclude door
Instrument dimension	550x450x1380(mm)
Power supply	AC220V, 50Hz, ≤500W



Model	BND-SPR Horizontal vertical flame tester	
Kinds	500W(5V class)	50W(HB/V class)
Test Flame	500W(burning test for V-0,V-1,V-2 classification)	50W(burning test for V-0,V-1,V-2 classification)
Burner Tube	Internal diameter: $\Phi 9.5\text{mm} \pm 0.3\text{mm}$	Internal diameter: $\Phi 9.5\text{mm} \pm 0.3\text{mm}$,
Burning Angle	$0^\circ, 20^\circ, 45^\circ$	$0^\circ, 20^\circ, 45^\circ$
Thermocouple	Type K (Ni/Cr - Ni/Al)	Type K (Ni/Cr - Ni/Al)
Thermocouple Size	0.5 mm	0.5 mm
Standard Copper Block	$9\text{mm} \pm 0.01\text{mm}$, weight: $10\text{g} \pm 0.05\text{g}$ before drilling.	$5.5\text{mm} \pm 0.01\text{mm}$, weight: $76\text{g} \pm 0.01\text{g}$ before drilling.
Time for Temperature to Increase	From $100^\circ\text{C} \pm 5^\circ\text{C}$ to $700^\circ\text{C} \pm 3^\circ\text{C}$; $54\text{s} \pm 2\text{s}$ (preset)	From $100^\circ\text{C} \pm 5^\circ\text{C}$ to $700^\circ\text{C} \pm 3^\circ\text{C}$; $44\text{s} \pm 2\text{s}$ (preset)
Gas Flow	$965 \pm 32\text{ml/min}$	$105 \pm 10\text{ml/min}$
Gas Supply	methane,min.98% purity	methane,min.98% purity
water-column	$125\text{mm} \pm 5\text{mm}$	$<10\text{mm}$
Test Time	$54 \pm 2\text{s}$	$44 \pm 2\text{s}$
Flame Height Indicator	$40 \pm 1\text{mm}$	$20 \pm 1\text{mm}$
Volume Of Chamber	$>0.5\text{m}^3$, black interior	$>0.5\text{m}^3$, black interior
Conform to standard	UL94,IEC60695-11-3,IEC60695-11-20	UL94,IEC60695-11-4,IEC60695-11-10



Model	BND-QNR Car Inner Ornament combustion test machine
Burner	$\Phi 9.5\text{mm} \pm 0.5\text{mm}$ One Bunsen burner about 100mm long
Test Angle	90° vertical burning
Flame Height	$20\text{mm} \pm 2\text{mm}$ to $100\text{mm} \pm 2\text{mm}$ (usually select 38mm)
Burning time	$0-999.9\text{s} \pm 0.1\text{s}$ adjustable (usually select 15s);
Flame time	$0-999.9\text{s} \pm 0.1\text{s}$, Automatic recording, manual suspended
Burning gas	Liquefied petroleum or coal gas
Temperature range	$0-400^\circ\text{C}$
Operation	Manual control test procedure
Working size	$385 \times 204 \times 360\text{ mm}$
Outside size	$550 \times 210 \times 550\text{mm}$
Supply Power	AC220V,50Hz, $\leq 300\text{W}$
Reference standards	FMVSS 571.302 ,ISO379 ,ASTM D5132 ,GB8410-2006

BND-HYW Salt spray test chamber



Model		BND-60	BND-90	BND-120
Inner size (W*H*D)		600*400*450	900*500*600	1200*500*1000
Exterior size(W*H*D)		1250*1050*910	1550*1210*1060	1900*1400*1300
Temp Range	Inside	Room temp.~50℃, ±0.5℃		
	Air	Room temp.~63℃, ±0.5℃		
	Salt water	Room temp.~50℃, ±0.5℃		
Saturated Air Pressure		0.8 ~ 2.0(kg/m)		
Spray Volume		0.5 ~ 3.0(m/80cm/hr)		
PH	Salt	6.5 ~ 7.2		
	Copper acetate	3.0 ~ 3.2		
Exter./Inner. Material		P.V.C & P.P		
System	Salt Spray Vehicle	Air+acid(base)liquid		
	Heating	SUS#304 & 316 stainless steel heater + talon		
	Controller	Hydrometer,salinomerer,fog collector,glass bar		
Other Components		Digital electronic control+S.S.SR		
Power supply		AC1220V10%50/60Hz		

BND-HSC Dust test chamber



Humidity range	R.T.+5-60℃(adjustable)
Speed of wind testing	≥7.5m/s
metal mesh diameter	50um
Test Chamber size	800×800×800mm
screen stencil diameter	75~100um
Talcum powder dosage	2kg~4kg/m3
Power	1KW, AC 220V
Testing dust	dry powder, silicate-cement, flue dust etc
Way of vibration	discontinuous or continuous(adjustable)
Blow the sand dust	discontinuous or continuous(adjustable)
cable hole	φ50mm(circumscribed power accepted)
Time control	continuous 1~9999(S,M,H)
	circle:99~99(S,M,H)(adjustable)
Weight	approx. 185kg

BND-HCY Ozone aging test chamber



Application:

It is widely used to control products quality in measuring quality control; Rubber & Plastics; automobile production; wire and cable; packing materials; instruments and meters; medical equipment; civilian nuclear energy; civil aviation; colleges and universities; research laboratories; inspection arbitration, and technical supervision departments and other rubber products.

type		BND/03-100	BND/03-225	BND/03-500	BND/03-010
Working camber size D*W*H		450*450*500	500*600*750	700*800*900	1000*1000*1000
Performance indicators	Temperature range	0~70			
	Humidity range	≥65R.H			
	Ozone concentration	0~200PPm,0~300PPm			
	Temperature fluctuation	±0.5℃			
Operation control system	Test device	Dynamic and static (optional)			
	sample holder rotation	360°rotation sample holder,(1cycle/min)			
	Gas flow rate	12~16mm/s			
	Temperature controller	Imported LED digital display P,I, D+S, S, R. Microcomputer integrated controller			
	Time controller	High-precision controller by hour,minute,second			
	Ozone concentration analysis	Imported concentration analysis regulator, 4~60mAoutput,RS232 communication port			
	Ozone generator	Silent discharge tube			
Security		Leakage, short circuit, over-temperature, motor overheating, Over current protection			
Reference Standards		JIS K 6259 ASTM1149 ASTM1171 ISO1431 DIN53509			

BND-HXD Xenon lamp climatic test chamber



Xenon lamp climate test chamber can be used to select a new material, or to change an existing material or to assess the durability of changed materials product. It can simulate the product under different environmental conditions to see the changes of the exposed material to the sun.

1. Working room size (mm):	(700 × 700 × 700 (width × depth × height))
2. Temperature range:	10 °C ~ 80 °C
3. Relative humidity range:	50% ~ 98% R.H
4. Black panel temperature:	63 °C, 100 °C (deviation ±3 °C)
5. Temperature fluctuation:	≤ ± 0.5 °C
6. Temperature evenness:	≤ ± 2.0 °C
7. Humidity fluctuation:	+ 2% ~ -3% R.H
8. Glass windows filter:	Boro silicate glass
9. Xenon light source:	imported air-cooled xenon arc light source
10. Xenon lamp power:	1.8KW, 2pcs means: 1.8KW × 2 = 3.6 KW
11. The total number of lamps:	2
12. Rainfall time:	1 to 9,999 minutes.
13. The rainfall cycle:	1 to 240 minutes.
14. Spray nozzle aperture:	Φ0.8mm (backwater with precision filter to prevent nozzle clogging)
15. Rain water pressure:	0.12 ~ 0.15kpa
16. Water cycle (water time / non-water time):	18min / 102min or 12min / 48min (water time / non-water time) water pressure 0.12 ~ 0.15Mpa
17. Heating power:	3.5KW
18. Humidification power:	2KW, sample tray size: 600 × 500mm
19. Light cycle continuously adjustable time:	1 to 999 hours
20. Spectral wavelength:	290nm ~ 800nm, continuously adjustable illumination period, the cumulative amount of radiation: 14,000 ~ 67,000 KJ/m.
21. Environment temperature:	5 °C ~ 35 °C
22. Environment Humidity:	≤85%R.H

BND-HZW UV aging test chamber



Model	UV aging testing chamber
Bulb number	UV Lamp 8, spare lamp: 4 ATLAS, UVA340, UVB313, UVC351
Recorder	Option
Radiometer	Option
UV temperature	From 50 °C to 75 °C
Testing capacity	48 piece (75 x 150 mm), 50 piece (75 x 150 mm)
Water and consumption	distilled water, 8 liters / day
Volume (W x D x H)	137 x 53 x 136 cm
Weight	136 kg
Power	1 φ, 120V/60Hz, 16A or 230V/50Hz, 9A, 1800W (max)

UV lamp can simulate the effect of the sun, condensation and water spray system can simulate the effect of rain and dew. The temperature can be controlled at the process of testing. A typical test cycle is usually testing at UV radiation of high temperature and the 100% humidity at dark; Typically used in paint and coatings, automotive, plastic products, wood products, glue, etc.

BND-HWS Temperature and humidity test chamber



Volume	Temp.	Humidity	Chamber inner size (Width*Depth*Height)	Chamber outer size (Width*Depth*Height)
80L / 100L	0 ~ 150C	20%RH ~ 98%RH	400*400*500mm	1000*870*1700 mm
150L	-20 ~ 150C		500*500*600 mm	1050*970*1750 mm
225L	-40 ~ 150C		600*500*750 mm	1150*970*1900 mm
408L	-60 ~ 150C		800*600*850 mm	1350*1150*1950 mm
800L	-----		1000*800*1000 mm	1450*1300*2100 mm
1000L	-70 ~ 150C (Customized)		1000*1000*1000 mm	1470*1400*2100 mm
Standard	IEC60068-2-1, IEC60068-2-2, IEC60068-2-3, IEC60068-2-30, IEC68-2-5, IEC68-2-78			
Application	To electrical, electronics, household appliances, automobiles, motorcycles, chemicals and other products from parts and materials for low-temperature test			

BND-HGD High and low temperature test chamber



Model	high and low temperature impact test chamber
Internal Dimension:	(W×H×D)50×40×40 cm
material:	SUS# Stainless steel plate
Refrigeration:	Cascade refrigeration system
Cooling method:	Water
Ambient temperature:	0°~30°
Preheating temperature:	60.00°C~200.00°C
Re-cooling temperature:	subzero 10.00°C~subzero 70.00°C
H.T. Shocking:	above freezing 60.00°C~150.00°C
L.T. Shocking:	subzero 10.00°C~subzero 65.00°C
Temperature uniformity:	±2.00°C
HT IN-Zone	subzero 65.00°C~above freezing 150.00°C/5min
LT IN-Zone	above freezing 150.00°C -subzero 65.00°C
Preheating time:	30MIN
Re-cooling time:	60MIN
Controller:	OYO8226
Setting range:	Temperature:>100.00°C freezing 200.00°C/TIME:OHIM~999H/CYCLE:0 ~9999
Resolution:	Temperature:0.1°C
Output mode:	PID+SSR(control method)
Power(K.W)	20

BND-HWBK Fast temperature change chamber

The chamber design advanced and reasonable structure, functional components and supporting products with the advanced international level, able to adapt to long-term, stable production of safe and reliable demand. allowing users to monitor the operation and are more simple and intuitive.



Model	BND--Z100	BND--Z150	BND-Z225
Interior Dimension (mm)	400x500x500	500x600x500	500x600x750
Inside Volume	100L	150L	225L
Model	BND-Z480	BND-Z800	BND-Z1000
Interior Dimension (mm)	600×800×850	800x1000x1050	1000×1000×1000
Inside Volume	408L	800L	1000L
Temp.Method	Balance the thermostat mode (BTC method)		
Temp. Range	-40°c~130°c(150°c); -60°c~130°c(150°c);		
Temp.Uniformity	±2°c		
Temp.Fluctuations	±0.5°c		
The Rate of Temp Change	3°C/min~15 °C/min(Optional) Linear 3°C/min~10 °C/min(Optional)		

BND-HZHD Low air pressure test chamber



model		BND-D500	BND-D1000
performance	temperature range	- 70~ + 150°C	
	temperature fluctuation	±0.5°C(normal pressures,empty)	
	temperature uniformity	≤2°C(normal pressures,empty)	
	temperature deviation	≤±3°C(normal pressures,empty)	
	heating time	60min	
	cooling time	90min	
	pressure range	normal pressures~0.5kPa	
	pressure deviation	~40kPa:±2kPa;40kPa~4kPa;±5%;4kPa ~1kPa;±0.1kPa(≈1mmHg)	
Inner dimension (mm)	D	700	1000
	W	800	1000
	H	900	1000
Exterior dimension (mm)	D	2750	3250
	W	1500	1400
	H	1750	2000
Electromotive cover height		235mm	
Total Power(kw)		20	38
Power Supply		AC380V 50Hz Three-phase four-wire + protective earth wire	

BND-HZK Vacuum drying oven

Vacuum drying oven designed for drying heat-sensitive, easily decomposed easy oxidizing substance,Able to house filled with inert gas,In particular, some components of complex objects can be quickly dried.



MODEL	BND-V6050	BND-V6051	BND-V6021	BND-V6020
Temperature range	10C-250C			
Timing range	1~9999min			
Vacuum degree	<133PA			
Temperature fluctuations	0.1C`			
Outside materials	Cold-rolled plate electrostatic spray			
Inner materials	304stainless steel	High temp paint	High temp paint	304 stainless steel
Outside size	610*450*460	610*450*460	590*490*450	590*490*450
Inner size	415*345*370	415*345*370	300*300*275	300*300*275
Power	220v/1400w	220v/1400w	220v/400w	220v/400w
Separator Number	2pcs	2pcs	1pcs	1pcs
GW	75kg	75kg	55kg	55kg

BND-HLY Rain test chamber



This chamber can imitating nature typical environmental conditions beyond the limitation of time and season. It is able to save a lot of human and financial resources, also research grant when using the stimulative environment instead. The test has the property of acceleration which can cut the period down.

model		BND-LY-800	BND-LY-1000
workroom size(D×W×H)mm		800×800×800	1000×1000×1000
technical index and material	Spraying Hole Diameter	Φ0.8 Φ0.4 Aperture Spacing 50mm	
	flow	0.067-0.074L/min(optional)	
	Water Pipe Diameter	Φ15～20mm	
	Test Bench Rotation Speed	5～17r/min(Step less-speed)	
	Swing Range	±45°,±60°,±90°,±180°	
	The level of pipe	800mm	
	water pressure	80-400kPa(optional)	
Standards Applied	◆GB10485-2006 Road vehicles—Lighting and light-signalling devices—Environmental endurance; ◆GB4208-2008 Degrees of protection provided by enclosure(IP code); ◆GB4942.1-2006 Degrees of protection provided by the integral design of rotating electrical machines (IP code) - Classification; ◆GB/T2423.38-2006 environmental test procedures for electric and electronic products Test R: Water test method; ◆GB/T2423.23-2006 Environmental testing for electric and electronic products ;◆QC/T413-02 basic technical condition for car electrical equipment		

BND-HTY Solar radiation test chamber



Solar Radiation Test Chamber is a comprehensive climate testing machine, can do climatic aging test and the light-fastness test of polymer materials which exposed at simulated sunlight. It simulates the light, temperature, rainfall, condensing, humidity to test the materials; it can be used for choosing new materials, improving existing materials, or assessment of change in material composition;

Model		BND-TY1
Standards Applied		GJB150.GJB150A
performance	Workroom Dimensions	1200×1100×1650(D×W×H)
	Temperature Range	10°C-+90°C
	Temperature fluctuation	≤±1°C
	temperature deviation	≤±2°C
	Humidity Range	50-95%RH
	Spectrum Wavelength	280-300nm
	Lighting intensity	0-1120w/m². divide into 8 block
	Irradiation distance	800mm
lighting supply		Air-cooled halogen lamps
total power		18kw
The test of Temperature and humidity		Constant or procedure
others		The rate of high temperature changes≤2°C/min;Variable rate of Sunshine heating effect ≤0.16°C/min; temperature of the Sample surface on top:96°C±8°C
controller		Temperature and humidity integrated control,color touch screen of English language ;The light energy of automatic measuring-controlling instrument

BND-HGF Blast oven



Model	BND-GF9015A BND-GF9035A	BND-GF9055A	BND-GF9075A	BND-GF9145A	BND-GF9245A
supply voltage	AC220V 50HZ				
temperature range	RT+10~300℃				
temperature fluctuation	+/- 1.0℃				
temperature resolution	0.1℃				
Work temperature	RT+5~40℃				
input power	600w/850W	1100W	1550W	2050W	2450w
volume	16L/30L	50L	80L	136L	220L
(mm) Inner dimension size W*D*H	250*260*250 340*320*320	420*395*350	450*400*450	550*450*550	600*500*750
Dimension W*D*H (mm)	530*480*420 620*530*490	720*590*520	740*618*630	840*670*730	880*720*930

This blast oven adopts advance modern numerical control equipment and laser equipment etc. It applies in drying curing,was-melting and sterilizing of the fields of colleges or universities,industrial mining enterprise, etc.

BND-HDQ nitrogen vacuum oven



The Nitrogen vacuum oven is mainly for some easy to decompose and oxidize to drying and keeping. It can fill the inert gas to inner box. Apply to Electronic, battery, chemical coating, vehicle and motor parts, metals, plastic, communication, epoxy resin, magnetic materials, wires and cables, sports equipment and other industry.

model	BND-30Z	BND-45Z	BND-50Z	BND-60Z
Dimension of exterior mm(W*H*D)	300×300×300	400×400×450	500×500×500	600×600×600
Dimension of inner mm(W*H*D)	500×760×470	600×860×620	790×1100×750	890×1200×850
Temperature Range	Rt~200°C(Adjustable, ≤400°C)			
temperature controller	PID.PV/SV, Button setting			
material	Inner box: mirror stainless steel; outer box: SECC steel plate, stoving varnish with fine powder			
accuracy(°C)	±0.5	±0.5	±0.5	±0.5
uniformity	±1.5	±1.5	±1.5	±2.0
voltage	220	220	220	220
power	2	2.5	5	7
grid filter	2	2	2	2
Remark	simple gate	simple gate	simple gate	simple gate

BND-HZZ high temperature and pressure cooking device



This machine is mainly for the test of performance about keeping, transportation and application of the electric and electronic products, components and parts, metal and materials in simulated high-temperature, humidity and pressure environment.

model(TCGW-01)		BND-GWZ1
studio size(mm)	diameter	240
	depth	300
Dimensions(D*W*H)		800*900*1500
Temperature Range		RT+10-130°C
Humidity Range		100%RH
Temperature fluctuation		±0.5°C
Temperature uniformity		±1°C
Test time		0-999H
pressure range		0-3kg/cm2
heating time		RT-130°C≈ 40mi
test method		steam and boil
outer box material		SUS304 pattern stainless steel plate
inner box material		SUS304 mirror stainless steel plate
sensor		PT100 platinum sensor
pressure gauge		arch culverts made in china
protector		overheat, Out of Phase Protection, water shortage, pressure, air burning
power supply		380
Power Output		4
Standards Applied		GB2423-2-1-89/GB2423-3-2-89/GB2423-3-89

BND-EK Walk-in environmental test chamber



Model		BND-EK-01Series	BND-EK-05Series	BND-EK-10Series
volume of the workroom(m³)		customized according to customers requirements.		
Specifications	temperature range	- 20°C - 40°C - 60°C ~ + 100°C		
	humidity range	20~98%R.H(+ 20°C ~ + 80°C)		
	temperature deviation	≤±2°C		
	humidity deviation	±2.0%RH(> 75%RH), ±3±2.0%RH(> 75%RH), ±3.0%RH(≤75%RH) 0%RH(≤75%RH)		
	temperature fluctuation	≤±0.5°C		
	heating rate	≥3-5°C/min (better than national standard)		
	Cooling rate	≥1-1.5°C/min (better than national standard)		
	refrigeration compressor	Hermetically sealed compressor "Taikang" imported From French / Semi-hermetic compressor Gulun of German		
	refrigerant	environmental protection HFC-R404A/HFC-R23		
	cooling mode	Air-Cooling or water-cooling		
	Airflow mode	single cycle, stem extension, Stainless Steel centrifuge blade.		
	mode of refrigerant	cell refrigeration/double refrigeration		
	Water supply	built-in water tank		
	dehumidification	freeze		
	control system	Fuji of Japan's /a LCD touch screen of Japan's OYO /LCD touch screen of Korea (TEMI880)		
Temperature Control		procedure&program		
Security device		Multiple alarm device such as: electric leakage, water shortage, overheat, over pressure of compressor, over-current		
Standard Configuration		internally heated hollow glass observation window		
Power Supply		380V±10%50Hz 3P+N+G		

BND-HSD Motor transport simulation shake table



Motor transport simulation shake table		
Overview	Simulation of motor transport vibration test-bed for specific categories of goods in the load of road transport vehicle in the course of an actual traffic capacity of the assessment, in the laboratory to obtain the actual condition of the goods effects, thereby articles and items of packaging to be in or Confirmed basis.	
Features	1 Vibration frequency digital, high-precision (show speed) 2 Synchronization mute broadband transmission, low noise, suitable for office and laboratory installation; 3 Fixture of the sample used rails, easy to operate security 4 Heavy channel steel base with rubber vibration and easy to install, load-keung, a smooth operation 5 According to reform Europe and the United States similar equipment, rotary vibration, in line with the norms in Europe and America 6 Applicable to toys, electronics, furniture, gifts, ceramics, packaging, transport industry on the packaging of products for testing.	
Product Spec.and Technical parameter table		
The biggest test load		100KG
frequency range		100-300r/min
amplitude range		(mm)25.4
direction of vibration		rotation
Time Range		24-40km/h
Table size(mm)		(m)0.01S-99.99H
voltage(V/Hz)		(L/W) 1200*1000
consumed power		220/50±2%
Weight		0.75
Standard		180KG
		European transport specification

BND-WSZ Three integrated chamber



Three integrated chamber				
Product Spec.and Technical parameter table				
model		BND-WSZ61	BND-WSZ62	BND-WSZ63
performance	temperature range	- 70°C ~ + 150°C		
	temperature fluctuation	±0.5°C		
	temperature uniformity	≤2°C		
	temperature deviation	±2°C		
	Rising and cooling rates of temperature	rates range:3°C/min~15°C/min(average: - 55°C ~ + 80°C)		
	humidity range	20~98%RH		
	humidity deviation	- 3 ~ + 2%R.H.(> 75%R.H.), ±5%(< 75%R.H.)		
construction	shell	cooling steel plate,surface spray		
	Inner	steel plate		
	insulate	Rigid Polyurethane Foam		
Cooling System	mode	cascade refrigerating compressor		
	compressor	Germany The GULUN Semi-closed compressor		
inspection window(mm)		400×500		
Cable port(mm)		Both sideΦ100		
Controller		color LCD touchscreen display		
recording equipment		temperature recorder(optional)		
communication Interface		RS485 interface,RS232 interface,The software of Upper computer (optional)		
Inner dimension(mm)	D	700	900	1250
	W	800	1150	1150
	H	900	1100	1100
Electromotor cover height (mm)		235		
Power Supply		AC380V 50Hz Three-phase four-wire + protective earth wire		
Standard Configuration		A copy of the instruction and test report for the product, A certificate and quality assurance.2 Shelf and 4 shelves .		

BND-RL Sharp edge tester



Sharp Edge Tester meets the standard requirement of UL1439D, and it is used for testing whether the sharp edge on metal and glass of the products, such as children toys, daily household appliances and electronic equipment, is hazardous to user in accessible places. It is mainly used for children safety testing.

Standard NO. of American UL-1439

Volume: 184×35×52 mm

Accessory: TC-3 TAPE KIT(21pcs)

BND-JD Sharp point tester



To determine whether accessible sharp points on toys are likely to cause injury. If the accessible sharp point penetrates a specified depth into the small rectangular opening of the tester, the LED is illuminated to indicate that the point is unacceptably sharp. Toys intended for use by children under 8 years old are subject to this requirement before or after use & abuse testing.

Dimensions: 112× 16× 16mm; Weight: 80g

Accessories: weight, batteries, bulb 2 pieces

Testing Standards : 16 CFR 1500.48, ASTM F963 4.8, EN-71 1998 8.14, ISO 8124.

BND-WD Inclined plane device



Application

Standard:IEC60335-1 CLAUSE 20.1

Application: Inclined plane device is used to test the stability of an apparatus that requires a surface in order to work . The device consists of a surface and an angle adjusting device, with angle of 0~15°

Types

Model	Surface diameter	Angle range	Bearing capacity	Rotate way
BND-WD3	1000mm	0-30°	125kg	Hand-actuated/dynamo-electric
BND-WD2	800mm	0-30°	80kg	Hand-actuated/dynamo-electric
BND-WD1	600mm	0-45°	50kg	Hand-actuated

BND-CSJ Black test corner

Application

The Black Test Corner is used for the measurement of the temperature radiated by different equipment during the tests from heating and abnormal operation. One is designed and made with the intention of determining the fulfillment of different norms as far as the registry from temperatures during the operation of the apparatus under test.



Technical parameters

Dimension	500*500*500mm, 800*800*1000mm, 1000*1000*1000mm (also accept customized)
Thermocouple	<0.3mm Import: K type
Thermocouple disposal	Disposal in a line bank (select and fit out thermocouple plug and socket)
Temperature sheet copper	Sheet Brass with 15mm diameter and 1mm thickness
Temperature point	20point, 32point, 48point
Temperature point disposal	100mm*100mm
Glued board	Thickness about 20mm, Berlin Black in face, The back paste gray film board
Active part	Install 4pcs active wheels
Provide	Personalized service

BND-GQCJ Drop Ball impact Strength Tester

Application

It is mainly used for mechanical strength testing equipment enclosure, test equipment enclosure should be able to ensure that the structure can be expected to withstand the operation does not produce within the provisions of the standard risk for damage to the outer surface of the enclosure will touch dangerous parts of the apparatus .

Features

- 1,Extensive use of linear motion in order to test the demand for different samples;
- 2,Ball Length:1300mm;
- 3,With a standard calibration device
- 4,Other parameters

Technical parameters

Item	Parameters
Impact height	1600mm MAX
Pendulum impact range	1650mm MAX
The largest sample	400*400*300H
Clamp release	Electronic control
Impact ball	1040g MAX
Standard	IEC60950-1



BND-KD Dielectric Strength Tester

Application

This machine is mainly used for testing thin-layer insulation material electric strength .The standing part used the whole structure is processed b304 plate material

It is mainly to improve the insulation board and creepage dielectric properties, surface brushed polished , bottom bracket the minimum distance from the edge of >35mm,the altitude of 2000mm designed to meet the strength test requirements of 12KV.



Technical parameters

Metal pole diameter	5±0.1mm
Metal club weight	100±2g
Max measure range	20mm
Max strength	<12KV(altitude below 2000m)
Creepage Distances	>35mm
standard	IEC60065 UL1310

BND-CTLJ Socket-outlet Torque Balance Tester

Application

Socket Torque Tester is for measuring and testing the torque strain exerted by appliances with plug pins on socket-out-let.

The balancing arm of the contact tubes of the socket-outlet at a distance of 8mm with the device not in engagement face of the socket-outlet.

With the device not in engagement, the balancing arm is in equilibrium, the engagement face socket-outlet being in the vertical position.

After the device has been engaged ,the torque to be applied to the socket-outlet to maintain its engagement face in the vertical plane is determined by the position of a weight on the balancing arm.



Plug	UL plug*1, Australia plug*1,all-purpose plug*1
Load	0.5N*2/1.25N*1/0.25N*1
Reference	IEC60884,IEC60598,IEC60065,BS1363.3,VDE0620

BND-GT Tumbling Barrel drop tester



Tumbling Barrel Tester is made to the specifications set forth in major international standards. Tumbling Barrel Tester employs a large clear acrylic access door for easy viewing and access to the chamber. Models are offered with a standard barrel with a drop height of 500mm. Barrels of other sizes are available as well for standards such as IEC60312 or DIN60312 where a drop height of 800mm (or 1000mm) is required.

Model	BND-GT1	BND-GT2
Power Supply	220V 50Hz or 115V 60Hz	220V 50Hz or 115V 60Hz
Barrel Wall Thickness	3mm	1.5mm
Inner Height	650mm	675mm or 1175mm(for 1m fall height)
Fall Height	500mm	500mm or 1000mm
Chute Length	275mm	275mm
Bottom Impact Surface	3mm steel	3mm steel backed with 19mm hardwood
Dimension (mm)	W*D*H=630x 600x 1250	W*D*H=630x 600x 1250
Conforms to standard	IEC60068-2-31,IEC60068-2-32	IEC60068-2-31,IEC60068-2-32

BND-DLS Free fall drop test equipment

This equipment is used to test the damage degree when the package is dropped, and test the impact resistance of the package during transportation, for example, to test the surface, edge and angle of the package through free-drop method.



Model	BND-DLS
Display Method	Digital height indicator (optional)
Drop Height	300~1500 mm
Drop height error	$\leq \pm 2\%$
parallel error	$\leq 2^\circ$
Specimen Max. Size	600×800×1000 mm (L×W×H)
Specimen Max. Weight	80 Kg
Control Box Size	1150*1650*12mm(L×W×H)
Machine height	2300mm
Weight	500 Kg
Power	AC 380V, 50HZ
Transmit Approach	Electric Transmission
Horsepower	1/2 HP
Design Criteria	ISO 2248, JIS Z0202-87, GB/T4857.5-92

During the products handling or transport process, there may be drop/ fall, which results in damage within the products. And this device simulates the drop/ fall of a finished product to evaluate the damage. All the angles of rhombohedrons and faces of the products can be tested.

BND-FFZ Wind proof tester

This wind proof tester is designed according to standard IEC60598 and GB7000.1-2007. Applied to provide standard environment condition for lamps product temperature measurement.



the housing structure	double hull rectangular metal structure
the door structure	two-door (open outwards)
the inner space	1800x1800x2000mm (LWH)
the inner space	2100x2100x2150mm (LWH)
the outer dimensions	150mm
level spacing	2mm
the panel aperture	40% of the total area
the effective orifice area	40% of the total area
Case Material	1mm cold plate (matte black spray)
the bottom of the material	18mm plywood (surface spray black)
reference standards	GB7000.1-2007/IEC60598 Appendix D

BND-DWJ Power cord flexibility tester

The power cord flexibility tester is special designed and manufactured according to clause 23.3 and 25.14 of IEC60335-1, GB4706-1, IEC60335-2-14, GB4706-30 and etc., it is used to check the power cord flexing (bending) resistance performance of the small household appliances (such as Coffee pot / electric iron), also applicable for power cord flexing endurance tester of plugs and sockets.



Specification:

Bending angle	45°, 60° or ≤90° (left and right)
Bending rate	8~60rpm (frequency control)
Test time	0~999999
Power output	3KVA
Maximum output voltage	240V
Maximum output current:	12A
Maximum capacity	15kg (300*250*250 L*W*H)
Weight	5N, 10N (each)

Test Probe A/B/C/D				
Product picture	Reference Standard			Specification
BND-A 	IEC60529	IEC61032	IEC60335	Ball Diameter:50mm
	IEC61029	IEC60745	IEC60065	Baffle Plate Diameter:45mm
	IEC60950			Baffle Plate Thickness:45mm
				Handle Diameter:10mm
				Handle Length:100mm
BND-B 	IEC61032	IEC60950	IEC60335	Knurled Finger Diameter:12mm
	IEC60529	IEC60045	IEC60884	Knurled Finger Length:80mm
	IEC60745			Baffle Plate Diameter:50mm
				Baffle Plate Length:100mm
				Baffle Thickness:20mm
BND-C 	IEC61032	IEC60529		Test Probe Length:100mm
				Test probe Diameter:2.5mm
				Dam-sphere Diameter:3.5mm
				Handle Diameter:10mm
				Handle Length:100mm
BND-D 	IEC61032	IEC60529		Test Probe Length:100mm
				Test probe Diameter:1.0mm
				Dam-sphere Diameter:3.5mm
				Handle Diameter:10mm
				Handle Length:100mm

Test probe C/D with force		
Product picture	Reference Standard	Specification
BNF-CF/DF 	IEC60335	Test Probe Length:100mm Test Probe Diameter:1.0mm/2.5mm Dam-sphere Diameter:35mm Handle Diameter:10mm Handle Length:100mm Force:1N/3N

Test Sphere			
Product picture		Reference Standard	Specification
BND-G 		IEC61032 IEC60529	Diameter:50mm,12.5mm Weight:227g,500g,535g,1024g
BND-2B 		IEC60529	Diameter: 12.5mm

Rigid Test Probe		
Product picture	Reference Standard	Specification
BND-11 	IEC61032 IEC60065 IEC60335-1 IEC60884-1	Nodular Finger Length:80mm Nodular Finger Diameter:12mm Dam-board Diameter:50mm Dam-board Thickness:5mm

Long/Short Test Pin		
Product picture	Reference Standard	Specification
BND-12 	IEC61032	The probe Diameter:4mm The probe Length:50mm Dam-board Diameter:25mm Dam-board Thickness:4mm
BND-13 	IEC60065 IEC60335-1 IEC61032	The probe Diameter:Head 3mm Tail 4mm The probe Length:15mm Dam-board Diameter:25mm Dam-board Thickness:4mm

Children Test Finger 18/19		
Product picture	Reference Standard	Specification
BND-18/19 	IEC61032 Figures 12 and 13 EN71 ASTM F963	NO.18: Knurled finger diameter:8.6mm Knurled finger length:57.9mm (Three knurls,19.3mm/knurl) Head Radius:2.8mm No.19: Knurled finger diameter:5.6mm Knurled finger Length:44mm (Three-knurls,14.6mm/knurl) Head Radius:2.8mm

31/32/41/43Probe		
Product picture	Reference Standard	Specification
BND-31 	IEC61032	Rod Diameter: 25±0.2 mm Rod Length: 80±0.2 mm Plate Former Diameter(Min): 60±0.2 mm Plate Back Diameter(Max): 110±0.2 mm Total Length: 150±0.2 mm
BND-32 	IEC61032	Dam-board Diameter:50mm Rod Diameter:25mm
BND-41 	IEC61032	Test Rod Diameter: 30mm Rigid Finger Length:80mm Handle Diameter:50mm Handle Length:80mm
BND-43 	IEC61032	Probe Thickness: 5±0.05 mm Probe width: 50±15 mm Probe Length: 80±0.2 mm Reference standards : IEC61032-1997 Bar Wide:50mm Thickness:5mm

Test Finger Probe		
Product picture	Reference Standard	Specification
BND-B90 	GR1089	Nodular Finger LENGTH:90MM Curved Finger Length:30/30/30mm Nodular Finger diameter:12mm
BND-BD125 	IEC61032	Nodular Finger Length:100MM Curved Finger Length:30/30/40mm Nodular Finger diameter:125mm
BND-BD50 	IEC61032 IEC60950 IEC60335 IEC60529 IEC60045 IEC60084 IEC60745-1	Knurled Finger Diameter:12mm Knurled Finger Length:80mm Baffle Plate Diameter:50mm Baffle Plate Length:100mm Baffle Thickness:20mm

Rigid Test Probe		
Product picture	Reference Standard	Specification
BND-11D 	IEC60335 UL1244	Nodular Finger Length:80mm Nodular Finger Diameter:12mm Dam-board Length:100mm Dam-board Diameter:50mm Dam-board Thickness:20mm
BND-1150 	IEC61032 IEC60335 IEC60065	Nodular Finger Length:80mm Nodular Finger Diameter:12mm Dam-board Thickness:5mm Dam-board Diameter:50mm With Dynamo-meter:10/20/30/40/50/75N

Test finger nail		
Product picture	Reference Standard	Specification
BND-ZJ 	IEC60335 UL1025 UL1278 UL507	Finger Tip;Middle finger ,Finger Base Force:10/20/30/40/50N

75mm test probe		
Product picture	Reference Standard	Specification
BND-TB75 	IEC60335	Probe Diameter:75mm Probe Length:50mm Baffle Plate Diameter:100mm Baffle Plate Thickness:10mm

Scratching Tool Tip		
Product picture	Reference Standard	Specification
BND-H101 	IEC60335-2-24	Hardened Steel K10

Wedge Probe		
Product picture	Reference Standard	Specification
BND-X102 	UL60950	Test Tool Total Length:300mm Test Tool Width:50mm The Bend Par Length:30/30/40mm

Telecom Test Probe

Product picture	Reference Standard	Specification
BND-TB12 	IEC60065 IEC60695 IEC60950	Probe Diameter:12mm Probe Length:80mm Baffle Plate Diameter:50mm


Test Hook Probe

Product picture	Reference Standard	Specification
BND-SG 	IEC60065	Length:180mm Width:5mm Thickness:1mm

Articulated UL Finger Probe

Product picture	Reference Standard	Specification
BND-UL100 	UL507 UL982	Test Finger Length:234mm The Bending Part Length:30/30/40mm


UL Test Probe

Product picture	Reference Standard	Specification
BND-TB160B 	UL507 UL1278	Total Length:88.9mm(3.5inch) Head Length:25.4mm(1inch) Head Radius:R3.175mm(1/8inch) Former Head Diameter:12.7mm(1/2inch) Tail Diameter:25.4mm(1inch)
BND-TB130A 	UL507 UL1026	Total Length:101.6mm(4inch) Head Length:12.7mm(1/2inch) Head Radius:14.3mm(9/16inch) Former Head Diameter:R4.8mm(3/16inch) Tail Diameter:19.1mm(3/4inch)
BND-TB140A 	UL507(S2140A)	Total Length:25.4mm(4inch) Head Length:101.6mm(1/2inch) Former Head Diameter:R12.7mm(1/42inch) Tail Diameter:31.75mm(1-1inch)

Knife probe

Product picture	Reference Standard	Specification
BND-KP 	UL749 Fig 3(SB0504A)	1,Probe I Length :127mm(5INCHES) 2,Probe Thickness:0.81mm(0.032INCH) 3,Standard:UL749 Fig3

Creepage Distance Test Probe

Product picture	Reference Standard	Specification
	IEC60065-2005	PD8:1.0/1.5/2.0/2.5/3.0/4.0/6.0/8.0mm
	IEC60598.1-2008	PD10:1.0/2.0/2.5/2.8/3.2/3.6/4.0/5.0/5.6/6.3mm
	IEC60335.1-2006	PD27:1/1.1/1.2/1.3/1.4/1.5/1.6/1.7/1.8/1.9/2.0/2.5/2.8/3.0/
	IEC60601.1-2005	3.2/3.3/4.0/4.5/5.0/5.5/6.0/6.3/6.4/7.0/8.0/9.0/10mm PD30:1/1.05/1.1/1.2/1.25/1.3/1.4/1.5/1.6/1.7/1.8/1.9/2.0/2.1/2.2/2.4/2.5/2.8/3.2/3.6/4.0/4.2/4.5/5.0/5.6/6.3/7.1/8.


Test chain

Product picture	Reference Standard	Specification
	Test chain is composed of copper and zinc alloy(Cu 63% Zn37%),without any surface treatment and coating , 200g/m load tensile resistance at $2.5 \pm 20\%$,according to IEC60598-1standards.	It mainly used for lighting without insulation, accessible and opposite SELV part accidental short circuit protection test

Glow wire loop

Product picture	Reference Standard	Specification
	Nickel/Chromium(80/20) $4.0\text{mm} \pm 0.04\text{mm}$ (before bending	It is the mainly used in glow wire test apparatus

Thermocouple type K

	Insulation type high temperature resistant armored thermocouples (443-7939,443-7951,443-7919,443-7921)	Length:500mm Thermocouples Diameter:0.5mm Temperature:-40~1100℃ Fixed Position:M8(British Thread)
	Thermocouples temperature probe portion is made of bent 310 stainless steel sheath,with excellent antioxidant properties,suitable for corrosive ,medium, and high voltage applications .	Note:This thermocouples is used to glow wire tester,needle flame tester,horizontal and vertical tester,wire and cable vertical burning tester and need to provide additionally temperature cooper head for needle flame tester and horizontal and vertical tester

Test foot probe		
Product picture	Reference Standard	Specification
BND-JM 	IEC 60335-2-92 Fig 103, UL 82 and UL 1447	The standard requires rotary power mowers to have protective shields. These shields prevent the operator's foot from contacting the blade, either under the mower's deck or in the discharge chute area, when the operator has his or her hands on the mower's controls. Generally, a shield must prevent a foot probe from entering the path of the mower blade or from forcing any part of the mower into the path of the blade. The only difference between the UL Foot Probe Model FP10 and International Foot Probe Model FP11 is the length of the simulated leg.

Product	BND-102 Ball Pressure Apparatus
Standard	IEC60695-10-2 IEC60884-1 IEC60320-1 IEC60335-1 IEC60598-1
BND-QY102 	Ball Pressure Apparatus is used for testing parts of non-metallic materials for resistance to heat. It is applicable to electrical equipment, its sub assemblies and components, and to solid electrical insulating materials except ceramics. Ball Pressure Apparatus is the requirement ball(R2.5mm) and total test force $20N \pm 0.2N$ ball pressure testing device , pressure level of the state and was placed in the heating chamber on the surface of the test.
Technical parameters:	
Ball diameter	5mm
Total test pressure	$20N \pm 0.2N$
Samples bearing	Diameter:50mm,Length:100mm Solid stainless steel cylinder
Production of materials	All used Stainless steel materials
Remark	Ball Pressure Instrument takes another a hot box(oven) supporting the use

product		Spring Operated Impact Hammer	
Standard		IEC60068-2-75 IEC884 UL1244	
BND-THC 		Impact hammers are used to check the durability of enclosures for electrical appliances of other electronic products. If damage occurs from the Impact Hammer test. Accessibility probes can be used to measure the extent or severity of the damage .The Impact Hammer simulates the mechanical impact to test household and similar electrical appliance shell, lever, handle, knobs, lights and other shell to withstand mechanical shocks.	
Technical parameters			
Length	211mm	Hammer Weight	60g
Weight	1250g	Hammer Radius	10mm
OD	50mm	The release force of impact	10N
Impact Components	Including the hit ball handle the hammer, Weight 250g		
Hammer head is made from white polyethylene			
Type	Impact Energy		
Single Impact Energy	0.14J±0.014J (BND-T014)		
Single Impact Energy	0.20J±0.02J (BND-T020)		
Single Impact Energy	0.35J±0.03J (BND-T035)		
Single Impact Energy	0.50J±0.04J (BND-T050)		
Single Impact Energy	0.70J±0.05J (BND-T070)		
Single Impact Energy	1.00J±0.05J (BND-T100)		
Single Impact Energy	2.00J±1.10J (BND-T200)		
Universal energy	0.14j~1.00J (BND-T106)		
Provide Customized Energy			

Freezing Load Test Package

Description

Now test package generally used in the test of refrigerators' performance, it has advantage of security, price and durability.

We have been engaged in production of test package for more than 20 years. Due to our wealth of experience and good reputation, we have supplied test package for a large number of refrigerator factory and laboratory all over the country even overseas.

The test package was made by skillful technique, using classy raw materials bring it's excellent quality. We offer after-sales service to ensure the use of test package during one-year warranty time.

We can provide custom made test package that comply with various standard, moreover provide copper pillars and plugs connect the thermocouple wire.

1.BND-RT01 Normal Test Package (Standard GB8059.1-4/ ISO 15502/ IEC 62552)



Size (mm)	Weight (g)	Tolerance of size	Tolerance of quality
25 × 50 × 100	125	When length is between 25mm to 50mm, tolerance is ±2mm; When length is between 100mm to 200mm, tolerance is ±3mm;	±2%
50 × 50 × 100	250		
25 × 100 × 100	250		
25 × 100 × 200	500		
50 × 100× 100	500		
50 × 100 × 200	1000		
It has two types: -1℃ and -5℃.			

*BND-RT02M / BND-RT03M is M-package, size is same as BND-RT01M.

2. BND-RT01M Test M Package(Standard:ISO 15502/IEC 62552/GB8059.1)



Size (mm)	Weight (g)	Tolerance of size	Tolerance of quality
50 × 100 × 100	500	50±2mm 100±3mm	±2%
It has a sensor hole in the geometry center of test package that embedded K type thermocouple wire.			

3. BND-RT02 Australia standard test package (Standard AS1731.4-2003)



Size (mm)	Tolerance of size	Density (Kg/m ³)	Tolerance of quality
25 × 50 × 100	±3%	480±80	±2% (Quality is calculated by the density and volume)
25 × 100 × 100			
50 × 100 × 100			
37.5 × 100 × 200			
50 × 100 × 200			

4. BND-RT03/BND-RT03M North American commercial test package



Size (mm)	Tolerance of Size	Requirement for volume
52 × 100 × 100	±2mm	≥473ml
*RT03M with thermocouple wire, size as same as BND-RT03.		
ANSI/ASHRAE Standard 72-2005		

5. BND-RT04/BND-RT04M Sawdust package



Size (mm)	Weight/tolerance (g)	Density/tolerance (Kg/m ³)
130 × 100 × 40	291 ± 41	560 ± 80
It was filled with hardwood sawdust that has been water-soaked or alternately is to be an equivalent package of frozen food such as chopped spinach.		
*RT04M with thermocouple wire, size as same as BND-RT04.		
Standard AHAMHRF-1 2007/ SASO 2664-2007		

BND-HD-CTZ1 Power Plug Integrated Tester

Product explanation:

This tester is a integrated tester for plug.It is used to test the continuity,polarity,insulation,high-volt,leakage current, high current on E-wire of power plug.It meets the requirements of many international standards such as BIS, UL, CSA, VDE, BSI, DIN, CCC, IEC,etc.It is a totally automatic testing machine makes your operation more convenient and simple.

Technical parameter:

Polarity test	Test E,L,N wires in sequence
Insulation test high-volt	DC 500V +- 10%
Insulation resistance	2,7,20,50,100MΩ(can be made to order)
Inner high-volt	0~5KV +-5% (adjustable)
Outer high-volt	0~5KV +-5% (adjustable)
Leakage current	0.5,1,3,5,10mA(can be made to order)
Rated power	500VA
E-wire test current	25A
Cylinder power	compressed air with 0.4 to 0.6Mpa
Dimensions	675mm W,480mm D,520mm H
Power source	AC 220V +-10%,50Hz
Weight	35 kg, approximate
Test Objects:	Power Plugs

NOTICE:

1,Inner high-volt is applied between L,N,E wires,and the outer high-volt is applied between L,N,E wires and jacket.

2,Both 3-wire and 2-wire power plug can be tested by this machine.



BND-HD-CTZ2 Power plug integrated tester

Application:

It is a integrated tester for plug.It used to test the continuity,insulation,high-volte,leakage current of power plug.meet the standards such as BIS,UL,CSA,VDE,BSI,DIN,IEC etc.

Technology parameter:

Items			explanation
High voltage teste	Output voltage	Outside high voltage	(L,N,E and cover)0-6KV(adjustable) Leakage current:2mA (fixed)
		Interelectrode high voltage	0-5kv(adjustable)
	Rated power		500VA
	Profile		50/60HZ Exchange sine wave
	Voltage calibration		Within +/-1%
	Switch		Zero level translators
Voltage digital meter	Proportion		1:25
	Rank		1.0 class
Fault judgeme nt	Judgement		The observed value is bigger than the datum value ,shuts off the output voltage and alarm
	Enact leakage current value (benchmark value)		0.5/1/3/5/10mA
	Judgement precision		+/-3%
	Inspects the no-load output voltage		About 200V 2.5mA stalls ,short L ,N and it must alarm
Dilectric resistanc e	Output voltage		500VD
	Voltage calibration		+/-3%
	Benchmark value		5/100MΩ
	Judgement		The measured object insulation resistance value is smaller than the benchmark value ,given the failure signal
	Judgement precision		+/-3%
Single polarity and continuo us testing	Polarity test		You have to test each wires in sequence
	CON test		You dont have to test each wiresin sequence



BND-HD-CTW Plug flexing tester



Introduction:

This BND-HD-8878E Plug Flexing Tester is designed and manufactured to meet the requirements of UL817, IEC60884, GB2099.1 standards. HD-8878E Plug Flexing Tester is mainly used for the flexing test of plug and plug wire.

Technology parameter:

Power source : AC 220V 50Hz 5A
 Clamping mechanism : 6 sets
 Motor power : 750W
 Flexing angle : 00~+-1200adjustable
 Test speed : 10~60cycles/m adjustable
 Counter : One counter for each work units
 Weight : 50g,100g,113g,200g,284g,300g,500g
 Dimension : 940mm L,450mm W,835mm H

BND-TL Torsion testing machine

basic introduction:

The current test is based on the relevant standards of UL817 Article 99.1 (Abrupt Pull Test: Cords employed a preceed conductor), Section 99.2 (Abrupt Pull Test: Two conductor representative devices) and Chapter 100 (Jacket Retention Test) It is required to check the connection strength between the insert and the wire and the anti-burst strength of the wire and the retention test of the outer or outer sheath of the power cord to assess the toughness of the plug and the adapter of the power cord and the wire assembly. Tensile strength.

Technical Parameters:

1. Power supply: AC 220 V, 50 Hz, 10 A;
2. Load current: AC 6 ~ 12 V, 40 A;
3. Power up time: 0 ~ 99 min adjustable;
4. Rotation time: ≤ 15 S;
5. Tensile height: 254 mm (10 "), 178 mm (7") 2 stalls;
6. Number of poles: 0 ~ 9999 times can be preset;
7. Weight: Rally weight - 2.5 Lb 6;
 Rotating weights - 3 Lb 6;
 Load weight - 15 Lb 6;
8. Station: 6
9. Reference standard: UL817 Art

According
to
GB2099.1
and



BND-PZ Multifunction Extension Tester



Application:

plug integrated test machine, use to test the power plug line and row of wire conduction, voltage, switch and neon test four Project special equipment, testing is completed, qualified products have OK tips, and can mark.

Technology parameter:

Power source: AC 220V, 50Hz

Rated power: 500VA

High voltage test voltage: 0-5kV

Waveform: 50Hz sine wave,

precision: $\pm 5\%$

Standards: BS

Leakage current: 0.5, 1, 2, 5, 10, 15 or 20mA, precision: $\pm 3\%$

Dimensions (L x W x H): 465 x 360 x 370mm

Test objects: perform the continuous, high voltage, indicate light test of multiple socket outlets

BND-KCS switch socket life span tester



Technical parameters:

Power source: 220V AC/50Hz

Rated power: 200W

Loading current: $< 30A$ (when work with a loading machine)

Operating model: touchscreen

Cylinder power: compressed air with 0.4 to 0.6MPa

Counter: 0 to 99,999 times

Working temperature: 0 to 400C

Working humidity: $< 85\%$ RH

Exterior dimensions (W x D x H): 1,000 x 680 x 500mm

Standards: GB2099.1, GB10592, IEC60884.1 and UL1054

Test objects: Used in plug and socket lifespan of insert and withdraws testing

BND-CBS insert and pull testing machine



Introduction :

Plug testing machine for connectors, plugs and other products for insertion and removal of the fatigue life of the test, with the number of settings, adjustable speed trip.

Product parameters:

- 1, the power supply voltage: 220V $\pm$ 10%
- 2, the number of times: 0 ~ 999999
- 3, speed range: 0 to 30 times / min
- 4, stroke adjustment range: 0 ~ 8cm
- 5, the machine weight (about): 80kg
- 6, the volume: 500 $\times$ 450 $\times$ 350mm
- 7, power supply: AC220V, 50Hz

BND-XZS Rotary Switch Life Testing Machine

Introduction :

according to GB15092.1, GB16915.1, and IEC61058, IEC60669 etc standard

Technical Features:

- 1, the test station: three
- 2, the number of tests: 0 ~ 999999 times adjustable
- 3, the rotation mode: one-way rotation or two-way rotation adjustable, stepper motor precise positioning
- 4, the rotation angle: 0 $^{\circ}$ ~ 360 $^{\circ}$ adjustable
- 5, test speed: 0 $^{\circ}$ ~ 90 $^{\circ}$ / s adjustable
- 6, rotating stalls: 0 ~ 99 stalls can be set
- 7, the control mode: the use of programmable logic controller (PLC) control
- 8, fixture: According to the user to provide various types of custom switches
- 9, table: length and width 700x600x300mm (desktop)
- 10, do electrical life test: the user should be equipped with power load control cabinet (optional purchase)



BND-FD Plug and socket segment capacity testing machine

Plug and socket breaking capacity testing machine is based on GB2099.1-1996 and GB16915.1-2003 the relevant technical requirements of the design of the equipment, suitable for plug socket capacity and plugging life test. Can be used with the company load machine composed of closed-loop load power test system, so that the plug socket in a critical environment for simulated aging power test. The test machine has a rhythm compact, beautiful appearance, reasonable layout, easy maintenance and other advantages.

Instrument parameters:

- 1, power: AC 220V $\pm$ 10%, 50Hz
- 2, the load current: not more than 40A
- 3, the work mode: two single-phase independent work station
- 4, the operating frequency: 5-30 continuously adjustable
- 5, the counter: the range of 0 ~ 9999 $\times$ 100 (can be preset)
- 6, the counter accuracy: $\pm$ 1 word, the timer accuracy: 0.01S

BND-HD-JHT-01 Plug insulation wear test machine**product manual:**

plug plug insulation sheath wear test machine is based on IEC60884-1: 2002 and BS1363.1 and other standards in the technical requirements of the design of the equipment, mainly for testing plug plug insulation jacket Wear resistance.

Technical Parameters:

- 1, the counter: count range 0 ~ 9999 *1,10,100 (can be preset) $\pm$ 1 word
- 2, U-type friction head diameter: 1 mm
- 3, friction angle: 10 degrees
- 4, weight weight: 4N
- 5, friction stroke: 9mm
- 6, friction speed: 15 times / minute (30 one way / minute)
- 7, the use of other environmental requirements: no dramatic shaking, shock, vibration, non-corrosive air
- 8, the outline size: 450 *250 *370mm (length* width*height)



BND-HD-NY High Voltage Tester

Product explanation:

This tester is designed to perform tests specified in many standards to check resistance of high-volt. It meets the requirements of many national and international standards such as BIS, UL, CSA, VDE, BSI, DIN, CCC, IEC, etc.

Features:

- * All of the test subjects will be done automatically.
- * If the sample is incompetent, there is a alarm by noise which is different from a eligible alarm.

Technical parameter:

Output volt: AC 0~5KV (adjustable).

Leakage current: 0.5, 1, 3, 5, 10mA.

Rated power: 800W

Test period: 60s.

Dimensions: 360mm W, 270mm D, 120mm H, approximate.

Power source: AC 220V +-10%, 50Hz

Weight: 7kg, approximate



BND-HD-WS2 temperature rising tester

Technical parameter:

Power source:	AC 220V 50Hz.
Rated power:	11KW
Loading voltage:	AC 40~280V(adjustable).
Loading current:	0~40A(adjustable).
Transformer capacity:	10KVA.
Testing units:	8units.
Testing temperature:	0~2000C.
Temperature precision:	+1%.
Security:	when current more than 45A,this machine will shut down at once.
Working temperature:	250C.
Working humidity:	less than 85%RH.
Exterior dimension:	820mm W,900mm D,1360mm H.
Standards:	IEC60884 UL817
Test projects	Power plug



BND-HD-NF01 plug insulation resistant to non-normal thermal test machine



Application:

Comply with IEC60884-1: 2006, GB2099.1-2008, VDE0620-1: 2010, IS1293-2005 Article 28.1.2, Figure 40 and other standards

Mainly used for plug insulation sheath resistant to non-normal heat test, the test machine temperature set a wide range of temperature stability, time to stop heating, test time to automatic alarm

Technology parameter:

Power supply: AC220V

Test temperature: room temperature - 200°C can be set

Measurement error: 0.5% F.S +/- 1dig

Control accuracy: +/- 1°C

Test time: 0-99H99M99S can be set

Number of stations: 1 station

Volume: 360 * 250 * 150mm

BND-WSD multi-function temperature rise tester

Introduction:

1, based on GB2099.1-2008, GB16915.1-2003 and IEC61058, IEC884-1 and other electrical accessories developed from the relevant standards.

2, can be used to assess the electrical accessories in the load current on the surface of the fever, the electrode temperature rise is in line with the requirements of the standard, can effectively detect the latch And the socket of the socket is thin, plug and socket are in line with the good.

3, the tester by the current regulator control part and the temperature sampling and measurement part (can be charged detection) component.

Technical Parameters:

1, the output current: AC 0 ~ 100A

2, the temperature range: 0 ~ 200 °C 1

3, the number of temperature measurement: 8 (K-type thermocouple, live detection)

4, the reference standard: GB2099.1-2008, GB16915.1-2003



BND-RYS Thermal compression test device



Introduction :

1, the device is based on GB2099.1-2008 and IEC60884-1: 2006 Article 25.4 (Figure 38) made of the requirements.

2, the device consists of two pieces of steel chuck, each clip with a radius of R25mm cylindrical surface. In a test environment (usually in the $80\text{ }^{\circ}\text{C} \pm 2\text{ }^{\circ}\text{C}$ high temperature environment), the sample after the application of 1 hour pressure should not appear in the standard sense Of the damage.

Technical Parameters:

1, surface radius: R25mm, edge radius 2.5mm

2, size: 60x15mm

3, weight: 20N

4, test temperature: $80\text{ }^{\circ}\text{C} \pm 2\text{ }^{\circ}\text{C}$ (customers need to bring their own high-temperature box)

5, Dimensions: 200X150X200mm

6, standard: GB2099.1-2008 and IEC60884-1: 2006 Article 25.4 (Figure 38)

BND-CTJ plug torque test device



Introduction:

1, based on GB4706.1-2005, GB8898, GB4943, GB7000.1 and other standards.

2. Used to check the magnitude of the torque exerted on the output receptacle after inserting the fixed output receptacle into the output receptacle.

3, the device is suitable for GB plug (universal plug), American standard UL plug Australian plug, (three round hole plug).

Technical Parameters:

1, the distance from the mating surface: 8mm;

2, the balance arm length: 200mm

3, the output socket: universal socket (10A two plug, 10A three plug GB standard, BS standard), UL socket, Australia socket (three round)

4, the balance weight: 1N, 1.25N, 2.5N each one;

5, the torque range: 0.055-0.4375 NM (conventional test for the 0.25 NM)

6, the reference standard: GB4706.1-2005 (Article 22.3), GB8898 (Article 15.4.1), GB4943 GB7000.1

BND-BCL Plug socket pull - out testing machine**Introduction:**

According to GB2099.1-2008 and IEC60884-1 and other standards

the device is suitable for rated voltage not exceeding 250V, rated current less than 16A plug socket.

Technical Parameters:

- 1, the main weight: a master weight 1pcs , additional main weight 4pcs
- 2, additional weight: 4N (408g), 5N (510g), 5.4N (551g) each one
- 3, transverse stress weight: 5N (510g) one
- 4, the standard test plug: Unipolar 10A, single pole 16A, two 10A, three 10A, three 16A each one
- 5, unipolar test bolt: 1.5N, 2N each one
- 6, horizontal stress bar: 1
- 7, clamping device: 1
- 8, the weight tray: 1
- 9, the reference standard: GB2099.1-2008, GB1002-2008

**BND-BC Pendulum impact testing machine****Introduction :**

in line with the standards GB2099.1, GB16915.1 and IEC60669, IEC60670 and other corresponding terms and requirements, for the assessment plug Sockets and other electrical accessories shell impact resistance performance.

Technical Features:

- 1, pendulum axis length: 1000mm
- 2, the impact of quality: 150g
- 3, the impact of height: 100,150,200,250 mm
- 4, test fixture: about 60 ° before and after translation and translation
- 5, Size: 500x600x1700mm



BND-GT Drum drop testing machine



Introduction :

1, according to GB2099.1-2008, GB2423.08, IEC60884-1, IEC60068-2-32, GB8898, and IEC61058, and other standards in the "machinery Strength "test requirements developed from.

2, for household and similar uses plug and socket electrical accessories for mechanical strength tests, assessment of electrical accessories, drop-resistant performance.

3, the device can change the roller shape to meet a variety of different standards.

Technical Parameters:

1, speed: 5 r / min

2, the counter: 0-999900 can be preset

3, the working power: AC 220V / 50HZ

4, size: length 800mm × width 800mm × height 900mm

BND-CLJ Socket-outlet torque balance tester

Application

Socket Torque Tester is for measuring and testing the torque strain exerted by appliances with plug pins on socket-out-let. The balancing arm of the contact tubes of the socket-outlet at a distance of 8mm with the device not in engagement face of the socket-outlet.

With the device not in engagement, the balancing arm is in equilibrium, the engagement face socket-outlet being in the vertical position.

After the device has been engaged, the torque to be applied to the socket-outlet to maintain its engagement face in the vertical plane is determined by the position of a weight on the balancing arm

Types:

Plug	UL plug*1, Australia plug*1, all-purpose plug*1
Load	0.5N*2/1.25N*1/0.25N*1
Reference	IEC60884, IEC60598, IEC60065, BS1363.3 VDE0620



BND-HXL Lateral Strain Test Equipment

Product Description

To determine the lateral strain imposed by equipment likely to be introduced into the socket-outlets, which having ratings up to and including 16 A and 250 V, in according to IEC60884-1 figure 13 and clause 13.14, VDE0620,

Each specimen is mounted on a vertical surface with the plane through the socket-contacts horizontal. The device is then fully engaged and a weight hung on it such that the force exerted is 5N.

Technology parameter:

1 weight, 5N

1 sets of test plug, according to clients requirements,

1 test frame.



BND-GWY High temperature pressure test device

Indentation Device

For pressure tests on plug pin insulating sleeves at temperatures to 200° C with 2.5N loads, according to IEC60884-1 figure 41, BS1363 figure 10.

This apparatus has a rectangular blade (see IEC60884-1 figure 41A) with an edge 0.7 mm wide, to be used in the case of round pins, or a blade having a round shape (see figure 41b), with a diameter of 6 mm and an edge of (0.7 ± 0.01) mm

in other cases, for simultaneous testing of 2 samples, with 2 testing frames, 2 load carriers and 2 sets of load weights, stand with bearing support T-shaped, rounded blade with radius 6 mm.

Ghness not exceeding 0.8mm.



BND-DW Low Temperature RAM Impact Test Apparatus



Application :

To determine the mechanical strength of insulated cords, cables, couplers, plug pin insulating sleeves and enclosures in the cold, according to IEC60884-1 figure 27 and 42, IEC60811-1-4 figure 2, VDE0620 figure 28 and 41.

Technology parameter:

- 1 steel block, height 40mm, width approx 200mm, mass 10kg,
- 2 columns, inclusive of upper crossbeam with fixing screw,
- 1 guide rod, three-edged, with slightly rounded edges, for heights of fall up to 100mm with maximum height of sample 40mm,
- 1 intermediate piece of steel, mass 100g, diameter 20mm, bottom side rounded R=300mm.
- 1 the mass of the falling weight is $(1\ 000 \pm 2)$ g, impact height: 10~250mm.
- 2 intermediate piece, of steel, mass 100 g, with striking bolt of diameter 20 mm and 6 mm, for impact tests according to IEC60884-1 Fig 27 and Fig 42.

Heat Resistance Compression Test Device

Standard: IEC 60884-1 2013 clause 24.19, 25.4 and figure 38.

Application:

This device is use for compression test for the verification of resistance to heat for accessories for electrical appliances and surface mounting box. Shrouds of portable socket-outlet, accessories for electrical appliances and surface mounting box.

Feature:

This compression test device is made up with moving jaw, fixed jaw, guides, and compression weights, use for compression test for the verification of resistance to heat for accessories for electrical appliances and surface mounting box with a heating chamber.

Parameter:

- 1.Compression weight: having a cylindrical face of 25 mm radius, corners are rounded with a radius of 2,5 mm
- 2.Compression force: 20N
- 3.Test time: 1 min, test at an temperature of (25 ± 5) °C - for shrouds of portable socket-outlets –;
- 1 hour, test at an temperature of (80 ± 2) °C - for accessories for electrical appliances and surface mounting box.

Screwed Gland Testing Machine

Standard: IEC 60884-1 2013 clause 24.6, IEC 60598-1 clause 4.12.5

Application:

This device is use for test the torque resistance strength of screwed gland of lamps and similar appliances.test Screwed gland of lamps and similar appliances.Floor type support, lifting weights mechanism drive turntable to achieve torque test.

Parameter:

- 1.Cylindrical metal rod: $\Phi 5$, $\Phi 7$, $\Phi 9$, $\Phi 10$, $\Phi 12$, $\Phi 14$, $\Phi 16$, $\Phi 18$, $\Phi 20$, $\Phi 22$, $\Phi 25$, $\Phi 30$, $\Phi 32$, $\Phi 40$ mm, one each, 14 pc in all
- 2.Weights: 20N, 40N, 50N, 60N weight with hook, one each; 10N, 20N weight with hole, one each. Can meet the test requirements to most screwed glands.
- 3.Diameter of the disc: 250mm(500mm disc for option, with less weights)

Diameter of test rod(mm)	Metal glands(N.m)	Glands of moulded material(N.m)
<7	6.25	2.5
7~14	6.25	3.75
14~20	7.5	5
>20	10	7.5



BND-FZ power Load Cabinet

Technical Parameters:

- 1, the input power: AC 220V, 40A, 50 / 60Hz;
 - 2, the output: resistive, resistive + inductive;
 - 3, the output current: AC 5-20A continuously adjustable (can be customized 30A, 40A, 60A);
 - 4, the output voltage: AC 0-300V continuously adjustable;
 - 5, power factor: 0.3-0.96 continuously adjustable;
 - 6, accuracy: V: 0.5, I: 0.5, COS: 0.03;
 - 7, the counter: 0 ~ 999999 times can be preset;
 - 8, work: intermittent or continuous mode;
 - 9, the number of output: 1 Road
 - 10, the reference standard: GB2099.1-2008, GB16915.1-2003, GB15092.1-2003
 - 11, the reference standard: Dimensions: 900 *1700 *760 (mm)
 - 12,type:Capacitance /resistance
- Note: the output current of 30A, 40A, 60A models were BND-FZ3, BND-FZ4, BND-FZ6 etc



BS1363 Plug and socket test gauge

No.	Product name	picture	standard
1	Figure 1 — Test pin		BS1363-Fig1
2	2a)Apparatus for mechanical strength test on resilient covers 2b)Hardwood block for Figure 2a)		BS1363-Fig2
3	Figure 5 — Gauge for plug pins		BS1363-Fig5
4	Figure 11 — Go gauge for socket-outlet		BS1363-Fig11max/min
5	Figure 12 — Contact test gauge		BS1363-Fig12
6	Figure 14 — Non-contact test gauge		BS1363-Fig14
7	Figure 15 — Turning moment gauge		BS1363-Fig15
8	Figure 16 — Withdrawal pull gauges for effectiveness of contact		BS1363-Fig16a/b
9	Figure 17a) — Test apparatus for temperature rise test Figure 17b) — Dummy front plate for temperature rise test		BS1363-Fig17a b
10	Figure 19 — Solid link for test on fuse clips		BS1363-Fig19
11	Figure 23 — Apparatus for pressure test		BS1363-Fig23
12	Figure 29 — Calibration jig for calibrated link		BS1363-Fig29
13	Figure 30 — Test plug for temperature rise		BS1363-Fig30