

Sulfur Dioxide Analyzer



MEZUS 110

| SO₂ Analyzer

MEZUS 110 SO₂ Analyzer is the analyzer that measures minimum amount of SO₂ in air correctly using the UV fluorescence method. The UV lamp with less change of sensitivity used for MEZUS 110 was applied and the self manufactured kicker to remove the obstacle components such as HC is installed.

To prevent the adhesion of specimen, the response chamber and specimen tube of special coating material was used to improve minimum detection and precision.

All gas analyzers of MEZUS series were equipped with screen interface design using TFT-LCD & Touch screen so that user can operate the analyzer and maximize the visual image, and MCU applied to the analyzer is ARM11 32bit processor and operates based on Linux Kernel 2.6 which maximizes the system stability due to multiprocessing.

In addition, the analyzer is equipped with automatic zero correction system (Auto Zero) for smooth measurement and various interfaces (Ethernet, RS232, RS485, USB, DIO, Analog out) so that user can use it more conveniently and usefully.

| Features

- Ranges 0-0.1 / 0.5 / 1 ppm, user selectable.
- 7inch TFT LCD & touch screen interface.
- Ethernet, RS-232, RS-485 & USB ports.
- USB interface utilizes for System Program Update.
- Temperature & pressure compensation
- Internal zero(optional)
- Stored data can be retrieved RS-232, USB Interface and TCP/IP network
- In built Data Logger Utilizes NAND-Flash to Store up to 5min/1year averaged data