

Gasmeter™ HEATED SAMPLING LINES



Gasmeter Heated Sampling Lines

Gasmeter heated sampling lines are designed for continuous transportation of gaseous media. They are flexible, heatable, and are used to keep the sample gas in gas phase and prevent condensation. This is especially when measuring water soluble compounds such as SO₂, NH₃, HCl, etc.

Options

- Other operation temperatures
- 115 VAC version (additional price per meter)
- ¼ inch tubing (additional price per meter)
- PFA tubing (additional price per meter)
- Integrated calibration gas tube (additional price per meter)
- Plastic corrugated tube (additional price per meter)

Basic specifications

Power supply:	230 VAC, 120 W/m
Carrying hose:	Heated PTFE core
Operation temperature:	200 °C maximum
Core:	6/4 mm (OD/ID) PTFE, exchangeable
Temperature sensor:	NiCrNi (k-type)
Thermal insulation:	Finely pored rubber tube at 100 °C, thermally insulated silicone tube at 200/250 °C
External protection:	Polyamide braiding with silicon end caps
Power supply line:	One meter long cord with a 7-pole circular plug (standard)
Circular connector:	1=phase, 3=neutral, 5(+), 6(-)=thermocouple, PE=protective earth
Connector:	Hirschmann CM06EA14S-61S or compatible

Gasmeter Technologies Oy shall not be liable for technical or editorial errors or omissions contained herein. The information in this document is provided "as is" without warranty of any kind and is subject to change without notice. Should you find any errors, we would appreciate if you notified us.