

Nickel is commonly utilized by the electroplating industry in processes utilizing stainless steel, cobalt or nickel alloys.

Even though nickel is regarded as non-toxic to humans, concentrations found in wastewater exceeding 0.5 mg/L can cause damage to certain plants and aquatic life.

Nickel is also used in batteries, fuel cells and hydrogenation of vegetable oils in the food industry.

Nitrates are present in nature as a result of decomposition of organic microorganisms or due to their use as fertilizers. Nitrates reduce to nitrites, which in turn easily combine to form substances dangerous to man.

A maximum level of 45 mg/L is established as a worldwide guideline for nitrate concentration in water. In Europe, the maximum consented level of nitrates in potable water is 50.0 mg/L, while in the USA the EPA has established a guideline for the maximum level of nitrate nitrogen of 10 mg/L (NO₃-N), which corresponds to 45.0 mg/L of nitrates.



SPECIFICATIONS

PARAMETER	CODE	RANGE	ACCURACY	NARROW BAND FILTER	METHOD
Nickel HR	HI 93726	0.00 to 7.00 g/L	±4% of reading	@ 555 nm	Adaptation of the photometric method.
Nickel LR	HI 93740	0.000 to 1.000 mg/L	±0.010 mg/L ±7% of reading	@ 555 nm	Adaptation of the PAN method
Nitrate	HI 93728	0.0 to 30.0 mg/L (NO ₃ -N)	±0.5 mg/L ±10% of reading	@ 555 nm	Adaptation of the cadmium reduction method.
Nitrate	HI 93828	0 to 100 mg/L (NO ₃)	±5 mg/L ±5% of reading	@ 555 nm	Adaptation of the cadmium reduction method.

SPECIFICATIONS common to all models

Light Source	LED (Light Emitting Diode)
Environment	0 to 50°C (32 to 122°F); RH max 95% non-condensing
Battery Type/Life	(1) 9V / approx. 40 hours of continuous use
Auto Shut-off	After 10 min. of non-use
Dimensions/Weight	180 x 83 x 46 mm (7.1 x 3.3 x 1.8"); 290 g (10 oz.)

ORDERING INFORMATION

HI 93726 is supplied with 9V battery, sample cuvetts and caps (2), transport cap (1) and instructions.

HI 93740 is supplied with 9V battery, sample cuvetts and caps (2), transport cap (1) and instructions.

HI 93728 is supplied with 9V battery, sample cuvetts and caps (2), transport cap (1) and instructions.

HI 93728C is supplied with HI 93728, hard carrying case, reagents and instructions.

HI 93828 is supplied with 9V battery, sample cuvetts and caps (2), transport cap (1) and instructions.

HI 93828C is supplied with HI 93828, hard carrying case, reagents and instructions.

REAGENTS AND STANDARDS

for HI 93726

HI 93726-01 Reagent kit for 100 tests (Ni HR)

HI 93726-03 Reagent kit for 300 tests (Ni HR)

for HI 93740

HI 93740-01 Reagent kit for 50 tests (Ni LR)

HI 93740-03 Reagent kit for 150 tests (Ni LR)

for HI 93728

HI 93728-01 Reagent kit for 100 tests (NO₃-N)

HI 93728-03 Reagent kit for 300 tests (NO₃-N)

SOLUTIONS

HI 93703-50 Cuvet cleaning solution, 250 mL

ACCESSORIES

HI 710009 Shockproof rubber boot, blue

HI 710010 Shockproof rubber boot, orange

HI 740029P 9V Batteries (10)

2HI 731318 Cuvet cleaning cloth (4)

HI 731321 Measuring cuvetts (4)

HI 731325 Cuvet caps (4)

HI 740218 Rugged carrying case



HI 710010 — Shockproof Boot