

Industrial TSS Sensor

Measurement principle

TSSCEM sensor light scattering method based on combination of infrared absorption, infrared light emitted by the light source after the scattering of TSS in the sample. Finally, by the photo detector conversion value of electrical signals, and obtaining the turbidity of the sample after the analog and digital signal processing.

Typical applications

- The hole of tap-water plant hole, sedimentation basin etc. Steps on-line monitoring and other aspects of the turbidity;
- The sewage treatment plant, on-line monitoring of TSS of different kinds of industrial production process of

Technical Parameters

Measure range	0.01-100 NTU, 0.01—4000NTU or 0 – 12000 mg/L
Accuracy	Less than the measured value of $\pm 1\%$, or $\pm 0.1\text{NTU}$, choose the big one
Pressure range	$\leq 0.4\text{Mpa}$
T _{response}	$\leq 5\text{s}$
Current speed	$\leq 2.5\text{m/s}$, 8.2ft/s
Calibration	Sample calibration, slope calibration
Sensor main material	Body: SUS316L + PVC (normal type), SUS316L Titanium + PVC (sea water type); O type circle: Fluorine rubber; cable: PVC
Power supply	12VDC
Output	3 Channels of 4-20mA
Alarm relay	Set up 3 channels of alarm relay, Procedures for setting response parameters and response values.
Communication interface	MODBUS RS485
Temperature storage	-15 to 65°C
Working temperature	0 to 45°C
Size	60mm x 256mm
Weight	1.65kg
Protection grade	IP68/NEMA6P
Cable length	Standard 10m cable, can extended to 100m

TSSCEM

