

Measurement principle

NH4CEM online fluoride/chloride/Ammonium composite electrode with fluoride single crystal film, PTFE annular liquid interface and solid electrolyte is compounded with pressure, anti-pollution and other characteristics. Widely used in semiconductor materials, solar energy materials, metallurgical industry, fluoride/chloride/Ammonium containing electroplating etc industry wastewater treatment process control, field of emission monitoring.

NH4CEM



Features

Online fluoride/chloride/Ammonium ion electrode is measured in aqueous solution fluoride/chloride/Ammonium ion concentration or boundary determination and indicator electrode fluoride/chloride/Ammonium ions to form stable complexes of ion

Technical

Measuring principle	Ion selective potentiometry
Measuring range	0.2ug/L ~ 2300mg/L
Automatic temperature compensation range	0 ~ 99.9°C, with 25°C as the reference temperature
Temperature range	0 ~ 99.9°C
Automatic temperature compensation	2.252K, 10K, PT100, PT1000etc
Water sample tested	0 ~ 99.9°C, 0.6MPa
Interference ions	AL ³⁺ , Fe ³⁺ , OH ⁻ etc
T _{response}	< 5s
Accuracy	± 5%
pH value range	5.00 ~ 10.00pH
Blank potential	>200mV (deionized water)
Electrode length	195mm
Basic material	PPS
Electrode thread	3/4 pipe thread (NPT)
Cable length	5 meters