

WTW Oxi 330i Meter Kit DO/Temp Meter

The WTW Oxi 330i handheld dissolved oxygen meter is robust, waterproof, easy to operate and provides assured accurate readings. In combination with galvanic oxygen probe CelloX® 325 (no polarization time required) the handheld dissolved oxygen meter is ready for immediate use anywhere. The handheld DO meter includes automatic temperature and air pressure compensation, salinity correction, GLP-supporting functions and built in datalogger. The handheld dissolved oxygen meter also has an auto ranging and auto read function, which checks the stability of the input signal, for ease of use and data reproducibility. Field kit includes stand and sample cup, manual, quick user guide and carrying case.



Specifications

O₂ Conc.

Range/Resolution:

0.00 ... 19.99 mg/l (19.9 mg/l*), 0.0 ... 90.0 mg/l (90 mg/l*)

Accuracy:

±0.5% of value

Temperature Compensation:

2% at 32 ... 104 (0 ... +40 °C)

Air Pressure Compensation:

Automatic with built-in pressure sensor (500 ... 1100 hPa)

Salinity Correction:

Automatic from 0.0 ... 70.0, adjustable via display

Calibration:

OxiCal® rapid calibration in OxiCal®-SL or OxiCal®-D

O₂ Saturation

Range/Resolution:

0.0 ... 199.9% (199%*), 0 ... 600%

Accuracy:

±0.5% of value

Temperature Compensation:

2% at 32 ... 104 (0 ... +40 °C)

Air Pressure Compensation:

Automatic with built-in pressure sensor (500 ... 1100 hPa)

Salinity Correction:

Automatic from 0.0 ... 70.0, adjustable via display

Calibration:

OxiCal® rapid calibration in OxiCal®-SL or OxiCal®-D

9333 - 41 Avenue
Edmonton, AB
Ph. (780) 469.1356
Fax (780) 469.2587

4511 Manhattan Road SE
Calgary, AB
Ph. (403) 287.2805
Fax (403) 287.3597

#34, 147 Citation Drive
Vaughan, ON
Ph. (905) 760.0170
Fax (905) 760.0171

1.888.RICEENG
www.riceeng.com
www.ricerentals.ca

WTW Oxi 330i Meter Kit DO/Temp Meter

Specifications continued

O₂ part. pressure

Range/Resolution:

0.0 ... 199.9 mbar (199 mbar*), 0 ... 1250 mbar

Accuracy:

±0.5% of value

Temperature Compensation:

2% at 32 ... 104 (0 ... +40 °C)

Air Pressure Compensation:

Automatic with built-in pressure sensor (500 ... 1100 hPa)

Salinity Correction:

Automatic from 0.0 ... 70.0, adjustable via display

Calibration:

OxiCal® rapid calibration in OxiCal®-SL or OxiCal®-D

Temperature

Range/Resolution:

-5.0 ... +50.0 °C

Accuracy:

±0.1 K

Temperature Compensation:

2% at 32 ... 104 (0 ... +40 °C)

Air Pressure Compensation:

Automatic with built-in pressure sensor (500 ... 1100 hPa)

Salinity Correction:

Automatic from 0.0 ... 70.0, adjustable via display

Calibration:

OxiCal® rapid calibration in OxiCal®-SL or OxiCal®-D