

Y610-A Multi-parameter Transmitter



Product introduction

Yosemitech Y610-A is a universal multi-parameter controller, which can connect intelligent sensor and multi-parameter sensor, realize sensor plug and play, real-time display of measurement values; Electrode installation and replacement are quick and convenient; A variety of data transmission methods can be selected, and has data storage and export functions. The multi-parameter transmitter has a simple interface and simple operation. According to the customers' different needs, the transmitter can simultaneously monitor a variety of different parameters online by selecting sensors, including DO, pH, ORP, conductivity (salinity), turbidity, suspended matter, sludge concentration, chlorophyll, blue-green algae, oil in water, chroma and transparency and other parameters. One transmitter multi-purpose, easy control of water quality problems.

Product features

- ◇ Strong versatility, supports any combination of Yosemitech water quality sensors. Plug and play, with automatic identification
- ◇ 7" color touch screen, easy to operate
- ◇ Automatic data storage, real-time curve display, USB data export support, and local data storage capacity of over 2 years
- ◇ Supports up to 8 channels of 4-20mA analog output with RS485 digital output, and more convenient for system integration
- ◇ Integrated 5-way relay, 2-way digital I/O, can be matched with DTU remote control, control function is more comprehensive;
- ◇ Wall-mounted design, small size, reliable and durable

Available sensors



Product specification

Y610-A Multi-parameter Transmitter	
Display	7" color touch screen, LED backlight
Resolution	800*480
I/O interface	Two channel
Electrical relay	Five channels
4-20mA	Standard 1 channel (expandable to 8 channels)
Measurement parameter	Support Yosemite's digital sensors, such as online multi-parameter, COD, ammonia nitrogen, ORP, salinity, BGA, chlorophyll, OIW, etc
Power supply	220V AC or 24V DC(optional)
Communication protocol	Supports RS-485, MODBUS protocol
Data storage	Continuous storage >2 years
Data copy	Supports USB disk export
Material	ABS housing
Working temperature	0-50°C
Size	225mm*229mm*119mm (height * width * thickness)
Installation	wall-mounted

Connectable Sensors			
	Model	Y504-A dissolved oxygen	
	Range	0-20mg/L or 0-200% saturation	
	Accuracy	±1% or ±0.3mg/L (take the bigger one)	
	Model	Y521-A Conductivity (salinity)	
	Conductivity range	0-5mS/cm or 0-100mS/cm	
	Salinity range	0-2.5ppt or 0-80ppt	
	Model	Y532-A pH sensor	
	Range	0-14 pH	
	Accuracy	±0.02 pH	
	Model	Y515-A Chlorophyll	
	Range	0-500µg/L	
	Accuracy	±5% or 0.5µg/L (take the bigger one)	
	Model	Y551-B/C COD sensor	
	Range	0-500mg/L or 0-1500mg/L	
	Accuracy	±5%	
	Model	Y512-A TSS	
	Range	0-4000mg/L (optional 0-15000mg/L)	
	Accuracy	±5%	
	Model	Y531-A Color	
	Range	0-500Hazen	
	Linearity	R ² > 0.999	
	Model	Y700-A Depth	
	Range	0m-2m...100m	
	Accuracy	±0.1% F.S.	

Note: The above technical parameters are all data in the laboratory standard liquid environment.