



PeCOD P100 Online COD - Chemical Oxygen Demand Analyser



Revolutionary Online COD - Chemical Oxygen Demand analysis system from Aquadiagnostic. The PeCOD online system is able to make measurements in real time on a 15-30 minute cycle time.

 AQUADIAGNOSTIC

1167345 AD/10010110	<u>On-line Sampling System for PeCOD On-Line COD Analyser System.</u> Description ### OnLine COD Analyser System. Includes two filter elements	POA
1167344 AD/PQA-100-0050	<u>PeCOD On-Line COD Analyser Unit (P100) for PeCOD On-Line COD Analyser System. Includes 2 Sensors</u> Description ### New Online COD analyser from Aquadiagnosti. Includes 2 Sensors	£25,337.48 ex. Vat
1167346 AD/10010120	<u>Weatherproof Enclosure for On-Line Analyser System.</u>	POA

Product Details

Revolutionary Online COD - Chemical Oxygen Demand analysis system from Aquadiagnostic. The PeCOD online system is able to make measurements in real time on a 15 minute cycle time. Ranges available from >25mg/l up to 15000 mg/l

[Click here](#) for a detailed survey and quote

PeCOD analysers accurately detect COD in samples from a variety of sources and overcome many of the problems encountered by existing COD methods. The core of the technology is the strong oxidation power which ensures complete oxidation of all oxidisable organic species in a simple and rapid fashion.

The patented PeCOD technology provides a unique nanotechnology-based photoelectrochemical technique capable of determining COD in natural and wastewater samples. It measures photocurrent charge originating from the oxidation of organic species contained in a sample to quantify COD. This means the end user obtains a real measurement of organic pollution, not an inferred one.

- Real time results (less than 15mins) to overcome the problems of time delays encountered by chemical oxidation methods
- Absolute COD measurement avoiding costly and time consuming regular calibration
- Complete oxidation leading to high accuracy and high reproducibility minimizing matrix variation problems.
- Direct signal acquisition resulting in high sensitivity and wide linear range
- Equivalent BOD
- No Hazardous reagents
- Small footprint & light weight less than 3.5kg makes it ideal for mounting on-line
- Splash resistant keypad
- Identical technologies across platforms (laboratory and on line unit) ensures consistency of results when switching between the two
- In line mixing avoids user intervention for difficult to analyse samples
- Unmatched ppb sensitivity (0.2 mg/l) and reproducibility (RSD=±3%)

The online system consists of the P100 analysis unit, Sample dilution system and waterproof enclosure as listed above. The unit is supplied with one dilution manifold