

# Automatic water sampler Liquistation CSF48

Fully automatic sampling in water,  
wastewater and industrial applications



More information and current pricing:

[www.endress.com/CSF48](http://www.endress.com/CSF48)

## Benefits:

- Automatic water sampling in full compliance with all relevant national and international standards such as ISO 5667
- 100% adaptable to any monitoring task from time- or flow-controlled sampling to event-controlled sampling
- By connecting up to four Memosens sensors, the sampler can be upgraded to a fully-fledged measuring station (e.g. for event monitoring)
- Offers all the benefits of the Liquiline platform, such as uniform operation of all devices, easy expandability and reduced need for spare part stock thanks to standardized components
- Fully integrable in any process control system thanks to digital fieldbus communication and remote access via web server
- Quick cleaning and maintenance thanks to easy, tool-free removal of wetted parts
- Heartbeat Technology enables status-oriented maintenance of the device, saving resources and costs

## Specs at a glance

- **Functions** Stationary sampler
- **Suction height** 6 m (19.69 ft) suction height 8 m (26.25 ft)  
suction height
- **Cabinet** Plastic PS Plastic ASA+PC Stainless Steel V2A Stainless Steel V4A
- **Process temperature** Sample temperature: 2 to 50 °C (36 to 122 °F)
- **Process pressure** Max. 0.8 bar (Max. 11.6 psi)

**Field of application:** Sampling made safe and easy. The Liquistation CSF48 automatic water sampler complies with worldwide water regulation, features a fail-safe cooling system and vandalism-proof housing guaranteeing outstanding safety for your samples. Easy, menu-guided sample programming and tool-free maintenance save you time in your everyday tasks. Liquistation can be upgraded to a complete measuring station for modern environmental monitoring at any time giving you the flexibility to address future demands.

## Features and specifications

---

### Watersampler

#### Measuring principle

Sampler

---

#### Functions

Stationary sampler

---

#### Application

Communal and industrial wastewater treatment plants

Laboratories and water management offices

Monitoring of liquid media in industrial processes

---

#### Dosing system

Vacuum pump system

Peristaltic pump system

Armature

---

#### Suction height

6 m (19.69 ft) suction height

8 m (26.25 ft) suction height

---

## Watersampler

### Cabinet

Plastic PS  
Plastic ASA+PC  
Stainless Steel V2A  
Stainless Steel V4A

### Distribution

Possible

### Process temperature

Sample temperature: 2 to 50 °C  
(36 to 122 °F)

### Cooling

Active, dynamic cooling unit

### Process pressure

Max. 0.8 bar  
(Max. 11.6 psi)

### Heating

Evaporator and defrosting unit mounted in compact housing

### Input

Analogue: 2, galvanically isolated  
Binary: 2, galvanically isolated  
Optional: 1 to 4 digital sensors

### Output / communication

Binary: 2, galvanically isolated  
Optional 2 to 6 relay, 2 to 6 current output

### Interface

CDI  
Optional: Ethernet, PROFIBUS DP, Modbus RS485, Modbus TCP

### Data logger

All events and data  
Sampling statistics

## Watersampler

### Power supply

Depending on version:

100 to 120/200 to 240 V AC  $\pm 10\%$ , 50/60 Hz

24 V DC  $+15\%$  -  $9\%$

### Dimension

1.258 x 753 x 625 mm (h x w x d)

49.5 x 29.7 x 24.6 inch (h x w x d)

### Weight

91 to 146 kg

### Accessories

Sampling from pressurized systems

Dosing system

Housing equipment

Electrical equipment

### Options

Connection to digital sensors with Memosens protocol,

Fieldbuscommunication

More information [www.endress.com/CSF48](http://www.endress.com/CSF48)