

Gasman Single-gas Monitor, CO

EW-86550-02

- **Datalog and download up to 3000 hours with time and date stamp**
- **Rechargeable lithium-ion battery for 12 hours of operation**
- **Rugged housing is IP 65/67 rated for dust and water resistance**

Gasman monitor is available in a variety of toxic gas configurations to meet your individual application. Small size and light weight ensure the monitors are comfortable to wear all day long. Visible flashing LED, audible 85 dB, and vibrating alarms quickly alert the wearer to potential gas hazards. Data is recorded by the monitor and can be downloaded to a PC or printer using the adapter/PC interface (sold separately).

What's included: calibration cap, pocket clip, and rechargeable lithium-ion battery. (Order adapter/PC interface separately.)

Approval: UL and cUL Class I Div. 1 Groups A, B, C, D (pending), ATEX, CE



Specifications

Product Type	Single Gas Monitors/Detectors
Resolution	1 ppm
Gas	Carbon Monoxide
Range	0 to 500 ppm
Function	STEL, TWA, peak hold, zero, low-battery indicator
Alarm	85 dB (audible), visible, vibrating
Alarm set points	30 ppm (low)
Dimensions	2 in W x 4 in H x 1.25 in D
Manufacturer number	GASMAN-CO
CE Compliance	Yes
Brand	Crowcon Gasman
Model	GASMAN-CO

Gasman Single-gas Monitor, SO₂

EW-86550-08

- **Datalog and download up to 3000 hours with time and date stamp**
- **Rechargeable lithium-ion battery for 12 hours of operation**
- **Rugged housing is IP 65/67 rated for dust and water resistance**

Gasman monitor is available in a variety of toxic gas configurations to meet your individual application. Small size and light weight ensure the monitors are comfortable to wear all day long. Visible flashing LED, audible 85 dB, and vibrating alarms quickly alert the wearer to potential gas hazards. Data is recorded by the monitor and can be downloaded to a PC or printer using the adapter/PC interface (sold separately).

What's included: calibration cap, pocket clip, and rechargeable lithium-ion battery. (Order adapter/PC interface separately.)

Approval: UL and cUL Class I Div. 1 Groups A, B, C, D (pending), ATEX, CE



Specifications

Product Type	Single Gas Monitors/Detectors
Resolution	0.1 ppm
Gas	Sulfur Dioxide
Range	0 to 10 ppm
Function	STEL, TWA, peak hold, zero, low-battery indicator
Alarm	85 dB (audible), visible, vibrating
Alarm set points	2 ppm (low)
Dimensions	2 in W x 4 in H x 1.25 in D
Manufacturer number	GASMAN-SO2
CE Compliance	Yes
Brand	Crowcon Gasman
Model	GASMAN-SO2

Gasman Single-gas Monitor, NO₂

EW-86550-12

- **Datalog and download up to 3000 hours with time and date stamp**
- **Rechargeable lithium-ion battery for 12 hours of operation**
- **Rugged housing is IP 65/67 rated for dust and water resistance**

Gasman monitor is available in a variety of toxic gas configurations to meet your individual application. Small size and light weight ensure the monitors are comfortable to wear all day long. Visible flashing LED, audible 85 dB, and vibrating alarms quickly alert the wearer to potential gas hazards. Data is recorded by the monitor and can be downloaded to a PC or printer using the adapter/PC interface (sold separately).

What's included: calibration cap, pocket clip, and rechargeable lithium-ion battery. (Order adapter/PC interface separately.)

Approval: UL and cUL Class I Div. 1 Groups A, B, C, D (pending), ATEX, CE



Specifications

Product Type	Single Gas Monitors/Detectors
Resolution	0.1 ppm
Gas	Nitrogen Dioxide
Range	0 to 10 ppm
Function	STEL, TWA, peak hold, zero, low-battery indicator
Alarm	85 (audible), visible, vibrating
Alarm set points	1 ppm (low)
Dimensions	2 in W x 4 in H x 1.25 in D
Manufacturer number	GASMAN-NO2
CE Compliance	Yes
Brand	Crowcon Gasman
Model	GASMAN-NO2

Gasman Single-gas Monitor, NO

EW-86550-10

- **Datalog and download up to 3000 hours with time and date stamp**
- **Rechargeable lithium-ion battery for 12 hours of operation**
- **Rugged housing is IP 65/67 rated for dust and water resistance**

Gasman monitor is available in a variety of toxic gas configurations to meet your individual application. Small size and light weight ensure the monitors are comfortable to wear all day long. Visible flashing LED, audible 85 dB, and vibrating alarms quickly alert the wearer to potential gas hazards. Data is recorded by the monitor and can be downloaded to a PC or printer using the adapter/PC interface (sold separately).

What's included: calibration cap, pocket clip, and rechargeable lithium-ion battery. (Order adapter/PC interface separately.)

Approval: UL and cUL Class I Div. 1 Groups A, B, C, D (pending), ATEX, CE



Specifications

Product Type	Single Gas Monitors/Detectors
Resolution	1 ppm
Gas	Nitrogen Monoxide
Range	0 to 100 ppm
Function	STEL, TWA, peak hold, zero, low-battery indicator
Alarm	85 dB (audible), visible, vibrating
Alarm set points	25 ppm (low)
Dimensions	2 in W x 4 in H x 1.25 in D
Manufacturer number	GASMAN-NO
CE Compliance	Yes
Brand	Crowcon Gasman
Model	GASMAN-NO

Gasman Single-gas Monitor, H₂S

EW-86550-04

- **Datalog and download up to 3000 hours with time and date stamp**
- **Rechargeable lithium-ion battery for 12 hours of operation**
- **Rugged housing is IP 65/67 rated for dust and water resistance**

Gasman monitor is available in a variety of toxic gas configurations to meet your individual application. Small size and light weight ensure the monitors are comfortable to wear all day long. Visible flashing LED, audible 85 dB, and vibrating alarms quickly alert the wearer to potential gas hazards. Data is recorded by the monitor and can be downloaded to a PC or printer using the adapter/PC interface (sold separately).

What's included: calibration cap, pocket clip, and rechargeable lithium-ion battery. (Order adapter/PC interface separately.)

Approval: UL and cUL Class I Div. 1 Groups A, B, C, D (pending), ATEX, CE



Specifications

Product Type	Single Gas Monitors/Detectors
Resolution	1 ppm
Gas	Hydrogen Sulfide

Range	0 to 250 ppm
Function	STEL, TWA, peak hold, zero, low-battery indicator
Alarm	85 dB (audible), visible, vibrating
Alarm set points	5 ppm - 20 ppm
Dimensions	2 in W x 4 in H x 1.25 in H
Manufacturer number	GASMAN-H2S
CE Compliance	Yes
Brand	Crowcon Gasman
Model	GASMAN-H2S