

Dust monitor

Product Description

DMSCEM is an on-line dust monitoring device using the mainstream technology of laser back-scattered light principle. DMSCEM is mainly used for continuous monitoring of various sources emissions of particulate matter concentrations. It can be either equipped with CEMS, or connected with dust monitoring network by a shared set of data acquisition and processing background. It is available for the monitoring and control of soot emission, flue gas DeSOx and removal of dust for power generation.

Application

Applicable to monitoring and controlling soot and desulfurization gas and applying large capacity boilers, industrial furnaces, industrial boilers in the fields of thermoelectricity, steel, petrochemical, chemicals, cement, ceramics, burning garbage.

Features

- Patented reigned zero and span calibration functions
- Large - screen display and infrared remote control
- Perfect laser protection
- Temperature compensation and automatic gain control.

Technical Data

Measuring Range	0 – 1000mg/m ³ (customizable)
Power Supply	< 5W
Accuracy	±2% F.S.
Repeatability	±2% F.S.
T _{response}	1s
Analog Output	4 – 20mA, maximum load 500Ω, 2x4 – 20mA (option)
Communication Interface	RS485 (option)
Ambient Temperature	-40°C – 70°C
Relative Humidity	5%Rh – 95%Rh
Max Flue Gas Temperature	600°C (higher temperatures to be customized)
Enclosure Rating	IP66
Flue Diameter	1m – 15m (customizable)
Human – machine Interaction	Infrared remote control + large-screen LCD display

DMSCEM



Principle

The laser beam (650 nm) comes across the detection area and produces scattered light after effect with dust particles. The back-scattered light crosses the lens converges into photosensitive detector. Analyzer circuit and control section converts light signal into signal output which is proportional to the dust concentration, and obtains dust particles emission concentration of pollution.

