

Flow rate, Temperature and pressure monitor

Product Description

This is an integration monitor of temperature, pressure and flow velocity which designed for high dust, high temperature and high humidity. The instrument uses precision micro-differential pressure/static pressure sensor and a unique pitot tube structural design, combined with automatic cleaning. It can be widely used for real-time and continuous measurements of flue gas temperature, pressure, and flow velocity as well as flow quantity.

Features

- Ultralow range pressure sensor to realize 1m/s flow velocity measurement
- Operation unit with LCD display: provide friendly human-machine interaction interface
- Able to set regular purging time, velocity field parameter, pitot coefficient and etc.
- Overvoltage protection to effectively prevent pressure sensor from damage and reduce operation cost
- Automatic zero calibration; strengthen output signal
- Anti-blocking and anti-corrosion design
- High accuracy, small impact and simple pipeline design
- Able to measure pressure of purging gas and determine if there is gas pressure

Technical Data

Velocity	0 – 15.5 m/s or 0 – 40m/s (customizable), accuracy: $\pm 5\%$
Temperature	0 – 300°C or 0 – 800°C (customizable), accuracy: $\pm 3^\circ\text{C}$
Pressure	-10kPa – 10kPa (customizable), accuracy: $\pm 2\%$
Measuring principle	Pitot method
Response Time	< 1s
Signal Output	3 x 4 – 20mA or 1x 232/485
Purging Pressure	0.3MPa~0.8MPa
Material of Pitot Tube	316L steel
Pressure Limit of Differential Pressure Transmitter	1.0MPa
Insert Length of Pitot Tube	400 – 2000mm (optional)
Working Temperature	-40°C – 70°C
Storage Humidity	0 – 85 %RH
Storage Temperature	0~50°C
Power supply	220VAC, 50Hz

FTPCEM

