

**ECOTECH**WORLD CLASS
environmental
MONITORING

Serinus 30 CO Analyzer

The new U.S. EPA approved Serinus 30 Carbon Monoxide (CO) analyzer is the next generation in ambient gas monitoring technology.

The Serinus 30 analyzer uses proven NDIR gas filter correlation technology to measure CO in ambient air (LDL <40 ppb, Range 0-200ppm). Combining several new technical advances and innovative features, the Serinus delivers Ecotech's renowned performance and excellent value.



Superior performance

- U.S. EPA approved (RFCA-0509-174) and EN approval (Sira MC 100166/00)
- New zero volume fittings and flexible Teflon® tubing improves system integrity
- All new electronics suite delivers better performance and instrument reliability
- Advanced diagnostics and status indicator deliver better instrument status information
- New intuitive menu system with "Quick Menu" and easier to read advanced GUI
- New removable flash memory stores eight years of data, including up to 12 individual parameters and event logs

Lower Cost of Ownership

- More affordable to purchase, operate and maintain!
- Utilises low cost consumables, spare parts and accessories
- User selectable operating temperature range delivers reduced power usage and a lower carbon footprint

Reduced Maintenance

- Improved remote diagnostics and maintenance functions
- Extensive use of standard components across the Serinus range reduces the cost of spare parts, accessories and consumable items
- Improved remote instrument diagnostics and maintenance functions including calibration, parameter set-up, operational status etc.
- New "dual particulate filter" can reduce scheduled maintenance calls by up to 50%



Specifications

Measurement Ranges:	0-200ppm (0-100ppm EN certified)
Concentration Display:	User selectable mg/m ³ , µg/m ³ , ppm, ppb, ppt.
Noise:	< 20 ppb
Lower Detectable Limit:	< 40 ppb
Linearity:	< 1%
Precision:	20 ppb or 0.1 % of reading (whichever is greater)
Zero Drift:	24 hours: < 0.1ppm 7 days: < 0.1 ppm
Span Drift:	24 hours: <0.1% of reading 7 days <0.5% of reading
Response time:	60 seconds to 95%
STP reference:	0°C, 20°C, 25°C at 101.3 kPa.
Sample Flow Rate:	1000 cc/min
Temperature Range:	0°- 40 °C
Power:	99-132 VAC, 198-264 VAC 47-63 Hz
Dimensions:	440 x 178 x 620 mm (w x h x d), 3.5 RU
Weight:	18.5 kg (bench) 12.8 kg (rack)

Communications

Communication ports:	USB port (digital communication) TCP/IP Ethernet Network connection (optional) RS232 Port 1: Digital communication RS232 Port 2: Multidrop port 25 pin I/O port (analogue outputs, analogue inputs, digital status inputs, digital status outputs)
Analogue Outputs:	Menu selectable current or voltage output 0-20mA, 4-20 mA. or 0-5 VDC (opt 0-10VDC) Menu selectable offset of 0%, 5% or 10%. Auto-ranging from 0-50 ppb to 0-20ppm (between two user specified full scale values)
Analogue inputs:	3 analogue inputs, 0-5v, 160µV resolution
Digital Status inputs:	8 logic level inputs
Digital Status outputs:	8 open collector outputs

Data Logging

Removable USB flash memory that stores data in the following formats:

- Instantaneous data from: 1, 3, 5, 10, 30, or 60 minute intervals
- Average data from: 1, 3, 5, 10, 15, 30 minutes, 1, 4, 8, 12, or 24 hours.
- Data storage of 8 years of 12 parameters, 1 minute data on 1 gigabyte memory

Options

- Internal low power pump (Max 6 watts)
- External AC powered pump (capable of operating 3 analyzers, excluding NO_x)
- Dual filter (particulate)
- TCP/IP network communication
- High pressure span/zero valves

World Wide contact details

Ph: (+61) 1300 364 946

Fax: (+61) 1300 668 763

Email: ecotech@ecotech.com.au

