

Casella MicroDust Pro Dust Monitor



Key Features

- Unique real-time graphical display
- Extensive range of 0.001 to 2,500mg/m³
- Removable sampling probe
- Sampling for respirable, PM_{2.5M} and PM₁₀ aerosol contaminants
- Rugged desing and construction

Applications

- Occupational health & safety monitoring
- Walk through surveys
- Site boundary monitoring & environmental measurement
- Industrial process monitoring
- Testing respiratory equipment or air filtration efficiency
- Research activities
- Food & beverage

The ideal rental solution for real-time detection and monitoring of airborne dusts, fumes and aerosols, the MicroDust Pro from Casella boasts a number of innovative features.

Lightweight, accurate, a large LCD screen and the ability to instantly display dust levels and trends, the MicroDust with its choice of ranges and a sensitivity of 0.001mg/m³ is ideal for applications in construction/demolition, pharmaceutical manufacturing, bakeries and mills aswell as general occupational health surveys.

Technical Specification

Title	Values
Sensor Type	Newar forward light scattering infra-red
Range	0 - 2.5, 0 - 25, 0 - 250, 0 - 2,500mg/m ³
Sensitivity	0.001mg/m ³
Zero Stability	+/- 0.002mg/m ³
Memory	64K Eeprom providing 15,700 data points
Logging Intervals	Adjustable from 1 to 600 seconds
Recorded Values	Average, Max/Min concentrations over logging intervals
Serial Interface	RS232
Analogue Output	0 - 2.5V DC FSD
Display	128 x 64pixel LCD graphics with backlight
Operating Temperature	0 - 50°C (non-condensing)
Power	4x AA rechargeable NiCad cells (Alkaline cells optional)
Operating Time	circa 9 hours or circa 20 hours with Alkaline cells

Dimensions



Title	(mm)	(inch)	(kg)	(lb)
	245 x 95 x 50mm	9.6 x 3.7 x 2in	0.97Kg	2.1Lbs

Europe: +44 (0)845 270 2707
www.ashtead-technology.com

