

We measure it.



# Flue gas analyzer for industry

**testo 340 – Portable measuring instrument for industrial emission measurement**

Measuring range extension for unrestricted measurement at high gas concentrations

Flue gas analysis with up to 4 gas sensors – freely configurable

Large selection of probes

Bluetooth interface

Convenient measurement data management

TÜV-tested /EN norm



The handy, easy-to-operate emission measuring instrument testo 340 is the right tool for many different emission measurements. The compact design and the reliable technology make it the ideal measuring instrument for commissioning, service and maintenance work and in test measurements on industrial burners, stationary industrial engines, gas turbines and thermal processes.

The unique measuring range extension allows unrestricted measurements to be carried out even at high gas concentrations. The testo 340 is equipped with an O<sub>2</sub> sensor as standard. Three further gas sensors can be configured individually, in order to be able to adapt the instrument optimally to the respective measurement task. The instrument can also be operated remotely from your Android Smartphone or tablet using the free App.

## Ordering data

### testo 340

testo 340 flue gas analyzer, incl. rechargeable battery, calibration protocol and carrying strap, equipped with O<sub>2</sub> sensor, integrated flow/differential pressure measurement

Part no. 0632 3340



testo 340 must be equipped with a second gas sensor otherwise the analyzer cannot function. Max. 3 additional sensors can be fitted.

| Options                                                           | Part no. |  |
|-------------------------------------------------------------------|----------|--|
| Option CO sensor, 0 to 10000 ppm, Resolution 1 ppm                |          |  |
| Option CO <sub>low</sub> sensor, 0 to 500 ppm, Resolution 0.1 ppm |          |  |
| Option NO sensor, 0 to 4000 ppm, Resolution 1 ppm                 |          |  |
| Option NO <sub>low</sub> sensor, 0 to 300 ppm, Resolution 0.1 ppm |          |  |
| Option NO <sub>2</sub> sensor, 0 to 500 ppm, Resolution 0.1 ppm   |          |  |
| Option: SO <sub>2</sub> sensor, 0 to 5,000 ppm, Resolution 1 ppm  |          |  |
| Option: BLUETOOTH® module                                         |          |  |
| Option: dilution of all sensors                                   |          |  |

| Accessories                                                                                                                                                   | Part no.  |  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|--|
| Transport case for flue gas analyzer and probes                                                                                                               | 0516 3400 |  |
| Mains unit international 100-240 V AC / 6.3 V DC for mains operation or battery charging in instrument, for mains operation or battery charging in instrument | 0554 1096 |  |
| Software "easyEmission", incl. USB connection cable instrument-PC                                                                                             | 0554 3334 |  |
| Multiple license/"easyEmission" software                                                                                                                      | 0554 3338 |  |
| Testo fast printer IrDA with wireless infrared interface; 1 roll thermal paper; 4 AA batteries                                                                | 0554 0549 |  |
| Testo Bluetooth®/IRDA printer incl. 1 roll of printer paper, rechargeable battery and mains unit                                                              | 0554 0620 |  |
| Spare thermal paper for printer, permanent ink                                                                                                                | 0554 0568 |  |
| Spare rechargeable battery with charger                                                                                                                       | 0554 1087 |  |
| Exchangeable filter NO sensor (1 off), blocks cross-gas SO <sub>2</sub>                                                                                       | 0554 4150 |  |
| Replacement filter CO sensor (1 pcs.)                                                                                                                         | 0554 4100 |  |

| Calibration Certificates                                                                                          | Part no.  |  |
|-------------------------------------------------------------------------------------------------------------------|-----------|--|
| ISO calibration certificate/flue gas                                                                              | 0520 0003 |  |
| ISO calibration certificate velocity, hot wire, vane anemometer, Pitot tube; calibration points 5; 10; 15; 20 m/s | 0520 0034 |  |



## Ordering suggestions

### Your low-budget entry into industrial emission measurement

|                                                                             | Part no.  |
|-----------------------------------------------------------------------------|-----------|
| testo 340 flue gas analyzer                                                 | 0632 3340 |
| Option CO (H <sub>2</sub> -compensated) measurement module, 0 to 10,000 ppm |           |
| Option BLUETOOTH® module                                                    |           |
| Flue gas probe modular 335 mm immersion depth                               | 0600 9766 |
| International mains unit 100-240 V                                          | 0554 1096 |
| testo BLUETOOTH® printer                                                    | 0554 0620 |
| Transport case for measuring instrument and probes                          | 0516 3400 |

### Monitoring and adjustment work on stationary industrial engines

|                                                                             | Part no.  |
|-----------------------------------------------------------------------------|-----------|
| testo 340 flue gas analyzer                                                 | 0632 3340 |
| Option CO (H <sub>2</sub> -compensated) measurement module, 0 to 10,000 ppm |           |
| Option NO measurement module, 0 to 4,000 ppm                                |           |
| Option NO <sub>2</sub> measurement module, 0 to 500 ppm                     |           |
| Option dilution of all sensors                                              |           |
| Flue gas probe for industrial engines, 335 mm immersion depth*              | 0600 7560 |
| International mains unit 100-240 V                                          | 0554 1096 |
| Software "easyEmission"                                                     | 0554 3334 |
| Transport case for measuring instrument and probes                          | 0516 3400 |

\* For measurement on stationary diesel engines, we recommend the flue gas probe with probe pre-filter (0600 7561).

### Service and maintenance work on industrial burners and furnaces

|                                                                             | Part no.  |
|-----------------------------------------------------------------------------|-----------|
| testo 340 flue gas analyzer                                                 | 0632 3340 |
| Option CO (H <sub>2</sub> -compensated) measurement module, 0 to 10,000 ppm |           |
| Option NO measurement module, 0 to 4,000 ppm*                               |           |
| Option SO <sub>2</sub> measurement module, 0 to 5,000 ppm                   |           |
| Flue gas probe modular 335 mm immersion depth                               | 0600 8765 |
| Software "easyEmission"                                                     | 0554 3334 |
| Transport case for measuring instrument and probes                          | 0516 3400 |

\*For the measurement of low NO values, we recommend the NOlow sensor (0393 1152).

### Measurements on turbines

|                                                                              | Part no.  |
|------------------------------------------------------------------------------|-----------|
| testo 340 flue gas analyzer                                                  | 0632 3340 |
| Option CO (H <sub>2</sub> -compensated) measurement module, 0 to 10,000 ppm* |           |
| Option NOlow measurement module, 0 to 300 ppm                                |           |
| Option NO <sub>2</sub> measurement module, 0 to 500 ppm                      |           |
| Option dilution of all sensors                                               |           |
| Flue gas probe for industrial engines, 335 mm immersion depth                | 0600 7560 |
| International mains unit 100-240 V                                           | 0554 1096 |
| Software "easyEmission"                                                      | 0554 3334 |
| Transport case for measuring instrument and probes                           | 0516 3400 |

\*For the measurement of low CO values, we recommend the COlow sensor (0393 1102).

# Gas sampling probes

## Standard gas sampling probes: Modular flue gas probes, available in 2 lengths, incl. probe stop, NiCr-Ni thermocouple, 2.2 m hose and particle filter

### Part no.

|                                                                                                                                                                                  |           |  |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|--|
| Modular flue gas probe 335 mm immersion depth, incl. cone, thermocouple NiCr-Ni (TI) Tmax 1000 °C and NO <sub>2</sub> /SO <sub>2</sub> special hose 2.2 m                        | 0600 9766 |  |
| Modular flue gas probe 700 mm immersion depth, incl. cone, thermocouple NiCr-Ni (TI) Tmax 500 °C and NO <sub>2</sub> /SO <sub>2</sub> special hose 2.2 m                         | 0600 9767 |  |
| Modular flue gas probe 335 mm immersion depth, incl. cone, thermocouple NiCr-Ni (TI) Tmax 1000 °C and NO <sub>2</sub> /SO <sub>2</sub> special hose 2.2 m                        | 0600 8764 |  |
| Modular flue gas probe, 700 mm immersion depth, incl. cone, thermocouple NiCr-Ni (TI) Tmax 1000 °C and NO <sub>2</sub> /SO <sub>2</sub> special hose 2.2 m                       | 0600 8765 |  |
| Modular flue gas probe with pre-filter Ø 14 mm 335 mm immersion depth, incl. cone, thermocouple NiCr-Ni (TI) Tmax 1000°C and NO <sub>2</sub> /SO <sub>2</sub> special hose 2.2 m | 0600 8766 |  |
| Modular flue gas probe with pre-filter Ø 14 mm 700 mm immersion depth, incl. cone, thermocouple NiCr-Ni (TI) Tmax 1000°C and NO <sub>2</sub> /SO <sub>2</sub> special hose 2.2 m | 0600 8767 |  |

## Probe accessories modular gas sampling probes

### Part no.

|                                                                                    |           |  |
|------------------------------------------------------------------------------------|-----------|--|
| Hose extension; 2.8 m; extension cable for probe                                   | 0554 1202 |  |
| Probe shaft with pre-filter, length 335 mm, incl. probe stop, Ø 8 mm, Tmax 1000 °C | 0600 3333 |  |
| Probe shaft with pre-filter, length 700 mm, incl. probe stop, Ø 8 mm, Tmax 1000 °C | 0600 3333 |  |
| Spare sintered filter, 2 off                                                       | 0554 3372 |  |
| Spare dirt filter, modular probe; 10 off                                           | 0554 3385 |  |
| Probe shaft, length 700 mm, incl. cone, Ø 8 mm, Tmax 500 °C                        | 0554 9767 |  |
| Probe shaft, length 335 mm, incl. cone, Ø 8 mm, Tmax 1000 °C                       | 0554 8764 |  |
| Probe shaft, length 700 mm, incl. cone, Ø 8 mm, Tmax. 1000 °C                      | 0554 8765 |  |

## Gas sampling probe for measurement on industrial engines

### Part no.

|                                                                                                                                                                                                                                                        |           |  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|--|
| Flue gas probe for industrial engines, 335 mm immersion probe incl. cone, integrated condensate trap and heat protection plate, Tmax 1000 °C, special hose for NO <sub>2</sub> /SO <sub>2</sub> measurements, length 2.2 m                             | 0600 7560 |  |
| Flue gas probe for industrial engines with probe shaft prefilter, immersion depth 335 mm, incl. cone, integrated condensate trap and heat protection plate, Tmax 1000 °C, special hose for NO <sub>2</sub> /SO <sub>2</sub> measurements, length 2.2 m | 0600 7561 |  |
| Thermocouple for exhaust gas temperature measurement, NiCr-Ni, length 400 mm, Tmax. +1000 °C with 2.4 m connection cable and additional temperature protection                                                                                         | 0600 8894 |  |
| Spare particle filter (10 off) for condensate trap in gas sampling hose                                                                                                                                                                                | 0554 3371 |  |

## Temperature probes

### Part no.

|                                                                                       |           |  |
|---------------------------------------------------------------------------------------|-----------|--|
| Mini ambient air probe; for separate ambient air temperature measurement; 0 to +80 °C | 0600 3692 |  |
| Combustion air temperature probe, immersion depth 60 mm                               | 0600 9797 |  |

## Pitot tubes

### Part no.

|                                                                                                                        |           |  |
|------------------------------------------------------------------------------------------------------------------------|-----------|--|
| Pitot tube, 350 mm long, stainless steel, measures flow velocity                                                       | 0635 2145 |  |
| Pitot tube, 1000 mm long, stainless steel, measures flow velocity                                                      | 0635 2345 |  |
| Connection hose; silicone; 5 m long; max. load 700 hPa (mbar)                                                          | 0554 0440 |  |
| Pitot tube, stainless steel, 750 mm long, measures flow velocity with temperature, 3x hoses (5 m long) and heat shield | 0635 2042 |  |

# Gas sampling probes

| Industrial probes                                                                                                                                                                                                                                                                                                                      | Details                                                                                                                                                                                                                                                                                                                                                                                                          | Part no.   |  |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|--|
| Industrial probe set 1200 °C<br>consisting of:<br>- unheated handle<br>- unheated probe shaft up to 1200 °C flue gas temperature<br>- unheated gas sampling hose incl. inline filter, length 4 m<br>- thermocouple Type K, length 1.2 m<br><br><i>The set can optionally come with an extension tube and probe preliminary filter.</i> | <b>Probe shaft:</b> T <sub>max.</sub> +1200 °C<br>Length 1.0 m, Ø 12 mm<br>Material 2.4856 alloy 625<br><b>Handle:</b> T <sub>max.</sub> +600 °C<br>Material: 1.4404 stainless steel<br><b>Gas sampling hose:</b> 2-chamber hose with PTFE inner core; length 4.0 m<br><b>TC:</b> Type K,<br>Length 1.2 m, Ø 2 mm<br>T <sub>max.</sub> +1200 °C                                                                  | 0600 7610  |  |
| Industrial probe set 1800 °C<br>consisting of:<br>- unheated handle<br>- unheated probe shaft up to 1800 °C flue gas temperature<br>- unheated gas sampling hose incl. inline filter, length 4 m<br><br><i>For temperature measurements &gt; +1370 °C, we recommend a thermocouple Type S.</i>                                         | <b>Probe shaft:</b> T <sub>max.</sub> +1800 °C<br>Material Al2O3 > 99.7%<br>Length 1.0 m, Ø 12 mm<br><b>Gas sampling hose:</b> 2-chamber hose with PTFE inner core; length 4.0 m<br><b>Handle:</b> T <sub>max.</sub> +600 °C<br>Material: 1.4404 stainless steel                                                                                                                                                 | 0600 7620  |  |
| Heated industrial probe set<br>consisting of:<br>- heated probe shaft up to 600 °C flue gas temperature<br>- heated gas sampling hose, length 4 m<br>- thermocouple Type K, length 1.2 m<br><br><i>The set can optionally come with an extension tube and probe preliminary filter.</i>                                                | <b>Probe shaft:</b> temperature-proof up to +600 °C<br>Voltage supply 230 V / 50 Hz<br>Length 1.0 m, Ø 25 mm<br>Heating temperature range +200 °C<br>Material stainless steel 1.4571<br><b>Gas sampling hose:</b> corrugated hose with PTFE inner core<br>Length 4.0 m; outside diameter 34 mm<br>Heating temperature range > +120 °C<br><b>TC:</b> Type K<br>Length 1.2 m, Ø 2 mm<br>T <sub>max.</sub> +1200 °C | 0600 7630  |  |
| Extension tube 1200 °C for extending the industrial probe set 1200 °C (0600 7610) and heated industrial probe set (0600 7630)<br><br><i>The extension tube can be screwed directly onto the unheated probe shaft up to +1200 °C and the heated probe shaft up to +600 °C.</i>                                                          | <b>Probe shaft:</b> T <sub>max.</sub> +1200 °C<br>Length 1.0 m, Ø 12 mm<br>Material 2.4856 alloy 625                                                                                                                                                                                                                                                                                                             | 0600 7617  |  |
| Thermocouple Type K, length 2.2 m                                                                                                                                                                                                                                                                                                      | Type K<br>Length 2.2 m, Ø 2 mm<br>T <sub>max.</sub> +1200 °C                                                                                                                                                                                                                                                                                                                                                     | 0600 7615  |  |
| Industrial probe preliminary filter for dust-laden flue gas<br><br><i>The probe preliminary filter can be screwed directly onto the unheated probe shaft up to +1200 °C and the heated probe shaft up to +600 °C.</i>                                                                                                                  | Material porous silicon carbide<br>T <sub>max.</sub> +1,000 °C,<br>Length 105 mm, Ø 30 mm<br>Filtration grade 10 µm                                                                                                                                                                                                                                                                                              | 0600 7616  |  |
| Heated gas sampling hose                                                                                                                                                                                                                                                                                                               | Corrugated hose with PTFE inner core<br>Length 4.0 m; outside diameter 34 mm<br>Heating temperature range > +120 °C                                                                                                                                                                                                                                                                                              | on request |  |
| Transport case for probes<br><i>Suitable for all probes with a total length &gt; 335 mm.</i>                                                                                                                                                                                                                                           |                                                                                                                                                                                                                                                                                                                                                                                                                  | 0516 7600  |  |
| Extension cable, 5 m long, between plug-in head cable and instrument                                                                                                                                                                                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                  | 0409 0063  |  |

## Technical data

|                                                                        | Measuring range           | Accuracy $\pm 1$ digit                                                                                                                                                                       | Resolution  | Adjustment time $t_{90}$ |
|------------------------------------------------------------------------|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|--------------------------|
| <b>O<sub>2</sub> measurement</b>                                       | 0 to 25 Vol. %            | $\pm 0.2$ Vol. %                                                                                                                                                                             | 0.01 Vol. % | <20 sec                  |
| <b>CO measurement (H<sub>2</sub> compensated)</b>                      | 0 to 10.000 ppm           | $\pm 10$ ppm or $\pm 10\%$ of m.v. (0 to 200 ppm)<br>$\pm 20$ ppm or $\pm 5\%$ of m.v. (201 to 2.000 ppm)<br>$\pm 10\%$ of m.v. (2.001 to 10.000 ppm)                                        | 1 ppm       | <40 sec                  |
| <b>CO<sub>low</sub> measurement (H<sub>2</sub> compensated)</b>        | 0 to 500 ppm              | $\pm 2$ ppm (0 to 39.9 ppm)<br>$\pm 5\%$ of m.v. (remaining range)*<br><small>* data corresponds to 20°C ambient temperature. Additional temperature coefficient 0.25% of reading/K.</small> | 0.1 ppm     | <40 sec                  |
| <b>NO measurement</b>                                                  | 0 to 4.000 ppm            | $\pm 5$ ppm (0 to 99 ppm)<br>$\pm 5\%$ of m.v. (100 to 1.999 ppm)<br>$\pm 10\%$ of m.v. (2.000 to 4.000 ppm)                                                                                 | 1 ppm       | <30 sec                  |
| <b>NO<sub>low</sub> measurement</b>                                    | 0 to 300 ppm              | $\pm 2$ ppm (0 to 39.9 ppm)<br>$\pm 5\%$ of m.v. (remaining range)                                                                                                                           | 0.1 ppm     | <30 sec                  |
| <b>NO<sub>2</sub> measurement*</b>                                     | 0 to 500 ppm              | $\pm 10$ ppm (0 to 199 ppm)<br>$\pm 5\%$ of m.v. (remaining range)                                                                                                                           | 0.1 ppm     | <40 sec                  |
| <b>SO<sub>2</sub> measurement*</b>                                     | 0 to 5.000 ppm            | $\pm 10$ ppm (0 to 99 ppm)<br>$\pm 10\%$ of m.v. (remaining range)                                                                                                                           | 1 ppm       | <40 sec                  |
| <b>Temperature meas.</b><br><small>Probe type Type K (NiCr-Ni)</small> | -40 to +1.200 °C          | $\pm 0.5$ °C (0 to +99 °C)<br>$\pm 0.5$ % of m.v. (remaining range)                                                                                                                          | 0.1 °C      |                          |
| <b>Draught measurement</b>                                             | -40 to +40 hPa            | $\pm 0.03$ hPa (-2.99 to +2.99 hPa)<br>$\pm 1.5$ % of m.v. (remaining range)                                                                                                                 | 0.01 hPa    |                          |
| <b>Differential pressure measurement</b>                               | -200 to 200 hPa           | $\pm 0.5$ hPa (-49.9 to 49.9 hPa)<br>$\pm 1.5$ % of m.v. (remaining range)                                                                                                                   | 0.1 hPa     |                          |
| <b>Absolute pressure measurement</b>                                   | 600 to +1.150 hPa         | $\pm 10$ hPa                                                                                                                                                                                 | 1 hPa       |                          |
| <b>Derived parameters</b>                                              |                           |                                                                                                                                                                                              |             |                          |
| Efficiency                                                             | 0 to 120 %                |                                                                                                                                                                                              | 0.1 %       |                          |
| Flue gas loss                                                          | 0 to 99.9 %               |                                                                                                                                                                                              | 0.1 %       |                          |
| Exhaust gas dewpoint                                                   | 0 to 99.9 °C              |                                                                                                                                                                                              | 0.1 °C      |                          |
| <b>CO<sub>2</sub> measurement</b><br>(Calculated from O <sub>2</sub> ) | 0 to CO <sub>2</sub> max. | $\pm 0.2$ Vol. %                                                                                                                                                                             | 0.1 Vol. %  | < 40 sec                 |

\*To avoid absorption, a maximum measurement duration of 2 hours should not be exceeded.



### Country permits BLUETOOTH® wireless transmission for testo 340

The BLUETOOTH® radio module used by Testo is permitted for the following countries and may only be used in those countries, i.e. the BLUETOOTH® wireless transmission may not be used in any other country!

### Europe including all EU member states

Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Great Britain, Greece, Hungary, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden and Turkey

### European countries (EFTA)

Iceland, Liechtenstein, Norway, Switzerland

### Non-European countries

Canada, USA, Japan, Ukraine, Australia, Columbia, El Salvador, Mexico, Venezuela, Ecuador, New Zealand, Bolivia, Dominican Republic, Peru, Chile, Cuba, Costa Rica, Nicaragua, Korea, Belarus.

# Technical data

## Measuring range extension

| Single dilution, factor 5 (standard)                            | Measuring range       | Accuracy                         | Resolution |
|-----------------------------------------------------------------|-----------------------|----------------------------------|------------|
| <b>CO measurement (H<sub>2</sub> compensated)</b>               | 700 ppm to 50.000 ppm | ±10 % of m.v. (additional error) | 1 ppm      |
| <b>CO<sub>low</sub> measurement (H<sub>2</sub> compensated)</b> | 300 ppm to 2.500 ppm  | ±10 % of m.v. (additional error) | 0.1 ppm    |
| <b>NO measurement</b>                                           | 500 ppm to 20.000 ppm | ±10 % of m.v. (additional error) | 1 ppm      |
| <b>NO<sub>low</sub> measurement</b>                             | 150 ppm to 1.500 ppm  | ±10 % of m.v. (additional error) | 0,1 ppm    |
| <b>SO<sub>2</sub> measurement</b>                               | 500 ppm to 25.000 ppm | ±10 % of m.v. (additional error) | 1 ppm      |

## Dilution of all sensors, factor 2 (option, Part no. 0440 3350)

|                                                                 |                                                                                 |                                                                                                  |             |
|-----------------------------------------------------------------|---------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|-------------|
| <b>O<sub>2</sub> measurement</b>                                | When measuring range extension switched on, over all sensors:<br>0 to 25 Vol. % | ±1 Vol.% additional error<br>(0 to 4.99 Vol.%)<br>±0.5 Vol.% additional error<br>(5 to 25 Vol.%) | 0.01 Vol. % |
| <b>CO measurement (H<sub>2</sub> compensated)</b>               | 700 ppm to 20.000 ppm                                                           | ±10 % of m.v. (additional error)                                                                 | 1 ppm       |
| <b>CO<sub>low</sub> measurement (H<sub>2</sub> compensated)</b> | 300 ppm to 1.000 ppm                                                            | ±10 % of m.v. (additional error)                                                                 | 0.1 ppm     |
| <b>NO measurement</b>                                           | 500 ppm to 8.000 ppm                                                            | ±10 % of m.v. (additional error)                                                                 | 1 ppm       |
| <b>NO<sub>low</sub> measurement</b>                             | 150 ppm to 600 ppm                                                              | ±10 % of m.v. (additional error)                                                                 | 0.1 ppm     |
| <b>NO<sub>2</sub> measurement</b>                               | 200 ppm to 1.000 ppm                                                            | ±10 % of m.v. (additional error)                                                                 | 0.1 ppm     |
| <b>SO<sub>2</sub> measurement</b>                               | 500 ppm to 10.000 ppm                                                           | ±10 % of m.v. (additional error)                                                                 | 1 ppm       |

## General technical data

|                                                                                                                |                                                                                                                          |
|----------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| Memory<br>Maximum<br>Per folder<br>Per site                                                                    | 100 folders<br>Max. 10 sites<br>Max. 200 logs<br>The max. number of logs is determined by the number of folders or sites |
| User-defined fuels                                                                                             | 10 user-defined fuels incl. test gas as fuel                                                                             |
| Regulated diaphragm pump<br>Pump flow<br>Hose length<br>Max. pos. press./flue gas<br>Max. neg. press./flue gas | 0.6 l/min (regulated)<br>max. 7.8 m (corresponds to two probe hose extensions)<br>+50 mbar<br>-200 mbar                  |
| Weight                                                                                                         | 960 g                                                                                                                    |
| Dimensions                                                                                                     | 283 x 103 x 65 mm                                                                                                        |
| Storage temperature                                                                                            | -20 to +50 °C                                                                                                            |
| Operating temperature                                                                                          | -5 to +50 °C                                                                                                             |

|                        |                                                                                                                                    |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| Display                | Graphic display 160 x 240 pixels                                                                                                   |
| Power supply           | Battery block 3.7 V / 2.4 Ah<br>Mains unit 6.3 V / 2 A                                                                             |
| Housing material       | TPE PC                                                                                                                             |
| Protection class       | IP40                                                                                                                               |
| Warranty<br>Analyzer   | 2 years (excluding working parts, e.g. sensors, sensor replacement filter)                                                         |
| Rech. batt.<br>Sensors | 1 year<br>CO, NO, CO <sub>low</sub> , NO <sub>low</sub> , NO <sub>2</sub> , SO <sub>2</sub> : 1 year<br>O <sub>2</sub> : 1.5 years |

