

We measure it.



Temperature measuring instrument (1-channel)

testo 720

Ideally suitable for applications in laboratories and industry

Continuous display of min./max. values

Audible alarm (adjustable limit values)

Resistant to aggressive media with TopSafe

Hold-button for freezing measurement display

Large illuminated display

Measurement data printout on site with Testo fast printer



The testo 720 is a robust temperature measuring instrument for precise air, surface and immersion measurements in the measuring range from -100 to +800 °C. It is possible to connect Pt100 probes as well as NTC probes to the one-channel measuring instrument.

In combination with the TopSafe, the testo 720 is resistant to aggressive media – as is the glass-coated probe, which has proven its worth in daily laboratory work.

You, as the user, can store limit values in the instrument yourself; as soon as these upper or lower limits are violated, an audible alarm sounds. The instrument also continuously shows all minimum and maximum values in its large backlit display. Using the optional Testo report printer, the measurement results can be directly printed out on site as required.

www.testo.com

Technical data / Accessories

testo 720

testo 720, 1 channel temperature measuring instrument Pt100/NTC, with battery and calibration protocol

Part no. 0560 7207



General technical data

Oper. temp.	-20 to +50 °C
Storage temp.	-30 to +70 °C
Battery type	9V block battery
Battery life	70 h
Dimensions	182 x 64 x 40 mm
Weight	171 g
Material/Housing	ABS
Warranty	2 years

Sensor types

	Pt100	NTC
Meas. range	-100 to +800 °C	-50 to +150 °C
Accuracy ±1 digit	±0.2% of mv (+200 to +800 °C) ±0.2 °C (remaining range)	±0.2 °C (-25 to +40 °C) ±0.3 °C (+40.1 to +80 °C) ±0.4 °C (+80.1 to +125 °C) ±0.5 °C (remaining range)
Resolution	0.1 °C	0.1 °C




Accessories

Part no.

Accessories for measuring instrument

9V rech. battery for instrument, instead of battery	0515 0025	
Recharger for 9V rechargeable battery for external recharging of 0515 0025 battery	0554 0025	
Testo fast printer with wireless infrared interface, 1 roll thermal paper and 4 AA batteries	0554 0549	
Spare thermal paper for printer (6 rolls), permanent ink	0554 0568	
TopSafe, protects from impact and dirt (incl. 2 attachment magnets)	0516 0221	
Case for measuring instrument and probes	0516 0210	
Transport case for meas. instr. and probes (405 x 170 x 85 mm)	0516 0201	
Transport case for measuring instrument, 3 probes and accessories (430 x 310 x 85 mm)	0516 0200	
Silicone heat paste (14g), Tmax = +260°C improves heat transfer in surface probes	0554 0004	
ISO calibration certificate/temperature for air/immersion probes, calibration points -18°C; 0°C; +60°C	0520 0001	
ISO calibration certificate/temperature Meas. instr. with air/immersion probe; cal. points 0°C; +150°C; +300°C	0520 0021	
ISO calibration certificate/temperature meas. instr. with air/immersion probe; calibration points 0°C; +300°C; +600°C	0520 0031	
DAkkS calibration certificate/temperature meas. instr. with air/immersion probe; calibration points -20 °C; 0 °C; +60 °C	0520 0211	
ISO calibration certificate/temperature meas. instr. with surface probe; calibration points +60°C; +120°C; +180°C	0520 0071	
DAkkS calibration certificate/temperature contact surface temperature probes; calibration points +100°C; +200°C; +300°C	0520 0271	




Probes

Probe type	Dimensions Probe shaft/probe shaft tip	Measuring range	Accuracy	t ₉₉	Part no.
Laboratory probes					
Laboratory probe Pt100, glass-coated, exchangeable glass pipe (Duran 50), resistant to corrosive substances, Fixed cable		-50 to +400 °C	Class A (-50 to +300 °C), Class B (remaining range) ¹⁾	45 s 12 s ¹⁾	0609 7072
Air probes					
Efficient, robust NTC air probe, Fixed cable 1.2 m		-50 to +125 °C	±0.2 °C (-25 to +80 °C) ±0.4 °C (remaining range)	60 s	0613 1712
Efficient, robust air probe, Pt100, Fixed cable		-50 to +400 °C	Class A (-50 to +300 °C), Class B (remaining range) ¹⁾	70 s	0609 1773
Surface probes					
Waterproof NTC surface probe for flat surfaces, Fixed cable 1.2 m		-50 to +150 °C	±0.5% of mv (+100 to +150 °C) ±0.2 °C (-25 to +74.9 °C) ±0.4 °C (remaining range)	35 s	0613 1912
Pipe wrap probe with Velcro for pipe diameter to max. 75 mm, Tmax. +75°C, NTC		-50 to +70 °C	±0.2 °C (-25 to +70 °C) ±0.4 °C (-50 to -25.1 °C)	60 s	0613 4611
Robust, waterproof surface temperature probe, Pt100, Fixed cable		-50 to +400 °C	Class B ¹⁾	40 s	0609 1973
Immers./penetr. probes					
Waterproof NTC immersion/penetration probe, Fixed cable		-50 to +150 °C	±0.5% of mv (+100 to +150 °C) ±0.2 °C (-25 to +74.9 °C) ±0.4 °C (remaining range)	10 s	0613 1212
Robust, waterproof Pt100 immersion/penetration probe, Fixed cable		-50 to +400 °C	Class A (-50 to +300 °C), Class B (remaining range) ¹⁾	12 s	0609 1273

◆ The measuring instrument inside TopSafe is waterproof with this probe.

1) According to standard 60751, the accuracies of Class A and B refer to -200 to +600 °C (Pt100)

Probes

Probe type	Dimensions Probe shaft/probe shaft tip	Measuring range	Accuracy	t ₉₉	Part no.
Food probes					
Stainless steel NTC food probe (IP65) with PUR cable, Fixed cable		-50 to +150 °C ²⁾	±0.5% of mv (+100 to +150 °C) ±0.2 °C (-25 to +74.9 °C) ±0.4 °C (remaining range)	8 s	0613 2211
Stainless steel NTC food probe (IP67) with PTFE cable to +250°C, Fixed cable		-50 to +150 °C	±0.5% of mv (+100 to +150 °C) ±0.2 °C (-25 to +74.9 °C) ±0.4 °C (remaining range)	8 s	0613 3311
Robust NTC food penetration probe with special handle, reinforced PUR cable, Fixed cable		-25 to +150 °C ²⁾	±0.5% of mv (+100 to +150 °C) ±0.2 °C (-25 to +74.9 °C) ±0.4 °C (remaining range)	7 s	0613 2411
Frozen food probe NTC, corkscrew design (incl. plug-in wire), Plug-in cable		-50 to +140 °C ²⁾	±0.5% of mv (+100 to +140 °C) ±0.2 °C (-25 to +74.9 °C) ±0.4 °C (remaining range)	20 s	0613 3211
Robust, Pt100 stainless steel food probe (IP65), Fixed cable		-50 to +400 °C	Class A (-50 to +300 °C), Class B (remaining range) ¹⁾	10 s	0609 2272

- ◆ The measuring instrument inside TopSafe is waterproof with this probe.
 1) According to standard 60751, the accuracies of Class A and B refer to -200 to +600 °C (Pt100)
 2) Long-term measurement range +125°C, short-term +150°C or +140°C (2 minutes)