

# Smoke tester

## testo 308

---

Easy, self-explanatory menu structure

---

Clear segment display

---

LED display illumination

---

Easy IR printout

---

TÜV-tested

---

Bluetooth interface (optional)

---

Easy exchange of soot filter roll

---

Spare battery chargeable separately or in instrument

---

Protection class IP40

---



The measuring instrument testo 308 is designed for easy electronic smoke count measurement. It determines the smoke count to one decimal position by constant sampling. The powerful LED backlighting guarantees good legibility even in unfavourable light conditions.

The Li-ion rechargeable battery in the testo 308 can also be used in the Testo flue gas analyzers (testo 327 and testo

330). Thanks to the easy menu structure and the ergonomic pistol grip, the measuring instrument is especially user-friendly. testo 308 achieves a high level of accuracy due to the heating of the measurement spot, thus preventing measurement errors caused by condensation. In addition to this, the infrared interface allows wireless communication with an IrDA printer, a flue gas analyzer and a Pocket PC.

## Smoke tester



High accuracy – the heated measurement spot prevents measurement errors caused by condensation



Infrared interface – time saving thanks to automatic analysis and digital transfer of measurement values



Fast and easy exchange of Li-ion rechargeable batteries



The integrated condensate trap can be emptied

### testo 308

testo 308 smoke tester, incl. rech. battery and calibration protocol for measuring soot count

Part no. 0632 0308



### Set testo 308

Set testo 308 smoke tester incl. mains unit and bag

Part no. 0563 3080

### testo 308 / BLUETOOTH®

testo 308 smoke tester with BLUETOOTH interface, incl. rech. battery and calibration protocol for measuring soot count

Part no. 0632 0309

## Technical data / Accessories

| Sensor type          | Photodiode |
|----------------------|------------|
| Meas. range          | 0 to 6 RZ  |
| Accuracy<br>±1 digit | ±0.2 RZ    |
| Resolution           | 0.1 RZ     |

### General technical data

|                       |                                                           |
|-----------------------|-----------------------------------------------------------|
| Pump capacity         | 1.63 ± 0.1 l                                              |
| Reference filter      | at 990 mbar and +20 °C ambient temperature                |
| Weight                | 600 g incl. battery                                       |
| Dimensions            | 270 x 63 x 120 mm                                         |
| Rech. battery         | Lithium ion battery, 2600 mA                              |
| Battery life          | 45 individual measurements                                |
| Battery charge        | in the instrument via mains unit or externally by charger |
| Display               | Segment display with background illumination              |
| Norms and tests       | 1. BlmSchV, METAS, EU-guideline 2004/108/EG               |
| Operating temperature | 0 to +40 °C                                               |
| Storage temperature   | -20 to +50 °C                                             |
| Protection class      | IP40                                                      |
| Interfaces            | IR/IRDA interface, BLUETOOTH® 1)                          |
| Gas sampling          | Stainless steel pipe ca. 220 mm, rubber hose 100 mm       |
| Warranty              | 2 years                                                   |

1) Country permits: The BLUETOOTH® wireless module used by Testo has permits for the following listed countries, and can only be used in those countries, i. e. BLUETOOTH® wireless transfer may not be used in any other country! Europe including all EU member states: Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Great Britain, Greece, Hungary, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden and Turkey; European countries (EFTA): Iceland, Liechtenstein, Norway and Switzerland; Non-European countries: Ukraine, Colombia and El Salvador.

| Accessories for measuring instrument                                                                   | Part no.  |  |
|--------------------------------------------------------------------------------------------------------|-----------|--|
| Instrument bag for smoke tester testo 308                                                              | 0516 0002 |  |
| Mains unit international 100-240 V AC / 6.3 V DC for mains operation or battery charging in instrument | 0554 1096 |  |
| Spare battery 2600 mA                                                                                  | 0515 0107 |  |
| Spare soot filter paper; 8 paper rolls                                                                 | 0554 0146 |  |
| Spare dirt filters testo 308, 10 off                                                                   | 0554 1101 |  |
| Cone with fixing screw                                                                                 | 0554 9010 |  |
| Testo fast printer IRDA with wireless infrared interface; 1 roll thermal paper; 4 AA batteries         | 0554 0549 |  |
| Basic system case testo 330-1/-2 LL for analyzer, probes and accessories                               | 0516 3330 |  |



0981 2674/msp/A/01.2014

Subject to change without notice.

