HB-60 Packaged Booster Set - Technical Datasheet

The HB-60 is a packaged booster set with two vertical multistage pumps in duty/standby configuration, a variable speed controller and a pressure vessel.

Technical data

Parameter	Value
Pumps	2 x 11 kW vertical multistage
Rated flow	60 m3/h
Rated discharge pressure	8.5 bar
Maximum inlet pressure	4 bar
Pressure vessel	300 litres
Supply voltage	400 V three-phase 50 Hz
Enclosure rating	IP55

Controller alarms

Code	Description	Controller action
AL-03	Low inlet pressure	Trips both pumps when inlet pressure stays below 0.5 bar for 10 seconds; automatic restart
AL-07	High discharge pressure	Trips both pumps above 10.5 bar; manual reset
AL-12	Pump 1 overload	Stops pump 1 and starts pump 2; manual reset
AL-13	Pump 2 overload	Stops pump 2 and starts pump 1; manual reset
AL-21	Pressure sensor fault	Runs one pump at fixed speed of 40 Hz
AL-30	Communication loss	Warning only; the set keeps running on local set-point

Routine maintenance

Check the pressure vessel pre-charge every 6 months: it must be 0.9 times the pressure set-point, measured with the vessel empty.

Swap duty and standby pumps manually every 3 months if automatic alternation is disabled. A full inspection by the manufacturer is recommended every 12 months.