# **LARAVEL**

# **Migrations**

### --> Client (1)

## --> Order (M)

```
In [2]:
```

```
public function up(): void
{
    Schema::create('orders', function (Blueprint $\$table) {
        $\$table->id();
        $\$table->string("object");
        $\$table->unsignedBigInteger("client_id");
        $\$table->timestamps();
        $\$table->foreign("client_id")->references("id")->on("clients")->onDelete("cascade");
    });
}
```

# **Models**

## --> Client (1)

```
In [ ]:
```

```
class Client extends Model
{
    use HasFactory;
    protected $\fillable = ["name", "lastname", "age"];

    public function orders()
    {
        return $\frac{1}{2}$this->hasMany(Order::class);
    }
}
```

}

### --> Order (M)

```
class Order extends Model
{
    use HasFactory;
    protected $fillable = ["object", "client_id"];

    public function client()
    {
        return $this->belongTo(Client::class);
    }
}
```

## **Views**

## welcome.blade.php

## --> Client (1)

```
In [ ]:
```

</html>

```
<html>
   <body>
       <h2>Index</h2>
       @foreach($clients as $c)
            Name: { { $ c->name } } 
            <button formaction="{{route('clients.show', $c->id)}}" method="GET">Show</bu</pre>
tton>
            <button formaction="{{route('clients.edit', $c->id)}}" method="GET">Edit</bu</pre>
tton>
       </form>
       @endforeach
        <br>
        <form action="{{route('clients.create')}}" method="GET">
            <button>Create new client
        </form>
       <br><a href="../"><button>Back to Welcome</button></a>
   </body>
</html>
```

```
In [ ]:
```

#### In [ ]:

```
<html>
   <body>
       <h2>Show</h2>
       ID: {{ $c->id}}
       Name: { { <math> c-> name } } 
       Lastname: {{$c->lastname}}
       Age: {{ $c->age}}
       <br>
       <form action="{{route('clients.destroy', $c->id)}}" method="POST">
           @csrf
           @method("DELETE")
           <button>Delete
       </form>
       <a href="{{route('clients.index')}}"><button>Back to home</button></a>
   </body>
</html>
```

#### In [ ]:

# --> Order (M)

#### In [ ]:

#### In [ ]:

#### In [ ]:

#### In [ ]:

# **Controllers**

### web.php

```
In []:
Route::resource("orders", OrderController::class);
Route::resource("clients", ClientController::class);
```

## --> Client (1)

```
In [ ]:
```

```
class ClientController extends Controller
   public function index()
       return view("clients.index", ["clients" => Client::all()]);
   public function create()
       return view("clients.create");
   public function store(Request $request)
       Client::create($request->all());
       return redirect() ->route("clients.index");
   public function show(Client $client)
       return view("clients.show", ["c" => $client]);
   public function edit(Client $client)
       return view("clients.edit", ["c" => $client]);
   public function update(Request $request, Client $client)
       $client->update($request->all());
       return redirect() ->route("clients.index");
   public function destroy(Client $client)
        $client->delete();
       return redirect() -> route("clients.index");
```

## --> Order (M)

```
In [ ]:
```

```
class OrderController extends Controller
{
   public function index()
```

```
return view("orders.index", ["orders" => Order::all()]);
public function create()
    return view("orders.create", ["clients" => Client::all()]);
public function store(Request $\frac{\partial}{2}\) request)
    Order::create($request->all());
    return redirect() ->route("orders.index");
public function show(Order $order)
   return view("orders.show", ["o" => $order]);
public function edit(Order $order)
    return view("orders.edit", ["o" => $order, "clients" => Client::all()]);
public function update(Request $ request, Order $ order)
    $order->update($request->all());
    return redirect() ->route("orders.index");
public function destroy(Order $order)
    $order->delete();
    return redirect() -> route("orders.index");
```