

**Washington State University**  
**CPT\_S 415 – Big Data**  
**Online**

Srinivasulu Badri

**Assignment 3**

Name: Nam Jun Lee

Student Number: 11606459

## 1. [RDF]

a. Consider a set of natural language sentences collected from Web pages.

- i. A human can like another human.
- ii. A human can have a gender property of a male, female or non-binary.
- iii. A human can be the father of another human.
- iv. A human can be the mother of another human.
- v. A human can be married to another human.
- vi. A human can have a Birth Year property of type "xs:Year".
- vii. If a human is married to another, then they like each other.
- viii. If a human is a mother or father, the human is a parent.

Write a RDF schema and give a graphical presentation to describe these relationships.

RDF schema:

```
<rdfs:Class rdf:ID="Human">
```

```
<rdfs:comment>
```

The class of Human.

Superclass of Man, Woman, NonBinary, Year classes

```
</rdfs:comment>
```

```
</rdfs:Class>
```

```
<rdfs:Class rdf:ID="AnotherHuman">
```

```
<rdfs:comment>
```

The class of AnotherHuman

This class represents other human

```
</rdfs:comment>
```

```
</rdfs:Class>
```

```
<rdfs:Class rdf:ID="Male">
```

```
<rdfs:comment>
```

The class of Man

Subclass of Human

</rdfs:comment>

<rdfs:subClassOf rdf:resource="#Human"/>

</rdfs:Class>

<rdfs:Class rdf:ID="Female">

<rdfs:comment>

The class of Female

Subclass of Human

</rdfs:comment>

<rdfs:subClassOf rdf:resource="#Human"/>

</rdfs:Class>

<rdfs:Class rdf:ID="NonBinary">

<rdfs:comment>

The class of NonBinary

Subclass of Human

</rdfs:comment>

<rdfs:subClassOf rdf:resource="#Human"/>

</rdfs:Class>

<rdfs:Class rdf:ID="Year">

<rdfs:comment>

The class of Year

Birth Year for Human

Subclass of Human

</rdfs:comment>

<rdfs:subClassOf rdf:resource="#Human"/>

</rdfs:Class>

<rdf:Property rdf:ID="canLike">

```
<rdfs:comment>
```

Inherits its domain ("Human") and range ("AnotherHuman")  
from its superproperty "isMarried"

```
</rdfs:comment>
```

```
<rdfs:domain rdfs:resource="#Human" />
```

```
<rdfs:range rdfs:resource="#AnotherHuman" />
```

```
<rdfs:subPropertyOf rdfs:resource="#isMarried" />
```

```
</rdf:Property>
```

```
<rdf:Property rdf:ID="canBe">
```

```
<rdfs:domain rdfs:resource="#Human" />
```

```
<rdfs:range rdfs:resource="#Man" />
```

```
<rdfs:range rdfs:resource="#Woman" />
```

```
<rdfs:range rdfs:resource="#NonBinary" />
```

```
</rdf:Property>
```

```
<rdf:Property rdf:ID="isMarried">
```

```
<rdfs:domain rdfs:resource="#Human" />
```

```
<rdfs:range rdfs:resource="#AnotherHuman" />
```

```
</rdf:Property>
```

```
<rdf:Property rdf:ID="isMotherOf">
```

```
<rdfs:comment>
```

Inherits its domain ("Woman") and range ("AnotherHuman")

Inherits its domain ("NonBinary") and range ("AnotherHuman")

from its superproperty "isParent"

```
</rdfs:comment>
```

```
<rdfs:domain rdfs:resource="#Woman" />
```

```
<rdfs:domain rdfs:resource="#NonBinary" />
```

```
<rdfs:range rdfs:resource="#AnotherHuman" />
```


```
<rdfs:subPropertyOf rdfs:resource="#isParentOf" />
</rdf:Property>
```

```
<rdf:Property rdf:ID="isFatherOf">
  <rdfs:comment>
    Inherits its domain ("Man") and range ("AnotherHuman")
    Inherits its domain ("NonBinary") and range ("AnotherHuman")
    from its superproperty "isParent"
  </rdfs:comment>
  <rdfs:domain rdfs:resource="#Man" />
  <rdfs:domain rdfs:resource="#NonBinary" />
  <rdfs:range rdfs:resource="#AnotherHuman" />
  <rdfs:subPropertyOf rdfs:resource="#isParentOf" />
</rdf:Property>
```

```
<rdf:Property rdf:ID="isParentOf">
  <rdfs:domain rdfs:resource="#Human" />
  <rdfs:range rdfs:resource="#AnotherHuman" />
</rdf:Property>
```

```
<rdf:Property rdf:ID="BirthYear">
  <rdfs:domain rdfs:resource="#Human" />
  <rdfs:range rdfs:resource="#Year" />
</rdf:Property>
```

Graphical Presentation of this schema:



b. Write an instance of the RDF schema in A that express the following with a complete information that can be inferred from the schema.

- i. Mary is a woman and she is John's wife.
- ii. Sophie, Sandra and Susan are women.
- iii. Mary and John has a son Frank.
- iv. John was born in 1950.
- v. Frank was born in 1980.
- vi. Susan is John's daughter.
- vii. Susan was born in 1978.
- viii. Frank likes Sophie
- ix. Sandra likes Frank.

All other information for everyone else is unknown.

Write a RDF document and give a graphical presentation to describe these facts

RDF document:

<rdf:RDF

xmlns:rdf="http://www.w3.org/1999/02/22-rdf-syntax-ns#"

xmlns:xsd="http://www.w3.org/2001/XMLSchema#"

xmlns:uni="http://www.mydomain.org/uni-ns">

<rdf:Description rdf:about="Human1">

<uni:name>Mary</uni:name>

<uni:gender>Woman</uni:gender>

<uni:BirthYear></uni:BirthYear>

<uni:Likes rdf:resource="Human2"/>

<uni:isMotherOf rdf:resource="Human3"/>

<uni:isParentOf rdf:resource="Human3"/>

</rdf:Description>

<rdf:Description rdf:about="Human2">


```
<uni:name>John</uni:name>
<uni:gender>Man</uni:gender>
<uni:BirthYear>1950</uni:BirthYear>
<uni:Likes rdf:resource="Human1"/>
<uni:isMarried rdf:resource="Human1"/>
<uni:isFatherOf>
  <rdf:Bag>
    <rdf:_1 rdf:resource="Human3"/>
    <rdf:_2 rdf:resource="Human4"/>
  </rdf:Bag>
</uni:isFatherOf>
<uni:isParentOf>
  <rdf:Bag>
    <rdf:_1 rdf:resource="Human3"/>
    <rdf:_2 rdf:resource="Human4"/>
  </rdf:Bag>
</uni:isParentOf>
</rdf:Description>
<rdf:Description rdf:about="Human3">
  <uni:name>Frank</uni:name>
  <uni:gender>Man</uni:gender>
  <uni:BirthYear>1980</uni:BirthYear>
  <uni:Likes rdf:resource="Human5"/>
</rdf:Description>
<rdf:Description rdf:about="Human4">
  <uni:name>Susan</uni:name>
  <uni:gender>Woman</uni:gender>
  <uni:BirthYear>1978</uni:BirthYear>
</rdf:Description>
<rdf:Description rdf:about="Human5">
```



```
<uni:name>Sophie</uni:name>
<uni:gender>Woman</uni:gender>
<uni:BirthYear></uni:BirthYear>
</rdf:Description>
<rdf:Description rdf:about="Human6">
  <uni:name>Sandra</uni:name>
  <uni:gender>Woman</uni:gender>
  <uni:BirthYear></uni:BirthYear>
  <uni:Likes rdf:resource="Human3"/>
</rdf:Description>
</rdf:RDF>
```

Graphical Presentation of the instance of schema:

Instance: 



### 3. [Property Graph]

Create a Labeled Property Graph to describe the project management data shown in Lecture 2-3. Describe the vertices and the edges along with their labels and properties. Draw the graph using a Graph database tool (Neo4j or other)

**Note:** Refer to the table included in the attachment with this assignment.

This data has a total of seven labels:

1. Project (4)
2. Employee (14)
3. Assign\_hours (21)
4. Job (9)
5. Participated\_In (21)
6. Worked\_for (21)
7. Job\_Is. (14)

1 to 4 labels are vertices, and 5 to 7 labels are edges.

The properties of Each label:

Project: PROJ\_NUM, PROJ\_NAME

Employee: EMP\_NUM, EMP\_NAME, EMP\_HIREDATE

Job: JOB\_CODE, JOB\_CLASS, CHR\_HOUR

Assign: PROJ\_NUM, EMP\_NUM, ASSIGN\_HOURS


Connect Information:

Participated\_In edges connect Project vertices and Assign\_hours vertices.

Worked\_For edges connect Employee vertices and Assign\_hours vertices.

Job\_Is edges connect Employee vertices and Job vertices.

Graph using Neo4j:



#### 4. [Approximate Query Processing]

This question continues our discussion on using data synopsis for query processing based on data-driven approximation. You are given a vector of numbers: [127, 71, 87, 31, 59, 3, 43, 99, 100, 42, 0, 58, 30, 88, 72, 130], each data point records the frequency of communication of a server in a 5-minute interval. For example, in the first 5 minutes, 127 contacts are observed. In the next 5 minutes, 71 contacts, ...

**Note:** For these questions, similar to the examples shown in the lectures, discard the lowest level (high-resolution) coefficients (i.e. only keep the first 50% of coefficients).


Resolution	Averages	Detail Coefficients
4	[127, 71, 87, 31, 59, 3, 43, 99, 100, 42, 0, 58, 30, 88, 72, 130]	----
3	[99, 59, 31, 71, 71, 29, 59, 101]	[28,28,28,-28,29,-29,-29,-29]
2	[79, 51, 50, 80]	[20,-21,21,-21]
1	[65, 65]	[14,-15]
0	[65]	[0]

- Give the Haar decomposition and draw a corresponding error tree for the contacts data vector.


According to table above,

Haar decomposition: [65, 0, 14, -15, 20, -21, 21, -21, 28, 28, 28, -28, 29, -29, -29, -29]

Error tree:



- b. Give the process and result for reconstructing the frequency during time interval [15, 20] using Haar decomposition




The frequency during time interval [15,20] is shown in red below. Where C0, C1, C2, C4, C9 are coefficients.

Therefore,  $A[15,20] = C0 + C1 + C2 - C4 - C9$

$$= 65 + 0 + 14 - 20 - 28$$

$$= 31$$

- c. Use Haar decomposition and error tree to compute the total number of communications between time interval [15, 30].



To calculate the total number of communications [15, 30] between time intervals, we must first find the time intervals [15, 20], time intervals [20, 25], and time intervals [25, 30].

The frequency during time interval [15,20] is shown in red below. Where C0, C1, C2, C4, C9 are coefficients.

Therefore,  $A[15,20] = C0 + C1 + C2 - C4 - C9$

$$= 65 + 0 + 14 - 20 - 28$$

$$= 31$$



The frequency during time interval [20,25] is shown in red below. Where C0, C1, C2, C5, C10 are coefficients.

$$\text{Therefore, } A[20,25] = C0 + C1 - C2 + C5 + C9$$

$$= 65 + 0 - 14 + (-20) + 28$$

$$= 59$$

The frequency during time interval [25,30] is shown in red below. Where C0, C1, C2, C5, C10 are coefficients.

$$\text{Therefore, } A[25,30] = C0 + C1 - C2 + C5 - C9$$

$$= 65 + 0 - 14 + (-20) - 28$$

$$= 3$$

Hence, the total number of communications between time interval [15, 30],

$$A[15,30] = A[15,20] + A[20,25] + A[25,30]$$

$$= 31 + 59 + 3$$

$$= 93$$