

Problem

Submissions

Leaderboard

Discussions

You can perform the following operations any number of times:

Fill either jug completely. Empty either jug completely. Pour water from one jug into the other until either the source jug is empty or the destination jug is full.

Given capacities A, B, and a target amount T, determine whether it is possible to measure exactly T liters of water in either jug.

Input Format

The first line contains an integer Q, the number of test cases. Each of the next Q lines contains three space-separated integers:
A B T

A — capacity of the first jug. B — capacity of the second jug. T — required amount of water.

Constraints

1 ≤ Q ≤ 100 1 ≤ A, B ≤ 10^9 0 ≤ T ≤ 10^9

Output Format

For each test case, print:

YES

if exactly T liters can be measured, otherwise print:

NO

Sample Input 0

5 3 4

Sample Output 0

YES

Sample Input 1

5 10 3

Sample Output 1

NO

Change Theme

Language

Java 15



```
1
2 import java.io.*;
3 import java.util.*;
4
5 public class Solution {
6     public static int gcd(int a,int b){
7         if(b==0)
8             return a;
9         return gcd(b,a%b);
10    }
11    public static void main(String[] args) {
12        Scanner sc=new Scanner(System.in);
13        int A=sc.nextInt();
14        int B=sc.nextInt();
15        int T=sc.nextInt();
16        if(T<=(A+B)&& T%gcd(A,B)==0)
17            System.out.println("YES");
18        else
19            System.out.println("NO");
20    }
21 }
22
```

Line: 22 Col: 1



Upload Code as File

Run Code

Submit Code



Test against custom input



Test case 0



Test case 1

Compiler Message

Success