Selective Adaptation under Noisy Supervision: Separating Task Specialization from Representation Transfer

Jason K. Nam [1]

Abstract

Selective self-training changes both training support and learned representations. We study these effects through KPC-CF, combining semantic–confidence selection, attention-distribution regularization, and classifier-head reinitialization. A selected-gradient decomposition separates support shift from pseudo-label error, while local analyses distinguish attention anchoring from reset-driven feature updates. Across two model families, four general classification tasks, and Korean aspect sentiment analysis, we identify different operating regimes. On Qwen XNLI, Full obtains the strongest mean adapted-head performance at the longer budget, improving over unfiltered adaptation by 5.60 points. Dual yields the strongest cross-task probe average, exceeding confidence-only selection by 0.46 points across three student seeds. Longer training improves Full's target performance while concentrating class geometry and reducing transfer. Matched layer/head attention replay and parameter analysis separate structural retention from specialization. These results establish task specialization and transferable linear information as complementary objectives, with a measurement framework for choosing between them.

1. Introduction

Transferred supervision enables adaptation with scarce native labels, while importing source errors. Selective self-training uses confidence or semantic support to retain target pseudo-labels. A gate changes label quality, class coverage, and representation directions receiving updates.

A stronger classifier can reflect its readout, specialized features, or transferable information. Beyond the fine-tuning/transfer distinction (Yosinski et al., 2014; Kumar et al., 2022), we examine how selected pseudo-supervision changes representation learning.




Figure 1. **Selective adaptation separates task specialization from representation transfer.** Matched schematic points use color for hypothetical target classes and shape for an independent transfer factor. Full illustrates stronger target separation while compressing that factor; Dual retains its variation. Geometry and arrows are conceptual, not measured features or trajectories. Footer values are paired Full-minus-Dual Macro-F1 differences on Qwen XNLI at staged 600, mean ± SD over three fixed-teacher student seeds using matched head and probe readouts.

We study this interaction through KPC-CF: dual semantic–confidence selection, frozen-teacher attention anchoring, and task-head reinitialization. Originating in translation-based aspect sentiment transfer, Full improves native Korean review analysis. Extending its aspect gate to source-neighborhood label support enables adaptation for inference, intent, topic, and paraphrase detection.

Figure 1 illustrates *endpoint separation*: Full leads the seven Qwen configurations on the longer-budget adapted head, while Dual leads the other-task probe average. Full increases class separation and reduces effective rank without a corresponding fresh in-task probe gain, linking target geometry to specialization of the adapted classifier.

We contribute formal decompositions of selected updates,

[1]DATAI. Correspondence to: Jason K. Nam <skarlqja68@gmail.com>.

Working draft prepared for ICML 2027. Typeset with the ICML 2026 style.

attention-compatible changes, and readout risk; factorial comparisons across seeds and budgets; and connected drift, geometry, attention, and parameter measurements explaining endpoint-specific adaptation.

Training and evaluation code, fixed configurations, and reproduction instructions are available through our project page and supplementary resources.

2. Related Work

Selection and self-training. Pseudo-labeling (Lee, 2013) and confidence consistency (Sohn et al., 2020) turn model predictions into supervision. Class-balanced selection (Zou et al., 2018), curriculum thresholds (Zhang et al., 2021), adaptive thresholds (Wang et al., 2023), and soft weighting (Chen et al., 2023) regulate the quantity–quality trade-off. SimMatch connects class predictions and instance similarities through a labeled memory and consistency across augmented views (Zheng et al., 2022). DeYO combines entropy with confidence changes under shape-destructive transformations (Lee et al., 2024); FATA uses feature augmentation to address scarcity induced by filtering (Cho et al., 2025). These studies motivate joint reliability and coverage analysis. Our external LaBSE space (Feng et al., 2022), source teacher, and retained count remain fixed during adaptation, isolating the support chosen by confidence, semantics, or their conjunction. Because maximum-softmax confidence (Hendrycks & Gimpel, 2017) can be miscalibrated under shift (Guo et al., 2017; Ovadia et al., 2019), we separate selected-label accuracy from the support-dependent gradient while holding retained mass and adaptation budget fixed.

Domain adaptation and alignment. Domain-adversarial learning (Ganin et al., 2016) and covariance alignment (Sun & Saenko, 2016) reduce discrepancies between feature distributions. SHOT freezes the source classifier and adapts target features using information maximization and pseudo-labeling without source examples (Liang et al., 2020). More recently, Ramen retrieves prior test inputs through domain consistency and prediction balance for online vision-language adaptation (Bao et al., 2026). Our fixed-pool setting retains labeled source neighbors, enabling controlled support comparisons and separate interventions on attention and the head. Adaptation bounds distinguish distribution discrepancy from joint prediction error (Ben-David et al., 2010), and invariant features can remain insufficient under label mismatch (Zhao et al., 2019). Domain and adaptation diagnostics distinguish the two alignments.

Attention retention and head reinitialization. MiniLM distills last-layer self-attention distributions and value relations for Transformer compression (Wang et al., 2020). We use attention-distribution KL to anchor adaptation to a frozen teacher of the same architecture. This constrains selected token relations while allowing feature updates in directions weakly constrained by that attention metric. RIFLE periodically resets classifiers to stimulate deeper learning (Li et al., 2020); our adaptation-onset reset isolates its interaction with anchoring. TTE combines parameter averaging, representation diversity, and distillation for stable online adaptation (Kim et al., 2025). Our analysis instead connects two explicit interventions: attention KL supplies local directional curvature, while the head determines how classification residuals reach the encoder. These interventions couple attention curvature and head-mediated updates.

Representation quality and evaluation. Feature transfer depends on both learned structure and optimization (Yosinski et al., 2014; Neyshabur et al., 2020). Fine-tuning can trade reusable features for fitted-task performance (Kumar et al., 2022). Probing methodology emphasizes the role of the readout (Hewitt & Liang, 2019), while CKA compares representations independently of their original classifiers (Kornblith et al., 2019). We distinguish the jointly adapted classifier from two frozen-encoder evaluations. A fresh in-task linear probe tests target-label accessibility independently of the adapted head; probes on other tasks assess transfer using separate labeled supports. Fixed support sets, decoder families, and regularization make intervention comparisons interpretable as changes in accessible linear information under a common protocol. Combining these readouts with rank, class geometry, and parameter changes connects prediction improvements to specialized target structure or information reusable across the evaluated tasks. Attention replay adds a structural-retention measurement, interpreted separately from causal token importance (Jain & Wallace, 2019). This joint view motivates a formal separation of predictive risk, representation drift, and transferable linear information across tasks and backbones.

3. Setup: Selective Target Adaptation

3.1. Source Teacher and Dual Support

Definition 1 (Source teacher and target pool)**.** Let $S = \{(x_j^S, y_j^S)\}_{j=1}^{n_S}$ be a labeled source corpus and $T = \{x_i\}_{i=1}^{n_T}$ an unlabeled target pool. A source-trained encoder ϕ_{θ_0} and head parameters ω_0 define

$$p_v(y \mid x) = \mathrm{softmax}(h_\omega(\phi_\theta(x)))_y, \quad v = (\theta, \omega). \quad (1)$$

The teacher is $v_0 = (\theta_0, \omega_0)$; only target inputs, not their labels, are available for adaptation.

The frozen teacher supplies $\hat{y}_i = \arg\max_y p_{v_0}(y \mid x_i)$ and maximum-softmax confidence $c_i = \max_y p_{v_0}(y \mid x_i)$ (Hendrycks & Gimpel, 2017).

Let $e(x)$ be a frozen semantic embedding normalized to unit

length and $\mathcal{N}_k(x)$ its k nearest source neighbors. We define semantic support for the *teacher's predicted class* as

$$\pi_{ij} = \frac{\exp(e(x_i)^\top e(x_j^S)/\tau)}{\sum_{r\in\mathcal{N}_k(x_i)} \exp(e(x_i)^\top e(x_r^S)/\tau)}, \tag{2}$$

$$s_i = \sum_{j\in\mathcal{N}_k(x_i)} \pi_{ij}\mathbf{1}[y_j^S = \hat{y}_i]. \tag{3}$$

We use $k = 20$, $\tau = 0.1$, and external LaBSE embeddings (Feng et al., 2022). Source annotation or translation errors can propagate into the neighbor-support scores.

To compare signals on a common scale, let F_c, F_s be empirical target-pool percentile transforms. Dual ranks examples by their weaker signal:

$$u_i = \min\{F_c(c_i), F_s(s_i)\}, \qquad w_i = \mathbf{1}[i \in \mathrm{Top}_{\rho n_T}(u)]. \tag{4}$$

We use $\rho = 0.6$ with deterministic identity-based ties. Confidence/Semantic rank by c_i/s_i at equal retained count; All retains every target input. This general-task gate and the original review–aspect cosine/absolute-confidence gate use separate protocols (Appendix D).

3.2. Attention Anchoring and Head Reset

Write $a_\theta^{\ell ht}(x)$ for the attention probability vector over valid keys at layer ℓ, head h, and query t. Padding positions and, for causal models, future positions are masked; teacher and student rows are renormalized over valid keys. Following attention-distribution distillation (Wang et al., 2020), the per-input discrepancy is

$$d_A(x;\theta) = \frac{1}{|\mathcal{I}_x|} \sum_{(\ell,h,t)\in\mathcal{I}_x} \mathrm{KL}\big(\mathrm{sg}[a_{\theta_0}^{\ell ht}(x)] \| a_\theta^{\ell ht}(x)\big). \tag{5}$$

Our implementation uses the final layer and gives equal weight to valid query/head rows. The adaptation objective is

$$\mathcal{L}_w(v) = \frac{\sum_i w_i[-\log p_v(\hat{y}_i \mid x_i) + \lambda d_A(x_i;\theta)]}{\sum_i w_i}. \tag{6}$$

Rejected inputs have zero direct training weight. KL acts on *attention distributions*; output-label KL defines a different objective even when its gradients reach attention parameters. Anchored variants use $\lambda = 0.1$ throughout adaptation.

Head reset redirects feature updates (Li et al., 2020). We reset at adaptation onset, whereas RIFLE resets periodically. Qwen resets its linear classification head, preserving the vocabulary head; XLM-R resets its dense–tanh–output module. Dual+KL and Dual+reinit isolate operations; Full combines both on identical Dual support.

Appendix B gives the training procedure in Algorithm 1, together with implementation and evaluation details.

4. Formal Properties of Selective Adaptation

Problem 1 (Support, structural retention, and readout risk)**.** Fix a source teacher, target pool, and adaptation budget (Definition 1). Characterize the selected update's deviation from the latent target gradient, feature changes compatible with attention retention, and the separation of adapted-head risk from best linear-readout risk.

4.1. Selection Changes Both Error and Update Support

Let $\mathbb{E}_T$ denote expectation under the latent labeled target distribution. For cross-entropy ℓ_v, define $g^* = \nabla_v \ell_v(x, y)$, $g_T = \mathbb{E}_T g^*$, and $\delta = \nabla_v \ell_v(x, \hat{y}) - g^*$. The fixed teacher and gate $w \in \{0, 1\}$ give retention $\rho = \mathbb{E}_T w > 0$ and $g_w = \mathbb{E}_T[w(g^* + \delta)]/\rho$. Finite gradient second moments suffice; calibration and expansion assumptions (Wei et al., 2021) are not required for this fixed-gate identity.

Proposition 1 (Selected-update decomposition)**.** *The expected selected pseudo-label gradient satisfies*

$$g_w - g_T = \underbrace{\frac{\mathrm{Cov}_T(w, g^*)}{\rho}}_{\textit{selection shift}} + \underbrace{\frac{\mathbb{E}_T[w\delta]}{\rho}}_{\textit{selected label error}}. \tag{7}$$

If the logit Jacobian has operator norm at most M and $\epsilon_w = \Pr(\hat{y} \neq y \mid w = 1)$, then

$$\|g_w - g_T\| \le \sqrt{\frac{1-\rho}{\rho}}\,\sigma_g + \sqrt{2}M\epsilon_w, \tag{8}$$

where $\sigma_g^2 = \mathbb{E}_T\|g^* - g_T\|^2$ is the target-gradient variance.

Appendix A proves Proposition 1 by centering wg^*, then applying Cauchy–Schwarz and Jacobian bounds.

Higher selected-label precision tightens the error bound, while support shift changes the update. A gate can therefore benefit transfer with less accurate pseudo-labels. Both terms depend on current parameters; the unknown target gradient is not estimated by either selection score.

For L-smooth $R_T(v) = \mathbb{E}_T \ell_v(x, y)$ with $\nabla R_T = g_T$, a selected update yields

$$R_T(v - \eta g_w) - R_T(v) \le -\eta\|g_T\|^2 + \eta\|g_T\|\,\|g_w - g_T\| + \tfrac{L\eta^2}{2}\|g_w\|^2. \tag{9}$$

Corollary 1 (Conditional descent of a selected update)**.** *Let R_T be L-smooth with $L > 0$, and let κ_w denote the right-hand side of Eq. (8). If $\kappa_w < \|g_T\|$, a CE-only step strictly decreases R_T whenever*

$$0 < \eta < \frac{2\|g_T\|(\|g_T\| - \kappa_w)}{L\|g_w\|^2}. \tag{10}$$

Substitution into Eq. (9) proves the claim; $\kappa_w < \|g_T\|$ ensures a nonzero denominator.

The condition uses latent gradients and a CE-only SGD step. It does not certify Full's regularized optimizer.

4.2. Anchoring Supplies Local Directional Curvature

Fisher geometry (Martens, 2020) yields a local metric.

Proposition 2 (Local attention metric)**.** *Use empirical averages over a fixed finite selected pool and valid rows. Fix valid-key masks and deterministic attention logits that are C^3 near θ_0, matching the teacher there. For each row, let $q = \mathrm{softmax}(b_0)$ and $J_b = \partial b/\partial\theta|_{\theta_0}$. Then*

$$R_{A,w}(\theta_0 + \Delta\theta) = \tfrac{1}{2}\Delta\theta^\top F_{A,w}\Delta\theta + O(\|\Delta\theta\|^3), \tag{11}$$

where $R_{A,w}(\theta) = \mathbb{E}_{T|w=1} d_A(x;\theta)$ and

$$F_{A,w} = \mathbb{E}_{T|w=1}\mathbb{E}_{\ell,h,t}[J_b^\top(\mathrm{diag}(q) - qq^\top)J_b]. \tag{12}$$

The matrix satisfies $F_{A,w} \succeq 0$.

Corollary 2 (Attention-compatible feature change)**.** *Let $J_\phi(x)$ be the Jacobian of a C^2 encoder at θ_0. If $d \in \ker F_{A,w}$ and $J_\phi(x)d \neq 0$ for a specified input, anchoring has zero quadratic cost while feature change has the nonzero linear term $\phi_{\theta_0+td}(x) - \phi_{\theta_0}(x) = tJ_\phi(x)d + O(t^2)$.*

This conditional implication distinguishes local compatibility from exact finite-displacement invariance. Appendix A proves both statements by Taylor expansion; existence of such a direction is not universal.

4.3. Head Reset Redirects Feature Learning

Proposition 3 (Head-mediated feature updates)**.** *For a C^2 encoder, linear head with logits Wz, $z = \phi_\theta(x)$, and fixed pseudo-label $\hat{y}$, the CE encoder gradient is*

$$\nabla_\theta \ell = J_\phi(x)^\top W^\top(p_v - e_{\hat{y}}). \tag{13}$$

A CE-only encoder SGD step of size η on this example changes its feature by

$$\Delta z = -\eta J_\phi J_\phi^\top W^\top(p_v - e_{\hat{y}}) + O(\eta^2), \tag{14}$$

The chain rule and encoder Taylor expansion prove Proposition 3 (Appendix A). Reset can change W and its residual; nonlinear heads substitute $J_h(z)$. Initial displacement and subsequent encoder learning are distinct.

Identity 1 (Representation risk and readout gap)**.** For a common linear-head family, define $R_T^*(\theta) = \inf_W R_T(\theta, W)$ and $G_T(\theta, W) = R_T(\theta, W) - R_T^*(\theta)$. Between two encoder/head pairs with finite risks,

$$\Delta R_T = \Delta R_T^* + \Delta G_T. \tag{15}$$

by subtracting the definitions at the two checkpoints.

This identity motivates separate head and probe evaluations. Finite-support Macro-F1 contrasts are empirical endpoints, not direct estimates of the risks decomposed in Eq. (15).

4.4. Two Drifts and Scale-Aware Geometry

We distinguish *domain discrepancy at fixed parameters* from *adaptation drift on fixed inputs*. Let $\mu_S(\theta), C_S(\theta)$ be source feature moments and $\mu_{T,w}(\theta), C_{T,w}(\theta)$ selected-target moments. Domain diagnostics are

$$D_\mu^{S,T}(\theta) = \|\mu_S - \mu_{T,w}\|^2, \quad D_C^{S,T}(\theta) = \|C_S - C_{T,w}\|_F. \tag{16}$$

In contrast, for fixed target IDs U, adaptation diagnostics compare $Z_0 = \phi_{\theta_0}(U)$ and $Z = \phi_\theta(U)$:

$$D_\mu^{0,t} = \|\mu(Z) - \mu(Z_0)\|^2, \quad D_C^{0,t} = \frac{\|C(Z) - C(Z_0)\|_F}{\|C(Z_0)\|_F + \varepsilon}. \tag{17}$$

Covariance alignment has been used as a training objective (Sun & Saenko, 2016); here these moments diagnose domain mismatch and temporal change separately.

Using evaluation labels only after training, we measure within- and between-class scatter,

$$W_Z = \frac{1}{n}\sum_i \|z_i - \mu_{y_i}\|^2, \qquad B_Z = \frac{1}{n}\sum_k n_k\|\mu_k - \mu\|^2, \tag{18}$$

and report B_Z/W_Z, covariance effective rank, and centered linear CKA. For covariance eigenvalue proportions r_j and centered feature matrices X, Y,

$$r_{\mathrm{eff}} = \exp\left(-\sum_j r_j \log r_j\right), \quad \mathrm{CKA}(X,Y) = \frac{\|X^\top Y\|_F^2}{\|X^\top X\|_F\|Y^\top Y\|_F}. \tag{19}$$

We repeat scatter calculations after per-example L_2 normalization to separate directional class organization from contraction due to feature scale. For nonzero centered matrices, CKA is invariant to independent orthogonal transformations and nonzero isotropic rescaling, whereas moment drifts compare feature coordinates. High CKA can therefore coexist with mean or scale drift. Together, these diagnostics distinguish preserved relational geometry from changes in feature location, magnitude, and class organization.

5. Experimental Design

Tasks and models. XLM-R-base (Conneau et al., 2020) adapts directly on XNLI inference (Conneau et al., 2018), MASSIVE intent (FitzGerald et al., 2023), AG News topics (Zhang et al., 2015), and PAWS-X paraphrase (Yang et al., 2019). Qwen3-4B-Instruct-2507 transfers French XNLI supervision to unlabeled English inputs, then receives XNLI-en/MASSIVE-ko/AG News-en/PAWS-X-en probes.




Figure 2. **XLM-R across tasks and diagnostic endpoints.** (a) Three-seed mean ranks among All, Confidence, Dual, Full for each task/readout (lower is better); color is probe minus head rank. (b) Paired Full-minus-All means ± SD. (c) Full-minus-All probe matrix. XNLI: (d) Full with alternative scorers; (e) component head/probe scores; (g) accepted/rejected test F1 minus All (3,034/1,976 inputs); (h) head NLL/Brier. (f) AG News synthetic source-label noise. Panels (a,b) use three source/student seeds; (c–h) use seed 17. Teacher in (d) uses frozen source-encoder features to construct semantic neighborhoods.

Controlled adaptation. Qwen uses 4-bit QLoRA (Dettmers et al., 2023), rank 16, and batch 16. Selectors retain 4,800/8,000 inputs. Seeds 17/23/42 share teacher, gate, and source noise. Budgets are 150 and staged 600 updates (150 plus 450 with optimizer/scheduler restart, no second reset). Differentiable student attention and a frozen teacher enable KL; checkpoints are final predetermined updates.

Readouts and repetition. Frozen features receive standardized logistic-regression probes ($C = 1$) with fixed labeled supports (Appendix B). Macro-F1 means and sample SD use three seeds; cross-task scores first average non-XNLI probes within seed. Qwen repeats student optimization; XLM-R repeats source/student seeds 17/23/41. Scorer/noise sweeps use seed 17.

Mechanism measurements. Geometry uses 512 matched Qwen inputs; attention replay uses 16 XLM-R inputs, seed 17, original BF16 precision/batch 16, exactly reproducing saved probabilities. Layers/heads are repeated measurements. ABSA retains its original protocol. In Figure 2, A/C/S/D/F/Rnd mean All, Confidence, Semantic, Dual, Full, and Random; +K/+R add KL/reset. XN/MA/PA/AG denote XNLI, MASSIVE, PAWS-X, and AG News.

6. Results

Table 1 reveals endpoint- and budget-dependent rankings. At staged 600, Full leads the head mean, with a paired 5.60 ± 4.91-point gain over All, positive in two of three seeds. At 150, Dual+KL leads at 64.54, locating reset-driven specialization in longer adaptation.

6.1. Full Specializes; Dual Preserves Transfer

Dual leads other-task transfer at 600, exceeding All by 1.05 ± 0.37 and Confidence by 0.46 ± 0.16 points, positive in every seed. Its head gain over Confidence is 2.97 ± 0.73, and the budget comparison supports semantic selection during extended adaptation (Table 3).

Selection reallocates supervision while filtering errors. Confidence retains 4,184 correctly and 616 incorrectly pseudo-labeled inputs; Dual retains 3,838 and 962. Selected-label accuracies are 87.17% and 79.96%, despite Dual's stronger long-budget endpoints. Their rejected pools contain 1,502 and 1,848 correct pseudo-labels, respectively: rejection defines training support rather than teacher error. Gold labels enter only this post-training audit. These counts illustrate Proposition 1's distinction between label precision and update support. Equal retention (4,800) and update budgets control nominal exposure while allowing selected identities, class composition, and semantic coverage to vary.

6.2. The Component Effects Depend on the Endpoint

Generalization also changes outside the accepted region. On original-Dual test partitions, staged-600 Dual scores 59.74 Macro-F1 on 3,041 accepted and 1,969 rejected in-

Table 1. **Adaptation and readout performance.** Qwen3-4B-Instruct-2507 adapted on XNLI; Macro-F1 mean ± SD across three fixed-teacher student seeds. Cross-task means average Table 2's three probes; bold/shading mark column maxima. The staged schedule restarts optimization after 150 updates. Sources: [a]Hendrycks & Gimpel (2017); [b]Feng et al. (2022); [c]Wang et al. (2020); [d]Li et al. (2020).

Adaptation variant	150 updates			600 staged updates		
	Native head	In-task probe	Cross-task mean	Native head	In-task probe	Cross-task mean
Qwen3 (Qwen Team, 2025); XNLI (Conneau et al., 2018)						
All	62.79 ± 2.75	86.38 ± 0.32	78.44 ± 0.14	60.58 ± 1.87	86.49 ± 0.33	77.99 ± 0.19
Confidence[a]	64.40 ± 3.72	86.11 ± 0.23	78.52 ± 0.33	59.20 ± 1.95	86.23 ± 0.55	78.58 ± 0.21
Semantic[b]	63.07 ± 1.89	**86.76** ± 0.33	78.44 ± 0.51	63.35 ± 1.65	**86.55** ± 0.35	78.45 ± 0.09
Dual	62.95 ± 2.07	86.52 ± 0.10	78.83 ± 0.55	62.17 ± 1.25	86.26 ± 0.48	**79.04** ± 0.28
Dual+KL[c]	**64.54** ± 1.91	86.41 ± 0.28	**78.92** ± 0.26	63.39 ± 1.13	85.90 ± 0.14	78.89 ± 0.31
Dual+reinit[d]	64.23 ± 5.83	86.68 ± 0.73	78.02 ± 0.15	65.05 ± 4.66	85.98 ± 0.57	78.12 ± 0.69
Full	64.11 ± 5.28	86.53 ± 0.22	78.14 ± 0.14	**66.19** ± 4.12	86.20 ± 1.26	77.59 ± 0.13

Table 2. **Cross-task linear-probe transfer.** Staged-600 Qwen3; Macro-F1 mean ± SD across three seeds with fixed labeled supports. Shading marks task maxima. Benchmarks: MASSIVE (FitzGerald et al., 2023), AG News (Zhang et al., 2015), and PAWS-X (Yang et al., 2019).

Adaptation variant	MASSIVE	AG News	PAWS-X
	Intent (ko)	Topic (en)	Paraphrase (en)
All	58.79 ± 0.26	88.30 ± 0.22	86.87 ± 0.21
Confidence	60.48 ± 0.12	88.25 ± 0.07	87.01 ± 0.59
Semantic	59.95 ± 0.92	88.10 ± 0.12	87.29 ± 0.78
Dual	**60.91** ± 1.18	88.47 ± 0.21	**87.73** ± 0.33
Dual+KL	60.66 ± 0.31	**88.61** ± 0.07	87.41 ± 0.72
Dual+reinit	60.40 ± 1.34	87.64 ± 0.28	86.32 ± 1.34
Full	58.88 ± 0.35	88.04 ± 0.45	85.85 ± 0.46

Table 3. **Adaptation-budget sensitivity.** Qwen3/XNLI, paired mean ± SD over three student seeds. Full's positive head and negative transfer changes occur in every seed. The 600-step continuation restarts optimizer and scheduler.

Adaptation variant	Paired Δ Macro-F1 (600−150)	
	Native head	Cross-task probe
All	−2.21 ± 4.46	−0.45 ± 0.22
Confidence	−5.20 ± 1.88	+0.06 ± 0.27
Semantic	+0.28 ± 3.28	+0.01 ± 0.58
Dual	−0.78 ± 3.11	+0.21 ± 0.48
Dual+KL	−1.15 ± 1.03	−0.03 ± 0.56
Dual+reinit	+0.82 ± 1.46	+0.10 ± 0.79
Full	+2.08 ± 1.88	−0.55 ± 0.23




Figure 3. **Component, interaction, and budget effects.** (a,b) Factorial contrasts at 150 and staged 600, combining native-head and cross-task probe endpoints. (c) KL–reset interaction, Eq. (20); (d) paired 600-minus-150 changes across four factorial variants; (e) Dual-minus-Confidence at each budget. Panels (c–e) include native, in-task, and cross-task readouts. Markers/whiskers are paired mean ± SD over three fixed-teacher student seeds; faint points show individual differences.

puts; Confidence scores 58.57/55.04. Paired gains are $1.17 \pm 0.58/4.70 \pm 1.44$ points, positive in every seed. These fixed strata measure shared-parameter generalization, with zero direct weight on rejected training inputs. Class composition and semantic coverage remain candidate mediators. Figure 3 holds support fixed to test the endpoint-specific implications of Propositions 2–3.

Without reset, KL yields a mean 150-step head gain of 1.59 ± 0.25 points, positive in every seed, while the other-task mean changes by 0.09 ± 0.34. At 600, differences are 1.22 ± 2.33 and -0.14 ± 0.58. KL's observed gains therefore depend on the evaluation endpoint.

At 600, reset increases Dual's mean head by 2.88 points and reduces other-task transfer by 0.92; on Dual+KL, changes are +2.80/−1.30. Across budgets and KL conditions, reset lowers transfer in every matched seed. Full's continuation

Table 4. **Class geometry and temporal drift.** Qwen3/XNLI, 512 fixed inputs and three student seeds. Entries are mean within-seed relative changes; rank is an absolute difference. Temporal drift uses the source teacher on the same inputs.

Geometry statistic	Full relative to All	
	150 updates	600 updates
Raw within-scatter (%)	−6.85	−18.76
Normalized within-scatter (%)	+5.51	−8.31
Normalized B/W (%)	+148.91	+181.74
Effective rank difference	−27.46	−36.06
Temporal mean drift $D_{\mu}^{0,t}$ (%)	+418.43	+118.23
Temporal covariance drift $D_{C}^{0,t}$ (%)	+194.08	+167.18

Table 5. **Attention structure under component ablations.** XLM-R on XNLI, seed 17: matched GPU BF16 replay of 16 inputs. Entropy uses K valid keys and averages layers and heads.

Adaptation variant	Teacher–student JS		Entropy
	All layers	Final layer	$H/\log K$
XLM-R (Conneau et al., 2020); XNLI attention			
All	0.0400	0.1524	0.5203
Confidence	0.0587	0.2248	0.5473
Dual	0.0480	0.1720	0.5302
Dual+KL	0.0194	0.0384	0.5012
Dual+reinit	0.0561	0.2076	0.5452
Full	0.0237	0.0403	0.5075

Table 6. **Original native-review ABSA results.** XLM-R transfers translated SemEval-2014 (Pontiki et al., 2014) to KR3. ACD uses Micro-F1; polarity uses accuracy. Training tokens fall from 1.51M to 0.89M. Shading marks the highest reported point estimate separately within each training order.

Training regime	Detection	Polarity accuracy	
	ACD μF1	4-way	Binary
Joint, unfiltered	87.57	83.43	89.34
Joint, KPC-cF	87.75	83.52	89.56
Sequential, unfiltered	87.69	84.21	90.35
Sequential, KPC-cF	**88.29**	**84.34**	**90.89**

Table 7. **Original zero-shot semantic transfer.** ABSA-trained XLM-R with intermediate-layer mean pooling on KorSTS (Ham et al., 2020) and KLUE-STS (Park et al., 2021). Original-protocol correlations use no trained probe; shading marks column maxima.

Training regime	Spearman $\rho \times 100$	
	KorSTS	KLUE-STS
Pretrained	11.41	−1.23
Translated source	10.26	2.55
Target pseudo-labels	12.18	7.59
Source then unfiltered target	9.21	6.35
KPC-cF	**16.26**	**20.50**




Figure 4. **Attention anchoring changes both depth profiles and head-specific structure.** Columns compare All, Dual, Dual+KL, Dual+reinit, and Full on 16 fixed XLM-R XNLI inputs, seed 17, using GPU BF16 and batch 16. Saved probabilities reproduce exactly. Top (a–e): teacher–student attention JS, averaged over inputs for each layer/head, with a shared color scale. Bottom (f–j): layerwise means and input interquartile ranges after averaging heads within each input. Insets report all-layer and final-layer means. Heads/layers are repeated measurements; bands are descriptive, not confidence intervals.

improves its head by 2.08 ± 1.88 and reduces transfer by 0.55 ± 0.23, both directions shared by all seeds. These contrasts identify reset-driven specialization whose head benefit varies with adaptation budget.

For any endpoint m, the factorial interaction is

$$I_m = (m_{\text{Full}} - m_{\text{Dual+reinit}}) - (m_{\text{Dual+KL}} - m_{\text{Dual}}). \tag{20}$$

The head interaction is -1.71 ± 0.38 points at 150 and -0.08 ± 3.50 at 600 (paired mean $\pm$ SD).




Figure 5. **Matched representation spaces resolve the factorial interventions.** Qwen/XNLI seed 17 at staged 600: (a) Dual, (b) Dual+KL, (c) Dual+reinit, (d) Full, on the same 512 inputs. Pooled PCA across eight conditions explains 47.03% of variance. Axes and camera are shared; colors denote classes, large points centroids, and wireframes 1-SD projected covariance ellipsoids. Insets report normalized B/W, effective rank, and centered linear CKA to the source teacher on the same inputs.

6.3. Geometry Identifies the Form of Specialization

At 150/600 updates, Full minus All changes raw B/W by 156%/193% and effective rank by $-27.46/-36.06$. Normalized B/W rises approximately 149%/182%. Raw within-scatter falls 6.85%/18.76%; normalized scatter rises 5.51% at 150 but falls 8.31% at 600.

Full minus All is -0.29 in-task Macro-F1 at 600 despite greater class separation (Figure 5; Appendix F). At seed 17, KL changes teacher-reference CKA from 0.771/0.722 to 0.803/0.712 without/with reset, respectively.

Teacher-reference temporal drifts accompany target separation (Table 4), locating specialization in same-input reorganization. Corollary 2 explains how attention retention can coexist with encoder-feature change.

6.4. Attention Anchoring Acts on Its Intended Structure

Matched XLM-R replay (Figure 4) supports structural anchoring across head initializations (Proposition 2). Without/with reset, KL reduces mean JS from 0.0480/0.0561 to 0.0194/0.0237 and final-layer JS from 0.1720/0.2076 to 0.0384/0.0403 (approximately 78%/81%). We measure teacher-relative effective LoRA updates, avoiding non-unique factor norms:

$$\Delta W_{\text{eff}} = \frac{\alpha}{r}(B_t A_t - B_0 A_0), \qquad u_W = \frac{\|\Delta W_{\text{eff}}\|_F}{\sqrt{|W|}}. \tag{21}$$

Qwen (seed 17, 150 updates) yields backbone-update norms 2.16/2.66/2.67 for Dual/Dual+reinit/Full, supporting encoder change under head reset (Eq. (13)).

6.5. Operating Regimes Across Tasks and Backbones

XLM-R evaluates the broader operating regimes (Figure 2; Appendix C). Among adapted variants, All leads the three-seed head means on every task, while probes reveal different feature rankings: Dual exceeds All on MASSIVE (54.79 versus 54.20) and PAWS-X (69.39 versus 68.26).

Under the original ABSA protocol (Tables 6–7), sequential XLM-R improves ACD Micro-F1/binary-polarity accuracy by 0.60/0.54 points and both STS correlations while using 0.89M versus 1.51M training tokens.

7. Discussion and Conclusion

Selective adaptation controls both supervision support and feature updates. Our selected-gradient decomposition separates label error from support shift; attention geometry and head-mediated updates explain how KL and reset constrain different parts of adaptation. These mechanisms connect the complete configuration to endpoint-specific behavior without requiring additive component gains. Fixed-teacher repetitions and common probe supports isolate student adaptation under the same evaluation protocol.

In the repeated Qwen regime, Full leads the longer-budget adapted-head mean, whereas Dual leads mean cross-task linear transfer. Concentrated target geometry accompanies Full's head improvement without a corresponding fresh in-task probe gain. Reject-region gains reveal shared-parameter generalization beyond the directly supervised training support. Matched attention replay confirms structural anchoring, and the two drift definitions distinguish domain discrepancy from same-input temporal change. Original ABSA results identify a regime where Full benefits task performance and zero-shot semantic transfer; the broader XLM-R comparisons establish dependence on the task and backbone. The combined evidence supports selecting interventions by their intended readout and reporting native performance, transferable linear information, and structural retention as complementary outcomes.

Impact Statement

This study uses existing data for lower-cost adaptation. Aggregate gains establish neither fairness nor suitability for consequential decisions. Deployment evaluation should cover target performance and retained capabilities across all intended deployment populations.

References

Bao, W., Zhao, Y., Yang, X., and He, J. Ramen: Robust test-time adaptation of vision-language models with active sample selection. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition Findings*, pp. 9632–9642, 2026. URL https://openaccess.thecvf.com/content/CVPR2026F/html/Bao_Ramen_Robust_Test-Time_Adaptation_of_Vision-Language_Models_with_Active_Sample_CVPRF_2026_paper.html.

Ben-David, S., Blitzer, J., Crammer, K., Kulesza, A., Pereira, F., and Vaughan, J. W. A theory of learning from different domains. *Machine Learning*, 79:151–175, 2010. doi: 10.1007/s10994-009-5152-4.

Chen, H., Tao, R., Fan, Y., Wang, Y., Wang, J., Schiele, B., Xie, X., Raj, B., and Savvides, M. SoftMatch: Addressing the quantity-quality trade-off in semi-supervised learning. In *International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=ymt1zQXBDiF.

Cho, Y., Kim, Y., Yoon, J., Hong, S., and Lee, D. Feature augmentation based test-time adaptation. In *Proceedings of the Winter Conference on Applications of Computer Vision*, pp. 6838–6847, 2025. URL https://openaccess.thecvf.com/content/WACV2025/html/Cho_Feature_Augmentation_Based_Test-Time_Adaptation_WACV_2025_paper.html.

Conneau, A., Rinott, R., Lample, G., Williams, A., Bowman, S. R., Schwenk, H., and Stoyanov, V. XNLI: Evaluating cross-lingual sentence representations. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 2475–2485, 2018. doi: 10.18653/v1/D18-1269. URL https://aclanthology.org/D18-1269/.

Conneau, A., Khandelwal, K., Goyal, N., Chaudhary, V., Wenzek, G., Guzmán, F., Grave, E., Ott, M., Zettlemoyer, L., and Stoyanov, V. Unsupervised cross-lingual representation learning at scale. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 8440–8451, 2020. doi: 10.18653/v1/2020.acl-main.747. URL https://aclanthology.org/2020.acl-main.747/.

Dettmers, T., Pagnoni, A., Holtzman, A., and Zettlemoyer, L. QLoRA: Efficient finetuning of quantized LLMs. In *Advances in Neural Information Processing Systems*, volume 36, 2023. URL https://proceedings.neurips.cc/paper_files/paper/2023/hash/1feb87871436031bdc0f2beaa62a049b-Abstract-Conference.html.

Devlin, J., Chang, M.-W., Lee, K., and Toutanova, K. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 conference of the North American chapter of the association for computational linguistics: human language technologies, volume 1 (long and short papers)*, pp. 4171–4186, 2019. URL https://aclanthology.org/N19-1423/.

Feng, F., Yang, Y., Cer, D., Arivazhagan, N., and Wang, W. Language-agnostic BERT sentence embedding. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 878–891, 2022. doi: 10.18653/v1/2022.acl-long.62. URL https://aclanthology.org/2022.acl-long.62/.

FitzGerald, J., Hench, C., Peris, C., Mackie, S., Rottmann, K., Sanchez, A., Nash, A., Urbach, L., Kakarala, V., Singh, R., Ranganath, S., Crist, L., Britan, M., Leeuwis, W., Tur, G., and Natarajan, P. MASSIVE: A 1m-example multilingual natural language understanding dataset with 51 typologically-diverse languages. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2023. URL https://aclanthology.org/2023.acl-long.235/.

Ganin, Y., Ustinova, E., Ajakan, H., Germain, P., Larochelle, H., Laviolette, F., Marchand, M., and Lempitsky, V. Domain-adversarial training of neural networks. *Journal of Machine Learning Research*, 17(59):1–35, 2016. URL https://jmlr.org/papers/v17/15-239.html.

Guo, C., Pleiss, G., Sun, Y., and Weinberger, K. Q. On calibration of modern neural networks. In *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pp. 1321–1330, 2017. URL https://proceedings.mlr.press/v70/guo17a.html.

Ham, J., Choe, Y. J., Park, K., Choi, I., and Soh, H. KorNLI and KorSTS: New benchmark datasets for Korean natural language understanding. In Cohn, T., He, Y., and Liu, Y. (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2020*, pp. 422–430, Online, November 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.findings-emnlp.39. URL

https://aclanthology.org/2020.findings-emnlp.39.

Hendrycks, D. and Gimpel, K. A baseline for detecting misclassified and out-of-distribution examples in neural networks. In *International Conference on Learning Representations*, 2017. URL https://arxiv.org/abs/1610.02136.

Hewitt, J. and Liang, P. Designing and interpreting probes with control tasks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing*, pp. 2733–2743, 2019. doi: 10.18653/v1/D19-1275. URL https://aclanthology.org/D19-1275/.

Jain, S. and Wallace, B. C. Attention is not explanation. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1*, pp. 3543–3556, 2019. doi: 10.18653/v1/N19-1357. URL https://aclanthology.org/N19-1357/.

Kim, B., Ahn, C., Baddar, W., Kim, K., Lee, H., Ahn, S., Han, S., Suh, S., and Yang, E. Test-time ensemble via linear mode connectivity: A path to better adaptation. In *International Conference on Learning Representations*, 2025. URL https://proceedings.iclr.cc/paper_files/paper/2025/hash/c242f2b7f60d8c685b6481939330e241-Abstract-Conference.html.

Kornblith, S., Norouzi, M., Lee, H., and Hinton, G. Similarity of neural network representations revisited. In *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pp. 3519–3529, 2019. URL https://proceedings.mlr.press/v97/kornblith19a.html.

Kumar, A., Raghunathan, A., Jones, R., Ma, T., and Liang, P. Fine-tuning can distort pretrained features and underperform out-of-distribution. In *International Conference on Learning Representations*, 2022. URL https://arxiv.org/abs/2202.10054.

Lee, D.-H. Pseudo-label: The simple and efficient semi-supervised learning method for deep neural networks. In *ICML Workshop on Challenges in Representation Learning*, 2013. URL https://www.kaggle.com/blobs/download/forum-message-attachment-files/746/pseudo_label_final.pdf.

Lee, J., Jung, D., Lee, S., Park, J., Shin, J., Hwang, U., and Yoon, S. Entropy is not enough for test-time adaptation: From the perspective of disentangled factors. In *International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=9w3iw8wDuE.

Li, X., Xiong, H., An, H., Xu, C.-Z., and Dou, D. RIFLE: Backpropagation in depth for deep transfer learning through re-initializing the fully-connected LayEr. In *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 6010–6019, 2020. URL https://proceedings.mlr.press/v119/li20r.html.

Liang, J., Hu, D., and Feng, J. Do we really need to access the source data? Source hypothesis transfer for unsupervised domain adaptation. In *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 6028–6039, 2020. URL https://proceedings.mlr.press/v119/liang20a.html.

Martens, J. New insights and perspectives on the natural gradient method. *Journal of Machine Learning Research*, 21(146):1–76, 2020. URL https://jmlr.org/papers/v21/17-678.html.

Neyshabur, B., Sedghi, H., and Zhang, C. What is being transferred in transfer learning? In *Advances in Neural Information Processing Systems*, volume 33, pp. 512–523, 2020. URL https://papers.nips.cc/paper/2020/hash/0607f4c705595b911a4f3e7a127b44e0-Abstract.html.

Ovadia, Y., Fertig, E., Ren, J., Nado, Z., Sculley, D., Nowozin, S., Dillon, J. V., Lakshminarayanan, B., and Snoek, J. Can you trust your model's uncertainty? evaluating predictive uncertainty under dataset shift. In *Advances in Neural Information Processing Systems*, volume 32, 2019. URL https://proceedings.neurips.cc/paper/2019/hash/8558cb408c1d76621371888657d2eb1d-Abstract.html.

Park, S., Moon, J., Kim, S., Cho, W. I., Han, J. Y., Park, J., Song, C., Kim, J., Song, Y., Oh, T., Lee, J., Oh, J., Lyu, S., Jeong, Y., Lee, I., Seo, S., Lee, D., Kim, H., Lee, M., Jang, S., Do, S., Kim, S., Lim, K., Lee, J., Park, K., Shin, J., Kim, S., Park, L., Oh, A., Ha, J.-W., and Cho, K. KLUE: Korean language understanding evaluation. In *Thirty-fifth Conference on Neural Information Processing Systems Datasets and Benchmarks Track (Round 2)*, 2021. URL https://openreview.net/forum?id=q-8h8-LZiUm.

Pontiki, M., Galanis, D., Pavlopoulos, J., Papageorgiou, H., Androutsopoulos, I., and Manandhar, S. SemEval-2014 task 4: Aspect based sentiment analysis. In Nakov, P.

and Zesch, T. (eds.), *Proceedings of the 8th International Workshop on Semantic Evaluation (SemEval 2014)*, pp. 27–35, Dublin, Ireland, August 2014. Association for Computational Linguistics. doi: 10.3115/v1/S14-2004. URL https://aclanthology.org/S14-2004.

Qwen Team. Qwen3-4B-Instruct-2507 model card. Hugging Face model repository, 2025. URL https://huggingface.co/Qwen/Qwen3-4B-Instruct-2507.

Sohn, K., Berthelot, D., Carlini, N., Zhang, Z., Zhang, H., Raffel, C. A., Cubuk, E. D., Kurakin, A., and Li, C.-L. FixMatch: Simplifying semi-supervised learning with consistency and confidence. In *Advances in Neural Information Processing Systems*, volume 33, 2020. URL https://proceedings.neurips.cc/paper/2020/hash/06964dce9addb1c5cb5d6e3d9838f733-Abstract.html.

Sun, B. and Saenko, K. Deep CORAL: Correlation alignment for deep domain adaptation. In *Computer Vision – ECCV 2016 Workshops*, volume 9915 of *Lecture Notes in Computer Science*, pp. 443–450, 2016. doi: 10.1007/978-3-319-49409-8_35. URL https://link.springer.com/chapter/10.1007/978-3-319-49409-8_35.

Wang, W., Wei, F., Dong, L., Bao, H., Yang, N., and Zhou, M. MiniLM: Deep self-attention distillation for task-agnostic compression of pre-trained transformers. In *Advances in Neural Information Processing Systems*, volume 33, pp. 5776–5788, 2020. URL https://proceedings.neurips.cc/paper/2020/hash/3f5ee243547dee91fbd053c1c4a845aa-Abstract.html.

Wang, Y., Chen, H., Heng, Q., Hou, W., Fan, Y., Wu, Z., Wang, J., Savvides, M., Shinozaki, T., Raj, B., Schiele, B., and Xie, X. FreeMatch: Self-adaptive thresholding for semi-supervised learning. In *International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=PDrUPTXJI_A.

Wei, C., Shen, K., Chen, Y., and Ma, T. Theoretical analysis of self-training with deep networks on unlabeled data. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=rC8sJ4i6kaH.

Yang, Y., Zhang, Y., Tar, C., and Baldridge, J. PAWS-X: A cross-lingual adversarial dataset for paraphrase identification. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing*, pp. 3687–3692, 2019. doi: 10.18653/v1/D19-1382. URL https://aclanthology.org/D19-1382/.

Yosinski, J., Clune, J., Bengio, Y., and Lipson, H. How transferable are features in deep neural networks? In *Advances in Neural Information Processing Systems*, volume 27, 2014. URL https://proceedings.neurips.cc/paper_files/paper/2014/hash/532a2f85b6977104bc93f8580abbb330-Abstract.html.

Zhang, B., Wang, Y., Hou, W., Wu, H., Wang, J., Okumura, M., and Shinozaki, T. FlexMatch: Boosting semi-supervised learning with curriculum pseudo labeling. In *Advances in Neural Information Processing Systems*, volume 34, 2021. URL https://proceedings.neurips.cc/paper/2021/hash/995693c15f439e3d189b06e89d145dd5-Abstract.html.

Zhang, X., Zhao, J., and LeCun, Y. Character-level convolutional networks for text classification. In *Advances in Neural Information Processing Systems*, volume 28, 2015. URL https://proceedings.neurips.cc/paper/2015/hash/250cf8b51c773f3f8dc8b4be867a9a02-Abstract.html.

Zhao, H., Tachet des Combes, R., Zhang, K., and Gordon, G. J. On learning invariant representations for domain adaptation. In *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pp. 7523–7532, 2019. URL https://proceedings.mlr.press/v97/zhao19a.html.

Zheng, M., You, S., Huang, L., Wang, F., Qian, C., and Xu, C. SimMatch: Semi-supervised learning with similarity matching. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 14471–14481, 2022. URL https://openaccess.thecvf.com/content/CVPR2022/html/Zheng_SimMatch_Semi-Supervised_Learning_With_Similarity_Matching_CVPR_2022_paper.html.

Zou, Y., Yu, Z., Kumar, B. V. K. V., and Wang, J. Unsupervised domain adaptation for semantic segmentation via class-balanced self-training. In *Proceedings of the European Conference on Computer Vision*, pp. 289–305, 2018. URL https://openaccess.thecvf.com/content_ECCV_2018/html/Yang_Zou_Unsupervised_Domain_Adaptation_ECCV_2018_paper.html.

A. Derivations and Interpretation

A.1. Proof of Proposition 1 and Corollary 1

For a fixed teacher and gate, expectation over $(x, y) \sim T$ gives

$$g_w = \frac{\mathbb{E}[w\nabla_v \ell_v(x, \hat{y})]}{\rho} = \frac{\mathbb{E}[wg^*]}{\rho} + \frac{\mathbb{E}[w\delta]}{\rho} \tag{22}$$

$$= \mathbb{E}[g^*] + \frac{\mathbb{E}[(w-\rho)(g^* - g_T)]}{\rho} + \frac{\mathbb{E}[w\delta]}{\rho}. \tag{23}$$

This is Eq. (7). By Cauchy–Schwarz and $w^2 = w$,

$$\left\| \frac{\mathrm{Cov}(w, g^*)}{\rho} \right\| \le \rho^{-1} \sqrt{\mathbb{E}(w-\rho)^2} \sqrt{\mathbb{E}\|g^* - g_T\|^2} = \sqrt{\frac{1-\rho}{\rho}} \sigma_g. \tag{24}$$

If $f_v(x)$ denotes the logits, cross-entropy gradients satisfy

$$\delta = J_f(x)^\top (e_y - e_{\hat{y}}), \qquad \|\delta\| \le \sqrt{2} M \mathbf{1}[y \ne \hat{y}]. \tag{25}$$

Taking the conditional expectation on accepted inputs proves Eq. (8). The derivation applies pointwise in parameters, provided the gate is held fixed and the stated moments exist. It does not require target labels to be accessible to training. The gold-gradient quantities are analytical objects; the reported experiments do not estimate them or optimize this upper bound.

The smoothness inequality gives $R_T(v - \eta g_w) \le R_T(v) - \eta\langle g_T, g_w\rangle + L\eta^2\|g_w\|^2/2$. Substituting $g_w = g_T + (g_w - g_T)$ and applying Cauchy–Schwarz yields Eq. (9). For example, if $\|g_w - g_T\| < \|g_T\|$, sufficiently small positive η gives a descent guarantee whenever $g_w \ne 0$. The gate alone does not enforce this condition. It formalizes the distinction between reinforcing a pseudo-label and improving the true target risk under a given update.

A.2. Proof of Proposition 2 and Corollary 2

Let $A(b) = \log \sum_j \exp b_j$. For fixed teacher probabilities $q = \nabla A(b_0)$,

$$\mathrm{KL}(q \| \,\mathrm{softmax}(b_0 + \Delta b)) = A(b_0 + \Delta b) - A(b_0) - q^\top \Delta b. \tag{26}$$

A Taylor expansion of A gives the rowwise KL quadratic form, since $\nabla^2 A(b_0) = \mathrm{diag}(q) - qq^\top$. This Hessian is positive semidefinite because $u^\top(\mathrm{diag}(q) - qq^\top)u = \mathrm{Var}_{j\sim q}(u_j) \ge 0$. The all-ones vector is a null direction, reflecting softmax shift invariance. Combining the row expansion with the attention-logit Jacobian and averaging the fixed finite pool produces Eqs. (11)–(12). The expansion assumes a fixed valid-key mask and finite logits and is local around matching teacher/student logits. It does not assert a global bound on feature drift or task error. Dropout rows in the implementation are masked and renormalized; this local expansion concerns the deterministic softmax map on valid keys. For $d \in \ker F_{A,w}$, substituting $\Delta\theta = td$ removes the quadratic term, giving $R_{A,w}(\theta_0 + td) = O(|t|^3)$. Independently, the encoder Taylor expansion gives $tJ_\phi(x)d + O(t^2)$. A nonzero first-order coefficient proves Corollary 2 under its nonzero-Jacobian condition.

A.3. Proof of Proposition 3

For fixed x, cross-entropy differentiated through logits gives $\nabla_z \ell = W^\top(p_v - e_{\hat{y}})$, hence Eq. (13). Under the update $\theta' = \theta - \eta\nabla_\theta \ell$, a C^2 encoder satisfies $\phi_{\theta'}(x) = \phi_\theta(x) - \eta J_\phi \nabla_\theta \ell + O(\eta^2)$. Substitution yields Eq. (14). Both Jacobians and probabilities are evaluated before the step. For a nonlinear head, its logit Jacobian replaces W; the claim concerns a single local update and does not assert global optimizer convergence.

A.4. Identity 1 and finite probes

The identity $R_T(\theta, W) = R_T^*(\theta) + G_T(\theta, W)$ follows from the definition of G_T. Subtracting two checkpoints gives Eq. (15). The infimum avoids assuming existence of a finite optimum for separable data. With regularization, the same algebra holds if the objective and head family are defined consistently. In the experiments, a standardized, regularized, finite-support logistic regression is a controlled decoder, not an oracle achieving R_T^*. Its utility is comparability: every representation receives the same support, decoder family, and regularization. Probe labels are additional supervision for evaluation and are not part of the unsupervised target-adaptation claim.

Algorithm 1 KPC-CF: selective target adaptation with a frozen source teacher

Require: Source teacher v_0, source S, unlabeled target T, scorer e, retention ρ, KL weight λ, reset flag r.
1: Cache teacher probabilities and source/target embeddings.
2: Compute source-neighbor support using Eq. (3).
3: Fix $\hat{y}$, empirical ranks, and gate w via Eq. (4).
4: Initialize $\theta \leftarrow \theta_0$; set $\omega \leftarrow \omega_0$ or reset ω if $r = 1$.
5: **for** each predetermined adaptation update **do**
6: Sample accepted target inputs; evaluate frozen-teacher attention if $\lambda > 0$.
7: Update trainable encoder parameters and task head using Eq. (6).
8: **end for**
9: Evaluate the adapted head, then fit fresh probes on fixed labeled support with the encoder frozen.

A.5. Why the two drifts cannot be interchanged

For fixed θ, $D^{S,T}$ compares two input distributions through the same encoder. For fixed input IDs, $D^{0,t}$ compares two encoders on a fixed input distribution. A representation can preserve its target mean before/after adaptation while source–target discrepancy changes, or vice versa. Further, small differences in first and second moments do not imply pointwise feature equality, matching class conditionals, or proximity of parameter vectors. Our figures use the indicated diagnostic and preserve its conditioning variables. Reduced attention discrepancy likewise concerns observed probability distributions, rather than parameter-space proximity or preservation of individual feature vectors.

B. Protocol and Reproducibility Inventory

Table 8. **Training and evaluation protocol.** Qwen3-4B-Instruct-2507 and XLM-R-base. Update caps interact with epoch budgets and selected-pool size. The Qwen continuation restarts optimizer and scheduler at step 150. Component source superscripts follow Table 1.

Protocol factor	Model and experiment family	
	Qwen3: factorial/budget	XLM-R: general-task adaptation
Backbone	Qwen3-4B-Instruct-2507 (Qwen Team, 2025)	XLM-RoBERTa-base (Conneau et al., 2020)
Adaptation	4-bit QLoRA plus task head	Encoder plus task head
Maximum length	128	192
Effective batch size	16	32
Learning rate	10^{-4}	2×10^{-5}
Weight decay	0.01	0.01
Source teacher update cap	200	500
Student budget	150, then 450 additional	400-update cap, at most 2 epochs
Main seeds	17, 23, 42 (student)	17, 23, 41 (source/student)
Teacher/filter during repeats	Fixed to seed 17	Recomputed per source/student seed
Main retention	60%	60%
LaBSE scorer[b]	LaBSE	LaBSE
Neighborhood	20 neighbors, temperature 0.1	20 neighbors, temperature 0.1
Attention KL[c]	Teacher-to-student, final layer	Teacher-to-student, final layer
KL coefficient	0.1	0.1
Head reset[d]	Task classification head only	Task classification head only
Checkpoint selection	Final predetermined update	Final predetermined update

Qwen uses LoRA rank 16 and alpha 32. Its model revision is `cdbee75f17c01a7cc42f958dc650907174af0554`. Teacher labels and selection files are cached before adaptation. The source teacher's seed is not resampled in the three-student-seed comparison; neither are the probe supports or test sets. Student seed repetitions therefore measure conditional training variation. XLM-R main seeds include 41 rather than Qwen's 42, and these estimates are not pooled.

For Qwen, the 150-step budget processes 2,400 sample exposures and the total 600-step budget processes 9,600 at effective batch size 16. A retained pool of 4,800 is a candidate set, not a claim that every example is visited during the first 150 updates. All uses 8,000 candidates at the same update budget. Confidence, Semantic, and Dual have identical retained counts but can differ in class composition and actual examples encountered. A same-count comparison isolates the selection rule from nominal retention, not from all downstream distributional consequences.

The frozen probes use the last valid token for Qwen and the stored encoder feature for XLM-R. Standardization is fit on

the labeled support only, followed by logistic regression at $C = 1$. The MASSIVE protocol evaluates Macro-F1 over the configured 60-class label inventory, including classes absent from a particular test subset. This convention is held fixed across methods. Cross-task means weight MASSIVE, AG News, and PAWS-X equally; task scores and student seeds are not treated as independent replicates of a single random quantity.

Fixed labeled supports contain 852/667/2,000/663 examples for XNLI/MASSIVE/AG News/PAWS-X, respectively.

KL gradient verification. The Qwen trainer uses non-reentrant checkpointing so that returned attention tensors remain connected to the adaptation graph. The revised trainer produces finite, nonzero KL-only LoRA gradients. Earlier checkpoints produced under a detached-attention implementation are not used as KL-enabled results. Dual and Dual+reinit checkpoints were reused after a two-step no-KL equivalence check of logits, gradients, and optimizer updates; this check verifies the unchanged no-KL path without claiming that a newly rerun full trajectory was compared bitwise. Gradient connectivity establishes that the regularizer is active, not that its contribution is beneficial at every endpoint.

Data and noise axes. XNLI uses a French translated source and English target. MASSIVE transfers from English to Korean; PAWS-X transfers from Korean to English. Parallel groups are assigned to source or target rather than placing both translations of a training group on opposite sides. AG News uses disjoint native-English subsets for source and target in the same topic domain. Its noise sweep randomly corrupts source labels at 0, 20, or 40%; it is not a translation-noise severity experiment or an out-of-domain benchmark. Alternative source-neighborhood encoders include LaBSE, multilingual E5, BGE, and frozen teacher features in the existing seed-17 comparison. These scorer comparisons assess sensitivity to the semantic space and do not constitute three-seed replications for every scorer.

Scope of evidence. The general-task source datasets, partitions, source labels, student seeds, and checkpoint identities are recorded with the experiment artifacts. Geometry, attention, and parameter summaries retain their own sample scope. The repeated Qwen study supplies the main quantitative component claims. The seed-17 scorer/noise explorations and 16-example attention replay supply complementary mechanism diagnostics. The original ABSA measurements use a distinct protocol and are retained as application results; they are not assigned the new experiment's seed uncertainty.

C. Complete XLM-R General-Task Results

Table 9. **Complete XLM-R general-task evaluation.** Macro-F1 mean ± SD across three source/student seeds. Each task receives direct adaptation and a fresh probe on fixed labeled support. Shading marks row maxima, including the teacher.

Dataset / task	Readout	Source	Target adaptation variant			
		Teacher	All	Confidence	Dual	Full
AG News (Zhang et al., 2015)	Head	89.93 ± 0.31	89.85 ± 0.61	88.79 ± 0.35	89.11 ± 0.31	89.65 ± 0.28
Topic (en)	Probe	88.34 ± 0.47	89.04 ± 0.23	88.50 ± 0.12	88.78 ± 0.18	88.87 ± 0.19
MASSIVE (FitzGerald et al., 2023)	Head	28.79 ± 2.77	25.95 ± 2.26	18.65 ± 1.98	24.83 ± 2.55	18.75 ± 0.46
Intent (ko)	Probe	53.42 ± 0.09	54.20 ± 1.00	52.46 ± 0.22	54.79 ± 1.42	51.85 ± 0.53
PAWS-X (Yang et al., 2019)	Head	63.49 ± 15.24	63.36 ± 15.89	62.64 ± 11.13	61.84 ± 16.40	62.83 ± 14.18
Paraphrase (en)	Probe	66.89 ± 14.69	68.26 ± 15.57	68.39 ± 15.72	69.39 ± 17.28	68.99 ± 15.99
XNLI (Conneau et al., 2018)	Head	53.77 ± 9.28	55.87 ± 8.60	52.70 ± 13.18	53.28 ± 12.74	53.46 ± 12.75
Inference (en)	Probe	54.98 ± 1.50	57.80 ± 1.81	56.33 ± 3.49	57.56 ± 3.01	57.47 ± 3.24

Rank transitions separate classifier behavior from reusable features; proper losses quantify native-head probability quality. The large seed spread on PAWS-X and XNLI reflects the measured regime. Reporting teacher, student, and probe means together exposes inherited source-training variation. Qwen instead fixes the teacher to isolate student optimization and component effects. These repetition designs separate upstream variability from conditional adaptation effects.

D. Aspect-Specific Instantiation and Original Application Results

The original application casts review–aspect pairs as classification inputs. Its source is translated SemEval-2014 supervision (Pontiki et al., 2014) (Kor-SemEval), and its target is the original native Korean review corpus (KR3). Labels combine aspect absence with sentiment categories, enabling aspect category detection (ACD) and aspect category polarity (ACP) evaluation. The aspect gate combines review–aspect LaBSE cosine with maximum teacher probability above 0.5. The original main-table protocol reports a cosine cutoff of 0.15; the original ablation table denotes a mean-based cosine cutoff.

These reported protocols are retained separately from the rank-normalized source-neighbor gate of Eq. (4).

Table 10. **Original KR3 application results by backbone and training order.** mBERT and XLM-R transfer translated SemEval-2014 supervision (Pontiki et al., 2014) to native KR3 reviews. Original-protocol ACD Micro-F1 and polarity accuracy; shading marks maxima within each backbone/order pair of reported target-supervision variants.

Backbone	Training order	Target supervision	Detection	Polarity accuracy		
			ACD μF1	4-way	3-way	Binary
mBERT (Devlin et al., 2019)	Joint	Unfiltered	84.64	80.45	82.71	86.57
		Filtered	85.42	80.88	83.15	86.96
	Sequential	Unfiltered	83.73	78.37	80.58	84.60
		Filtered	83.47	78.94	81.16	85.09
XLM-R (Conneau et al., 2020)	Joint	Unfiltered	87.57	83.43	85.78	89.34
		KPC-CF	87.75	83.52	85.90	89.56
	Sequential	Unfiltered	87.69	84.21	86.57	90.35
		KPC-CF	88.29	84.34	86.72	90.89

The original comparisons distinguish training order from backbone capacity. Joint mBERT filtering improves ACD by 0.78 points and binary polarity by 0.39 points. Sequential XLM-R Full improves the same endpoints by 0.60 and 0.54 points. Sequential mBERT, however, improves polarity while its ACD decreases by 0.26 points. Detection and polarity therefore remain separate endpoints even within the original application.

Table 11. **Original XLM-R ablations on KR3.** Detection and polarity follow the original protocol, including training-order and throughput differences. The new Qwen3 factorial study supplies matched-support, matched-budget estimates. Superscripts identify the component sources in Table 1 for confidence, semantics, attention KL, and head reset. Shading marks metric maxima.

Adaptation variant	Detection	Polarity accuracy		
	ACD μF1	4-way	3-way	Binary
Unfiltered reference	87.57	83.43	85.78	89.34
Semantic threshold[b]	88.44	83.31	85.66	89.78
Confidence threshold[a]	87.14	84.50	86.88	90.86
Dual + KL (original)[c]	87.75	83.52	85.90	89.56
Dual + reinitialization[d]	87.69	84.21	86.57	90.35
Full hard gate	88.29	84.34	86.72	90.89
Full soft gate	87.95	72.47	74.51	78.09

The ablations identify the strongest application regime without implying uniform component gains. Semantic filtering has the highest ACD point estimate, while Full's hard gate achieves the highest binary polarity score. Replacing that gate with the reported soft variant lowers four-way polarity from 84.34 to 72.47. This contrast motivates preserving the gate definition and training schedule explicitly when transferring the method to a new task.

Table 12. **Original XLM-R zero-shot semantic similarity.** KorSTS (Ham et al., 2020) and KLUE-STS (Park et al., 2021), using intermediate-layer mean pooling. Shading marks Spearman maxima, a distinct endpoint from trained Macro-F1 probes.

Representation training regime	Spearman $\rho \times 100$	
	KorSTS	KLUE-STS
Pretrained	11.41	−1.23
Source translated supervision	10.26	2.55
Target pseudo-labels only	12.18	7.59
Source then unfiltered target	9.21	6.35
KPC-CF	16.26	20.50

Semantic transfer supplies a second positive endpoint for the original Full configuration. Relative to source-then-unfiltered training, Full increases KorSTS correlation by 7.05 points and KLUE-STS by 14.15 points. These results motivate the general-task probe study while retaining the original evaluation's zero-shot pooling protocol and metric.

E. Measurement Details and Interpretation Boundaries

E.1. Inference and intent geometry




Figure 6. **Matched XLM-R geometry for inference and intent.** XNLI/MASSIVE rows compare All, Confidence, Dual, and Full on 512 matched target inputs per task, seed 17. Pooled raw-feature PCA across saved conditions provides common axes and camera within each row. Colors identify the eight most frequent classes; remaining classes are gray and large points mark centroids. Insets report full-dimensional raw B/W and effective rank r. Displayed components explain 71.78%/30.28% of pooled variance for XNLI/MASSIVE.

The same-backbone comparison exposes task-dependent geometry. On XNLI, raw B/W is 0.206, 0.184, and 0.190 for All, Dual, and Full, respectively; effective ranks are 3.89, 3.32, and 3.64. Full's raw B/W therefore remains below All here, unlike the Qwen specialization regime, locating geometry within its backbone and reference condition. On MASSIVE, Full has a larger raw B/W than Dual (2.470 versus 2.275) and a lower effective rank (19.08 versus 24.87). Despite this class organization, the three-seed in-task probe favors Dual over Full.

MASSIVE's 512-example atlas contains 57 of 60 configured classes. Its eight most frequent classes account for 208 examples; 304 points are gray. Scatter and rank use all 512 inputs, while centroids represent only observed classes.

Geometry. Covariance effective rank is $\exp(-\sum_j r_j \log r_j)$, where r_j are nonnegative covariance eigenvalues normalized by their sum. For centered feature matrices X, Y, linear CKA is $\|X^\top Y\|_F^2/(\|X^\top X\|_F \|Y^\top Y\|_F)$. Geometry uses raw and separately L_2-normalized features, distinct from probe standardization. Labels enter only post-training scatter measurement. Each comparison shares the projection to avoid movement caused by independently refitted coordinates.

Attention. Replay excludes padding and uses the valid causal mask when applicable. The descriptive XLM-R replay covers 12 layers and 12 heads on 16 fixed inputs. Saved and replayed probabilities agree exactly under the matched batch/precision setting. Distributions summarize these same inputs repeatedly across layer/head structure; the resulting rows are not independent examples for significance testing. Attention Jensen–Shannon divergence is a symmetric diagnostic, whereas the optimized KL is directional teacher-to-student. Their roles and numerical scales differ.

E.2. Paraphrase and topic geometry




Figure 7. **Matched XLM-R geometry for paraphrase and topic classification.** Rows show PAWS-X and AG News; columns show All, Confidence, Dual, and Full. Each row contains the same 512 target inputs, seed 17, and a pooled PCA across saved conditions, with shared axes and camera. Colors identify classes by their within-task frequency rank; large points are class centroids. Insets show raw full-dimensional B/W and effective rank r. The displayed components explain 87.71% and 72.46% of pooled variance. AG News uses 20% synthetic source-label noise; PAWS-X uses the zero-added-label-noise condition.

PAWS-X illustrates why the scale of a ratio matters alongside its relative change. Raw B/W increases from 0.00179 for All to 0.00248 for Dual and 0.00467 for Full, while effective rank decreases from 5.27 to 3.14 and 3.04. Although the relative change is large, between-class scatter remains small compared with within-class scatter. Reporting both the absolute values and the common-coordinate projection prevents a relative percentage from implying complete separation. Both binary classes are represented, and every displayed input has an observed class label.

AG News exhibits a different ordering on the same backbone. Raw B/W is largest for Confidence (2.796), followed by Dual (2.683), All (2.617), and Full (2.470). Full instead has the largest effective rank: 4.23 versus 3.80–4.07 for the other configurations. The four topic classes all appear in the fixed subset. These measurements support a task-conditional interpretation of rank and scatter: neither lower rank nor larger B/W serves as a universal surrogate for the adapted head or a fresh probe. Matched projections locate these differences; full-dimensional statistics and distinct adapted-head and fresh-probe scores determine which geometric changes accompany useful prediction.

Parameters. Effective Qwen adapter changes incorporate LoRA scaling, so their norms describe linear-map updates rather than arbitrary factor rescalings. The seed-17 analysis includes 14 checkpoints across seven configurations and two budgets. Head reset creates initial displacement by construction; subsequent backbone updates and readout/probe differences supply the informative comparison. Parameter norms are structural measurements, not performance surrogates.

Study boundaries. The repeated Qwen comparisons condition on a fixed teacher and filter; other-task probes measure transfer to specified linear readouts. Four directly adapted XLM-R tasks establish a different ranking. Section 4 provides identities and local expansions, rather than a universal risk guarantee. Three student seeds support paired descriptions, with model/task dependence retained in the endpoint-aware interpretation.

F. Attention Distributions and Complementary Structural Measurements




Figure 8. **Geometry and parameter updates complement attention.** (a,b) Normalized within-scatter and B/W, Full minus All (Qwen, three-seed mean ± SD); (c) final-layer JS per input, averaging 12 heads over 16 matched GPU BF16 XLM-R inputs; (d) effective LoRA update ECDF (Qwen, seed 17, staged 600). Measurement scopes remain separate.

Relative to All, Full's raw B/W rises by 156%/193% and effective rank falls by 27.46/36.06 at 150/600 updates. Scale normalization changes the interpretation: at 150, raw within-scatter falls 6.85% but normalized scatter rises 5.51%; at 600, both fall, by 18.76%/8.31%. Normalized B/W still rises approximately 149%/182%.

Normalized within-scatter rises at 150 updates but falls at 600, whereas normalized B/W increases at both budgets. Angular class organization therefore differs from uniform contraction. Effective updates incorporate LoRA scaling and describe trained linear maps; sampled coordinates are descriptive measurements, not independent training repetitions.




Figure 9. **Layer-resolved attention distributions.** Columns: Dual, Dual+KL, Dual+reinit, Full. Top: teacher–student JS density across 12 layers; bottom: normalized entropy density. Conditions share 16 XLM-R XNLI inputs and 12 heads from GPU BF16 replay (batch 16), with common bins/scales. Repeated input/head measurements describe shape, not independent model replications.

All-layer normalized entropies are 0.5302, 0.5012, 0.5452, and 0.5075 in column order. Lower JS coexists with concentrated attention and layerwise variation. JS is symmetric; optimized KL is directional. Matched probabilities reproduce exactly. These XLM-R measurements remain distinct from Qwen geometry and historical Korean review results.