

Column1	Column2	Column3	Column5
Ref	Qty	Value	Footprint
C1, C2, C3, C14, C15, C18, C19,	7	10uF	Capacitor_SMD:C_0603_1608Metric
C4, C5, C6, C8, C9, C10, C11, C12, C13, C17, C20, C21, C22, C23, C25, C26,	16	100nF	Capacitor_SMD:C_0603_1608Metric
C7,	1	4.7uF	Capacitor_SMD:C_0603_1608Metric
C16,	1	22uF	Capacitor_SMD:C_0603_1608Metric
D1, D2, D3, D4,	4	LED	LED_SMD:LED_0603_1608Metric
IC1,	1	TPS2114PW	SOP65P640X120-8N
J1,	1	Conn_01x06	Connector_Molex:Molex_KK-254_AE-6410-06A_1x06_P2.54mm_Vertical
J2,	1	Conn_02x02_Odd_Even	Connector_Molex:Molex_Micro-Fit_3.0_43045-0412_2x02_P3.00mm_Vertical
J3, J4,	2	Conn_01x03	Connector_Molex:Molex_KK-254_AE-6410-03A_1x03_P2.54mm_Vertical
J6,	1	Cortex Debug Connector	My Connectors:20021521-00010T1LF
L1,	1	10uH	Inductor_SMD:L_0603_1608Metric
R1, R7, R10, R13,	4	2k2	Resistor_SMD:R_0603_1608Metric
R3, R4, R5, R6, R8, R9, R11,	7	10k	Resistor_SMD:R_0603_1608Metric
R12,	1	400	Resistor_SMD:R_0603_1608Metric
U1,	1	ATSAME53J18A-M	Package_DFN_QFN:QFN-64-1EP_9x9mm_P0.5mm_EP4.7x4.7mm
U2,	1	ISM330DHCXTR	IMU:ISM330DHCXTR
U3,	1	MLX90395KGO-BBA-101-SP	Magnetometer:MLX90395KGO-BBA-101-SP
U4,	1	MS5611-01BA	Package_LGA:LGA-8_3x5mm_P1.25mm
U5,	1	AZ1117-3.3	Package_TO_SOT_SMD:SOT-89-3
U6,	1	2201778-1	My SD-card:2201778-1
U7,	1	2468	Battery:BatteryHolder_Keystone_2468_2xAAA

Column6	Column7
Description	Vendor
Unpolarized capacitor, small symbol	
Unpolarized capacitor, small symbol	
Unpolarized capacitor, small symbol	
Unpolarized capacitor, small symbol	
Light emitting diode	
Dual In/Single Out Autoswitching Power MUX, Manual/Auto Switching, Adj. Cur Limit, Switch Status	
Generic connector, single row, 01x06, script generated (kicad-library-utils/schlib/autogen/connector/	
Generic connector, double row, 02x02, odd/even pin numbering scheme (row 1 odd numbers, row 2	
Generic connector, single row, 01x03, script generated (kicad-library-utils/schlib/autogen/connector/	
Generic connector, double row, 02x05, odd/even pin numbering scheme (row 1 odd numbers, row 2	
Inductor, small symbol	
Resistor, small symbol	
Resistor, small symbol	
Resistor, small symbol	
SAM E53 Microchip SMART ARM Cortex-M4F based MCU, 256K Flash, 128K SRAM, QFN-64	
Barometric pressure sensor, 10cm resolution, 10 to 1200 mbar, I2C and SPI interface up to 20MHz, LC	
1A 20V Fixed LDO Linear Regulator, 3.3V, SOT-89/SOT-223/TO-220/TO-252/TO-263	
KEYSTONE - 2462 - BATTERY HOLDER	