




ulm university

universität

uulm



Rens W. van der Heijden,
Henning Kopp, Frank Kargl

2018-07-13


Multi-source Fusion Operations in Subjective Logic

FUSION Conference 2018


Motivation




Motivation




Motivation



Motivation



Motivation



Subjective Logic Introduction

$$X \in \mathbb{X} = \{x_1, x_2, x_3\}$$

Subjective Logic Introduction

$$X \in \mathbb{X} = \{x_1, x_2, x_3\}$$

$$\omega_X^A$$

Subjective Logic Introduction

$$X \in \mathbb{X} = \{x_1, x_2, x_3\}$$

$$\omega_X^A = (\quad , \mathbf{a}_X^A)$$

Subjective Logic Introduction

$$X \in \mathbb{X} = \{x_1, x_2, x_3\}$$

$$\omega_X^A = (\mathbf{b}_X^A, \quad , \mathbf{a}_X^A)$$

Subjective Logic Introduction

$$X \in \mathbb{X} = \{x_1, x_2, x_3\}$$

$$\omega_X^A = (\mathbf{b}_X^A, u_X^A, \mathbf{a}_X^A)$$

Subjective Logic Introduction

$$X \in \mathbb{X} = \{x_1, x_2, x_3\}$$

$$\omega_X^A = (\mathbf{b}_X^A, u_X^A, \mathbf{a}_X^A) \quad c_X^A = 1 - u_X^A = \sum_x \mathbf{b}_X^A(x)$$

Subjective Logic Introduction

$$X \in \mathbb{X} = \{x_1, x_2, x_3\}$$

$$\omega_X^A = (\mathbf{b}_X^A, u_X^A, \mathbf{a}_X^A) \quad c_X^A = 1 - u_X^A = \sum_x \mathbf{b}_X^A(x)$$

$$\text{multinomial opinions: } \mathbf{b}_X^A : \mathbb{X} \rightarrow [0, 1]$$

Subjective Logic Introduction


$$X \in \mathbb{X} = \{x_1, x_2, x_3\}$$

$$\omega_X^A = (\mathbf{b}_X^A, u_X^A, \mathbf{a}_X^A) \quad c_X^A = 1 - u_X^A = \sum_x \mathbf{b}_X^A(x)$$

multinomial opinions: $\mathbf{b}_X^A : \mathbb{X} \rightarrow [0, 1]$


hyper-opinions: $\mathbf{b}_X^A : \mathcal{P}(\mathbb{X}) \rightarrow [0, 1]$

Subjective Logic Multinomial Example



Domain $\mathbb{X} = \{r, g, b\}$


Subjective Logic Multinomial Example



Domain $\mathbb{X} = \{r, g, b\}$

Use ω_X^A to model whether the die is weighted, e.g., by repeated experiments

Subjective Logic Multinomial Example




Domain $\mathbb{X} = \{r, g, b\}$

Use ω_X^A to model whether the die is weighted, e.g., by repeated experiments

Fusion?

Subjective Logic Multinomial Example




Domain $\mathbb{X} = \{r, g, b\}$

Use ω_X^A to model whether the die is weighted, e.g., by repeated experiments


Fusion? \rightarrow combine results from different actors

Subjective Logic Hyper-opinion Example



Domain $\mathbb{X} = \{r, g, b\}$ for observations

Subjective Logic Hyper-opinion Example



Domain $\mathbb{X} = \{r, g, b\}$ for observations under:

- low light condition (green/blue indist.): $b_X^{LL}(\{g, b\})$
- colorblindness condition (red/green indist.): $b_X^{CB}(\{r, g\})$

→ no assignment of relative belief (as in multinomial case)!

Subjective Logic Fusion

Available binary operators:

- Cumulative Belief Fusion
- Belief Constraint Fusion (aka Dempster's Rule)
- Averaging Belief Fusion
- Weighted Belief Fusion
- Consensus & Compromise Fusion

Subjective Logic Fusion

Available binary operators:

- Cumulative Belief Fusion
- Belief Constraint Fusion (aka Dempster's Rule)
- Averaging Belief Fusion
- Weighted Belief Fusion
- Consensus & Compromise Fusion

Multi-source generalizations do not exist for all these operators!

Subjective Logic Fusion: Previous Work

Jøsang et al. (FUSION 2017) provide:

- Cumulative Belief Fusion
- Belief Constraint Fusion (aka Dempster's Rule)
- Averaging Belief Fusion
- Weighted Belief Fusion
- Consensus & Compromise Fusion

Subjective Logic Fusion: Commutativity

Dempster's Rule is commutative:

- Cumulative Belief Fusion
- **Belief Constraint Fusion (aka Dempster's Rule)**
- Averaging Belief Fusion
- Weighted Belief Fusion
- Consensus & Compromise Fusion

Subjective Logic Fusion: Our Work

We define multi-source fusion operations for:

- Cumulative Belief Fusion
- Belief Constraint Fusion (aka Dempster's Rule)
- Averaging Belief Fusion
- **Weighted Belief Fusion**
- **Consensus & Compromise Fusion**

Subjective Logic Fusion: WBF generalization

Two-source:

$$\mathbf{b}_X^{\hat{\diamond}^A}(x) = \frac{\mathbf{b}_X^A(x) \cdot c_X^A \cdot u_X^B + \mathbf{b}_X^B(x) \cdot c_X^B \cdot u_X^A}{u_X^A + u_X^B - 2u_X^A u_X^B}$$

Subjective Logic Fusion: WBF generalization

Two-source:

$$\mathbf{b}_X^{\hat{\diamond}\mathbb{A}}(x) = \frac{\mathbf{b}_X^A(x) \cdot c_X^A \cdot u_X^B + \mathbf{b}_X^B(x) \cdot c_X^B \cdot u_X^A}{u_X^A + u_X^B - 2u_X^A u_X^B}$$

Multi-source:

$$\mathbf{b}_X^{\hat{\diamond}\mathbb{A}}(x) = \frac{\sum_{A \in \mathbb{A}} \mathbf{b}_X^A(x) (1 - u_X^A) \prod_{A' \in \mathbb{A}, A' \neq A} u_X^{A'}}{\left(\sum_{A \in \mathbb{A}} \prod_{A' \neq A} u_X^{A'} \right) - |\mathbb{A}| \cdot \prod_{A \in \mathbb{A}} u_X^A}$$

Conclusion & Take-away

- Multi-source Fusion Operations

Conclusion & Take-away

- Multi-source Fusion Operations
- Proof of WBF through Dirichlet HPDFs (Theorem 1)

Conclusion & Take-away

- Multi-source Fusion Operations
- Proof of WBF through Dirichlet HPDFs (Theorem 1)
- Multi-source CCF provides valid opinions (Remark 4)

Conclusion & Take-away

- Multi-source Fusion Operations
- Proof of WBF through Dirichlet HPDFs (Theorem 1)
- Multi-source CCF provides valid opinions (Remark 4)
- Multi-source CCF is a valid generalization (Remark 5)

Conclusion & Take-away

- Multi-source Fusion Operations
- Proof of WBF through Dirichlet HPDFs (Theorem 1)
- Multi-source CCF provides valid opinions (Remark 4)
- Multi-source CCF is a valid generalization (Remark 5)
- Binomial Implementation:

<https://github.com/vs-uulm/subjective-logic-java>

Conclusion & Take-away

- Multi-source Fusion Operations
- Proof of WBF through Dirichlet HPDFs (Theorem 1)
- Multi-source CCF provides valid opinions (Remark 4)
- Multi-source CCF is a valid generalization (Remark 5)
- Binomial Implementation:

<https://github.com/vs-uulm/subjective-logic-java>

Next steps:

- Efficient representations

Conclusion & Take-away

- Multi-source Fusion Operations
- Proof of WBF through Dirichlet HPDFs (Theorem 1)
- Multi-source CCF provides valid opinions (Remark 4)
- Multi-source CCF is a valid generalization (Remark 5)
- Binomial Implementation:

<https://github.com/vs-uulm/subjective-logic-java>

Next steps:

- Efficient representations
- Computational efficiency of CCF

Questions?

Contact information

Web: <https://namnatulco.eu/work>

Email: rens.vanderheijden@uni-ulm.de

Twitter: [@namnatulco](https://twitter.com/namnatulco)

Acknowledgments & Licenses

We thank the following people for the fruitful discussions that led to this paper:

- David Köhler (Ulm University)
- Audun Jøsang (University of Oslo)

These slides are licensed as CC4.0-BY-SA. The title image is used under a CC0 License and can be found here:

[https://pixabay.com/en/
liquid-colors-ocean-waves-mix-1908965/](https://pixabay.com/en/liquid-colors-ocean-waves-mix-1908965/)

Slide & TikZ templates are available here:

<https://github.com/vs-uulm/latexslides-uulm>
<https://github.com/vs-uulm/tikz-vanet>

Backup Slides

Multi-source Weighted Belief Fusion

Definition (WBF of opinions for multiple sources)

Let \mathbb{A} be a finite set of actors and let $\omega_X^A = (\mathbf{b}_X^A, u_X^A, \mathbf{a}_X^A)$ denote the multinomial opinion held by $A \in \mathbb{A}$ over X . Then we define the weighted belief fusion of these opinions as the opinion $\omega_X^{\hat{\mathbb{A}}} = (\mathbf{b}_X^{\hat{\mathbb{A}}}, u_X^{\hat{\mathbb{A}}}, \mathbf{a}_X^{\hat{\mathbb{A}}})$ as follows:

Case 1: $(\forall A \in \mathbb{A} : u_X^A \neq 0) \wedge (\exists A \in \mathbb{A} : u_X^A \neq 1)$

$$\begin{aligned} \mathbf{b}_X^{\hat{\mathbb{A}}}(x) &= \frac{\sum_{A \in \mathbb{A}} \mathbf{b}_X^A(x) (1 - u_X^A) \prod_{A' \in \mathbb{A}, A' \neq A} u_X^{A'}}{\left(\sum_{A \in \mathbb{A}} \prod_{A' \neq A} u_X^A \right) - |\mathbb{A}| \cdot \prod_{A \in \mathbb{A}} u_X^A} \\ u_X^{\hat{\mathbb{A}}} &= \frac{\left(|\mathbb{A}| - \sum_{A \in \mathbb{A}} u_X^A \right) \cdot \prod_{A \in \mathbb{A}} u_X^A}{\left(\sum_{A \in \mathbb{A}} \prod_{A' \neq A} u_X^A \right) - |\mathbb{A}| \cdot \prod_{A \in \mathbb{A}} u_X^A} \\ \mathbf{a}_X^{\hat{\mathbb{A}}}(x) &= \frac{\sum_{A \in \mathbb{A}} \mathbf{a}_X^A(x) (1 - u_X^A)}{|\mathbb{A}| - \sum_{A \in \mathbb{A}} u_X^A} \end{aligned}$$