



# Certified Kubernetes Administrator (CKA)

By Cloud Mentor Pro

Updated: 10/04/2026



# Table of Contents

- Section 22 - Hướng dẫn schedule exam & Practice killer.sh

# Section 22 - Hướng dẫn schedule exam & Practice killer.sh

# Hướng dẫn schedule exam

Cloud Blog Pro

AWS Blog - Cộng đồng VN

Trang chủTags

Tìm kiếm

MỤC LỤC

1. Tổng quan quy trình

2. Tạo tài khoản

3. Setup Profile

4. (Optional) Request thêm thời gian

5. Đăng ký lịch thi

Bước 1: Truy cập dashboard

Bước 2: Kiểm tra thông tin

Bước 3: Click "Schedule"

Bước 4: Chọn lịch

6. Ngày thi (Exam Day)

Trước khi thi

Setup phòng thi

Quy trình thi với PSI

Một số lưu ý quan trọng

Giao diện thi

7. Kết quả

Email kết quả

Xem chứng chỉ

Kết quả cá nhân (Mình đạt: 100/100 ^\_^)

Tips thực chiến

Trước khi thi

Trong lúc thi

Tổng kết

Hướng dẫn đăng ký & thi CKA

kubernetes  
AND  
CLOUD NATIVE  
ASSOCIATE

kubernetes  
AND  
CLOUD NATIVE  
SECURITY  
ASSOCIATE

CERTIFIED  
kubernetes  
ADMINISTRATOR

CERTIFIED  
kubernetes  
APPLICATION  
DEVELOPER

CERTIFIED  
kubernetes  
SECURITY  
SPECIALIST

k8s

Hướng dẫn đăng ký & thi CKA (Certified Kubernetes Administrator)

Phong Nguyen Van

5 tháng 4, 2026

6 phút đọc

16 lượt xem

Chia sẻ

1. Tổng quan quy trình

Để thi chứng chỉ CKA (Certified Kubernetes Administrator), bạn sẽ đi qua các bước sau:

© Copyright by Cloud Mentor Pro | Confidential

<https://blog.cloudmentor.pro/posts/huong-dan-dang-ky-thi-cka-certified-kubernetes-administrator>

5

# Killer.sh

# Khi kích hoạt sẽ có 36h, không giới hạn số lần

The screenshot displays the CKA Simulator interface. On the left, a sidebar shows 'Preview Question 1' with instructions to use the context 'k8s-c2-AC' and find information about etcd on cluster2-master1. The main area is split into two panes. The top pane shows a terminal window with a Pod spec for 'with-node-affinity'. The bottom pane shows the output of the 'k get ns' command, listing namespaces and their ages. To the right, a browser window displays the Kubernetes documentation for 'Assigning Pods to Nodes', showing a Pod spec example with node affinity rules.

**Preview Question 1**

Use context: `kubectl config use-context k8s-c2-AC`

The cluster admin asked you to find out the following information about etcd running on cluster2-master1:

- Server private key location
- Server certificate expiration date
- Is client certificate authentication enabled

Write these information into `/opt/course/p1/etcd-info.txt`

Finally you're asked to save an etcd snapshot at `/etc/etcd-snapshot.db` on cluster2-master1 and display its status.

```
apiVersion: v1
kind: Pod
metadata:
  name: with-node-affinity
spec:
  affinity:
    nodeAffinity:
      requiredDuringSchedulingIgnoredDuringExecution:
        nodeSelectorTerms:
          - matchExpressions:
              - key: kubernetes.io/os
                operator: In
                values:
                  - linux
```

```
-- INSERT --
```

```
k8s@terminal:~$ k get ns
NAME                STATUS   AGE
default              Active   3d3h
kube-node-lease      Active   3d3h
kube-public          Active   3d3h
kube-system          Active   3d3h
project-cl3          Active   3d2h
project-cl4          Active   3d2h
project-hamster      Active   3d2h
project-snake        Active   3d2h
project-tiger        Active   3d2h
```

**Assigning Pods to Nodes | Kubernetes — Mozilla Firefox**

your Pod spec.

For example, consider the following Pod spec:

```
pod/pod-with-node-affinity.yaml

apiVersion: v1
kind: Pod
metadata:
  name: with-node-affinity
spec:
  affinity:
    nodeAffinity:
      requiredDuringSchedulingIgnoredDuringExecution:
        nodeSelectorTerms:
          - matchExpressions:
              - key: kubernetes.io/os
                operator: In
                values:
                  - linux
      preferredDuringSchedulingIgnoredDuringExecution:
        - weight: 1
          preference:
            matchExpressions:
              - key: another-node-label-key
                operator: In
                values:
                  - another-node-label-value
  containers:
    - name: with-node-affinity
      image: k8s.gcr.io/pause:2.0
```

In this example, the following rules apply:

- The node *must* have a label with the key `topology.kubernetes.io/zone`

CKA Simulator

0 minutes

Solutions

< Question 17 >

Use context: `kubect1 config use-context k8s-c1-H`

In *Namespace* `project-tiger` create a *Pod* named `tigers-reunite` of image `httpd:2.4.41-alpine` with labels `pod-container` and `container-pod`. Find out on which node the *Pod* is scheduled. Ssh into that node and find the containerd container belonging to that *Pod*.

Using command `crictl`:

1. Write the ID of the container and the `info.runtimeType` into `/opt/course/17/pod-container.txt`

2. Write the logs of the container into `/opt/course/17/pod-container.log`

Flag this >

To exit full screen, press and hold `Esc`

Expired

Inside the Remote Desktop you need to open:

- Terminal Emulator for kubectl
- Firefox to access the K8s Docs

ĐỀ BÀI: <https://killer.sh/attendee/6367e9df-4857-433d-88a6-9413ff3f0a04>



You can access this page also inside the Remote Desktop by using the icons on the desktop

- Score
- Questions and Answers
- Preview Questions and Answers
- Exam Tips

Expand All

## CKA Simulator Kubernetes 1.28

<https://killer.sh>

### Pre Setup

Once you've gained access to your terminal it might be wise to spend ~1 minute to setup your environment. You could set these:

```
alias k=kubectl          # will already be pre-configured
export do="--dry-run=client -o yaml" # k create deploy nginx --image=nginx $do
export now="--force --grace-period 0" # k delete pod x $now
```

### Vim

The following settings will already be configured in your real exam environment in `~/.vimrc`. But it can never hurt to be able to type these down:

```
set tabstop=2
set expandtab
set shiftwidth=2
```

More setup suggestions are in the **tips** section.

### ▸ Question 1 | Contexts

**SOLUTION:** <https://killer.sh/attendee/6367e9df-4857-433d-88a6-9413ff3f0a04/content>