Feature Engineering — v2

Chest X-Ray Multi-Condition Detection — DataML Challenge

Update covering feature set F (adds GLRLM, Gabor, Hu moments to the 10 families from set E)

1. Why hand-crafted features

The challenge rules do not allow neural networks or pretrained models, so the model cannot learn its own features from raw pixels the way a CNN would. Instead, every feature is written by hand using classical image processing (NumPy, OpenCV, scikit-image, SciPy, PyWavelets). Each feature is a formula that turns one X-ray image into a small set of numbers describing one specific property of the image — brightness, texture, or shape.

Thirteen feature families have now been designed in total (up from ten in the previous version), each capturing one specific property of the image. The notebook groups them into feature sets of increasing size, A through F. Feature set F is now the active setting, and includes all thirteen families: intensity, spatial, texture, gradient, morphology, symmetry, wavelet, frequency, blob, ROI, GLRLM, Gabor, and Hu moments — 219 raw numeric features per X-ray image.

2. Feature families used (feature set F)

Every family is computed on the same preprocessed image, so the comparison between families is fair. Families K, L, and M are new in this version.

Family	#Feat.	What it measures	Why included	Disease sign targeted
A. Intensity	31	Overall brightness of the image: global stats, percentiles, a 16-bin brightness histogram.	Diseased tissue often looks denser (whiter) or hazier than normal air-filled lung, shifting overall brightness stats.	Infiltration, Effusion
B. Spatial grid	48	3x3 grid + top/middle/bottom zones; brightness stats per cell/zone.	Tells the model where in the chest something looks unusual, not just whether the whole image looks unusual.	Effusion (lower), Pneumothorax (upper)
C. Texture (LBP+GLCM)	30	Local pattern of the image: smooth, patchy, or repeating.	Some conditions create patchy/irregular tissue patterns instead of a smooth lung field.	Infiltration, Nodule
D. Gradient/edge	12	How sharp and in what direction intensity changes are, plus edge density.	Some conditions produce a sharp boundary line a normal lung field does not have.	Pneumothorax, Nodule
E. Morphology (shape)	8	Shape stats of bright/dark regions: count, size, roundness, solidity.	A round, solid, well-defined shape is a basic sign of a nodule.	Nodule
F. Symmetry	5	Compares left half of the chest to the right half (brightness, histogram, edge density).	The two lungs are normally close to mirror images; many conditions affect only one side.	Pneumothorax, Effusion

G. Wavelet	28	Multi-resolution (DWT, db4, level 2) detail decomposition: LL approximation + LH/HL/HH detail bands per level.	Captures fine, localized texture at multiple zoom levels that single-scale texture stats miss.	Nodule, Infiltration
H. Frequency (FFT)	4	Ratio of image energy across low/mid/high spatial-frequency radial bands + spectral entropy.	Diffuse haze concentrates energy at low frequencies; small sharp structures push energy higher.	Infiltration, Nodule
I. Blob/lesion	5	Detects small round blob-like structures via Laplacian-of-Gaussian (blob_log).	Targets round, spot-like lesions directly instead of inferring shape indirectly through morphology.	Nodule
J. ROI-aware	7	Repeats brightness + left/right stats restricted to the segmented lung mask only.	Removes rib cage, spine, and background contamination from whole-image averages.	Effusion, Pneumothorax
K. GLRLM (new)	10	Gray-Level Run-Length Matrix: length of runs of similar intensity, horizontal & vertical.	Short high-intensity runs are a proxy for nodular texture vs. the long smooth runs typical of normal lung parenchyma. Complements GLCM (pairwise co-occurrence) with a run-length view.	Nodule, Infiltration
L. Gabor (new)	24	Multi-frequency (3), multi-orientation (4) Gabor filter response: mean + std per combination.	Captures oriented, fine-grained texture that plain LBP/GLCM can under-represent.	Infiltration, Atelectasis
M. Hu moments (new)	7	7 rotation/scale/translation-invariant moment descriptors of the lung mask shape (log-scaled).	Captures gross distortion of the lung silhouette — e.g. a collapsed lung (Atelectasis) or a flattened diaphragm line (Effusion) changes the overall shape.	Atelectasis, Effusion
Total (feature set F)	**219**	**Combined raw feature count extracted per image, before cleaning.**		

3. Full list of features, by family

The detailed breakdown behind the counts in Section 2 — actual column names produced by extract_all_features() for feature set F. Numbered suffixes index histogram bins, grid cells, GLCM angle/distance combinations, wavelet levels, or Gabor frequency/orientation combinations, rather than being separate hand-picked features.

A. Intensity (31 features)

Global distribution stats (9): int_mean, int_median, int_std, int_var, int_min, int_max, int_skew, int_kurt, int_entropy

Percentiles (6): int_p5, int_p25, int_p50, int_p75, int_p95, int_iqr

Brightness histogram (16): int_hist_0 … int_hist_15

B. Spatial grid (48 features)

3×3 grid cells (36): grid_{row}_{col}_mean, grid_{row}_{col}_std, grid_{row}_{col}_p75, grid_{row}_{col}_entropy

Top/middle/bottom zones (12): zone_top_mean, zone_top_std, zone_top_p75, zone_top_entropy, zone_mid_(…), zone_bottom_(…)

C. Texture — LBP + GLCM (30 features)

Local Binary Pattern histogram (18): lbp_s1_0 … lbp_s1_17

GLCM stats (12): glcm_s1_contrast_mean/std, glcm_s1_dissimilarity_mean/std, glcm_s1_homogeneity_mean/std, glcm_s1_energy_mean/std, glcm_s1_correlation_mean/std, glcm_s1_ASM_mean/std

Note: single-scale only (s1) under feature set F — see Section 9 limitation.

D. Gradient / edge (12 features)

Gradient magnitude & edge density (4): grad_mag_mean, grad_mag_std, grad_mag_p95, edge_density

Gradient orientation histogram (8): grad_orient_hist_0 … grad_orient_hist_7

E. Morphology — shape (8 features)

Connected-component shape stats (6): morph_n_components, morph_area_mean, morph_area_max, morph_circularity_mean, morph_eccentricity_mean, morph_solidity_mean

Top-hat / black-hat filtering (2): morph_tophat_mean, morph_blackhat_mean

F. Symmetry (5 features)

Left–right comparison (5): sym_intensity_mean_diff, sym_intensity_abs_diff, sym_intensity_std_diff, sym_hist_divergence, sym_edge_density_diff

G. Wavelet (28 features) — carried over from set D

LL approximation band (4): wav_LL_mean, wav_LL_std, wav_LL_energy, wav_LL_entropy

Per level (2 levels × 3 subbands × 4 stats = 24): wav_L{1,2}_LH_(mean/std/energy/entropy), wav_L{1,2}_HL_(…), wav_L{1,2}_HH_(…)

H. Frequency — FFT (4 features) — carried over from set D

freq_low_energy_ratio, freq_mid_energy_ratio, freq_high_energy_ratio, freq_spectral_entropy

I. Blob / lesion (5 features) — carried over from set E

blob_count, blob_mean_radius, blob_max_radius, blob_mean_contrast, blob_density

J. ROI-aware (7 features) — carried over from set E

roi_segmentation_ok, roi_intensity_mean, roi_intensity_std, roi_intensity_p90, roi_left_right_mean_diff, roi_area_frac, roi_bbox_aspect

K. GLRLM (10 features) — new

Horizontal & vertical run-length stats (2 dirs × 5 stats): glrlm_horiz_SRE, glrlm_horiz_LRE, glrlm_horiz_GLN, glrlm_horiz_RLN, glrlm_horiz_RP, glrlm_vert_SRE, glrlm_vert_LRE, glrlm_vert_GLN, glrlm_vert_RLN, glrlm_vert_RP

SRE = short-run emphasis, LRE = long-run emphasis, GLN = gray-level non-uniformity, RLN = run-length non-uniformity, RP = run percentage.

L. Gabor (24 features) — new

3 frequencies (0.1, 0.25, 0.4) × 4 orientations (0°, 45°, 90°, 135°) × 2 stats (mean, std): gabor_f{freq}_t{theta}_mean, gabor_f{freq}_t{theta}_std, e.g. gabor_f0.1_t0_mean … gabor_f0.4_t2.36_std

M. Hu moments (7 features) — new

Log-scaled Hu invariants of the lung mask (rotation/scale/translation invariant): hu_0 … hu_6

219 raw features in total (31+48+30+12+8+5+28+4+5+7+10+24+7) are extracted per image under feature set F. This is the number produced before any cleaning — see Section 7.

4. Two versions of the image feed the features

Preprocessing produces two aligned versions of each X-ray:

- base — normalized only. Used for plain brightness/region stats (intensity, spatial grid, symmetry, frequency), because CLAHE would distort raw brightness comparisons.
- texture — CLAHE + gamma correction. Used for texture, edge, shape, wavelet, blob, GLRLM, and Gabor families, since these depend on local contrast being visible.

The two new texture-family functions (GLRLM, Gabor) additionally downsize the texture image first — GLRLM to 96×96, Gabor to 128×128 — purely to keep per-image runtime bounded; this does not change which image version (base vs. texture) they draw from.

Hu moments are the one new family that does not measure pixel intensity at all — it is computed directly on the binary lung mask from Section 5, so it is unaffected by either normalization or CLAHE.

5. Why a lung-area mask was added

A chest X-ray contains the lungs, rib cage, spine, and black background. Bones and background do not carry disease information but still affect an average taken over the whole image. The lung-area mask (Otsu thresholding + morphology + convex hull) is now used by two families: ROI-aware (intensity/left-right stats restricted to the mask) and Hu moments (shape descriptors of the mask itself). A segmentation-quality flag (roi_segmentation_ok) is stored so unreliable segmentations can be identified rather than silently trusted by either family.

6. How the features connect to the spatial grid

The spatial grid family is what lets location matter to the model. Without it, two X-rays with the same overall brightness would look identical even if one has a problem confined to the top of one lung and the other is uniformly hazy. Splitting the image into a grid and into top/middle/bottom zones lets the same intensity-style statistics be computed per region instead of only once for the whole image. This part of the pipeline is unchanged from the previous version.

7. Cleaning and selecting features before modelling

Raw feature extraction now produces 219 columns for feature set F (up from 134 under set C). The same two cleanup steps still apply:

- Feature cleaning (unconditional, no label used): near-constant columns dropped (variance threshold); when two columns correlate >0.95, one of the pair is dropped as redundant. The exact final column count is dataset-dependent and is printed by clean_features().
- Feature selection (inside the training fold only, mutual information): for each condition separately, only the top-k features most informative for that condition are kept before scaling and training — never touching validation/test data.

8. How feature usefulness was checked

The same three diagnostics from the previous version are still run:

- Mutual information ranking — per-condition, per-feature top-10 bar charts, and a family-averaged radar chart.
- PCA 2D projection — cleaned features reduced to 2D per condition, to see whether positive cases cluster separately from normal scans.
- Left–right symmetry check — average left/right brightness difference, condition vs. normal, with sample size and standard error shown.

These checks are diagnostic, not proof of causation — high mutual information means a feature is statistically useful for telling a condition apart from normal in this dataset, not that it captures the true clinical cause.

9. Limitations to keep in mind

- Texture is still single-scale under feature set F. extract_all_features() only switches on multi-scale texture (scales=(1,2,4)) when cfg["feature_set"] is exactly "D" or "E" — feature set F falls through to the single-scale branch even though it is a superset of both. Texture family C therefore stays at 30 features, not the larger multi-scale count set D/E would otherwise produce.
- The family-level mutual-information radar chart doesn't see the 3 new families yet. FAMILY_PREFIXES (used to build that chart) only lists prefixes through roi_ — glrlm_, gabor_, and hu_ have no entry, so GLRLM/Gabor/Hu are silently excluded from the family-averaged radar chart, even though their individual columns still appear in the per-condition top-10 mutual-information bar charts.
- 219 is the raw, pre-cleaning count for feature set F only. It is not the number of features the models are ultimately trained on, since clean_features() and the per-label mutual-information selector both reduce it further downstream.
- Feature-to-condition mapping in the Section 2 table is a reasonable expectation based on how these conditions typically present, not a guarantee — mutual information and PCA are what actually test it on this dataset.
- Classical hand-crafted features are inherently more limited than what a CNN could learn directly from pixels; this is a constraint of the challenge rules, not a design choice.