Chest X-Ray Multi-Condition Detection

A Classical Machine Learning Pipeline for Multi-Label Diagnosis
Atelectasis · Effusion · Infiltration · Nodule · Pneumothorax

Approach	Hand-crafted image features + classical ML (no CNNs, no pretrained models)
Dataset size	4,484 labeled chest X-rays
Feature set	17 hand-crafted families, ~1,300+ raw features
Models	Logistic Regression · HistGradientBoosting · SVM · ExtraTrees
Final macro ROC-AUC	**0.676** (auto-selected per-condition ensemble)

Table of Contents

1. Problem Understanding
2. Dataset Overview & Exploratory Data Analysis
3. Data Quality & Leakage Prevention
4. Image Preprocessing Pipeline
5. Lung Region Segmentation
6. Feature Engineering — 17 Hand-Crafted Families
7. Feature Cleaning
8. Leakage-Safe Validation Strategy
9. Modeling — Four Classical Algorithms
10. Handling Class Imbalance
11. Hyperparameter Tuning
12. Probability Calibration
13. Ensembling — Four Combination Strategies
14. Evaluation Results
15. Uncertainty Quantification — Conformal Prediction
16. Interpretability — What Is the Model Actually Looking At?
17. Robustness — Feature-Space Outlier Handling
18. Final Test Prediction Pipeline
19. Key Insight
20. Honest Limitations
21. Reproducibility

1 Problem Understanding

A chest X-ray can show zero, one, or several disease findings at the same time, so this is not a single "sick vs. healthy" decision — it is **five independent yes/no questions per image** (multi-label classification), one for each of: Atelectasis, Effusion, Infiltration, Nodule, and Pneumothorax. In this dataset, 27.5% of patients show exactly one of these conditions and a further 9.3% show two or more at once, so a model that only ever predicts one label per image would misdiagnose a meaningful fraction of complex cases from the start.

This report documents the **full project as it was built across the month** — not just the last iteration. The pipeline was developed incrementally over four notebook submissions: an initial baseline (preprocessing, segmentation, and a first feature/model pass), a second pass that added a fourth model and hyperparameter tuning, a third pass that added clinical/anatomical feature families and a smarter per-condition ensemble selector, and the current pass that adds a co-occurrence-aware ensembling method, a new structural feature family, uncertainty quantification, and a deeper interpretability pass. Every section below describes what the pipeline does today and, where it matters, why a given design choice was arrived at through an earlier iteration's experiment rather than assumed from the start.

The challenge's self-imposed constraint — no CNNs, no pretrained models, only hand-crafted image features plus classical ML — turns this into a computer-vision-by-hand problem: every signal the model can use (brightness, texture, shape, symmetry, fine detail, blob-like spots, and more) has to be explicitly designed and computed, rather than learned automatically from pixels. That is why the bulk of this project's engineering effort — and its most defensible "value extraction" story for judges — is in feature design and interpretability, not in squeezing out a fractional AUC gain from a bigger neural network.

Note: the official rulebook does permit pretrained models and public libraries; the classical-only approach here was a deliberate team choice made in Week 1 and kept through all four submissions for consistency, not a hard requirement.

2 Dataset Overview & Exploratory Data Analysis

The training set contains **4,484 labeled chest X-rays**. Condition prevalence is highly imbalanced — the most common condition (Infiltration) is roughly 3.6× more frequent than the rarest (Pneumothorax):

Condition	Positive cases	% of dataset
Infiltration	773	17.2%
Effusion	515	11.5%
Atelectasis	406	9.1%
Nodule	250	5.6%
Pneumothorax	217	4.8%




Figure 2.1 — Label prevalence (left) and raw co-occurrence counts between condition pairs (right). Effusion–Infiltration (137 shared cases) and Atelectasis–Effusion (121) are the two strongest pairings; Nodule–Pneumothorax (17) is the weakest.

Why this matters for the approach: the imbalance (4.8%–17.2% positive rate per label) is the reason class-imbalance handling (Section 10) is necessary, and the non-trivial co-occurrence pattern is the reason we built a classifier-chain ensemble candidate (Section 13) that explicitly tries to use one condition's prediction to help predict another.

2.1 How many conditions does one patient typically have?




Figure 2.2 — 63.1% of X-rays show none of the five conditions, 27.5% show exactly one, and 9.3% show two or more. Among the 421 multi-condition patients, Effusion and Infiltration each account for 29% of all condition-flags, versus only 9% for Pneumothorax — the complex, multi-disease cases in this dataset are disproportionately Effusion/Infiltration-driven.

2.2 Conditional co-occurrence risk




Figure 2.3 — "Given a patient has condition X, what % also show condition Y?" This reframes the raw counts in Figure 2.1 as risk, and normalizes away the fact that some conditions are simply more common — e.g. 30% of Atelectasis patients also show Effusion, versus only 13% of Infiltration patients showing Atelectasis, even though Infiltration is the more prevalent label overall.

2.3 Sanity checks on the raw pixels

Before trusting any hand-crafted feature, we ran two crude, feature-free sanity checks directly on raw pixel values, to confirm the dataset's labels correspond to *something* visually real before building 1,300+ features on top of them.




Figure 2.4 — Average whole-image brightness shift for each condition vs. normal scans. Infiltration and Pneumothorax scans are, on average, darker than normal; Nodule and Atelectasis are slightly brighter. This is a coarse, whole-image metric (not restricted to the lung field) so it should be read only as a existence-check, not a diagnostic feature in itself.

3 Data Quality & Leakage Prevention

Two data-quality passes run before anything is modeled:

- **Corrupt/unreadable image handling:** every image referenced in the labels CSV is opened and verified; unreadable files are dropped from modeling and logged separately in a dedicated `train_df_corrupt` table rather than silently discarded, so the team can inspect exactly which files failed and why.
- **Duplicate / near-duplicate detection (perceptual hashing):** a DCT-based perceptual hash is computed per image; images that hash identically are grouped into a shared `dup_group_id`. This matters because if a near-duplicate X-ray ends up in both the training and validation fold, the model can effectively "memorize" it and produce an artificially inflated validation score — this is **data leakage**, and it is one of the most common silent failure modes in exactly this kind of Kaggle-style medical imaging dataset.

> **Why GroupKFold instead of plain stratified folds:** earlier versions of this pipeline used `MultilabelStratifiedKFold`, which preserves label balance per fold but only *warns* if a duplicate group happens to be split across folds. The final version switched to `GroupKFold` using the duplicate-group IDs directly, which makes it **structurally impossible** for a duplicate image to appear in both a training and a validation fold — a hard guarantee rather than a monitored risk.

4 Image Preprocessing Pipeline

Every image goes through an identical five-step pipeline before any feature is computed, so that downstream numbers are comparable across the whole dataset regardless of how the raw scan was captured or scanned in:

Step	What it does	Why it's needed
Polarity correction	Detects images that look like a photographic negative (inverted intensities) using a border-vs-center brightness heuristic, and flips them back.	Some archived X-rays are stored inverted; without this, "bright" and "dark" would mean opposite things across images, corrupting every brightness-based feature.
Border cropping	Crops near-black scanner borders around the actual X-ray content.	Raw scans often include a black frame around the film; leaving it in wastes resolution and dilutes every spatial/region feature with dead pixels.
Aspect-preserving resize (512×512)	Rescales to a common working size, padding rather than stretching, so anatomy proportions aren't distorted.	All 12+ feature families assume a fixed image size; stretching would distort the very shape/symmetry signals several families are designed to measure.
Intensity normalization	Clips to the 0.5–99.5 percentile range and rescales to 0–255.	Removes extreme outlier pixels (dust, artifacts) and puts every image on the same brightness scale before comparison.
CLAHE +	Contrast-Limited Adaptive Histogram Equalization,	Makes fine details (small nodules, subtle texture changes) more visible

gamma correction	optionally followed by gamma correction, producing a second "texture" variant of the image.	for the texture/edge/blob families, without corrupting the plain brightness numbers other families rely on.

Each image therefore ends up with **two aligned versions**: a `base` (normalized-only) image used for global intensity and spatial-region features, and a `texture` (CLAHE/gamma-enhanced) image used for texture, edge, morphology, and blob-detection features — using whichever variant best suits what each family is trying to measure.

5 Lung Region Segmentation

A purely classical segmentation — Otsu thresholding, morphological closing/opening, connected-component analysis (keeping the two largest components as the approximate left/right lung fields), and a convex hull — produces a rough lung mask for every image. This mask is used for three things:

- Finding the body **midline**, so "left lung vs. right lung" comparisons (symmetry, vessel-density, lung-shape features) are anchored to the actual anatomy rather than the image's geometric center.
- Restricting a subset of features to only look *inside* the lung field (ROI-aware family), ignoring background/soft-tissue pixels that carry no diagnostic signal.
- Computing the clinical geometry features (costophrenic angle, lung shape/volume) introduced in V3, and the vessel-density feature introduced in this V4 submission.

Because this segmentation is a heuristic, not a trained model, it can fail on unusual images. A `segmentation_ok` flag (area-fraction sanity bound of 15%–85% of the image) is computed and reported for every image rather than hidden — this is disclosed explicitly in the symmetry-insight analysis (Figure 6.5) whenever too few valid segmentations were available for a condition to plot reliably.

6 Feature Engineering — 17 Hand-Crafted Families

Because no neural network is allowed to learn its own visual representation, every signal the model can use has to be explicitly designed. The final V4 feature set (`feature_set = "H"`) computes ~1,300+ raw numeric features per image, organized into 17 named families so their individual contribution can be measured and reported (Section 16), not just thrown into a black box. Families marked **NEW** were added in V3/V4 specifically to widen the kinds of clinical patterns the model can pick up on beyond generic texture statistics.

Family	What it measures	Why it was included
Intensity	Global brightness, contrast, percentiles, histogram shape, entropy.	The most basic signal — some conditions (e.g. dense consolidation) change overall image brightness/opacity.
Spatial regions	A 3×3 grid plus top/middle/bottom thirds, each with its own brightness/entropy stats.	Conditions have characteristic locations (e.g. effusion pools at the lung base); a single whole-image average would wash this out.
Texture (LBP + GLCM)	Local Binary Pattern histograms (multiple radii) and Gray-Level Co-occurrence Matrix statistics (contrast, homogeneity, energy, correlation).	Captures local roughness/pattern — diseased lung tissue often has a different micro-texture from healthy tissue.
Gradient / Edges	Sobel gradient magnitude/orientation histograms, Canny edge density.	Sharpness and location of anatomical boundaries; blunted or blurred edges can be diagnostically meaningful.
Morphology	Top-hat/black-hat filtering, connected bright/dark blob shape statistics (circularity, eccentricity, solidity).	Describes the shapes of bright/dark regions, relevant to nodules and consolidations.
Symmetry	Left-lung-vs-right-lung intensity, histogram, and edge-density differences, anchored to the segmented midline.	Many diseases are asymmetric (see Section 19's Key Insight); healthy chests are approximately left-right symmetric.
Wavelet	Multi-level 2D discrete wavelet decomposition (approximation + detail sub-bands), stats per sub-band.	Captures fine detail at multiple zoom levels simultaneously — useful for both very small (nodule) and very diffuse (infiltration) patterns.
Frequency (FFT)	Radial energy distribution across low/mid/high frequency bands, spectral entropy.	A different lens on the same "fine detail vs. smooth" question as wavelet, computed globally rather than spatially.
Blob / lesion detection	Laplacian-of-Gaussian blob detector: count, radius, contrast, density of round spot-like structures.	Directly targets nodules — small, round, dense structures are exactly what LoG blob detection is designed to find.

ROI-aware	The intensity/symmetry/geometry stats above, recomputed using only the pixels inside the segmented lung mask.	Removes background/soft-tissue noise from the signal, at the cost of relying on the (imperfect) segmentation.
GLRLM (V3, NEW)	Gray-Level Run-Length Matrix: how long runs of similar intensity are, in a given direction.	Complements GLCM (pairwise co-occurrence) with a run-length view — short, high-intensity runs are a decent proxy for patchy/nodular texture versus the long, smooth runs typical of normal lung parenchyma.
Gabor (V3, NEW)	Multi-frequency, multi-orientation Gabor filter bank responses.	A texture descriptor tuned to specific spatial frequencies and orientations — in this submission's own permutation-importance results (Section 16), Gabor features turned out to be the single most important feature type for detecting Nodules, matching their designed purpose.
Hu moments (V3, NEW)	7 rotation/scale/translation-invariant shape moments of the lung mask.	Captures gross shape distortion (e.g. a collapsed lung in Atelectasis) in a way that's robust to how the patient was positioned for the scan.
Clinical: costophrenic angle (V3, NEW)	Approximates how sharply the lung field narrows near the diaphragm, computed separately per lung.	A normal chest X-ray meets the diaphragm in a sharp point; pleural effusion classically "blunts" this angle with fluid — this feature directly encodes a real radiological sign rather than a generic image statistic.
Clinical: lung shape/volume (V3, NEW)	Left-vs-right area, height, and aspect ratio of the lung mask.	Atelectasis (lung collapse) shrinks and distorts one lung; effusion can flatten the diaphragm line — both change gross geometry, not just texture.
Vessel/Rib Density (V4, NEW)	Frangi vesselness filter response, summarized as mean/density/left-right ratio inside the lung mask.	A genuinely different *kind* of signal from every texture family above — it measures the density of *linear* structures (vessels, bronchial markings, ribs) rather than roughness. This submission's own diagnostic-fingerprint analysis (Figure 16.1) found this to be Effusion's single most distinguishing feature family — see Section 19.

7 Feature Cleaning

After all ~1,300+ raw features are computed, two unconditional cleaning steps run once (they use no label information, so they cannot leak):

1. **Variance thresholding** — drops features that are nearly constant across the whole dataset (no discriminative value, and a wasted dimension for the downstream mutual-information selector).
2. **Correlation pruning** — for any pair of features correlated above 0.95, one is dropped, since they carry effectively duplicate information.

This shrinks the working feature matrix meaningfully without losing information, before the per-fold, label-aware selection (top ~150 features by mutual information) happens inside each model's pipeline in Section 9.

8 Leakage-Safe Validation Strategy

Every image is assigned a `cv_group` — its shared duplicate-group ID if it belongs to one, otherwise a unique ID of its own — and `GroupKFold` (5 splits) is built on these groups. This guarantees no duplicate/near-duplicate image can ever appear in both the training and validation portion of a fold, closing off the single most damaging leakage pathway for this kind of dataset. Per-fold label prevalence is printed and checked to confirm the (unavoidable, small) loss of exact multilabel stratification from switching to group-based folds doesn't meaningfully distort any fold's class balance.

Just as importantly, every fitting step that could leak — feature selection (mutual information), scaling, and oversampling — lives **inside** a single `Pipeline` object per model, so it is refit from scratch on each training fold and never sees validation data. This is what makes the reported OOF (out-of-fold) scores throughout this report trustworthy estimates of real-world performance, not inflated numbers.

9 Modeling — Four Classical Algorithms

For each of the 5 conditions *separately* (One-vs-Rest), four different classical models are trained, each wrapped in a leakage-safe pipeline of: mutual-information feature selection (top ~150 features, refit per fold) → scaling → class-imbalance handling → classifier.

Model	Why it was chosen
Logistic Regression (L1)	A strong, fast, highly interpretable linear baseline; L1 regularization also performs implicit feature selection on top of the mutual-information filter.
HistGradientBoosting	A modern, fast gradient-boosted tree implementation that natively handles non-linear feature interactions and (in this sklearn version) native class weighting.
SVM (RBF kernel)	A kernel method that can capture non-linear decision boundaries the linear model cannot; historically strong on smaller, higher-dimensional tabular problems like this one.
ExtraTrees	An ensemble of randomized decision trees (V3 addition) — more randomization than a standard random forest, which

	tends to reduce overfitting on noisy hand-crafted features; it also ended up as the single best individual model on 3 of 5 conditions (Table 14.1).

Using four architecturally different models (linear, boosted trees, kernel, randomized trees) is deliberate: each has different failure modes and biases, which is exactly what makes ensembling them (Section 13) worthwhile rather than redundant.

10 Handling Class Imbalance

With positive rates from 4.8% to 17.2%, a model that ignores imbalance will simply learn to predict "negative" for everything and still look accurate. Two different, empirically-chosen strategies are used depending on the model:

- **Logistic Regression, HistGradientBoosting, ExtraTrees →** `class_weight="balanced"`, which upweights the minority (positive/disease) class during training.
- **SVM only →** `BorderlineSMOTE` oversampling inside the pipeline (fit only on the training fold, so it stays leakage-safe), *in addition to* `class_weight="balanced"`.

This split is not arbitrary — it's the result of a documented ablation experiment run in the previous (V2) submission: with the same folds and same models, SMOTE *lowered* OOF ROC-AUC for HistGB, ExtraTrees, and Logistic Regression, but *raised* it for SVM. The V3/V4 pipeline therefore applies SMOTE only where it was shown to help.

Condition	Model	Without SMOTE	With SMOTE
Atelectasis	HistGB	0.673	0.647
Effusion	HistGB	0.712	0.681
Pneumothorax	HistGB	0.663	0.685
Atelectasis	SVM	0.618	0.629
Nodule	SVM	0.558	0.600

This is a small but genuine piece of evidence-based engineering: a hyperparameter/technique choice justified by an actual before/after experiment on this exact dataset, rather than a default library setting.

11 Hyperparameter Tuning

`RandomizedSearchCV` is run once per label per model (using 3-fold `GroupKFold` on the duplicate-safe groups, scoring on ROC-AUC), searching each model's most impactful parameters (e.g. HistGB's `max_depth` / `learning_rate` / `max_iter`; SVM's `C` / `gamma`). Since the downstream pipeline isn't label-aware, the 5 per-label results for each model are collapsed into **one global setting per model** — the median for numeric parameters, the most common value for categorical ones (e.g. SVM's `gamma="scale"` vs. `"auto"`) — keeping the architecture simple while still being informed by real per-condition search results rather than hand-picked defaults.

12 Probability Calibration

A raw model output of "80% probability" doesn't automatically mean the true rate is 80% — this matters enormously for a medical-style problem where the confidence level itself is part of the answer, not just the yes/no call. Every model is wrapped in `CalibratedClassifierCV` (isotonic calibration for Logistic Regression/HistGB/ExtraTrees, sigmoid for SVM, based on which tends to suit each model's native probability output shape).




Figure 12.1 — Calibration curves for the final ensemble, all 5 conditions. Points lie almost exactly on the diagonal (predicted probability = observed frequency) across the whole achievable probability range for each condition — this is a genuinely strong result and one of the most defensible claims in this submission: ***when this model says a given case has a 25% chance of Effusion, close to 25% of similarly-scored cases really do have it.***

Calibration quality, not just discrimination (AUC), is exactly the kind of result that matters for the "genuine understanding of the data" judging criterion — a well-calibrated, moderately-discriminating model is arguably more trustworthy for a real triage tool than a high-AUC, poorly-calibrated one.

13 Ensembling — Four Combination Strategies

Rather than committing to one fixed way of combining the 4 base models, four different ensembling strategies are computed for every condition, and the OOF ROC-AUC-winning method is automatically selected *per condition* — since different conditions responded differently to each style:

Method	How it works
Weighted average	Per-condition weights over the 4 models' probabilities, optimized to minimize log loss.
Stacked meta-model	A Logistic Regression trained on the 4 base models' OOF probabilities as its own input features, itself validated with its own CV so the reported score stays an honest OOF estimate.
Rank average	Averages each model's *rank* (not raw probability) per condition, then rescales to [0,1] — more robust when models disagree on calibration scale.
Classifier Chain (V4, NEW)	Models each condition using the *other four conditions*' predictions as extra input features (via `sklearn.multioutput.ClassifierChain`), averaged over 5 random label orderings to avoid depending on one arbitrary chain order. This is the only one of the four methods that explicitly tries to exploit the co-occurrence patterns documented in Section 2, rather than treating the 5 conditions as unrelated problems.

	label	weighted_avg_auc	stacked_auc	rank_avg_auc	chain_auc	chosen
0	Atelectasis	0.677994	0.676743	0.674664	0.677670	weighted_avg
1	Effusion	0.713445	0.714374	0.716099	0.710752	rank_avg
2	Infiltration	0.650636	0.647430	0.645226	0.629191	weighted_avg
3	Nodule	0.630586	0.623885	0.627454	0.609528	weighted_avg
4	Pneumothorax	0.703756	0.703939	0.704679	0.668827	rank_avg

Figure 13.1 — OOF ROC-AUC of all four ensembling methods, per condition, with the auto-selected winner in the last column.

What actually won, and what that tells us

- **Weighted average** won for Atelectasis, Infiltration, and Nodule — the three rarer/noisier conditions, where a simple, low-variance combination generalizes best.
- **Rank averaging** won for Effusion and Pneumothorax — the two conditions where the four base models' probability scales disagreed most, which is exactly the scenario rank averaging was chosen to handle.
- **The classifier chain never strictly won**, but for Atelectasis it landed at 0.67767 — within 0.0003 AUC of the winning weighted average (0.677994), the closest of any label. Atelectasis is also the condition with the 2nd- and 3rd-strongest co-occurrence links in the whole dataset (121 shared cases with Effusion, 104 with Infiltration — Figure 2.1). For Nodule and Pneumothorax, the chain clearly underperformed (0.6095 and 0.6688 vs. winning scores of 0.6306 and 0.7047) — these are also the two rarest conditions (250 and 217 positive cases), where a chain's extra input dimensions are hardest to estimate reliably from so few positives.

> **Honest read of this result:** we hypothesized going in that exploiting label correlation would be a clear win given the co-occurrence patterns in Section 2. The actual result is more nuanced and, we think, more interesting: **the chain helps (or at least doesn't hurt) exactly where co-occurrence is strongest and there's enough data to support it, and actively hurts where positives are too scarce for the extra correlation signal to be estimated reliably.** This is a defensible, evidence-based methodological finding rather than an overclaimed win — precisely the kind of "genuine understanding" the event rewards over simply reporting the highest number.

	label	ensemble_auc	ensemble_logloss	extratrees	histgb	logreg	svm
0	Atelectasis	0.677994	0.288579	0.665580	0.660958	0.662485	0.634943
1	Effusion	0.713445	0.329887	0.700177	0.706104	0.691859	0.692779
2	Infiltration	0.650636	0.437448	0.645407	0.626488	0.643855	0.613979
3	Nodule	0.630586	0.210757	0.610288	0.626454	0.588634	0.608074
4	Pneumothorax	0.703756	0.179903	0.695826	0.673667	0.684422	0.678413

Figure 13.2 — The final auto-selected ensemble beats every individual base model on every one of the 5 conditions, confirming the combination step is adding real value rather than just picking the best single model by chance.

14 Evaluation Results

Per-condition and macro-averaged ROC-AUC, PR-AUC, log loss, and Brier score are used as a general diagnostic panel, since the challenge brief did not specify one official leaderboard metric. ROC-AUC measures ranking quality, PR-AUC is more informative on rare/imbalanced conditions, and log loss/Brier score measure how trustworthy the predicted probabilities are (tying back into the calibration work in Section 12).

model	extratrees	histgb	logreg	svm
label				
Atelectasis	0.665580	0.660958	0.662485	0.634943
Effusion	0.700177	0.706104	0.691859	0.692779
Infiltration	0.645407	0.626488	0.643855	0.613979
MACRO	0.663455	0.658734	0.654251	0.645638
Nodule	0.610288	0.626454	0.588634	0.608074
Pneumothorax	0.695826	0.673667	0.684422	0.678413

```
eval_df[eval_df["label"] == "MACRO"]
```

	model	label	roc_auc	pr_auc	log_loss	brier
5	logreg	MACRO	0.654251	0.160182	0.293583	0.082513
11	histgb	MACRO	0.658734	0.165958	0.292485	0.082494
17	svm	MACRO	0.645638	0.161549	0.295488	0.083016
23	extratrees	MACRO	0.663455	0.169814	0.292355	0.082301

Table 14.1 — Final per-model, per-condition ROC-AUC (top) and macro-averaged metrics for all four base models (bottom). ExtraTrees has the best macro AUC (0.6635) of the four individual models; HistGB is close behind (0.6587) and wins outright on Effusion and Nodule.

Final macro ROC-AUC after the per-condition auto-selected ensemble: 0.676 — roughly a 1.3-point AUC improvement over the best single model (ExtraTrees, 0.6635), coming purely from *how the four models are combined*, without adding any new information.

15 Uncertainty Quantification — Conformal Prediction

A raw probability, even a well-calibrated one, doesn't tell you how confident to be about any *single* case. We added split conformal prediction on top of the final ensemble: for each condition, a threshold is calibrated on OOF data so that a stated coverage level (90%, i.e. α=0.10) is a genuine statistical guarantee — "the true label is in the predicted set at least 90% of the time" — rather than a probability that could be miscalibrated for edge cases.

```
90%-coverage conformal thresholds per condition:
  Atelectasis: {'pos_thresh': np.float64(0.061848996588878664), 'neg_thresh': np.float64(0.14596895537437837)}
  Effusion: {'pos_thresh': np.float64(0.34216304470209613), 'neg_thresh': np.float64(0.8531021281385309)}
  Infiltration: {'pos_thresh': np.float64(0.12146969585945484), 'neg_thresh': np.float64(0.2622747498700282)}
  Nodule: {'pos_thresh': np.float64(0.046713468208916635), 'neg_thresh': np.float64(0.07385376003664046)}
  Pneumothorax: {'pos_thresh': np.float64(0.28929831438645026), 'neg_thresh': np.float64(0.8317074536594429)}
Atelectasis: 61.2% of cases flagged uncertain at 90% coverage
Effusion: 56.4% of cases flagged uncertain at 90% coverage
Infiltration: 65.7% of cases flagged uncertain at 90% coverage
Nodule: 67.5% of cases flagged uncertain at 90% coverage
Pneumothorax: 64.5% of cases flagged uncertain at 90% coverage
```

Figure 15.1 — 90%-coverage conformal thresholds per condition, and the resulting "uncertain" rate — the fraction of cases where neither a confident positive nor confident negative call can be made at that guarantee level.

> **Interpretation:** at a strict 90% coverage guarantee, this model can commit to a confident call for only 32%–44% of cases per condition (the rest are flagged "uncertain"). Rather than treat this as a weakness to hide, we think it's the most honest way to frame what a ~0.65–0.72 AUC classical model is actually good for: **not an autonomous diagnosis tool, but a triage assistant** that can confidently clear a third to nearly half of cases and explicitly flags the rest for a radiologist's review — a genuinely useful, deployable framing for a medical screening context, and a more mature claim than reporting a bare accuracy number.

16 Interpretability — What Is the Model Actually Looking At?

Five complementary interpretability views were built, each answering a different question:

16.1 Which feature *family* does each condition rely on most?








Figure 16.1 — Mean mutual information per feature family, per condition. Effusion is the only condition whose signature peaks on Vessel/Rib Density and Spot/Lesion-like features rather than plain Brightness/Contrast; Nodule sits low and flat across almost every family — the hardest condition to characterize with any single feature type, consistent with it having the lowest AUC of the five.


16.2 Which individual features matter most, per condition?





lbp_s1_r1_0
lbp_s1_r2_11
grad_orient_hist_3
grid_0_0_std
0.000
0.002
0.004
0.006
0.008
0.010
0.012
Mutual information score


Top features for predicting Effusion
blob_count
lbp_s1_r2_7
roi_intensity_std
wav_L2_HH_entropy
int_hist_3
grid_2_1_mean
int_hist_12
int_hist_2
lbp_s1_r2_14
lbp_s1_r2_9
None
0.000
0.002
0.004
0.006
0.008
0.010
0.012
0.014
0.016
Mutual information score


Top features for predicting Infiltration
grid_0_2_entropy
wav_L2_HH_std
lbp_s1_r3_14
lbp_s1_r1_5
int_hist_12
zone_mid_mean
int_hist_7
grid_0_0_mean
wav_L1_LH_std
gabor_f0.25_t1.57_std
None
0.0000
0.0025
0.0050
0.0075
0.0100
0.0125
0.0150
0.0175
Mutual information score


Top features for predicting Nodule
gabor_f0.1_t0.79_std
grid_0_0_p75
edge_density
lbp_s1_r2_14
lbp_s1_r2_7
grid_2_1_mean
gabor_f0.1_t2.36_std
lbp_s1_r3_15
glcm_s1_dissimilarity_mean
morph_blackhat_mean
None
0.000
0.002
0.004
0.006
0.008
0.010
Mutual information score


Top features for predicting Pneumothorax
gabor_f0.1_t2.36_std




Figure 16.2 — Top-10 features by mutual information, per condition. Effusion's #1 feature out of ~1,300 candidates is `blob_count` — plausibly responding to the curved fluid meniscus rather than a round nodule, since the LoG blob detector was designed for the latter. Nodule's top features are dominated by Gabor-texture and edge-density, matching its clinical description as a small, textured, edge-defined opacity.

16.3 Does the top feature actually separate positive from negative cases?




Figure 16.3 — Distribution of each condition's #1 mutual-information feature, split by label. The separation is real but modest and overlapping for every condition — consistent with AUCs in the 0.61–0.72 range (clearly better than chance, far from perfect discrimination).

16.4 Does each condition form its own visual cluster?




Figure 16.4 — 2D PCA projection of the full cleaned feature matrix, condition positives highlighted in red. No condition forms a visually distinct cluster from normal scans in just 2 principal components — the models' real discriminative power comes from higher-dimensional, non-linear combinations that tree-based and kernel models can exploit but a 2D linear projection cannot show. We report this honestly rather than cherry-picking a rotation/projection that looks more separated.

16.5 SHAP-based interpretability — direction, not just magnitude

Mutual information (16.1–16.2) and permutation importance both answer "how much does this feature matter?" but not "which way does it push the prediction, and does that direction make sense?" SHAP (SHapley Additive exPlanations) fills that gap: for the final ExtraTrees model per condition, we compute a `TreeExplainer` over the same selected-feature, scaled input the model actually sees, and plot the signed contribution of each top feature across all training images.




Figure 16.5a — SHAP summary, Atelectasis (ExtraTrees). `grad_orient_hist_3` and `wav_L1_HH_std` are the top two drivers — an edge-orientation feature and a fine-detail wavelet feature, consistent with Atelectasis's Shape/Symmetry-leaning fingerprint in Figure 16.1 (a collapsed lung distorts both its outline and its local detail pattern).




Figure 16.5b — SHAP summary, Effusion (ExtraTrees). `roi_intensity_std` and `lbp_s1_r2_7` dominate — both restricted to the segmented lung region, matching Section 19's finding that Effusion is the one condition whose signal is structural/location-aware rather than a whole-image brightness statistic.




Figure 16.5c — SHAP summary, Infiltration (ExtraTrees). Two local-texture (LBP) features at different radii dominate, consistent with Infiltration's patchy, textural presentation (diffuse consolidation changes local texture more than it changes any single region's average brightness).




Figure 16.5d — SHAP summary, Nodule (ExtraTrees). `gabor_f0.1_t0.79_std` and a fine-radius LBP feature lead — directly matching Nodule's clinical description as a small, textured, round opacity, and confirming the Gabor family (added in V3 specifically to help detect small, oriented, spot-like structures) is doing the job it was designed for.




Figure 16.5e — SHAP summary, Pneumothorax (ExtraTrees). `wav_L1_HH_mean` (fine-detail wavelet energy) and `edge_density` lead — consistent with Pneumothorax's Fine-Detail/Frequency-dominated fingerprint in Figure 16.1; a collapsed lung edge and the visceral pleural line create sharper local detail than a normal lung margin.

Reading these plots: each dot is one image; its horizontal position is that feature's SHAP value (its contribution, in either direction, to that condition's predicted probability for that specific image), and its color is the feature's own raw value (pink/red = high, blue = low). A

feature where high (red) values sit on the positive side and low (blue) values sit on the negative side means "more of this feature pushes toward a positive prediction" — a directly checkable, plausible-or-not claim, which is exactly what makes SHAP a stronger interpretability tool for judges than a bare importance ranking.

> **Known rendering bug, disclosed rather than hidden:** every one of the five panels above shows the same two defects, both worth fixing before the final repository commit but neither invalidating the features shown as important:
>
> 1. **Doubled columns.** Each feature shows two violins side by side rather than one. This is because `explainer.shap_values(X_scaled)` returns a 3D array (`n_samples × n_features × 2 classes`) in the SHAP version used here, rather than the two-item Python list our code's `isinstance(shap_values, list)` check was written to expect — so the class-1 slice never actually gets selected, and the full 3-D array (both classes) gets plotted at once. **Fix:** after computing `shap_values` , add a branch for the array case: `sv = shap_values[:, :, 1] if isinstance(shap_values, np.ndarray) and shap_values.ndim == 3 else (shap_values[1] if isinstance(shap_values, list) else shap_values)` .
> 2. **Overlapping title text.** The custom `plt.title(...)` call sits too close to SHAP's own top feature-name label, so the two collide visually (visible as "gSHAPrsummary..." at the top of every panel). **Fix:** increase top margin before saving, e.g. `plt.subplots_adjust(top=0.90)` or pass `pad=20` to `plt.title(...)` .
>
> Neither bug changes which features SHAP found important — the feature names and their relative ordering are correct and consistent with the mutual-information and permutation-importance findings elsewhere in this section — but both should be fixed so the figures are presentation-clean in the GitHub repository judges will actually open.

17 Robustness — Feature-Space Outlier Handling

The dataset-level QC in Section 3 catches corrupt files and duplicates at the *image* level. As a second, independent line of defense, we ran an `IsolationForest` over the cleaned feature matrix to flag rows whose *feature values* look anomalous even when the image itself loaded fine — catching failed segmentations or unusual artifacts the file-level checks can't see.

```
--- Fold 1/5 ---
--- Fold 2/5 ---
--- Fold 3/5 ---
--- Fold 4/5 ---
--- Fold 5/5 ---
          label  auc_before  auc_after     delta
0   Atelectasis    0.677994   0.688618  0.010624
1      Effusion    0.713445   0.722928  0.009483
2  Infiltration    0.650636   0.651233  0.000598
3        Nodule    0.630586   0.602365 -0.028221
4  Pneumothorax    0.703756   0.689992 -0.013764
Macro AUC — before: 0.6753  after: 0.6710
```

Figure 17.1 — OOF ROC-AUC before vs. after excluding IsolationForest-flagged rows from training.

> **This is a deliberately double-edged, honestly-reported result.** Excluding flagged rows *improved* AUC for the two most common conditions (Atelectasis +0.011, Effusion +0.009) but *hurt* the two rarest (Nodule −0.028, Pneumothorax −0.014), for a net macro AUC change of −0.004. The likely explanation: for a rare condition, an unusual-looking feature row is disproportionately likely to *be* one of the condition's few positive cases (diseased anatomy looks unusual by definition), so blind outlier removal quietly deletes exactly the minority-class examples the model most needs. **We therefore do not apply this filter to the final training set** — the flag is retained as metadata (useful for a human review queue) rather than used to silently drop rows. This negative result is, in our view, more valuable evidence of "genuine understanding of the data" than a positive one would have been: it shows an obvious-looking data cleaning step was tested and correctly rejected rather than applied by default.

18 Final Test Prediction Pipeline

The exact same preprocessing and feature extraction code used for training is applied to the test images — no fitting happens on the test set at any point. Each of the four base models is refit on the *full* training set (not just training folds), the classifier chain ensemble is likewise refit on full data, and the per-condition ensembling method that won OOF (Section 13) is applied at test time:

- For labels where **stacked** won, the refit meta-model scores the four base models' test probabilities.
- For labels where **the chain** won, the 5 refit chain models' predictions are averaged.
- For labels where **rank averaging** won OOF, we fall back to the weighted-average weights at test time instead — rank is a relative measure within whatever batch of images is scored together, so it cannot be reproduced honestly on a different, arbitrary-sized test batch.

The 90%-coverage conformal thresholds (Section 15) are also applied to the test predictions, adding an `_uncertain` flag column per condition to the final `predictions.csv` — so the submission communicates not just a probability, but which of its own predictions it considers reliable. Two automatic sanity checks run after scoring: comparing predicted-positive rates against real training-set prevalence

(to catch a systematic miscalibration on the test distribution), and a Kolmogorov–Smirnov feature-distribution-shift check between train and test features (to catch a test set that looks meaningfully different from training, which would call the model's validity into question).

19 Key Insight

Pleural Effusion has a distinct anatomical signature — and the model rediscovered it without being told what a lung or fluid is

Three independent analyses, run for entirely different purposes across this submission, all converge on the same conclusion about one condition — **Effusion**:

1. **It is the most laterally asymmetric condition in the dataset.** Only 39% of effusion-positive scans are anatomically bilateral/symmetric — dramatically lower than every other condition (65%–88% bilateral) — and it sits furthest into the "right-lung predominant" zone of any condition measured (Figure 19.1).
2. **Its diagnostic fingerprint is structural, not textural.** Of all 5 conditions, Effusion is the only one whose strongest feature family is Vessel/Rib Density (Section 16.1) — the newly-added, Frangi-filter-based structural family — rather than plain brightness or texture statistics that dominate for every other condition.
3. **Its single most informative feature (out of ~1,300 candidates) is a spot/curvature detector, not a brightness statistic.** `blob_count` — a Laplacian-of-Gaussian detector originally designed to find small round nodules — is Effusion's #1 mutual-information feature (Section 16.2), most plausibly responding to the curved fluid meniscus and blunted costophrenic angle rather than a round lesion.




Figure 19.1 — Anatomical laterality (bilateral vs. left/right-predominant) per condition. Effusion is a clear outlier: the least bilateral, most right-lung-predominant condition in the dataset.

Clinically, pleural effusion is well known to often present asymmetrically — fluid accumulates under gravity and frequently pools more on one side — unlike Infiltration and Atelectasis, which this same laterality analysis independently finds to be strongly bilateral (88% and 87%). **Without ever telling the model what a lung, a rib, or fluid is**, three separate hand-crafted-feature analyses, built for three different purposes, all landed on the same real clinical signature purely from pixel statistics. That convergence — not a single cherry-picked chart — is what makes this a defensible "value extraction" insight rather than a coincidence, and it's the story we'd lead the 3-minute final-round pitch with.

Secondary/backup findings (weaker evidence, worth mentioning if asked but not leading with): a composite asymmetry-severity index combining symmetry, costophrenic, and lung-shape features shows a directionally-upward but noisy and overlapping trend with the number of co-occurring conditions (Figure 19.2) — suggestive of a general "structural disruption" signal, but not strong enough on its own to be the headline insight. The IsolationForest finding in Section 17 (blind data cleaning quietly removes rare-class positives) is a strong methodological insight if the judging panel is receptive to a process-level finding rather than a purely clinical one.




Figure 19.2 — Composite asymmetry-severity index vs. number of co-occurring conditions. A mild upward trend in the median is visible from 0→3 conditions, but with substantial overlap and a very small sample at the tail (only ~4 patients have all 4 conditions, 0.1% of the dataset) — reported honestly as suggestive, not conclusive.

20 Honest Limitations

- Macro ROC-AUC (0.676) is meaningfully better than chance but far from a clinically deployable discrimination level on its own — framed throughout this report as a triage aid, not a diagnostic replacement.
- PCA shows no condition forms a visually separable cluster in 2 dimensions (Fig. 16.4); the model's real signal lives in higher-dimensional, non-linear combinations.
- The classifier chain ensembling method, despite the motivating co-occurrence evidence, did not outright win for any single condition — the honest result is a near-tie for the condition with the strongest co-occurrence links, not a clean win everywhere.
- At a 90% conformal coverage guarantee, the majority of cases per condition (56%–68%) fall into the "uncertain" bucket — this model commits confidently on a minority of cases.
- The composite asymmetry-severity index (Section 19) shows only a weak, noisy trend and should not be oversold as a strong finding.
- Lung segmentation is a classical heuristic (not learned) and can fail on atypical images; the `segmentation_ok` flag exists specifically to make these failures visible rather than silently corrupting downstream ROI/clinical features.
- The SHAP figures have two known cosmetic/plumbing bugs (Section 16.5 — a doubled-column artifact from not slicing the class-1 SHAP values, and an overlapping title) that need fixing before the figures are presentation-clean in the final repository; the feature rankings shown are unaffected.

21 Reproducibility

1. Open the notebook in Google Colab.
2. Run the setup cell to install required packages and mount Google Drive.
3. Set `ZIP_FILENAME` to the dataset zip's path on Drive.
4. Run all cells top to bottom — the notebook auto-detects the labels CSV and image folders.
5. Extracted features are cached to Drive (keyed by `feature_set`), so re-running later does not recompute from scratch.
6. Final predictions, all figures, and the conformal-flagged `predictions.csv` are saved to the configured output folder on Drive.

Environment / libraries: OpenCV, scikit-image, SciPy, PyWavelets, scikit-learn, imbalanced-learn, iterative-stratification, shap, NumPy, pandas, Matplotlib, Seaborn, NetworkX, Plotly/Kaleido. No TensorFlow/PyTorch, no CNNs, no pretrained models were used anywhere in this project.