

RobotFramework_Testsuites

v. 0.2.2

Mai Dinh Nam Son

18.07.2022

Contents

1	Introduction	1
1.1	RobotFramework AIO testsuites management documentation	1
2	Description	2
2.1	Getting Started	2
2.1.1	How to install	2
2.2	Features	3
2.2.1	Using configuration files in Json format	3
2.2.2	Define 4 levels of configuration	3
2.2.3	Access dictionary object of configuration by traditional way or using ”.”	4
3	CConfig.py	5
3.1	Class: dotdict	5
3.2	Class: CConfig	5
3.2.1	Method: loadCfg	6
3.2.2	Method: updateCfg	6
3.2.3	Method: verifyRbfwVersion	6
3.2.4	Method: bValidateMinVersion	7
3.2.5	Method: bValidateMaxVersion	7
3.2.6	Method: bValidateSubVersion	7
3.2.7	Method: tupleVersion	8
3.2.8	Method: versioncontrol_error	8
4	COnFailureHandle.py	9
4.1	Class: COnFailureHandle	9
4.1.1	Method: is_noney	9
4.1.2	Method: register_keyword_run_on_failure	9
5	CSetup.py	10
5.1	Class: CSetupKeywords	10
5.1.1	Method: testsuite_setup	10
5.1.2	Method: testsuite_teardown	11
5.1.3	Method: testcase_setup	11
5.1.4	Method: testcase_teardown	11
5.1.5	Method: update_config	11
5.2	Class: CGeneralKeywords	11
5.2.1	Method: get_config	12
5.2.2	Method: load_json	12

6	CStruct.py	13
6.1	Class: CStruct	13
7	Event.py	14
7.1	Class: Event	14
7.1.1	Method: trigger	14
8	ScopeEvent.py	15
8.1	Class: ScopeEvent	15
8.1.1	Method: trigger	15
8.2	Class: ScopeStart	15
8.3	Class: ScopeEnd	15
9	__init__.py	16
9.1	Function: on	16
9.2	Function: dispatch	16
9.3	Function: register_event	16
10	LibListener.py	17
10.1	Class: LibListener	17
11	__init__.py	18
11.1	Class: RobotFramework_Testsuites	18
11.1.1	Method: get_keyword_tags	18
11.1.2	Method: get_keyword_documentation	18
11.1.3	Method: failure_occurred	18
11.2	Class: CTestsuitesCfg	18
12	version.py	19
12.1	Function: robfwaio_version	19
13	Appendix	20
14	History	21

Chapter 1

Introduction

1.1 RobotFramework AIO testsuites management documentation

This is the documentation for robotframework-testsuitesmanagement library

The RobotFramework_Testsuites package works together with [JsonPreprocessor](#) Python package to provide the enhanced features such as json configuration files, 4 different levels of configuration, global parameters, schema validation, etc

This testsuites management package will support testing for many variants of product on the same Robot project by switching between different configuration files via variant name.

Chapter 2

Description

2.1 Getting Started

2.1.1 How to install

Firstly, clone **RobotFramework-Testsuites** repository to your machine

```
git clone
↳ https://github.com/test-fullautomation/robotframework-testsuitesmanagement.git
```

Go to **robotframework-testsuitesmanagement**, using the 2 common commands below to build or install this package:

```
setup.py build      will build the package underneath 'build/'
setup.py install    will install the package
```

After the build processes are completed, the package is located in **build/**, and the documents are located in **doc/_build/**.

We can use `--help` to discover the options for build command, ex:

```
setup.py build      will build the package underneath 'build/'
setup.py install    will install the package

Global options:
--verbose (-v)      run verbosely (default)
--quiet (-q)        run quietly (turns verbosity off)
--dry-run (-n)      don't actually do anything
--help (-h)         show detailed help message
--no-user-cfg       ignore pydistutils.cfg in your home directory
--command-packages  list of packages that provide distutils commands

Information display options (just display information, ignore any commands)
--help-commands     list all available commands
--name              print package name
--version (-V)      print package version
--fullname           print <package name>-<version>
--author            print the author's name
--author-email       print the author's email address
--maintainer        print the maintainer's name
--maintainer-email   print the maintainer's email address
--contact           print the maintainer's name if known, else the author's
--contact-email      print the maintainer's email address if known, else the
                    author's
--url               print the URL for this package
--license            print the license of the package
```

```

--licence          alias for --license
--description      print the package description
--long-description print the long package description
--platforms       print the list of platforms
--classifiers      print the list of classifiers
--keywords         print the list of keywords
--provides         print the list of packages/modules provided
--requires         print the list of packages/modules required
--obsoletes        print the list of packages/modules made obsolete

usage: setup.py [global_opts] cmd1 [cmd1_opts] [cmd2 [cmd2_opts] ...]
   or: setup.py --help [cmd1 cmd2 ...]
   or: setup.py --help-commands
   or: setup.py cmd --help

```

2.2 Features

2.2.1 Using configuration files in Json format

Nowadays, Json is the leading of structuring data for exchange not only for web applications but also for other software applications. Json format is used to represent data, and become the universal standard of data exchange, that the reason we decided using Json format as configuration file for RobotFramework AIO.

Together with JsonPreprocessor package, RobotFramework.Testsuites supports configuring RobotFramework AIO automation test project with json files which allow user adds the comments, imports params from other json files. Adding comments and importing json files are enhanced features which are developed and documented in JsonPreprocessor python package.

2.2.2 Define 4 levels of configuration

RobotFramework.Testsuites management defines 4 different configuration levels, from level 1 to level 4 level 1 is highest priority, and level 4 is lowest priority:

Level 1: Loads configuration file via input parameter of robot command

This is highest priority of loading configuration method, that means, configuration level 2 or 3 will be ignored even it is set.

This level 1 configuration is designed to force RobotFramework AIO executing with the configuration file for some purpose:

- In case the use wants to execute the robot run with specific configuration file for the particular purposes.
- User re-produces and verifies an issue or a corner case with new configuration file and doesn't want to modify the current configuration file.

User can address the json configuration file when executing robot testsuite with input parameter `--variable config_file:"<path_to_json_file>"`

```
robot --variable config_file:"<path_to_json_file>" <path_to_testsuite>
```

Level 2: Loads Json configuration according to variant name

This level 2 is designed for the scenario that user creates the automation testing project which running for many different variants. When trigger robot run, it will load the appropriate json configuration file.

To set RobotFramework AIO run with level 2, first user has to create a json file which contains different variants point to different configuration files.

For example, we create the `variants_cfg.json` with content below:

```
{
  "default": {
    "name": "<default_cfg_file>",
    "path": "<path>"
  },
  "variant_0": {
    "name": "<file_name_variant_0>",
    "path": "<path>"
  },
  "variant_1": {
    "name": "<file_name_variant_1>",
    "path": "<path>"
  },
  "variant_2": {
    "name": "<file_name_variant_2>",
    "path": "<path>"
  }
}
```

Then the path of `variants_cfg.json` file has to add as input parameter of `testsuites.testsuite_setup` in Suite Setup of a testsuite.

In case of user wants to set configuration level 2 for entire RobotFramework test project instead of individual robot testsuite file, `__init__.robot` file has to be created at the highest folder of RobotFramework test project, and the path of `variants_cfg.json` file has to be added as input parameter of `testsuites.testsuite_setup` in Suite Setup of the `__init__.robot` file.

```
*** Settings ***
Library          RobotFramework-Testsuites      WITH NAME    testsuites
Suite Setup      testsuites.testsuite_setup     <Path-to-the-file-variants_cfg.json>
```

Level 3: Find the “config/“ folder in current testsuite directory

Configuration level 3 is triggered only in case of level 1 and level 2 were not set.

The configuration level 3 will check in `config/` folder in current testsuite directory the existence of json file which has the same name with testsuite file (ex: `abc.robot` & `./config/abc.json`), then it will load this configuration file. In case there is no json file has the same name with robot testsuite file, it will check the existence of `./config/robot_config.json` then load this `./config/robot_config.json` file as configuration file.

Level 4: Lowest priority level, it reads default configuration file

In case testsuites management library detects that configuration level 1, level 2, and level 3 are not set, the robot execution will use the configuration level 4 by default.

The default configuration file (`robot_config.json`) in installation directory:

```
\RobotFramework-Testsuites\Config\robot_config.json
```

2.2.3 Access dictionary object of configuration by traditional way or using “.”

User can access dictionary object which is defined in configuration file in robot test script by called `${dict}[abc][def]` or `${dict}.abc.def`

Note: In case a parameter name contains a “.”, then it is not possible to use dotdict but the traditional way `${dict}[abc][def]` is still working.

Chapter 3

CConfig.py

3.1 Class: dotdict

Imported by:

```
from RobotFramework.Testsuites.Config.CConfig import dotdict
```

Subclass: dotdict

Subclass of dict, with "dot" (attribute) access to keys.

3.2 Class: CConfig

Imported by:

```
from RobotFramework.Testsuites.Config.CConfig import CConfig
```

Class: CConfig

Defines the properties of configuration and holds the identified config files.

The loading configuration method is divided into 4 levels, level1 is highest priority, Level4 is lowest priority.

Level1: Handed over by command line argument.

Level2: Read from content of json config file

```
{
  "default": {
    "name": "robot_config.json",
    "path": ".../config/"
  },
  "variant_0": {
    "name": "robot_config.json",
    "path": ".../config/"
  },
  "variant_1": {
    "name": "robot_config_variant_1.json",
    "path": ".../config/"
  },
  ...
  ...
}
```

According to the ConfigName, Testsuites-Management package will choose the corresponding config file.

".../config/" indicats the relative path to json config file, Testsuites-Management will recursively find the config folder.

Level3: Read in testsuite folder /config/robot_config.json

Level4: Read from RobotFramework AIO install folder /RobotFramework/defaultconfig/robot_config.json

3.2.1 Method: loadCfg

Method: loadCfg

This loadCfg method uses to load configuration's parameters from json files.

Arguments:

- No input parameter is required

Returns:

- No return variable

3.2.2 Method: updateCfg

Method: updateCfg

This updateCfg method updates preprocessor, global or local params base on RobotFramework AIO local config or any json config file according to purpose of specific testsuite.

Arguments:

- sUpdateCfgFile

/ *Condition:* required / *Type:* string

The path of json file which wants to update configuration parameters.

Returns:

- No return variable

3.2.3 Method: verifyRbfwVersion

Method: verifyRbfwVersion

This verifyRbfwVersion validates the current RobotFramework AIO version with maximum and minimum version (if provided in the configuration file).

In case the current version is not between min and max version, then the execution of testsuite is terminated with "unknown" state

Arguments:

- No input parameter is required

Returns:

- No return variable

3.2.4 Method: bValidateMinVersion

Method: bValidateMinVersion

This bValidateMinVersion validates the current version with required minimum version.

Arguments:

- tCurrentVersion
/ *Condition*: required / *Type*: tuple
Current RobotFramework AIO version.
- tMinVersion
/ *Condition*: required / *Type*: tuple
The minimum version of RobotFramework AIO.

Returns:

- True or False

3.2.5 Method: bValidateMaxVersion

Method: bValidateMaxVersion

This bValidateMaxVersion validates the current version with required minimum version.

Arguments:

- tCurrentVersion
/ *Condition*: required / *Type*: tuple
Current RobotFramework AIO version.
- tMinVersion
/ *Condition*: required / *Type*: tuple
The minimum version of RobotFramework AIO.

Returns:

- True or False

3.2.6 Method: bValidateSubVersion

Method: bValidateSubVersion

This bValidateSubVersion validates the format of provided sub version and parse it into sub tuple for version comparision.

Arguments:

- sVersion
/ *Condition*: required / *Type*: string
The version of RobotFramework AIO.

Returns:

- lSubVersion
/ *Type*: tuple /

3.2.7 Method: tupleVersion

Method: tupleVersion

This tupleVersion returns a tuple which contains the (major, minor, patch) version.
(remaining content needs to be fixed and restored)

Arguments:

- sVersion
/ *Condition*: required / *Type*: string
The version of RobotFramework AIO.

Returns:

- lVersion
/ *Type*: tuple /

3.2.8 Method: versioncontrol_error

Method: versioncontrol_error

Wrapper version control error log:

Log error message of version control due to reason and set to unknown state.
reason can only be "conflict_min", "conflict_max" and "wrong_minmax".

Arguments:

- reason
/ *Condition*: required / *Type*: string
- version1
/ *Condition*: required / *Type*: string
- version2
/ *Condition*: required / *Type*: string

Returns:

- No return variable

Chapter 4

COnFailureHandle.py

4.1 Class: COnFailureHandle

Imported by:

```
from RobotFramework.Testsuites.Keywords.COnFailureHandle import COnFailureHandle
```

4.1.1 Method: is_noney

4.1.2 Method: register_keyword_run_on_failure

TBD

Chapter 5

CSetup.py

5.1 Class: CSetupKeywords

Imported by:

```
from RobotFramework.Testsuites.Keywords.CSetup import CSetupKeywords
```

Class: CSetupKeywords

This CSetupKeywords class uses to define the setup keywords which are using in suite setup and teardown of

robot test script.

Testsuite Setup keyword loads the RobotFramework AIO configuration, checks the version of RobotFramework AIO,

and logs out the basic information of the robot run.

Testsuite Teardown keyword currently do nothing, it's defined here for future requirements.

Testcase Setup keyword currently do nothing, it's defined here for future requirements.

Testcase Teardown keyword currently do nothing, it's defined here for future requirements.

5.1.1 Method: testsuite_setup

Method: testsuite_setup

This testsuite_setup defines the Testsuite Setup which is used to loads the RobotFramework AIO configuration,

checks the version of RobotFramework AIO, and logs out the basic information of the robot run.

Arguments:

* sTestsuiteCfgFile

/ *Condition*: required / *Type*: string

sTestsuiteCfgFile='' and vairiable config_file is not set Robotframework AIO will check

for configuration level 3, and level 4.

sTestsuiteCfgFile is set with a <json.config_file_path> and vairiable config_file is not set

Robotframework AIO will load configuration level 2.

Returns:

- No return variable

5.1.2 Method: testsuite_teardown

Method: testsuite_teardown

This testsuite_teardown defines the Testsuite Teardown keyword, currently this keyword does nothing,

it's defined here for future requirements.

5.1.3 Method: testcase_setup

Method: testcase_setup

This testcase_setup defines the Testcase Setup keyword, currently this keyword does nothing,

it's defined here for future requirements.

5.1.4 Method: testcase_teardown

Method: testcase_teardown

This testcase_teardown defines the Testcase Teardown keyword, currently this keyword does nothing,

it's defined here for future requirements.

5.1.5 Method: update_config

Method: update_config

This update_config defines the Update Config keyword which is using update the configuration object of RobotFramework AIO.

Arguments:

- sCfgFile
/ *Condition*: required / *Type*: string
The path of Json configuration file.

Returns:

- No return variable

5.2 Class: CGeneralKeywords

Imported by:

```
from RobotFramework.Testsuites.Keywords.CSetup import CGeneralKeywords
```

Class: CGeneralKeywords

This CGeneralKeywords class uses to define the keywords which will be using in RobotFramework AIO test script.

Get Config keyword gets the current config object of robot run.

Load Json keyword loads json file then return json object.

In case, new robot keyword is required, it will be defined and implemented in this class.

5.2.1 Method: get_config

Method: get_config

This get_config defines the Get Config keyword gets the current config object of RobotFramework AIO.

Arguments:

- No parameter is required

Returns:

- oConfig.oConfigParams
/ *Type: json* /

5.2.2 Method: load_json

Method: load_json

This load_json defines the Load Json keyword which loads json file then return json object.

Arguments:

- jsonfile
/ *Condition: required* / *Type: string*
The path of Json configuration file.
- level
/ *Condition: required* / *Type: int*
Level = 1 -> loads the content of jsonfile.
level != 1 -> loads the json file which is set with variant (likes loading config level2)

Returns:

- oJsonData
/ *Type: json* /

Chapter 6

CStruct.py

6.1 Class: CStruct

Imported by:

```
from RobotFramework.Testsuites.Utls.CStruct import CStruct
```

Class: CStruct

This `CStruct` class creates the given attributes dynamically at runtime.

Chapter 7

Event.py

7.1 Class: Event

Imported by:

```
from RobotFramework.Testsuites.Utils.Events.Event import Event
```

7.1.1 Method: trigger

Chapter 8

ScopeEvent.py

8.1 Class: ScopeEvent

Imported by:

```
from RobotFramework.Testsuites.Utills.Events.ScopeEvent import ScopeEvent
```

8.1.1 Method: trigger

8.2 Class: ScopeStart

Imported by:

```
from RobotFramework.Testsuites.Utills.Events.ScopeEvent import ScopeStart
```

8.3 Class: ScopeEnd

Imported by:

```
from RobotFramework.Testsuites.Utills.Events.ScopeEvent import ScopeEnd
```

Chapter 9

`__init__.py`

9.1 Function: `on`

9.2 Function: `dispatch`

9.3 Function: `register_event`

Chapter 10

LibListener.py

10.1 Class: LibListener

Imported by:

```
from RobotFramework.Testsuites.Utils.LibListener import LibListener
```

Class: LibListener

This `LibListener` class defines the hook methods.

- `_start_suite` hooks to every starting testsuite of robot run.
- `_end_suite` hooks to every ending testsuite of robot run.
- `_start_test` hooks to every starting test case of robot run.
- `_end_test` hooks to every ending test case of robot run.

Chapter 11

__init__.py

11.1 Class: RobotFramework_Testsuites

Imported by:

```
from RobotFramework_Testsuites.__init__ import RobotFramework_Testsuites
```

RobotFramework_Testsuites is the Bosch testing library for Robot Framework. RobotFramework_Testsuites control peripheral devices, tools and target under testing. Method: run_keyword -----

11.1.1 Method: get_keyword_tags

11.1.2 Method: get_keyword_documentation

11.1.3 Method: failure_occurred

11.2 Class: CTestsuitesCfg

Imported by:

```
from RobotFramework_Testsuites.__init__ import CTestsuitesCfg
```

Chapter 12

version.py

12.1 Function: robfwaio_version

Return testsuitemanagement version as Robot framework AIO version

Chapter 13

Appendix

About this package:

Table 13.1: Package setup

Setup parameter	Value
Name	RobotFramework_Testsuites
Version	0.2.2
Date	18.07.2022
Description	Functionality to manage RobotFramework testsuites
Package URL	robotframework-testsuitesmanagement
Author	Mai Dinh Nam Son
Email	son.maidinhnam@vn.bosch.com
Language	Programming Language :: Python :: 3
License	License :: OSI Approved :: Apache Software License
OS	Operating System :: OS Independent
Python required	>=3.0
Development status	Development Status :: 4 - Beta
Intended audience	Intended Audience :: Developers
Topic	Topic :: Software Development

Chapter 14

History

0.1.0	06/2022
<i>Initial version</i>	

RobotFramework-Testsuites.pdf*Created at 02.11.2022 - 15:16:59**by GenPackageDoc v. 0.32.0*
