

[Hadoop] Lab02 Sqoop를 이해하기

학습 목표

가. Sqoop은 무엇일까?

나. sqoop의 tool를 이용하여 MySQL의 Table를 HDFS로 데이터를 옮기는 것에 대해 이해한다.

01 스쿱(Sqoop)은 무엇일까?

- 스쿱은 하둡 생태계에 속하는 아파치 프로젝트이다.
- 스쿱은 클러스터 간에 데이터 이동하는 대신 **JDBC드라이버를 사용**한다.
- JDBC 드라이버를 이용한 관계형 데이터베이스(RDBMS)에 데이터를 내보내거나 가져오도록 설계되었다.

02 작업을 위한 사전준비

(가) Cloudera를 시작한다.

(나) mysql 의 기본 암호 설정 및 root의 localhost를 확인한다.

암호 재설정

```
$ mysql -u root -p
Enter password:[cloudera]
UPDATE mysql.user
    SET Password=PASSWORD('1234')
WHERE User='root';
FLUSH PRIVILEGES;
```

localhost 확인

MySQL 5.7미만

```
mysql> SELECT Host, User FROM mysql.user;
```

[결과 내용]

```
mysql> select host, user from mysql.user;
```

```
+-----+-----+
| host          | user  |
+-----+-----+
```

```

| %          | hiveuser |
| 127.0.0.1  | root    |
| localhost  |         |
| localhost  | hive    |
| localhost  | hiveuser|
| localhost  | hue     |
| localhost  | root    |
| localhost  | training |
| localhost.localdomain |
| localhost.localdomain | root    |
+-----+-----+
10 rows in set (0.00 sec)

```

도움말

sqoop help

sqoop list-tables --> 엔터를 치면 상세한 내용이 나온다.

03 Mysql 전체 테이블 리스트 확인해보기

[사용법]

```

sqoop list-tables
  --connect <jdbc-uri>      # JDBC connect 문자열을 지정
  --username dbuser        # user(사용자를 지정한다.)
  --password dbpassword    # db의 password를 지정한다.

```

[실행 명령어]

```
sqoop list-tables --connect jdbc:mysql://localhost/dbname --username root --password 1234
```

[실행결과]

```

[training@localhost Desktop]$ sqoop list-tables --connect jdbc:mysql://localhost/training --username root --password 1234
18/05/13 08:30:17 WARN tool.BaseSqoopTool: Setting your password on the command-line is insecure. Consider using -P instead.
18/05/13 08:30:17 INFO manager.MySQLManager: Preparing to use a MySQL streaming resultset.

```

```

Movies
bible_freq
cityByCountry
countries
shake_freq

```

04 전체 테이블 임포트하기

```

sqoop import-all-tables \
  --connect jdbc:mysql://localhost/training \

```

```
--username root \
--password 1234
```

05 하나의 테이블 импорт

Movies의 테이블을 импорт한다.

```
sqoop import --table Movies \
--connect jdbc:mysql://localhost/training \
--username root --password 1234 \
--fields-terminated-by "\t"
```

[실행결과]

```
[training@localhost Desktop]$ sqoop import --table Movies \
> --connect jdbc:mysql://localhost/training \
> --username root --password 1234 \
> --fields-terminated-by "\t"
18/05/13 08:40:29 WARN tool.BaseSqoopTool: Setting your password on the command-line is insecure. Consider using -P instead.
18/05/13 08:40:29 INFO manager.MySQLManager: Preparing to use a MySQL streaming resultset.
18/05/13 08:40:29 INFO tool.CodeGenTool: Beginning code generation
18/05/13 08:40:30 INFO manager.SqlManager: Executing SQL statement: SELECT t.* FROM `Movies` AS t LIMIT 1
18/05/13 08:40:30 INFO manager.SqlManager: Executing SQL statement: SELECT t.* FROM `Movies` AS t LIMIT 1
18/05/13 08:40:30 INFO orm.CompilationManager: HADOOP_HOME is /usr/lib/hadoop
Note: /tmp/sqoop-training/compile/94861fefc5b305b7642ab8ebd7b520f4/Movies.java uses or overrides a deprecated API.
Note: Recompile with -Xlint:deprecation for details.
18/05/13 08:40:34 INFO orm.CompilationManager: Writing jar file: /tmp/sqoop-training/compile/94861fefc5b305b7642ab8ebd7b520f4/Movies.jar
18/05/13 08:40:34 WARN manager.MySQLManager: It looks like you are importing from mysql.
18/05/13 08:40:34 WARN manager.MySQLManager: This transfer can be faster! Use the --direct
18/05/13 08:40:34 WARN manager.MySQLManager: option to exercise a MySQL-specific fast path.
18/05/13 08:40:34 INFO manager.MySQLManager: Setting zero DATETIME behavior to convertToNull (mysql)
18/05/13 08:40:34 INFO mapreduce.ImportJobBase: Beginning import of Movies
18/05/13 08:40:37 WARN mapred.JobClient: Use GenericOptionsParser for parsing the arguments. Applications should implement Tool for the
same.
18/05/13 08:40:39 INFO db.DataDrivenDBInputFormat: BoundingValsQuery: SELECT MIN(`movieid`), MAX(`movieid`) FROM `Movies`
18/05/13 08:40:39 INFO mapred.JobClient: Running job: job_201805091052_0005
18/05/13 08:40:40 INFO mapred.JobClient: map 0% reduce 0%
18/05/13 08:40:58 INFO mapred.JobClient: map 50% reduce 0%
18/05/13 08:41:10 INFO mapred.JobClient: map 75% reduce 0%
18/05/13 08:41:11 INFO mapred.JobClient: map 100% reduce 0%
18/05/13 08:41:14 INFO mapred.JobClient: Job complete: job_201805091052_0005
18/05/13 08:41:14 INFO mapred.JobClient: Counters: 23
18/05/13 08:41:14 INFO mapred.JobClient: File System Counters
18/05/13 08:41:14 INFO mapred.JobClient: FILE: Number of bytes read=0
18/05/13 08:41:14 INFO mapred.JobClient: FILE: Number of bytes written=797564
```

```

18/05/13 08:41:14 INFO mapred.JobClient: FILE: Number of read operations=0
18/05/13 08:41:14 INFO mapred.JobClient: FILE: Number of large read operations=0
18/05/13 08:41:14 INFO mapred.JobClient: FILE: Number of write operations=0
18/05/13 08:41:14 INFO mapred.JobClient: HDFS: Number of bytes read=450
18/05/13 08:41:14 INFO mapred.JobClient: HDFS: Number of bytes written=234674
18/05/13 08:41:14 INFO mapred.JobClient: HDFS: Number of read operations=4
18/05/13 08:41:14 INFO mapred.JobClient: HDFS: Number of large read operations=0
18/05/13 08:41:14 INFO mapred.JobClient: HDFS: Number of write operations=4
18/05/13 08:41:14 INFO mapred.JobClient: Job Counters
18/05/13 08:41:14 INFO mapred.JobClient:   Launched map tasks=4
18/05/13 08:41:14 INFO mapred.JobClient:   Total time spent by all maps in occupied slots (ms)=54156
18/05/13 08:41:14 INFO mapred.JobClient:   Total time spent by all reduces in occupied slots (ms)=0
18/05/13 08:41:14 INFO mapred.JobClient:   Total time spent by all maps waiting after reserving slots (ms)=0
18/05/13 08:41:14 INFO mapred.JobClient:   Total time spent by all reduces waiting after reserving slots (ms)=0
18/05/13 08:41:14 INFO mapred.JobClient: Map-Reduce Framework
18/05/13 08:41:14 INFO mapred.JobClient:   Map input records=1682
18/05/13 08:41:14 INFO mapred.JobClient:   Map output records=1682
18/05/13 08:41:14 INFO mapred.JobClient:   Input split bytes=450
18/05/13 08:41:14 INFO mapred.JobClient:   Spilled Records=0
18/05/13 08:41:14 INFO mapred.JobClient:   CPU time spent (ms)=5660
18/05/13 08:41:14 INFO mapred.JobClient:   Physical memory (bytes) snapshot=198574080
18/05/13 08:41:14 INFO mapred.JobClient:   Virtual memory (bytes) snapshot=1552662528
18/05/13 08:41:14 INFO mapred.JobClient:   Total committed heap usage (bytes)=63963136
18/05/13 08:41:14 INFO mapreduce.ImportJobBase: Transferred 0 bytes in 39.0823 seconds (0 bytes/sec)
18/05/13 08:41:14 INFO mapreduce.ImportJobBase: Retrieved 1682 records.

```

[HDFS 확인]

[training@localhost Desktop]\$ **hadoop fs -ls -R**

```

drwxr-xr-x  - training supergroup          0 2018-05-13 08:41 Movies
-rw-r--r--  1 training supergroup          0 2018-05-13 08:41 Movies/_SUCCESS
drwxr-xr-x  - training supergroup          0 2018-05-13 08:40 Movies/_logs
drwxr-xr-x  - training supergroup          0 2018-05-13 08:40 Movies/_logs/history
-rw-r--r--  1 training supergroup      87015 2018-05-13 08:40 Movies/_logs/history/0.0.0.0_1525877582151_job_201805091052_0005_conf.xml
-rw-r--r--  1 training supergroup     22177 2018-05-13 08:41 Movies/_logs/history/job_201805091052_0005_1526215239637_training_Movies.jar
-rw-r--r--  1 training supergroup     58800 2018-05-13 08:40 Movies/part-m-00000
-rw-r--r--  1 training supergroup     58986 2018-05-13 08:40 Movies/part-m-00001
-rw-r--r--  1 training supergroup     58458 2018-05-13 08:41 Movies/part-m-00002
-rw-r--r--  1 training supergroup     58430 2018-05-13 08:41 Movies/part-m-00003

```

데이터 확인

[training@localhost Desktop]\$ **hadoop fs -cat Movies/part-m-00000**

...

(참고 mysql 확인시)

```
mysql> desc Movies;
```

Field	Type	Null	Key	Default	Extra
movieid	int(11)	NO	PRI	0	
movie_name	varchar(255)	YES		NULL	
release_date	char(11)	YES		NULL	
imdb_url	varchar(255)	YES		NULL	
unknown_genre	tinyint(4)	YES		NULL	
action	tinyint(4)	YES		NULL	
adventure	tinyint(4)	YES		NULL	
animation	tinyint(4)	YES		NULL	
children	tinyint(4)	YES		NULL	
comedy	tinyint(4)	YES		NULL	
crime	tinyint(4)	YES		NULL	
documentary	tinyint(4)	YES		NULL	
drama	tinyint(4)	YES		NULL	
fantasy	tinyint(4)	YES		NULL	
film_noir	tinyint(4)	YES		NULL	
horror	tinyint(4)	YES		NULL	
musical	tinyint(4)	YES		NULL	
mystery	tinyint(4)	YES		NULL	
romance	tinyint(4)	YES		NULL	
sci-fi	tinyint(4)	YES		NULL	
thriller	tinyint(4)	YES		NULL	
war	tinyint(4)	YES		NULL	
western	tinyint(4)	YES		NULL	

23 rows in set (0.01 sec)

[실습 1-1] training database안에 cityByCountry를 HDFS 시스템으로 임포트 해 보자.

06 부분적인 테이블 임포트

```
mysql> desc Movies;
```

Field	Type	Null	Key	Default	Extra
movieid	int(11)	NO	PRI	0	
movie name	varchar(255)	YES		NULL	
release date	char(11)	YES		NULL	
imdb_url	varchar(255)	YES		NULL	
unknown_genre	tinyint(4)	YES		NULL	
action	tinyint(4)	YES		NULL	
adventure	tinyint(4)	YES		NULL	
animation	tinyint(4)	YES		NULL	
children	tinyint(4)	YES		NULL	
comedy	tinyint(4)	YES		NULL	
crime	tinyint(4)	YES		NULL	
documentary	tinyint(4)	YES		NULL	
drama	tinyint(4)	YES		NULL	
fantasy	tinyint(4)	YES		NULL	
film_noir	tinyint(4)	YES		NULL	
horror	tinyint(4)	YES		NULL	
musical	tinyint(4)	YES		NULL	
mystery	tinyint(4)	YES		NULL	
romance	tinyint(4)	YES		NULL	
sci_fi	tinyint(4)	YES		NULL	
thriller	tinyint(4)	YES		NULL	
war	tinyint(4)	YES		NULL	
western	tinyint(4)	YES		NULL	

23 rows in set (0.00 sec)

(가) Mysql의 Movies 테이블의 일부 컬럼 импорт

우리는 movieid, movie_name, release_date, action, adventure를 импорт해보자.

```
sqoop import --table Movies \
  --connect jdbc:mysql://localhost/training \
  --username root --password 1234 \
  --columns "movieid, movie_name, release_date, action, adventure"
```

[실행결과]

```
[training@localhost Desktop]$ sqoop import --table Movies \
```

```
> --connect jdbc:mysql://localhost/training \
```

```
> --username root --password 1234 \
```

```
> --columns "movieid, movie_name, release_date, action, adventure"
```

```
18/05/13 12:28:48 WARN tool.BaseSqoopTool: Setting your password on the command-line is insecure. Consider using -P instead.
```

```
18/05/13 12:28:49 INFO manager.MySQLManager: Preparing to use a MySQL streaming resultset.
```

```
18/05/13 12:28:49 INFO tool.CodeGenTool: Beginning code generation
```

```
18/05/13 12:28:49 INFO manager.SqlManager: Executing SQL statement: SELECT t.* FROM `Movies` AS t LIMIT 1
```

```
18/05/13 12:28:49 INFO manager.SqlManager: Executing SQL statement: SELECT t.* FROM `Movies` AS t LIMIT 1
```

```
18/05/13 12:28:49 INFO orm.CompilationManager: HADOOP_HOME is /usr/lib/hadoop
```

```
Note: /tmp/sqoop-training/compile/92c1fc3258c9ee22643bc5a9f58a25e6/Movies.java uses or overrides a deprecated API.
```

```
Note: Recompile with -Xlint:deprecation for details.
```

```
18/05/13 12:28:52 INFO orm.CompilationManager: Writing jar file: /tmp/sqoop-training/compile/92c1fc3258c9ee22643bc5a9f58a25e6/Movies.jar
```

```
18/05/13 12:28:52 WARN manager.MySQLManager: It looks like you are importing from mysql.
```

```
18/05/13 12:28:52 WARN manager.MySQLManager: This transfer can be faster! Use the --direct
```

```
18/05/13 12:28:52 WARN manager.MySQLManager: option to exercise a MySQL-specific fast path.
```

```
18/05/13 12:28:52 INFO manager.MySQLManager: Setting zero DATETIME behavior to convertToNull (mysql)
```

```
18/05/13 12:28:52 INFO mapreduce.ImportJobBase: Beginning import of Movies
```

```
18/05/13 12:28:55 WARN mapred.JobClient: Use GenericOptionsParser for parsing the arguments. Applications should implement Tool for the same.
```

```
18/05/13 12:28:57 INFO db.DataDrivenDBInputFormat: BoundingValsQuery: SELECT MIN(`movieid`), MAX(`movieid`) FROM `Movies`
```

```
18/05/13 12:28:58 INFO mapred.JobClient: Running job: job_201805131018_0015
```

```
18/05/13 12:28:59 INFO mapred.JobClient: map 0% reduce 0%
```

```
18/05/13 12:29:20 INFO mapred.JobClient: map 50% reduce 0%
```

```
18/05/13 12:29:34 INFO mapred.JobClient: map 100% reduce 0%
```

```
18/05/13 12:29:37 INFO mapred.JobClient: Job complete: job_201805131018_0015
```

```
18/05/13 12:29:37 INFO mapred.JobClient: Counters: 23
```

```
18/05/13 12:29:37 INFO mapred.JobClient: File System Counters
```

```
18/05/13 12:29:37 INFO mapred.JobClient: FILE: Number of bytes read=0
```

```
18/05/13 12:29:37 INFO mapred.JobClient: FILE: Number of bytes written=796816
```

```
18/05/13 12:29:37 INFO mapred.JobClient: FILE: Number of read operations=0
```

```
18/05/13 12:29:37 INFO mapred.JobClient: FILE: Number of large read operations=0
```

```
18/05/13 12:29:37 INFO mapred.JobClient: FILE: Number of write operations=0
```

```
18/05/13 12:29:37 INFO mapred.JobClient: HDFS: Number of bytes read=450
```

```
18/05/13 12:29:37 INFO mapred.JobClient: HDFS: Number of bytes written=75356
```

```
18/05/13 12:29:37 INFO mapred.JobClient: HDFS: Number of read operations=4
```

```
18/05/13 12:29:37 INFO mapred.JobClient: HDFS: Number of large read operations=0
```

```
18/05/13 12:29:37 INFO mapred.JobClient: HDFS: Number of write operations=4
```

```
18/05/13 12:29:37 INFO mapred.JobClient: Job Counters
```

```
18/05/13 12:29:37 INFO mapred.JobClient: Launched map tasks=4
```

```
18/05/13 12:29:37 INFO mapred.JobClient: Total time spent by all maps in occupied slots (ms)=65796
```

```
18/05/13 12:29:37 INFO mapred.JobClient: Total time spent by all reduces in occupied slots (ms)=0
```

```

18/05/13 12:29:37 INFO mapred.JobClient: Total time spent by all maps waiting after reserving slots (ms)=0
18/05/13 12:29:37 INFO mapred.JobClient: Total time spent by all reduces waiting after reserving slots (ms)=0
18/05/13 12:29:37 INFO mapred.JobClient: Map-Reduce Framework
18/05/13 12:29:37 INFO mapred.JobClient: Map input records=1682
18/05/13 12:29:37 INFO mapred.JobClient: Map output records=1682
18/05/13 12:29:37 INFO mapred.JobClient: Input split bytes=450
18/05/13 12:29:37 INFO mapred.JobClient: Spilled Records=0
18/05/13 12:29:37 INFO mapred.JobClient: CPU time spent (ms)=7150
18/05/13 12:29:37 INFO mapred.JobClient: Physical memory (bytes) snapshot=198578176
18/05/13 12:29:37 INFO mapred.JobClient: Virtual memory (bytes) snapshot=1552662528
18/05/13 12:29:37 INFO mapred.JobClient: Total committed heap usage (bytes)=63963136
18/05/13 12:29:37 INFO mapreduce.ImportJobBase: Transferred 0 bytes in 44.062 seconds (0 bytes/sec)
18/05/13 12:29:37 INFO mapreduce.ImportJobBase: Retrieved 1682 records.

```

만약 다른 조건으로 다른 디렉터리로 임포트(보내기)하고 싶다면 아래를 참조하자.

```

sqoop import --table Movies \
--connect jdbc:mysql://localhost/training \
--username root --password 1234 \
--columns "movieid, action" \
--target-dir training/MovieTbl

```

[결과 확인]

[training@localhost Desktop]\$ hadoop fs -ls -R Movies

```

-rw-r--r-- 1 training supergroup 0 2018-05-13 11:09 Movies/_SUCCESS
drwxr-xr-x - training supergroup 0 2018-05-13 11:08 Movies/_logs
drwxr-xr-x - training supergroup 0 2018-05-13 11:08 Movies/_logs/history
-rw-r--r-- 1 training supergroup 86828 2018-05-13 11:08 Movies/_logs/history/0.0.0.0_1526221129783_job_201805131018_0004_conf.xml
-rw-r--r-- 1 training supergroup 22177 2018-05-13 11:09 Movies/_logs/history/job_201805131018_0004_1526224117409_training_Movies.jar
-rw-r--r-- 1 training supergroup 43644 2018-05-13 11:08 Movies/part-m-00000
-rw-r--r-- 1 training supergroup 43866 2018-05-13 11:08 Movies/part-m-00001
-rw-r--r-- 1 training supergroup 43338 2018-05-13 11:09 Movies/part-m-00002
-rw-r--r-- 1 training supergroup 43274 2018-05-13 11:09 Movies/part-m-00003

```

[training@localhost Desktop]\$ hadoop fs -ls -R training/MovieTbl

```

...
-rw-r--r-- 1 training supergroup 22167 2018-05-13 12:12
training/MovieTbl/_logs/history/job_201805131018_0013_1526227932030_training_Movies.jar
-rw-r--r-- 1 training supergroup 2418 2018-05-13 12:12 training/MovieTbl/part-m-00000
-rw-r--r-- 1 training supergroup 2520 2018-05-13 12:12 training/MovieTbl/part-m-00001

```



```
-rw-r--r--  1 training supergroup      2782 2018-05-13 12:12 training/MovieTbl/part-m-00002
-rw-r--r--  1 training supergroup      2947 2018-05-13 12:12 training/MovieTbl/part-m-00003
...
```

```
[training@localhost Desktop]$ hadoop fs -cat  Movies/part-m-00000
```

```
[training@localhost Desktop]$ hadoop fs -cat  Movies/part-m-00000
```

[실습 1-2] training database안에 cityByCountry의 city, lat, lng를 HDFS 시스템으로 다른 디렉터리로 training/cityByCountry1 로 импорт 해 보자.

07 HDFS에서 RDBMS로 데이터 보내기

```
sqoop export \
--connect jdbc:mysql://localhost/training \
--username root \
--password 1234 \
--table sample_tbl \
--export-dir training/MovieTbl
```

에러 발생 한다면.

```
18/05/13 11:44:19 ERROR manager.SqlManager: Error executing statement: com.mysql.jdbc.exceptions.jdbc4.MySQLSyntaxErrorException: Table
'training.sample_tbl' doesn't exist
com.mysql.jdbc.exceptions.jdbc4.MySQLSyntaxErrorException: Table 'training.sample_tbl' doesn't exist
    at sun.reflect.NativeConstructorAccessorImpl.newInstance0(Native Method)
```

```
CREATE TABLE sample_tbl (
    movieid int(11),
    action      tinyint(4)
);
```

[만약 잘못되어 삭제할때는 Drop table 이용]

```
Drop TABLE sample_tbl ;
```

[결과 확인]

```
mysql> show tables;
+-----+
| Tables_in_training |
```

```
+-----+
| Movies  
| bible_freq  
| cityByCountry  
| countries  
| sample_tbl  
| shake_freq  
+-----+
6 rows in set (0.00 sec)
```

```
mysql> select * from sample_tbl;
```

```
+-----+-----+
| movieid | action |
+-----+-----+
|      1 |      0 |
|      2 |      1 |
|      3 |      0 |
|      4 |      1 |
|      5 |      0 |
|      6 |      0 |
|      7 |      0 |
|      8 |      0 |
| ..... |
|    412 |      0 |
|    413 |      0 |
|    414 |      0 |
|    415 |      0 |
|    416 |      0 |
|    417 |      0 |
|    418 |      0 |
|    419 |      0 |
|    420 |      0 |
|    421 |      0 |
+-----+-----+
```

```
421 rows in set (0.00 sec)
```

[실습 1-3] 도전과제

cityByCountry1의 HDFS의 파일을 sample_tbl2의 테이블로 옮겨보자.

REF

(1) 하둡과 빅데이터 분석 실무

Last : 2019.02.13