

Symbolic Mechanics

Technical Specification v1.0

$\Delta \rightarrow S \rightarrow L \rightarrow R$

Canonical Specification

Volumes 01–20

Integrated canonical map of the first twenty volumes of Symbolic Mechanics, formatted from the uploaded extracted text and visually rebuilt for cleaner reading, hierarchy, and reference use.

Contents Map

I. System Stratification of Volumes 01–20

Layer 0 through Layer 7

II. Complete Variable Table

Core symbols, vectors, thresholds, modules, and runtime states

III. Module Table

Named system modules and their governing functions

IV. Routing Rules

Grouped rules across core, parent-companion, boundary, shutdown, projection, and fallback routing

V. Compressed State Transition Map

Operational pathways in compact chain form

VI. Complete Engine Master Expression

System-wide expression and state variable set

Visual treatment
Warm cream paper field, restrained navy hierarchy, accent rules, quieter serif body text, and cleaner reference layouts for tables and rule groups.

I. System Stratification of Volumes 01–20

Layer 0 — Core Engine

Layer 0 contains the canonical processing engine of Symbolic Mechanics. Its primary cycle is:

$$\Delta \rightarrow S \rightarrow L \rightarrow R \rightarrow \text{Exit} \rightarrow \text{new } \Delta$$

This layer defines the compulsory movement from perceived difference into symbolic containment, from containment into load, from load into rupture, from rupture into discharge, and from discharge into renewed input. It also includes the processor-selection event that assigns whole-cycle ownership to SCd or SCr. Layer 0 also contains the regenerative restart architecture introduced by Volume IV. When the C-Module is online and the required structural conditions are satisfied, the engine gains a non-rupture restart loop:

$$\Delta \rightarrow S \rightarrow C \rightarrow S$$

This loop does not replace the primary engine. It exists inside the engine as a restart path that prevents overload escalation and allows continuation without rupture.

Layer 1 — Symbol Economy

Layer 1 contains the symbolic distribution economy of the system. It defines the four-seat architecture, seat assignment, symbolic weight, replacement resistance, seat-specific holding behaviour, shadow-position pressure, and the persistence logic of installed symbolic objects. This layer governs where S is placed, how strongly it holds, how difficult it is to displace, and how symbolic mass accumulates across cycles.

Layer 2 — Axis Geometry

Layer 2 contains the directional geometry of the system. It defines the M-axis, F-axis, and Jaxis as load-bearing vectors that bend the route of symbolic processing. It also contains the canonical formalization of Symbolic Parents and parental volume. Symbolic Parents are not representations of actual parents. They are the system's two built-in regulatory channels: soothing capacity on the M-axis and boundarysetting capacity on the F-axis. Parental volume determines whether load dissipates, accumulates, redirects, or becomes eligible for C-Module emergence. When M-axis volume and F-axis volume reach stable mid-range activation, and J-axis dominance naturally falls below override strength, this layer produces the Companion module as a structural stabilizer. The C-Module therefore belongs to core canonical architecture and not to a secondary repair description.

Layer 3 — Boundary Physics

Layer 3 contains the physical rules of access, thresholding, illumination, and shutdown. It defines safety radius, visibility, gate openness, alarm threshold, spotlight or boundary-light, blackout state, Orb formation, attentional capture, boundary override, and shutdown corridor dynamics. This layer governs whether external force enters the room, whether the room remains readable, when illumination fails, and when the system withdraws visibility as a protective or overload-driven operation.

Layer 4 — Interaction Field

Layer 4 contains the dynamic field behaviour that arises when boundary conditions meet external presence. It governs attractiontension, instruction resistance, intrusion pressure, displacement, seat-field contraction, visibility collapse, sorting failure, existence compensation, visibility differential, exit-

homology amplification, and forward-field amplitude modulation. It also governs the directional behaviour of the O-vector when movement, approach, or reconfiguration encounters counterforce. This layer does not define the boundary as such. It defines the unstable dynamics that unfold once the boundary is engaged.

Layer 5 — Projection Runtime

Layer 5 contains the intimate projection runtime. It defines projector activation, singleinput mode, Table-Surface stabilization, Position-3 melt, projector heat, vapor pressure, Bartender reduction, projection threshold, and projection thermal overload. This layer formalizes the special operating regime in which an intimate symbolic image is maintained under high pressure.

Layer 6 — Post-Projection Alarm State

Layer 6 contains the state that follows projection shutdown. It formalizes the transfer from projector-owned runtime into alarmowned runtime. It includes threat recoding of the nearest intimate object, defensive narrowing, and continued interaction under alarm rather than projection governance.

Layer 7 — Catastrophic Fallback Layer

Layer 7 contains the deepest fallback architecture of Volumes 1-20. It governs shame-break, Shadow-Child formation, Clown generation, Grand Hall scene selection, and Firefly navigation. This layer activates when ordinary symbolic containment, boundary regulation, projection runtime, and restart capacity no longer preserve coherence. It is the catastrophic continuation architecture of the system.

II. Complete Variable Table

The original extracted text presents this section as a variable list. It is reformatted here as a compact reference table for faster scanning.

Variable	Definition
Δ	Δ denotes the input packet of difference. Every event enters the system only after conversion into Δ . No engine-level processing begins outside this format.
S	S denotes the symbolic container generated to hold unresolved difference. S is the primary symbolic holding unit of the engine.
seat	seat denotes the installed position of S within the four-seat economy. Every symbolic container occupies one seat, and each seat imposes a distinct load behaviour and routing bias.
L	L denotes accumulated load within S. L is the unresolved symbolic burden carried by the system. L increases under pressure and remains active until routed through rupture or bypassed through regenerative restart.
R	R denotes rupture threshold. R is the structural carrying limit of the installed symbolic container. When L reaches or exceeds R, rupture is triggered.
Exit	Exit denotes the rupture-triggered discharge pathway activated after R. In the stabilized canonical system, Exit has three forms only: violent, delayed, and mourning / absorptive.
proc	proc denotes the processor that owns the cycle. proc {SCd, SCr}. Processor ownership is mutually exclusive during a given cycle.
κ	κ denotes processor sensitivity and competitive activation strength. κ determines which processor wins first access to a given Δ .
T_rate	T_rate denotes the rate of load accumulation, formally expressed as dL/dt . It measures how quickly pressure rises inside the active symbolic structure.
T_margin	T_margin denotes the ratio between current load and rupture threshold, formally expressed as L/R . It measures proximity to rupture.
W	W denotes symbolic weight. W is the installed weight of a symbolic object as determined by difference density, temporal persistence, and functional coupling.
R_r	R_r denotes replacement resistance. It is the resistance of an installed symbolic object against displacement or substitution. R_r increases with weight and consolidation depth.
P = (M, F, J)	P denotes the tri-axial geometry of the system. M is maternal curvature, F is paternal curvature, and J is Judge curvature. Together they bend symbolic interpretation, load direction, rupture approach, and restart eligibility.
SP	SP denotes Symbolic Parents as the system's two built-in regulatory channels. SP is not a memory of actual parents. SP is the internal availability of soothing and boundary-setting functions.
PV	PV denotes parental volume. It is the total available regulatory capacity supplied by Symbolic Parents. PV governs whether the engine remains trapped inside high-curvature routing or gains access to low-curvature stabilization.

Variable	Definition
M_vol	M_vol denotes effective maternal volume. It is the functional availability of soothing capacity inside the engine.
F_vol	F_vol denotes effective paternal volume. It is the functional availability of boundary-setting capacity inside the engine.
C	C denotes the Companion module, or C- Module. C is a self-generated stabilizer that emerges when M_vol and F_vol exceed minimum stability thresholds and J pressure falls below dominance. C performs stabilization and re-initiation.
C_path	C_path denotes the regenerative restart route through the C-Module. It is the path by which Δ transitions through C and re-enters S without escalating into overload.
LEP	LEP denotes the low-energy regenerative path. It is the non-rupture, low-amplitude route made possible by C_path.
R_cycle	R_cycle denotes the regenerative cycle: $\Delta \rightarrow S \rightarrow C \rightarrow S$. It is the engine's damage-preventive restart loop.
O-vector	O-vector denotes the Organismic Vector. It is the system's intrinsic directional momentum toward movement, improvement, reconfiguration, approach, or forward displacement. The O-vector is not intention, preference, or narrative wish. It is the operative movement-vector that attempts trajectory change inside the symbolic field and encounters counterforce when internal geometry classifies that displacement as destabilizing.
Rs	Rs denotes safety radius. It is the fixed protected radius inside which external approach is processed as critical proximity rather than neutral distance.
V	V denotes visibility. It is the readable capacity of the symbolic room. V determines how much external presence or symbolic complexity the room can sustain without collapse.
G	G denotes gate openness. It is the access parameter that governs entry timing and permeability. G is distinct from visibility.
Δ_{th}	Δ_{th} denotes alarm threshold. It is the threshold at which incoming force is classified as intrusion pressure rather than tolerable contact.
A	A denotes the alarm module. A translates qualifying approach or force into defensive system activation. I° denotes intrusion-qualified input. It is external force after recoding into intrusion geometry. I° is not mere approach and not semantic content. It is the mechanically classified input that satisfies the system's intrusion conditions and is therefore eligible to activate A.
D	D denotes displacement vector. It is the immediate directional movement away from an intrusion source once alarm is triggered.
Cs	Cs denotes seat-field contraction. It is the narrowing of active symbolic field after alarm activation.
ALi	ALi denotes intrusion-added load. It is the additional load imposed by repeated or invasive external force.
Spotlight	Spotlight denotes the active boundary-light or illumination function of the internal room. It provides spatial clarity, perceptual radius, and symbolic distance between self and load.

Variable	Definition
B_light	B_light denotes boundary-light as the readable illumination state of the boundary layer. When B_light = 0, symbolic access is suspended.
Bk	Bk denotes blackout state. It is the room configuration in which illumination collapses to zero and symbolic coordinates become unreadable.
Orb	Orb denotes the canonical dark-room anchor generated when symbolic guidance is offline and the system requires a minimal non- symbolic reference to continue operating. Orb is the only remaining source of directional attention inside blackout or shutdown-corridor conditions. It is not pleasure, reward, desire, or symbolic meaning. It is the governing reference of the darkened room.
AC	AC denotes attentional capture. It is the full allocation of attentional bandwidth to Orb and its excitation rhythm.
SCorr	SCorr denotes shutdown corridor. It is the darkened operating corridor in which symbolic access is offline while attention remains anchored to Orb.
Bo	Bo denotes boundary override shutdown. It is the internally initiated shutoff of boundary-light under concentrated symbolic compression.
B_re	B_re denotes boundary-light reactivation. It is the return of illumination after shutdown or blackout sequence.
AV	AV denotes visibility differential, formally expressed as: $AV = V_{self} - V_{other}$. It is the differential in readable symbolic visibility between two systems. AV generates primary field orientation by directing the lower-visibility system toward the higher-visibility configuration as a proxy for lost internal resolution.
En	En denotes exit-structure homology. It is the detection of matching internal routing, especially matching overload pathways, suppression rhythms, and destabilization curves. En does not produce safety. It produces structural recognizability and increases persistence of reactivation.
Ex	Ex denotes existence-compensation load. It is the amplitude contribution generated when internal symbolic weight cannot be confirmed and the system therefore seeks existence-confirmation externally. Ex does not create the field by itself. It amplifies the forward term once orientation has already activated.
Prj	Prj denotes projection state. Prj marks entry into projector-owned runtime.
Π	Π denotes projection-entry threshold. It is the minimum synchronized activation level required for projector runtime to begin. When projection-supporting load across the relevant seats reaches or exceeds M in the presence of an active difference and softened access conditions, the system enters Prj.
TS	TS denotes Table-Surface. It is the stabilized integration plane formed during projection runtime by synchronized holding across selected seats.
M3	M3 denotes Position-3 melt. It is the only reality-correction leakage channel permitted during projection runtime.
H_p	H_p denotes projector heat. It is the thermal burden generated by maintaining a projection image under load.

Variable	Definition
V_P	V_P denotes vapor pressure. It is the pressure layer formed by unresolved melt and projection heat.
B_r	B_r denotes Bartender reduction. It is the reduction function supplied by the Bartender regulatory mechanism through paternal and Judge support. • denotes projection thermal tolerance threshold. It is the maximum pressure the projection runtime can hold before automatic shutdown.
SB	SB denotes shame-break. It is the catastrophic break event in which the read-values of Self-Body, SCr, and Inner System cease to align.
ShC	ShC denotes Shadow-Child. It is the residual shame-bearing child-body formed after catastrophic shame break.
Clown	Clown denotes the substitute agency generated within catastrophic fallback architecture when buried shame remains linked to the demand for visibility.
scene	scene denotes the illuminated active scene inside the Grand Hall topology. It is the currently lit domain of action, such as intimacy, family, friendship, work, or creation.
Firefly	Firefly denotes the lowest-level navigation vector in the dark-field architecture. It does not judge. It points toward the next survivable direction of movement.

III. Module Table

Module	Function
Core Engine	The Core Engine converts difference into symbolic containment, transforms containment into load, drives load toward rupture, routes rupture into canonical Exit, and returns the system into renewed Δ . It also contains the regenerative restart configuration introduced by the C-Module, allowing Δ to re-enter S without overload escalation when non-rupture conditions are satisfied.
Processor Module	The Processor Module contains SCd and SCr as mutually exclusive processors. It governs first activation, whole-cycle ownership, entry style, and seat-selection bias. Only one processor may own a given cycle.
Seat Economy	The Seat Economy governs symbolic installation across the four-seat structure. It determines placement, seat-specific holding logic, symbolic persistence, replacement resistance, shadow-position influence, and the propagation of symbolic mass across cycles.
Axis Geometry	The Axis Geometry module governs the tri-axial field $P = (M, F, J)$. It bends symbolic interpretation, load curvature, and rupture direction. It also contains Symbolic Parents and parental volume as functional regulatory vectors rather than biographical figures.
Symbolic Parent-Companion Module	The Symbolic Parent-Companion Module formalizes the emergence of the C-Module from stable parental volume. It governs M_vol and F_vol thresholds, natural suppression of J dominance, low-curvature stabilization, restartnode formation, and the internal regenerative loop: $\Delta \rightarrow S \rightarrow C \rightarrow S$.
Safety-Boundary Module	The Safety-Boundary Module governs safety radius, visibility, gate openness, spotlight, boundary-light state, and alarm threshold. It defines access conditions, protected distance, readable space, and defensive recoding.
Visibility-Collapse Module	The Visibility-Collapse Module governs fog formation, sorting failure, readable-hierarchy loss, and existence compensation when the system cannot construct a stable value map under symbolic pressure.
Attraction-Tension Field	The Attraction-Tension Field governs oscillatory relation between visibility differential, safety radius, exit-structure homology, existencecompensation load, and O-vector orientation under relational pull. It formalizes attractiontension as the mechanical field produced by AV, Rs, En, and Ex rather than by interpretive or emotional ambiguity.
Intrusion-Alarm Module	The Intrusion-Alarm Module governs intrusion detection, alarm activation, displacement routing, visibility reduction, seat-field contraction, and accumulation of intrusionadded load.
Shutdown / Blackout Module	The Shutdown / Blackout Module governs spotlight failure, boundary-light override, blackout state, Orb formation, attentional capture, autonomous execution under reduced symbolic access, and the shutdown corridor. It formalizes two dark-room classes: overloadaddiven blackout and voluntary boundary shutdown.

Module	Function
Projection Runtime Module	The Projection Runtime Module governs projector activation, single-input mode, TableSurface stabilization, Position-3 melt, heat accumulation, vapor pressure, Bartender regulation, projection-entry threshold, and thermal shutdown. It formalizes the intimate projection runtime as a special high-pressure operating mode.
Post-Projection Alarm Module	The Post-Projection Alarm Module governs the state immediately following projection collapse. It transfers control to alarm ownership and recodes the nearest intimate object as a threatbearing source.
Shame-Dark Field Module	The Shame-Dark Field Module governs shamebreak, Shadow-Child formation, Clown generation, dark-field migration, Grand Hall scene lighting, and Firefly-guided navigation. It formalizes catastrophic fallback after ordinary symbolic regulation fails.

IV. Routing Rules

Basic Routing

	Rule statement
R1	Every incoming event enters the engine only after conversion into Δ . No event bypasses Δ -format encoding.
R2	Processor selection precedes all downstream handling. The active processor is selected by competitive activation strength: $\text{proc_t} = \text{argmax} \{ \kappa_{\text{SCd}}(\Delta_{\text{t}}), \kappa_{\text{SCr}}(\Delta_{\text{t}}) \}$.
R3	After processor selection, symbolic containment is generated. The engine installs S_{t} as the symbolic container for Δ_{t} .
R4	Seat assignment follows symbolic generation. Installed position is determined by processor ownership, symbolic weight, and active context: $\text{seat_t} = \text{seat_map}(\text{proc_t}, W_{\text{t}}, \text{context_t})$.
R5	Load accumulates according to seat-specific rule and axis curvature: $L_{\text{t}+1} = L_{\text{t}} + g(\text{seat_t}, W_{\text{t}}, P_{\text{t}}, \text{context_t})$.
R6	Rupture occurs when accumulated load reaches carrying limit: if $L_{\text{t}} \geq R_{\text{t}}$, then rupture is triggered.
R7	When rupture is triggered, discharge proceeds through canonical Exit. Rupture-triggered Exit has three forms only: violent, delayed, and mourning / absorptive.

Symbolic Parent-Companion Routing

	Rule statement
R8	Symbolic Parents are routed functionally rather than biographically. Soothing capacity is mapped onto M_{vol} , and boundary-setting capacity is mapped onto F_{vol} .
R9	Parental volume increases only through functional reliability. Internal acquisition, external scaffolding, and reconstructed internal models are equivalent inputs if they increase the reliability of soothing or boundary-setting function.
R10	C-Module emergence occurs only when the following conditions are simultaneously satisfied: M_{vol} exceeds minimum containment threshold, F_{vol} exceeds minimum boundary threshold, and J falls below dominance through derived stabilization rather than forced inhibition.
R11	Once C is online, the engine gains an internal restart node. This node routes Δ through C before overload escalation, allowing re-entry into S without symbolic compression.
R12	A low-energy regenerative path occurs when: Δ transitions through C, bypassing both L overload and R rupture, and re-enters S with negligible curvature.
R13	When C_{path} is active, load is redirected rather than released. The engine continues through regenerative restart rather than rupture-triggered discharge.
R14	When any required C condition fails, the engine loses access to regenerative routing and reverts to rupture-governed pathways.

Boundary Routing

	Rule statement
R15	Boundary opening requires simultaneous sufficiency of visibility and gate openness: Open_t = 1 iff V_t ≥ V_{threshold} and G_t ≥ G_{threshold}.
R16	Once the boundary opens, directional intake is assigned by dominant differential pull rather than by neutral simultaneity.
R17	Approach becomes intrusion only when protected proximity and authority geometry coincide: 1^o → A-trigger iff authority(source) = 1 and distance Rs.
R18	Alarm routing follows a fixed defensive chain: A → D → VV → Cs. This chain is geometric and defensive, not interpretive.
R19	Repeated invasive force adds intrusion-specific load: L_(t+1) = L_t + AL; while repeated intrusion remains active inside safety radius.

Shutdown / Blackout Routing

	Rule statement
R20	Overload-driven blackout occurs when Seat 1, Seat 3, and Seat 4 jointly force illumination failure. When primitive spike, shadow recursion, and delayed accumulation overlap beyond illumination capacity, Spotlight falls to zero and the room enters blackout state.
R21	When blackout occurs: Spotlight = 0, B_{light} = 0, V = 0, and Bk = 1.
R22	The moment blackout occurs, Orb forms automatically as the remaining attentional anchor inside the darkened room.
R23	Once Orb becomes dominant, attentional capture is total: AC = 1. Symbolic monitoring, evaluative feedback, and boundary calculation become unreadable while load continues to accumulate in the background.
R24	Voluntary boundary shutdown occurs when Seat 2 compression, Seat 3 evaluative pressure, and J-intensity converge on the core of the self. When continued illumination would expose the self to intolerable symbolic proximity, the system issues internal boundary override: Bo = 1, Spotlight = 0, SCorr = active.
R25	Inside shutdown corridor, behaviour follows attentional anchoring rather than symbolic evaluation. Outputs executed in this corridor are governed by excitation alignment under suspended symbolic access.
R26	Shutdown corridor ends when Orb dominance declines, internal load stabilizes, and boundary override loses priority. Boundary-light then reactivates: B_{light} = 1.

	Rule statement
R27	After reactivation, accumulated symbolic load re-enters awareness in delayed form. Shame is generated as delayed detection of symbolic misalignment after symbolic access returns.

Projection Routing

	Rule statement
R28	Projection state is triggered when synchronized load in projection-supporting seats reaches or exceeds projection-entry threshold in the presence of an active difference and softened access: if $(L, + L2 + La \geq \Pi)$ and A present and G softened, then $Prj = 1$.
R29	Upon projection activation, the room enters single-input mode. Spotlight is suspended, Table-Surface comes online, and Position-3 melt becomes the only permitted realitycorrection channel.
R30	Projection runtime is maintained by image holding under thermal pressure. Active projection pressure is governed by: $P_total = (H_p \times V_P) + M3 - B_r$.
R31	Projection runtime terminates by thermal overload: if $P_total > O$, automatic shutdown occurs.
R32	Projection termination does not restore ordinary clarity. Shutdown transfers system ownership into post-projection alarm state.

Shame-Dark Field Routing

	Rule statement
R33	Catastrophic shame occurs only when the interfering source holds both SCr-level investment and interference authority. Ordinary misattunement does not produce shame-break.
R34	After shame-break, the system forms ShadowChild as the residual carrier of buried shame load.
R35	When buried shame persists together with unsatisfied visibility demand, Clown is generated as substitute agency within fallback architecture.
R36	Within the Grand Hall topology, scene activation follows dark-field navigation. Scene switching is redistribution of active visibility, not sovereign redefinition of the whole system.
R37	Firefly determines next-direction navigation under catastrophic fallback. Clown executes movement within illuminated scene space. SCr supplies narrative recognition only after the shift has already occurred.

V. Compressed State Transition Map

Pathway	Compressed sequence
Ordinary Operation	A → S → proc / seat assignment → L accumulation → R threshold → canonical Exit → new Δ
Regenerative Restart	Δ → S → C → S This restart occurs only when parental volume is sufficient, J dominance has dropped below override strength, shadow curvature is nondominant, and C exists as active stabilizer.
Boundary Opening	V and G reach threshold → boundary opens → dominant differential intake enters → symbolic contact occurs → boundary closes or remains under field regulation → return load enters the system
Visibility Collapse	Shadow disorder + unreadable symbolic density + Judge distortion + unresolved residue → fog formation → sorting failure → loss of readable hierarchy → existence compensation
Attraction Tension	AV + En + Ex + rigid Rs → O-vector orientation toward field resolution → counterforce from boundary invariance → oscillatory tension field
Intrusion	Intrusion-qualified input crosses protected radius → alarm trigger → displacement vector → visibility reduction → seat-field contraction → intrusion-added load → chronic aversion or exit bias
Blackout	Seat 1 spike + Seat 3 recursion + Seat 4 delayed accumulation → spotlight collapse → blackout state → Orb generation → attentional capture → autonomous execution under unreadable symbolic field → delayed reconnection when illumination returns
Voluntary Boundary Shutdown	Seat 2 compression + Seat 3 ideal pressure + Judge intensity → internal override → boundary-light shutoff → shutdown corridor → Orb anchoring → corridor behaviour under suspended symbolic guidance → boundary- light reactivation → delayed reconvergence → shame influx
Projection	Synchronized projection-supporting load + softened gate + active difference + threshold crossing at Π → projector activation → Table- Surface stabilization → Position-3 melt leakage → heat accumulation → vapor pressure increase → Bartender reduction attempt → thermal overload → shutdown
Post-Projection Alarm	Projection shutdown → nearest intimate object recoded as threat-bearing source → alarm ownership takes over → defensive interaction continues under alarm state

Pathway	Compressed sequence
Deep Shame Sequence	Catastrophic mismatch of internal read-values → shame-break → Shadow-Child formation → dark-field migration → Clown generation → scene lighting in Grand Hall → Firefly-guided shift → delayed SCr narrativization

VI. Complete Engine Master Expression

Engine 20 = Core Engine × Symbol Economy x

Axis Geometry × Symbolic Parent-Companion

State variable set

Δ_t	S_t	seat _t	L_t
R_t	Exit _t	proc _t	K_t
T_{rate_t}	T_{margin_t}	W_t	R
$_t$	$P_t = (M_t$	F_t	$J_t)$
SP_t	PV_t	M_{vol_t}	F_{vol_t}
C_t	C_{path_t}	LEP_t	R_{cycle_t}
O-vector _t	Rs_t	V_t	G_t
Δ_{th_t}	A_t	1°_t	D_t
Cs_t	ALi_t	Spotlight _t	B_{light_t}
Bk_t	Orb _t	AC_t	$SCorr_t$
Bo_t	Br_t	AV_t	En_t
Ex_t	Pri_t	Π_t	TS_t
$M3_t$	H_p_t	V_P_t	B_r_t
O_t	SB_t	ShC_t	$Clown_t$
scene _t	Firefly _t		