

Contents

1	Introduction	2
1.1	Assimilating pedestrian dynamics	2
1.2	Challenges	2
1.3	Relevance	3
1.4	Pedestrian dynamics background	3
1.5	Recording technique of measure	3
1.5.1	Kinect sensor: depth map based pedestrian tracking	3
1.5.2	ProRail cameras	3
1.6	Theoretical tools	3
1.6.1	Markov Chain	3
1.6.2	Cellular-Automata	3
1.6.3	Lattice-Boltzman	3
1.7	Presenting datasets	4
1.7.1	Utrecht Centraal (Floorefield 10)	4
2	Propose data assimilation technique	5
2.1	Learning transition matrices from data	5
2.1.1	Model D2Q9	8
2.1.2	Model D2Q9Q9	9
2.1.3	Model TD2Q9	11
2.1.4	Model TD2Q9Q9	12
2.2	Simulations	12
2.2.1	Trajectories simulation	14
2.2.2	Distribution simulation	15
2.3	Approximation of path integrals: 3D histogram	17
2.3.1	3D comparison between real data and simulations	17
3	Results	20
3.1	Comparison of assimilation methods	20
3.1.1	Real data - D2Q9	20
3.1.2	Real data - D2Q9Q9	20
3.1.3	Real data - TD2Q9	20
3.1.4	Real data - TD2Q9Q9	20
3.2	Simulation with generative models	20
3.2.1	Real data - D2Q9	20
3.2.2	Real data - D2Q9Q9	23
3.2.3	Real data - TD2Q9	24
3.2.4	Real data - TD2Q9Q9	27
4	Conclusion	29
5	Appendix	30
5.1	Package pathintegralanalytics - code description	30
5.1.1	Explanation of the library	30
5.1.2	UML diagram	30